

SBOS514C -MARCH 2010-REVISED OCTOBER 2013

# Micro-Power, Zerø-Drift, Rail-to-Rail Out Instrumentation Amplifier

Check for Samples: INA333-HT

#### **FEATURES**

Low Offset Voltage: 25 μV (max at 25°C),
 G > 100

Low Drift: 0.2 μV/°C, G ≥ 1000
 Low Noise: 55 nV/√Hz, G ≥ 100

• High CMRR: 100 dB (min at 25°C), G ≥ 10

Supply Range: +1.8 V to +5.5 V

Input Voltage: (V-) +0.1 V to (V+) -0.1 V
 Output Range: (V-) +0.05 V to (V+) -0.05V

Low Quiescent Current: 198 μA

RFI Filtered Inputs

#### **APPLICATIONS**

- Down-Hole Drilling
- High Temperature Environments

# SUPPORTS EXTREME TEMPERATURE APPLICATIONS

- Controlled Baseline
- One Assembly/Test Site
- One Fabrication Site
- Available in Extreme (-55°C/210°C)
   Temperature Range (1)
- Extended Product Life Cycle
- Extended Product-Change Notification
- Product Traceability
- Texas Instruments' high temperature products utilize highly optimized silicon (die) solutions with design and process enhancements to maximize performance over extended temperatures.
- (1) Custom temperature ranges available

#### DESCRIPTION

The INA333 is a low-power, precision instrumentation amplifier offering excellent accuracy. The versatile 3-op amp design, small size, and low power make it ideal for a wide range of portable applications.

A single external resistor sets any gain from 1 to 1000. The INA333 is designed to use an industry-standard gain equation:  $G = 1 + (100k\Omega/R_G)$ .


The INA333 provides very low offset voltage (25  $\mu$ V at 25°C, G  $\geq$  100), excellent offset voltage drift (0.2  $\mu$ V/°C, G  $\geq$  100), and high common-mode rejection (100 dB at 25°C, G  $\geq$  10). It operates with power supplies as low as 1.8 V (±0.9V), and quiescent current is only 50  $\mu$ A—ideal for battery-operated systems. Using autocalibration techniques to ensure excellent precision over the extended industrial temperature range, the INA333 also offers exceptionally low noise density (55 nV/ $\sqrt{Hz}$ ) that extends down to dc.

The INA333 is is specified over the  $T_A = -55^{\circ}\text{C}$  to +210°C temperature range.

松

Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.







This integrated circuit can be damaged by ESD. Texas Instruments recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage.

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.

#### ORDERING INFORMATION(1)

| T <sub>A</sub> | PACKAGE <sup>(2)</sup> | ORDERABLE PART<br>NUMBER | TOP-SIDE MARKING | PACKAGE QTY   CARRIER |
|----------------|------------------------|--------------------------|------------------|-----------------------|
|                | KCD                    | INA333SKGD1              | NA               | 240   TRAY            |
|                | KGD                    | INA333SKGD2              | NA               | 10   TRAY             |
| –55°C to 210°C | JD                     | INA333SJD                | INA333SJD        | 1   TUBE              |
|                | HKJ                    | INA333SHKJ               | INA333SHKJ       | 1   TUBE              |
|                | HKQ                    | INA333SHKQ               | INA333SHKQ       | 1   TUBE              |


- (1) For the most current package and ordering information see the Package Option Addendum at the end of this document, or see the TI web site at www.ti.com.
- (2) Package drawings, standard packaging quantities, thermal data, symbolization, and PCB design guidelines are available at www.ti.com/packaging.


#### **ABSOLUTE MAXIMUM RATINGS(1)**

|   |                               | INA333                   | UNIT |
|---|-------------------------------|--------------------------|------|
| Supply voltage                              |                               | +7                       | V    |
| Analog input vol                            | tage range <sup>(2)</sup>     | (V–) – 0.3 to (V+) + 0.3 | V    |
| Output short-cird                           | cuit <sup>(3)</sup>           | Continuous               |      |
| Operating temperature range, T <sub>A</sub> |                               | -55 to +210              | °C   |
| Storage tempera                             | ature range, T <sub>STG</sub> | -65 to +210              | °C   |
| Junction temper                             | ature, T <sub>J</sub>         | +210                     | °C   |
|   | Human body model (HBM)        | 4000                     | V    |
| ESD rating                                  | Charged device model (CDM)    | 1000                     | V    |
|   | Machine model (MM)            | 200                      | V    |

- (1) Stresses above these ratings may cause permanent damage. Exposure to absolute maximum conditions for extended periods may degrade device reliability. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those specified is not implied.
- (2) Input terminals are diode-clamped to the power-supply rails. Input signals that can swing more than 0.3V beyond the supply rails should be current limited to 10mA or less.
- (3) Short-circuit to ground.

#### **PIN CONFIGURATIONS**







#### **BARE DIE INFORMATION**

| DIE THICKNESS | BACKSIDE FINISH        | BACKSIDE<br>POTENTIAL | BOND PAD METALLIZATION COMPOSITION |
|---------------|------------------------|-----------------------|------------------------------------|
| 15 mils.      | Silicon with backgrind | V-                    | Al-Si-Cu (0.5%)                    |

### Origin








# Table 1. Bond Pad Coordinates in Microns<sup>(1)</sup>

| DESCRIPTION      | PAD NUMBER | X MIN   | Y MIN  | X MAX   | Y MAX  |
|------------------|------------|---------|--------|---------|--------|
| $R_{G}$          | 1          | 250     | 1604.8 | 326     | 1680.8 |
| V <sub>IN-</sub> | 2          | 21.2    | 1300   | 97.2    | 1376   |
| V <sub>IN+</sub> | 3          | 21.2    | 978.5  | 97.2    | 1054.5 |
| NC               | 4          | 21.2    | 748.65 | 97.2    | 824.65 |
| V-               | 5          | 31.3    | 300    | 107.3   | 376    |
| REF              | 6          | 1072.15 | 21.2   | 1148.15 | 97.2   |
| V <sub>OUT</sub> | 7          | 1299.8  | 216.2  | 1375.8  | 292.2  |
| V+               | 8          | 1289.7  | 700    | 1365.7  | 776    |
| $R_{G}$          | 9          | 1071    | 1604.8 | 1147    | 1680.8 |

#### (1) Substrate is N/C





#### THERMAL CHARACTERISTICS FOR JD PACKAGE

over operating free-air temperature range (unless otherwise noted)

|                   | PARAMETER                                  | TEST CONDITIONS                | MIN | TYP          | MAX | UNIT |
|-------------------|--|--------------------------------|-----|--------------|-----|------|
| 0                 | Junction-to-ambient thermal resistance (1) | High-K board (2), no airflow   |     | 64.9<br>83.4 |     |      |
| $\theta_{JA}$ Jur |  | No airflow                     |     |              |     |      |
| $\theta_{JB}$     | Junction-to-board thermal resistance       | High-K board without underfill |     | 27.9         |     | °C/W |
| $\theta_{JC}$     | Junction-to-case thermal resistance        |                                |     | 6.49         |     | °C/W |

The intent of θ<sub>JA</sub> specification is solely for a thermal performance comparison of one package to another in a standardized environment. This methodolgy is not meant to and will not predict the performance of a package in an application-specific environment.

#### THERMAL CHARACTERISTICS FOR HKJ OR HKQ PACKAGE

over operating free-air temperature range (unless otherwise noted)

|                 | PARAME                              | to ceramic side of case 5.7             |  |  |      | UNIT   |
|-----------------|-------------------------------------|---|--|--|------|--------|
|                 | lunction to cope thermal registance | to ceramic side of case                 |  |  | 5.7  | °C/W   |
| θ <sub>JC</sub> | Junction-to-case thermal resistance | to top of case lid (metal side of case) |  |  | 13.7 | · C/VV |

# ELECTRICAL CHARACTERISTICS: $V_s = +1.8 \text{ V to } +5.5 \text{ V}$

At  $T_A = +25$ °C,  $R_L = 10$ k $\Omega$ ,  $V_{REF} = V_S/2$ , and G = 1, unless otherwise noted.

|   |   | T,         | <sub>λ</sub> = −55°C to +12 | 25°C                       |                                  | T <sub>A</sub> = +210°0 | 3            |                        |
|---|---|------------|-----------------------------|----------------------------|----------------------------------|-------------------------|--------------|------------------------|
| PARAMETER   | TEST CONDITIONS   | MIN        | TYP                         | MAX                        | MIN                              | TYP                     | MAX          | UNIT                   |
| INPUT <sup>(1)</sup>                                |   |            |                             |                            |                                  |                         |              |                        |
| Offset voltage, V <sub>OSI</sub> RTI <sup>(2)</sup> |   |            | ±10 ±25/G                   | ±25 ±75/G                  |                                  | ±15                     |              | μV                     |
| vs Temperature                                      |   |            |                             | ±0.1 ±0.5/G <sup>(3)</sup> |                                  | 0.2(4)(5)               |              | μV/°C                  |
| vs Power supply PSR                                 | $1.8 \text{ V} \le \text{V}_{\text{S}} \le 5.5 \text{ V}$ |            | ±1 ±5/G                     | ±5 ±15/G                   |                                  | 2.5 <sup>(4)</sup>      |              | μV/V                   |
| Long-term stability                                 |   |            | See note (6)                |                            |                                  |                         |              |                        |
| Turn-on time to specified $V_{\mathrm{OSI}}$        |   | See        | Typical characte            | eristics                   | See Typical characteristics      |                         | cteristics   |                        |
| Impedance   |   |            |                             |                            |                                  |                         |              |                        |
| Differential Z <sub>IN</sub>                        |   |            | 100    3                    |                            |                                  | 100    3                |              | GΩ    pF               |
| Common-mode Z <sub>IN</sub>                         |   |            | 100    3                    |                            |                                  | 100    3                |              | $G\Omega \parallel pF$ |
| Common-mode V <sub>CM</sub> voltage range           | $V_O = 0 V$   | (V-) + 0.1 |                             | (V+) - 0.1                 | (V-) + 0.1                       |                         | (V+) - 0.1 V | V                      |
| Common-mode CMR rejection                           | DC to 60 Hz   |            |                             |                            |                                  |                         |              |                        |
| G = 1   | $V_{CM} = (V-) + 0.1 V \text{ to}$<br>(V+) - 0.1 V        | 80         | 90                          |                            |                                  |                         |              | dB                     |
| G = 10  | $V_{CM} = (V-) + 0.1 V \text{ to}$<br>(V+) - 0.1 V        | 100        | 110                         |                            |                                  |                         |              | dB                     |
| G = 100   | $V_{CM} = (V-) + 0.1 V \text{ to}$<br>(V+) - 0.1 V        | 100        | 115                         |                            |                                  | 110                     |              | dB                     |
| G = 1000  | $V_{CM} = (V-) + 0.1 V \text{ to}$<br>(V+) - 0.1 V        | 100        | 115                         |                            |                                  | 113                     |              | dB                     |
| INPUT BIAS CURRENT                                  |   |            |                             |                            |                                  |                         |              |                        |
| Input bias current I <sub>B</sub>                   |   |            | ±70                         | ±200                       |                                  | ±1260                   | ±2044        | pA                     |
| vs Temperature                                      |   | See Typ    | ical Characteri             | stic curve                 | See Typical Characteristic curve |                         | pA/°C        |                        |
| Input offset current I <sub>OS</sub>                |   |            | ±50                         | ±200                       |                                  |                         |              | pA                     |
| vs Temperature                                      |   | See Typ    | ical Characteri             | stic curve                 | See Typ                          | ical Characte           | ristic curve | pA/°C                  |

Total  $V_{OS}$ , Referred-to-input =  $(V_{OSI}) + (V_{OSO}/G)$ . RTI = Referred-to-input.

Copyright © 2010-2013, Texas Instruments Incorporated

JED51-7, high effective thermal conductivity test board for leaded surface mount packages.

Temperature drift is measured from -55°C to +125°C.

G = 1000

Temperature drift is measured from 125°C to +210°C.

<sup>300-</sup>hour life test at +150°C demonstrated randomly distributed variation of approximately 1 µV.





# ELECTRICAL CHARACTERISTICS: $V_S = +1.8 \text{ V to } +5.5 \text{ V (continued)}$

At  $T_A = +25$ °C,  $R_L = 10$ k $\Omega$ ,  $V_{REF} = V_S/2$ , and G = 1, unless otherwise noted.

|                                    |                 |   | 7   | Γ <sub>A</sub> = -55°C to +12 | 5°C   |     | T <sub>A</sub> = +210°C   |      |                    |
|------------------------------------|-----------------|---|-----|-------------------------------|-------|-----|---------------------------|------|--------------------|
| PARAMETER                          |                 | TEST CONDITIONS   | MIN | TYP                           | MAX   | MIN | TYP                       | MAX  | UNIT               |
| INPUT VOLTAGE NOIS                 | SE              |   |     |                               |       |     |                           |      |                    |
| Input voltage noise                | e <sub>NI</sub> | $G = 100, R_S = 0 Ω$  |     |                               |       |     |                           |      |                    |
| f = 10 Hz                          |                 | -   |     | 42                            |       |     | 63                        |      | nV/√ <del>Hz</del> |
| f = 100 Hz                         |                 |   |     | 40                            |       |     | 70                        |      | nV/√ <del>Hz</del> |
| f = 1 kHz                          |                 |   |     | 50                            |       |     | 55                        |      | nV/√ <del>Hz</del> |
| f = 0.1Hz to 10 Hz                 |                 |   |     | 2                             |       |     | 6                         |      | $\mu V_{PP}$       |
| Input current noise                | i <sub>N</sub>  |   |     |                               |       |     |                           |      |                    |
| f = 10Hz                           |                 |   |     | 100                           |       |     |                           |      | fA/√ <del>Hz</del> |
| f = 0.1Hz to 10Hz                  |                 |   |     | 2                             |       |     |                           |      | pA <sub>PP</sub>   |
| GAIN                               |                 |   |     |                               |       |     |                           |      |                    |
| Gain equation                      | G               |   |     | 1 + (100kΩ/R <sub>G</sub> )   | ı     |     | 1 + (100kΩ/R <sub>G</sub> | )    | V/V                |
| Range of gain (7)                  |                 |   | 1   |                               | 1000  | 100 |                           | 1000 | V/V                |
| Gain error                         |                 | $V_S = 5.5 \text{ V},$<br>$(V-) + 100\text{mV} \le V_O \le$<br>(V+) - 100mV |     |                               |       |     |                           |      |                    |
| G = 1                              |                 |   |     | ±0.02                         | ±0.1  |     |                           |      | %                  |
| G = 10                             |                 |   |     | ±0.05                         | ±0.5  |     |                           |      | %                  |
| G = 100                            |                 |   |     | ±0.01                         | ±0.5  |     | ±1.3                      |      | %                  |
| G = 1000                           |                 |   |     | ±0.43                         | ±1.15 |     | ±1.7                      |      | %                  |
| GAIN (continued)                   |                 |   |     |                               |       |     |                           |      |                    |
| Gain vs Temperature                |                 |   |     |                               |       |     |                           |      |                    |
| G = 1                              |                 |   |     | ±1                            | ±5    |     |                           |      | ppm/°C             |
| G > 1 <sup>(8)</sup>               |                 |   |     | ±15                           | ±50   |     |                           |      | ppm/°C             |
| Gain nonlinearity                  |                 | $V_S = 5.5 \text{ V},$<br>$(V-) + 100\text{mV} \le V_O \le$<br>(V+) - 100mV |     |                               |       |     |                           |      |                    |
| G = 1 to 1000                      |                 | $R_L = 10 \text{ k}\Omega$  |     | 10                            |       |     | 10                        |      | ppm                |
| OUTPUT                             |                 | -   |     |                               |       |     |                           |      |                    |
| Output voltage swing from rail (9) | om              | $V_S = 5.5 \text{ V}, \text{ R}_L = 10 \text{ k}\Omega$                     |     | See note (9)                  | 50    |     |                           | 185  | mV                 |
| Capacitive load drive              |                 |   |     | 500                           |       |     | 500                       |      | pF                 |
|                                    | $I_{SC}$        | Continuous to common  |     | <b>-</b> 55, <b>+</b> 5       |       |     | -36, +1                   |      | mA                 |
| FREQUENCY<br>RESPONSE              |                 |   |     | ·                             |       |     |                           |      |                    |
| Bandwidth, -3dB                    |                 |   |     |                               |       |     |                           |      |                    |
| Range of gain <sup>(7)</sup>       |                 |   |     |                               |       |     |                           |      |                    |
| G = 1                              |                 |   |     | 150                           |       |     |                           |      | kHz                |
| G = 10                             |                 |   |     | 35                            |       |     |                           |      | kHz                |
| G = 100                            |                 |   |     | 3.5                           |       |     | 3.1                       |      | kHz                |
| G = 1000                           |                 |   |     | 350                           |       |     | 300                       |      | Hz                 |
|                                    | SR              | V <sub>S</sub> = 5 V, V <sub>O</sub> = 4 V Step                             |     |                               |       |     |                           |      |                    |
| G = 1                              |                 | J , JF  |     | 0.16                          |       |     | 0.25                      |      | V/µs               |
| G = 100                            |                 |   |     | 0.06                          |       |     | 0.04                      |      | V/µs               |
| Settling time to 0.01%             | t <sub>S</sub>  |   |     |                               |       |     |                           |      |                    |
| G = 1                              |                 | V <sub>STEP</sub> = 4 V   |     | 35                            |       |     | 32                        |      | μs                 |
| G = 100                            |                 | V <sub>STEP</sub> = 4 V   |     | 240                           |       |     | 326                       |      | μs                 |
| Settling time to                   | ts              |   |     |                               |       |     |                           |      |                    |
| 0.001%                             | -               |   |     |                               |       |     |                           |      |                    |

<sup>(7)</sup> Not recommend gain < 100 for 210°C application.

Submit Documentation Feedback

Copyright © 2010–2013, Texas Instruments Incorporated


<sup>(8)</sup> Does not include effects of external resistor R<sub>G</sub>.

<sup>(9)</sup> See Typical Characteristics curve, Output Voltage Swing vs Output Current (Figure 31).

# ELECTRICAL CHARACTERISTICS: $V_S = +1.8 \text{ V to } +5.5 \text{ V (continued)}$

At  $T_A = +25$ °C,  $R_L = 10$ k $\Omega$ ,  $V_{REF} = V_S/2$ , and G = 1, unless otherwise noted.

|                                  |                         | T <sub>A</sub> | = -55°C to +1 | 25°C  |      | T <sub>A</sub> = +210°C | •     |      |
|----------------------------------|-------------------------|----------------|---------------|-------|------|-------------------------|-------|------|
| PARAMETER                        | TEST CONDITIONS         | MIN            | TYP           | MAX   | MIN  | TYP                     | MAX   | UNIT |
| G = 1                            | V <sub>STEP</sub> = 4 V |                | 60            |       |      | 55                      |       | μs   |
| G = 100                          | $V_{STEP} = 4 V$        |                | 500           |       |      | 530                     |       | μs   |
| Overload recovery                | 50% overdrive           |                | 52            |       |      | 28                      |       | μs   |
| REFERENCE INPUT                  |                         |                |               |       |      |                         |       |      |
| R <sub>IN</sub>                  |                         |                | 300           |       |      | 300                     |       | kΩ   |
| Voltage range                    |                         | V-             |               | V+    | V-   |                         | V+    | V    |
| POWER SUPPLY                     |                         |                |               |       |      |                         |       |      |
| Voltage range                    |                         |                |               |       |      |                         |       |      |
| Single                           |                         | +1.8           |               | +5.5  | +1.8 |                         | +5.5  | V    |
| Dual                             |                         | ±0.9           |               | ±2.75 | ±0.9 |                         | ±2.75 | V    |
| Quiescent current I <sub>Q</sub> | $V_{IN} = V_{S}/2$      |                | 50            | 75    |      |                         |       | μΑ   |
| vs Temperature                   |                         |                |               | 80    |      | 198                     | 345   | μΑ   |
| TEMPERATURE RANGE                |                         |                |               |       |      |                         |       |      |
| Specified temperature range      |                         | -55            |               | +125  | -55  |                         | +210  | °C   |
| Operating temperature range      |                         | -55            |               | +125  | -55  |                         | +210  | °C   |



#### Notes

- 1. See datasheet for absolute maximum and minimum recommended operating conditions.
- 2. Silicon operating life design goal is 10 years at 105°C junction temperature (does not include package interconnect life).

Figure 1. INA333SKGD1 Operating Life Derating Chart



#### TYPICAL CHARACTERISTICS

At  $T_A = +25$ °C,  $V_S = 5$ V,  $R_L = 10$ k $\Omega$ ,  $V_{REF} =$  midsupply, and G = 1, unless otherwise noted.






Figure 2.

# INPUT VOLTAGE OFFSET DRIFT (125°C to +210°C)



# OUTPUT VOLTAGE OFFSET DRIFT (-40°C to +125°C)



# INPUT VOLTAGE OFFSET DRIFT (-40°C to +125°C)




Figure 3.

#### **OUTPUT OFFSET VOLTAGE**




Figure 5.

#### **OFFSET VOLTAGE vs COMMON-MODE VOLTAGE**






Figure 7.





### **TYPICAL CHARACTERISTICS (continued)**

At  $T_A$  = +25°C,  $V_S$  = 5V,  $R_L$  = 10k $\Omega$ ,  $V_{REF}$  = midsupply, and G = 1, unless otherwise noted.




















### TYPICAL CHARACTERISTICS (continued)

At  $T_A = +25^{\circ}C$ ,  $V_S = 5V$ ,  $R_L = 10k\Omega$ ,  $V_{REF} =$  midsupply, and G = 1, unless otherwise noted. **SMALL-SIGNAL STEP RESPONSE SMALL-SI** 




SMALL-SIGNAL STEP RESPONSE


Gain = 100


(Ap/Np/Np/Qp)


Gain = 100

Time (100µs/div)












### TYPICAL CHARACTERISTICS (continued)

At  $T_A = +25$ °C,  $V_S = 5V$ ,  $R_L = 10k\Omega$ ,  $V_{REF} = midsupply$ , and G = 1, unless otherwise noted.







TYPICAL COMMON-MODE RANGE vs OUTPUT VOLTAGE







TYPICAL COMMON-MODE RANGE vs OUTPUT VOLTAGE



TYPICAL COMMON-MODE RANGE vs OUTPUT VOLTAGE






Figure 25.





### TYPICAL CHARACTERISTICS (continued)

At  $T_A$  = +25°C,  $V_S$  = 5V,  $R_L$  = 10k $\Omega$ ,  $V_{REF}$  = midsupply, and G = 1, unless otherwise noted.












Figure 30.





Figure 29.

Figure 31.

### **TYPICAL CHARACTERISTICS (continued)**






Figure 33.

#### SBOS514C - MARCH 2010-REVISED OCTOBER 2013



#### APPLICATION INFORMATION

Application information below is provided for commercial temperature as a reference and not for high temperature.

It is not recommended to use a gain < 100 for high temperature (210°C) applications. For gains > 100 in such applications, a compensation circuit is needed at pins 1 and 8. The circuit is needed at each pin and consists of a resistor in series with a capacitor referenced to ground. Recommended values for the resistor and capacitor are 3.5 k $\Omega$  and 10 nF respectively.

Figure 34 shows the basic connections required for operation of the INA333. Good layout practice mandates the use of bypass capacitors placed close to the device pins as shown.

The output of the INA333 is referred to the output reference (REF) terminal, which is normally grounded. This connection must be low-impedance to assure good common-mode rejection. Although 15  $\Omega$  or less of stray resistance can be tolerated while maintaining specified CMRR, small stray resistances of tens of ohms in series with the REF pin can cause noticeable degradation in CMRR.

#### SETTING THE GAIN

Gain of the INA333 is set by a single external resistor,  $R_{\rm G}$ , connected between pins 1 and 8. The value of  $R_{\rm G}$  is selected according to Equation 1:

$$G = 1 + (100 \text{ k}\Omega/R_G)$$
 (1)

Table 2 lists several commonly-used gains and resistor values. The 100 k $\Omega$  term in Equation 1 comes from the sum of the two internal feedback resistors of A<sub>1</sub> and A<sub>2</sub>. These on-chip resistors are laser trimmed to accurate absolute values. The accuracy and temperature coefficient of these resistors are included in the gain accuracy and drift specifications of the INA333.

The stability and temperature drift of the external gain setting resistor,  $R_{\rm G}$ , also affects gain. The contribution of  $R_{\rm G}$  to gain accuracy and drift can be directly inferred from the gain Equation 1. Low resistor values required for high gain can make wiring resistance important. Sockets add to the wiring resistance and contribute additional gain error (possibly an unstable gain error) in gains of approximately 100 or greater. To ensure stability, avoid parasitic capacitance of more than a few picofarads at the  $R_{\rm G}$  connections. Careful matching of any parasitics on both  $R_{\rm G}$  pins maintains optimal CMRR over frequency.






Figure 34. Basic Connections

Table 2. Commonly-Used Gains and Resistor Values

| DESIRED GAIN | R <sub>G</sub> (Ω) | NEAREST 1% $R_G$ ( $\Omega$ ) |
|--------------|--------------------|-------------------------------|
| 1            | NC <sup>(1)</sup>  | NC                            |
| 2            | 100k               | 100k                          |
| 5            | 25k                | 24.9k                         |
| 10           | 11.1k              | 11k                           |
| 20           | 5.26k              | 5.23k                         |
| 50           | 2.04k              | 2.05                          |
| 100          | 1.01k              | 1k                            |
| 200          | 502.5              | 499                           |
| 500          | 200.4              | 200                           |
| 1000         | 100.1              | 100                           |

(1) NC denotes no connection. When using the SPICE model, the simulation will not converge unless a resistor is connected to the R<sub>G</sub> pins; use a very large resistor value.




#### INTERNAL OFFSET CORRECTION

The INA333 internal op amps use an auto-calibration technique with a time-continuous 350-kHz op amp in the signal path. The amplifier is zero-corrected every 8  $\mu s$  using a proprietary technique. Upon power-up, the amplifier requires approximately 100  $\mu s$  to achieve specified  $V_{OS}$  accuracy. This design has no aliasing or flicker noise.

#### **OFFSET TRIMMING**

Most applications require no external offset adjustment; however, if necessary, adjustments can be made by applying a voltage to the REF terminal. Figure 35 shows an optional circuit for trimming the output offset voltage. The voltage applied to REF terminal is summed at the output. The op amp buffer provides low impedance at the REF terminal to preserve good common-mode rejection.



(1) REF200 and OPA333 are not tested or characterized at 210°C.

Figure 35. Optional Trimming of Output Offset Voltage

#### **NOISE PERFORMANCE**

The auto-calibration technique used by the INA333 results in reduced low frequency noise, typically only 50 nV/ $\sqrt{\text{Hz}}$ , (G = 100). The spectral noise density can be seen in detail in Figure 10. Low frequency noise of the INA333 is approximately 1  $\mu\text{V}_{PP}$  measured from 0.1 Hz to 10 Hz, (G = 100).

#### **INPUT BIAS CURRENT RETURN PATH**

The input impedance of the INA333 is extremely high—approximately 100 G $\Omega$ . However, a path must be provided for the input bias current of both inputs. This input bias current is typically  $\pm 70$  pA. High input impedance means that this input bias current changes very little with varying input voltage.

Input circuitry must provide a path for this input bias current for proper operation. Figure 36 illustrates various provisions for an input bias current path. Without a bias current path, the inputs will float to a potential that exceeds the common-mode range of the INA333, and the input amplifiers will saturate. If the differential source resistance is low, the bias current return path can be connected to one input (see the thermocouple example in Figure 36). With higher source impedance, using two equal resistors provides a balanced input with possible advantages of lower input offset voltage as a result of bias current and better high-frequency common-mode rejection.




Figure 36. Providing an Input Common-Mode Current Path

#### INPUT COMMON-MODE RANGE

The linear input voltage range of the input circuitry of the INA333 is from approximately 0.1 V below the positive supply voltage to 0.1 V above the negative supply. As a differential input voltage causes the output voltage to increase, however, the linear input range is limited by the output voltage swing of amplifiers A<sub>1</sub> and A<sub>2</sub>. Thus, the linear common-mode input range is related to the output voltage of the complete amplifier. This behavior also depends on supply voltage—see Typical Characteristic curves Typical Common-Mode Range vs Output Voltage (Figure 22 to Figure 25).

Input overload conditions can produce an output voltage that appears normal. For example, if an input overload condition drives both input amplifiers to the respective positive output swing limit, the difference voltage measured by the output amplifier is near zero. The output of the INA333 is near 0 V even though both inputs are overloaded.

#### **OPERATING VOLTAGE**

The INA333 operates over a power-supply range of +1.8 V to +5.5 V (±0.9 V to ±2.75 V). Supply voltages higher than +7 V (absolute maximum) can permanently damage the device. Parameters that vary over supply voltage or temperature are shown in the Typical Characteristics section of this data sheet.

#### LOW VOLTAGE OPERATION


The INA333 can be operated on power supplies as low as ±0.9 V. Most parameters vary only slightly throughout this supply voltage range—see the Typical Characteristics section. Operation at very low supply voltage requires careful attention to assure that the input voltages remain within the linear range. Voltage swing requirements of internal nodes limit the input common-mode range with low power-supply voltage. The Typical Characteristic curves Typical Common-Mode Range vs Output Voltage (Figure 22 to Figure 25) show the range of linear operation for various supply voltages and gains.

#### SINGLE-SUPPLY OPERATION

The INA333 can be used on single power supplies of +1.8 V to +5.5 V. Figure 37 illustrates a basic single-supply circuit. The output REF terminal is connected to mid-supply. Zero differential input voltage demands an output voltage of mid-supply. Actual output voltage swing is limited to approximately 50 mV above ground, when the load is referred to ground as shown. The typical characteristic curve *Output Voltage Swing vs Output Current* (Figure 31) shows how the output voltage swing varies with output current.

With single-supply operation,  $V_{\text{IN+}}$  and  $V_{\text{IN-}}$  must both be 0.1V above ground for linear operation. For instance, the inverting input cannot be connected to ground to measure a voltage connected to the noninverting input.

To illustrate the issues affecting low voltage operation, consider the circuit in Figure 37. It shows the INA333 operating from a single 3-V supply. A resistor in series with the low side of the bridge assures that the bridge output voltage is within the common-mode range of the amplifier inputs.



(1) R<sub>1</sub> creates proper common-mode voltage, only for low-voltage operation—see the *Single-Supply Operation* section.

Figure 37. Single-Supply Bridge Amplifier

#### INPUT PROTECTION

The input terminals of the INA333 are protected with internal diodes connected to the power-supply rails. These diodes clamp the applied signal to prevent it from damaging the input circuitry. If the input signal voltage can exceed the power supplies by more than 0.3 V, the input signal current should be limited to less than 10 mA to protect the internal clamp diodes. This current limiting can generally be done with a series input resistor. Some signal sources are inherently current-limited and do not require limiting resistors.


#### **GENERAL LAYOUT GUIDELINES**

Attention to good layout practices is always recommended. Keep traces short and, when possible, use a printed circuit board (PCB) ground plane with surface-mount components placed as close to the device pins as possible. Place a 0.1-µF bypass capacitor closely across the supply pins. These guidelines should be applied throughout the analog circuit to improve performance and provide benefits such as reducing the electromagnetic-interference (EMI) susceptibility.

Instrumentation amplifiers vary in the susceptibility to radio-frequency interference (RFI). RFI can generally be identified as a variation in offset voltage or dc signal levels with changes in the interfering RF signal. The INA333 has been specifically designed to minimize susceptibility to RFI by incorporating passive RC filters with an 8-MHz corner frequency at the  $V_{\rm IN+}$  and  $V_{\rm IN-}$  inputs. As a result, the INA333 demonstrates remarkably low sensitivity compared to previous generation devices. Strong RF fields may continue to cause varying offset levels, however, and may require additional shielding.

#### **APPLICATION IDEAS**

Additional application ideas are shown in Figure 38 to Figure 41.









Figure 38. ECG Amplifier With Right-Leg Drive



(1) OPA333 is not tested or characterized at 210°C.

Figure 39. Single-Supply, Very Low Power, ECG Circuit

#### TINA-TI (FREE DOWNLOAD SOFTWARE)

#### Using TINA-TI SPICE-Based Analog Simulation Program with the INA333


TINA is a simple, powerful, and easy-to-use circuit simulation program based on a SPICE engine. TINA-TI is a free, fully functional version of the TINA software, preloaded with a library of macromodels in addition to a range of both passive and active models. It provides all the conventional dc, transient, and frequency domain analysis of SPICE as well as additional design capabilities.

Available as a free download from the Analog eLab Design Center, TINA-TI offers extensive post-processing capability that allows users to format results in a variety of ways.

Virtual instruments offer users the ability to select input waveforms and probe circuit nodes, voltages, and waveforms, creating a dynamic quick-start tool.

Figure 40 and Figure 41 show example TINA-TI circuits for the INA333 that can be used to develop, modify, and assess the circuit design for specific applications. Links to download these simulation files are given below.


**NOTE:** these files require that either the TINA software (from DesignSoft) or TINA-TI software be installed. Download the free TINA-TI software from the TINA-TI folder.




- (1) The following link launches the TI logarithmic amplifiers web page: Logarithmic Amplifier Products Home Page
- (2) OPA369 and OPA335 are not characterized at 210°C.

Figure 40. Low-Power Log Function Circuit for Portable Battery-Powered Systems (Example Glucose Meter)

To download a compressed file that contains the TINA-TI simulation file for this circuit, click the following link: Log Circuit.







- (1) RWa, RWb, RWc, and RWd simulate wire resistance. These resistors are included to show the four-wire sense technique immunity to line mismatches. This method assumes the use of a four-wire RTD.
- (2) In this diagram, only INA333 is tested and characterized at 210°C.

Figure 41. Four-Wire, 3V Conditioner for a PT100 RTD With Programmable Gain Acquisition System

To download a compressed file that contains the TINA-TI simulation file for this circuit, click the following link: PT100 RTD.

www.ti.com 11-Nov-2025

#### PACKAGING INFORMATION

| Orderable part number | Status | Material type | Package   Pins   | Package qty   Carrier | RoHS | Lead finish/<br>Ball material | MSL rating/<br>Peak reflow | Op temp (°C) | Part marking   |
|-----------------------|--------|---------------|------------------|-----------------------|------|-------------------------------|----------------------------|--------------|----------------|
|                       | ` ,    | .,            |                  |                       | . ,  | (4)                           | (5)                        |              | . ,            |
| INA333SHKJ            | Active | Production    | CFP (HKJ)   8    | 25   TUBE             | Yes  | Call TI                       | N/A for Pkg Type           | -55 to 210   | INA333S<br>HKJ |
| INA333SHKJ.A          | Active | Production    | CFP (HKJ)   8    | 25   TUBE             | Yes  | Call TI                       | N/A for Pkg Type           | -55 to 210   | INA333S<br>HKJ |
| INA333SHKQ            | Active | Production    | CFP (HKQ)   8    | 25   TUBE             | Yes  | AU                            | N/A for Pkg Type           | -55 to 210   | INA333S<br>HKQ |
| INA333SHKQ.A          | Active | Production    | CFP (HKQ)   8    | 25   TUBE             | Yes  | AU                            | N/A for Pkg Type           | -55 to 210   | INA333S<br>HKQ |
| INA333SJD             | Active | Production    | CDIP SB (JD)   8 | 45   TUBE             | Yes  | Call TI                       | N/A for Pkg Type           | -55 to 210   | INA333SJD      |
| INA333SJD.A           | Active | Production    | CDIP SB (JD)   8 | 45   TUBE             | Yes  | Call TI                       | N/A for Pkg Type           | -55 to 210   | INA333SJD      |
| INA333SKGD1           | Active | Production    | XCEPT (KGD)   0  | 240   NOT REQUIRED    | Yes  | Call TI                       | N/A for Pkg Type           | -55 to 210   |                |
| INA333SKGD1.A         | Active | Production    | XCEPT (KGD)   0  | 240   NOT REQUIRED    | Yes  | Call TI                       | N/A for Pkg Type           | -55 to 210   |                |
| INA333SKGD2           | Active | Production    | XCEPT (KGD)   0  | 10   TUBE             | Yes  | Call TI                       | N/A for Pkg Type           | -55 to 210   |                |
| INA333SKGD2.A         | Active | Production    | XCEPT (KGD)   0  | 10   TUBE             | Yes  | Call TI                       | N/A for Pkg Type           | -55 to 210   |                |

<sup>(1)</sup> Status: For more details on status, see our product life cycle.

<sup>(2)</sup> Material type: When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

<sup>(3)</sup> RoHS values: Yes, No, RoHS Exempt. See the TI RoHS Statement for additional information and value definition.

<sup>(4)</sup> Lead finish/Ball material: Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

<sup>(5)</sup> MSL rating/Peak reflow: The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

<sup>(6)</sup> Part marking: There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.



# PACKAGE OPTION ADDENDUM

www.ti.com 11-Nov-2025

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

#### OTHER QUALIFIED VERSIONS OF INA333-HT:

Catalog: INA333

Automotive : INA333-Q1

NOTE: Qualified Version Definitions:

- Catalog TI's standard catalog product
- Automotive Q100 devices qualified for high-reliability automotive applications targeting zero defects

# **PACKAGE MATERIALS INFORMATION**

www.ti.com 23-May-2025

#### **TUBE**




\*All dimensions are nominal

| Device       | Package Name | Package Type | Pins | SPQ | L (mm) | W (mm) | T (µm) | B (mm) |
|--------------|--------------|--------------|------|-----|--------|--------|--------|--------|
| INA333SHKJ   | HKJ          | CFP          | 8    | 25  | 506.98 | 26.16  | 6220   | NA     |
| INA333SHKJ.A | HKJ          | CFP          | 8    | 25  | 506.98 | 26.16  | 6220   | NA     |
| INA333SHKQ   | HKQ          | CFP          | 8    | 25  | 506.98 | 26.16  | 6220   | NA     |
| INA333SHKQ.A | HKQ          | CFP          | 8    | 25  | 506.98 | 26.16  | 6220   | NA     |
| INA333SJD    | JD           | CDIP SB      | 8    | 45  | 506.98 | 15.24  | 12290  | NA     |
| INA333SJD.A  | JD           | CDIP SB      | 8    | 45  | 506.98 | 15.24  | 12290  | NA     |

HKQ (R-CDFP-G8)

CERAMIC GULL WING



NOTES:


- All linear dimensions are in inches (millimeters).
- This drawing is subject to change without notice.
- This package can be hermetically sealed with a metal lid.
- D. The terminals will be gold plated.E. Lid is not connected to any lead.



# JD (R-CDIP-T\*\*)

# CERAMIC SIDE-BRAZE DUAL-IN-LINE PACKAGE

20 PINS SHOWN




NOTES:

- A. All linear dimensions are in inches (millimeters).
- B. This drawing is subject to change without notice.
- C. This package is hermetically sealed with a metal lid.
- D. The terminals are gold plated.
- E. Falls within MIL STD 1835 CDIP2 T8, T14, T16, T18, T20 and T24 respectively.



# HKJ (R-CDFP-F8)

## CERAMIC DUAL FLATPACK



NOTES:

- A. All linear dimensions are in inches (millimeters).
- B. This drawing is subject to change without notice.
- C. This package can be hermetically sealed with a metal lid.
- D. The terminals will be gold plated.



#### IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you fully indemnify TI and its representatives against any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale, TI's General Quality Guidelines, or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products. Unless TI explicitly designates a product as custom or customer-specified, TI products are standard, catalog, general purpose devices.

TI objects to and rejects any additional or different terms you may propose.

Copyright © 2025, Texas Instruments Incorporated

Last updated 10/2025