

# LM393B, LM2903B, LM193, LM293, LM393 and LM2903 Dual Comparators

## 1 Features

- NEW [LM393B](#) and [LM2903B](#)
- Improved specifications of B-version
  - Maximum rating: up to 38V
  - ESD rating (HBM): 2kV
  - Low input offset: 0.37mV
  - Low input bias current: 3.5nA
  - Low supply-current: 200µA per comparator
  - Faster response time of 1µsec
  - Extended temperature range for LM393B
  - Available in tiny 2 x 2mm WSON package
- B-version is drop-in replacement for LM293, LM393 and LM2903, A and V versions
- Common-mode input voltage range includes ground
- Differential input voltage range equal to maximum-rated supply voltage: ±38 V
- Low output saturation voltage
- Output compatible with TTL, MOS, and CMOS

## 2 Applications

- [Vacuum robot](#)
- [Single phase UPS](#)
- [Server PSU](#)
- [Cordless power tool](#)
- [Wireless infrastructure](#)
- [Appliances](#)
- [Building automation](#)
- [Factory automation & control](#)
- [Motor drives](#)
- [Infotainment & cluster](#)

## 3 Description

The [LM393B](#) and [LM2903B](#) devices are the next generation versions of the industry-standard LM393 and LM2903 comparator family. These next generation B-version comparators feature lower offset voltage, higher supply voltage capability, lower supply current, lower input bias current, lower propagation delay, and improved 2 kV ESD performance and input ruggedness through dedicated ESD clamps. The LM393B and LM2903B can drop-in replace the LM293, LM393 and LM2903, for both "A" and "V" grades.

All devices consist of two independent voltage comparators that are designed to operate from a single power supply over a wide range of voltages. Quiescent current is independent of the supply voltage.

### Device Information

| PART NUMBER                                                                     | PACKAGE <sup>(1)</sup> | BODY SIZE (NOM) |
|---------------------------------------------------------------------------------|------------------------|-----------------|
| LM393B, LM2903B, LM193, LM293, LM293A, LM393, LM393A, LM2903, LM2903V, LM2903AV | SOIC (8)               | 4.90mm x 3.91mm |
| LM393B, LM2903B, LM293, LM293A, LM393, LM393A, LM2903                           | VSSOP (8)              | 3.00mm x 3.00mm |
| LM293, LM393, LM393A, LM2903                                                    | PDIP (8)               | 9.81mm x 6.35mm |
| LM393, LM393A, LM2903                                                           | SO (8)                 | 6.20mm x 5.30mm |
| LM393B, LM2903B, LM393, LM393A, LM2903, LM2903V, LM2903AV                       | TSSOP (8)              | 3.00mm x 4.40mm |
| LM393B, LM2903B                                                                 | SOT-23 (8)             | 2.90mm x 1.60mm |
| LM393B, LM2903B                                                                 | WSON (8)               | 2.00mm x 2.00mm |

(1) For all available packages, see the orderable addendum at the end of the data sheet.

### Family Comparison Table

| Specification                           | <a href="#">LM393B</a> | <a href="#">LM2903B</a> | <a href="#">LM393</a><br><a href="#">LM393A</a> | <a href="#">LM2903</a> | <a href="#">LM2903V</a><br><a href="#">LM2903AV</a> | <a href="#">LM193</a> | <a href="#">LM293</a><br><a href="#">LM293A</a> | Units |
|-----------------------------------------|------------------------|-------------------------|-------------------------------------------------|------------------------|-----------------------------------------------------|-----------------------|-------------------------------------------------|-------|
| Supply Voltage                          | 2 to 36                | 2 to 36                 | 2 to 30                                         | 2 to 30                | 2 to 32                                             | 2 to 30               | 2 to 30                                         | V     |
| Total Supply Current<br>(5V to 36V max) | 0.6 to 0.8             | 0.6 to 0.8              | 1 to 2.5                                        | 1 to 2.5               | 1 to 2.5                                            | 1 to 2.5              | 1 to 2.5                                        | mA    |
| Temperature Range                       | –40 to 85              | –40 to 125              | 0 to 70                                         | –40 to 125             | –40 to 125                                          | –55 to 125            | –25 to 85                                       | °C    |
| ESD (HBM)                               | 2000                   | 2000                    | 2000                                            | 2000                   | 2000                                                | 2000                  | 2000                                            | V     |
| Offset Voltage<br>(Max over temp)       | ± 4                    | ± 4                     | ± 9<br>± 4                                      | ± 15                   | ± 15<br>± 4                                         | ± 9                   | ± 9<br>± 4                                      | mV    |
| Input Bias Current (typ / max)          | 3.5 / 25               | 3.5 / 25                | 25 / 250                                        | 25 / 250               | 25 / 250                                            | 25 / 100              | 25 / 250                                        | nA    |
| Response Time (typ)                     | 1                      | 1                       | 1.3                                             | 1.3                    | 1.3                                                 | 1.3                   | 1.3                                             | µsec  |



## Table of Contents

|                                                                                               |           |                                                                      |           |
|-----------------------------------------------------------------------------------------------|-----------|----------------------------------------------------------------------|-----------|
| <b>1 Features</b> .....                                                                       | <b>1</b>  | 5.12 Typical Characteristics, LMx93x and LM2903x.....                | <b>11</b> |
| <b>2 Applications</b> .....                                                                   | <b>1</b>  | <b>6 Detailed Description</b> .....                                  | <b>17</b> |
| <b>3 Description</b> .....                                                                    | <b>1</b>  | 6.1 Overview.....                                                    | <b>17</b> |
| <b>4 Pin Configuration and Functions</b> .....                                                | <b>3</b>  | 6.2 Functional Block Diagram.....                                    | <b>17</b> |
| <b>5 Specifications</b> .....                                                                 | <b>4</b>  | 6.3 Feature Description.....                                         | <b>17</b> |
| 5.1 Absolute Maximum Ratings.....                                                             | <b>4</b>  | 6.4 Device Functional Modes.....                                     | <b>17</b> |
| 5.2 Recommended Operating Conditions.....                                                     | <b>4</b>  | <b>7 Application and Implementation</b> .....                        | <b>18</b> |
| 5.3 Thermal Information: LMx93x and LM2903x.....                                              | <b>5</b>  | 7.1 Application Information.....                                     | <b>18</b> |
| 5.4 ESD Ratings.....                                                                          | <b>5</b>  | 7.2 Typical Application.....                                         | <b>18</b> |
| 5.5 Electrical Characteristics LM393B.....                                                    | <b>6</b>  | <b>8 Device and Documentation Support</b> .....                      | <b>21</b> |
| 5.6 Electrical Characteristics LM2903B.....                                                   | <b>7</b>  | 8.1 Receiving Notification of Documentation Updates....              | <b>21</b> |
| 5.7 Switching Characteristics LM393B and LM2903B.....                                         | <b>7</b>  | 8.2 Support Resources.....                                           | <b>21</b> |
| 5.8 Electrical Characteristics for LM193, LM293, and<br>LM393 (without A suffix).....         | <b>8</b>  | 8.3 Trademarks.....                                                  | <b>21</b> |
| 5.9 Electrical Characteristics for LM293A and LM393A....                                      | <b>9</b>  | 8.4 Electrostatic Discharge Caution.....                             | <b>21</b> |
| 5.10 Electrical Characteristics for LM2903,<br>LM2903V, and LM2903AV.....                     | <b>10</b> | 8.5 Glossary.....                                                    | <b>21</b> |
| 5.11 Switching Characteristics: LM193, LM239,<br>LM393, LM2903, all 'A' and 'V' versions..... | <b>10</b> | <b>9 Revision History</b> .....                                      | <b>21</b> |
|                                                                                               |           | <b>10 Mechanical, Packaging, and Orderable<br/>Information</b> ..... | <b>22</b> |

## 4 Pin Configuration and Functions





Figure 4-1. D, DGK, JG, P, PS, DDF or PW Package 8-Pin SOIC, VSSOP, PDIP, SO, or TSSOP Top View



Connect thermal pad directly to GND pin.

Figure 4-2. DSG Package 8-Pin WSON With Exposed Pad Top View

Table 4-1. Pin Functions

| NAME            | PIN                                  |     | I/O    | DESCRIPTION                        |
|-----------------|--------------------------------------|-----|--------|------------------------------------|
|                 | SOIC, VSSOP, PDIP, SO, DDF and TSSOP | DSG |        |                                    |
| 1OUT            | 1                                    | 1   | Output | Output pin of comparator 1         |
| 1IN–            | 2                                    | 2   | Input  | Negative input pin of comparator 1 |
| 1IN+            | 3                                    | 3   | Input  | Positive input pin of comparator 1 |
| GND             | 4                                    | 4   | —      | Ground                             |
| 2IN+            | 5                                    | 5   | Input  | Positive input pin of comparator 2 |
| 2IN–            | 6                                    | 6   | Input  | Negative input pin of comparator 2 |
| 2OUT            | 7                                    | 7   | Output | Output pin of comparator 2         |
| V <sub>CC</sub> | 8                                    | 8   | —      | Positive Supply                    |
| Thermal Pad     | —                                    | PAD | —      | Connect directly to GND pin        |

## 5 Specifications

### 5.1 Absolute Maximum Ratings

over operating free-air temperature range (unless otherwise noted) <sup>(1)</sup>

|                                                                           |                 | MIN  | MAX       | UNIT |
|---------------------------------------------------------------------------|-----------------|------|-----------|------|
| V <sub>CC</sub> Supply voltage <sup>(2)</sup>                             | Non-B Versions  | -0.3 | 36        | V    |
|                                                                           | B Versions Only |      | 38        |      |
| V <sub>ID</sub> Differential input voltage <sup>(3)</sup>                 | Non-B Versions  | -36  | 36        | V    |
|                                                                           | B Versions Only | -38  | 38        |      |
| V <sub>I</sub> Input voltage (either input)                               | Non-B Versions  | -0.3 | 36        | V    |
|                                                                           | B Versions Only |      | 38        |      |
| I <sub>IK</sub> Input current <sup>(5)</sup>                              |                 |      | -50       | mA   |
| V <sub>O</sub> Output voltage                                             | Non-B Versions  | -0.3 | 36        | V    |
|                                                                           | B Versions Only |      | 38        |      |
| I <sub>O</sub> Output current                                             | Non-B Versions  |      | 20        | mA   |
|                                                                           | B Versions Only |      | 25        |      |
| I <sub>SC</sub> Duration of output short circuit to ground <sup>(4)</sup> |                 |      | Unlimited |      |
| T <sub>J</sub> Operating virtual-junction temperature                     |                 |      | 150       | °C   |
| T <sub>stg</sub> Storage temperature                                      |                 | -65  | 150       | °C   |

- (1) Stresses beyond those listed under *Absolute Maximum Ratings* can cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under *Recommended Operating Conditions* is not implied. Exposure to absolute-maximum-rated conditions for extended periods can affect device reliability. Production Processing Does Not Necessarily Include Testing of All Parameters.
- (2) All voltage values, except differential voltages, are with respect to network ground.
- (3) Differential voltages are at IN+ with respect to IN-.
- (4) Short circuits from outputs to V<sub>CC</sub> can cause excessive heating and eventual destruction.
- (5) Input current flows thorough parasitic diode to ground and turns on parasitic transistors that increases I<sub>CC</sub> and can cause the output to be incorrect. Normal operation resumes when input current is removed.

### 5.2 Recommended Operating Conditions

Over operating free-air temperature range (unless otherwise noted)

|                                              |                                    | MIN  | MAX        | UNIT |
|----------------------------------------------|------------------------------------|------|------------|------|
| Supply voltage, V <sub>S</sub> = (V+) – (V-) | non-V devices                      | 2    | 30         | V    |
|                                              | V devices                          | 2    | 32         |      |
|                                              | "B" version devices                | 2    | 36         |      |
| Input voltage range, V <sub>IVR</sub>        | non-B devices                      | 0    | (V+) – 2.0 | V    |
|                                              | "B" version devices                | -0.1 |            |      |
| Ambient temperature, T <sub>A</sub>          | LM193                              | -55  | 125        | °C   |
|                                              | LM2903, LM2903V, LM2903AV, LM2903B | -40  | 125        |      |
|                                              | LM393B                             | -40  | 85         |      |
|                                              | LM293, LM293A                      | -25  | 85         |      |
|                                              | LM393, LM393A                      | 0    | 70         |      |

### 5.3 Thermal Information: LMx93x and LM2903x

| THERMAL METRIC <sup>(1)</sup> |                                              | LMx93x, LM2903x |             |               |                |                 |               | UNIT |
|-------------------------------|----------------------------------------------|-----------------|-------------|---------------|----------------|-----------------|---------------|------|
|                               |                                              | D<br>(SOIC)     | P<br>(PDIP) | PW<br>(TSSOP) | DGK<br>(VSSOP) | DDF<br>(SOT-23) | DSG<br>(WSON) |      |
|                               |                                              | 8<br>PINS       | 8<br>PINS   | 8<br>PINS     | 8<br>PINS      | 8<br>PINS       | 8<br>PINS     |      |
| R <sub>θJA</sub>              | Junction-to-ambient thermal resistance       | 148.5           | 114.9       | 200.6         | 193.7          | 197.9           | 96.9          | °C/W |
| R <sub>θJC(top)</sub>         | Junction-to-case (top) thermal resistance    | 90.2            | 93.8        | 89.6          | 82.9           | 119.2           | 119.0         | °C/W |
| R <sub>θJB</sub>              | Junction-to-board thermal resistance         | 91.8            | 77.7        | 131.3         | 115.5          | 115.4           | 63.1          | °C/W |
| ψ <sub>JT</sub>               | Junction-to-top characterization parameter   | 38.5            | 60.4        | 22.1          | 20.8           | 19.4            | 12.4          | °C/W |
| ψ <sub>JB</sub>               | Junction-to-board characterization parameter | 91.1            | 76.7        | 129.6         | 113.9          | 113.7           | 63.0          | °C/W |
| R <sub>θJC(bot)</sub>         | Junction-to-case (bottom) thermal resistance | -               | -           | -             | -              | -               | 37.8          | °C/W |

(1) For more information about traditional and new thermal metrics, see the [Semiconductor and IC Package Thermal Metrics](#) report.

### 5.4 ESD Ratings

|                    |                         |                                                                                | VALUE | UNIT |
|--------------------|-------------------------|--------------------------------------------------------------------------------|-------|------|
| V <sub>(ESD)</sub> | Electrostatic discharge | Human body model (HBM), per ANSI/ESDA/JEDEC JS-001 <sup>(1)</sup>              | ±2000 | V    |
|                    |                         | Charged-device model (CDM), per JEDEC specification JESD22-C101 <sup>(2)</sup> | ±1000 |      |

(1) JEDEC document JEP155 states that 500V HBM allows safe manufacturing with a standard ESD control process.

(2) JEDEC document JEP157 states that 250V CDM allows safe manufacturing with a standard ESD control process.

## 5.5 Electrical Characteristics LM393B

$V_S = 5V$ ,  $V_{CM} = (V-)$ ;  $T_A = 25^\circ C$  (unless otherwise noted).

| PARAMETER    |                                                                                                                            | TEST CONDITIONS                                                   | MIN  | TYP        | MAX        | UNIT    |
|--------------|----------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------|------|------------|------------|---------|
| $V_{IO}$     | Input offset voltage                                                                                                       | $V_S = 5$ to $36V$                                                | -2.5 | $\pm 0.37$ | 2.5        | mV      |
|              |                                                                                                                            | $V_S = 5$ to $36V$ , $T_A = -40^\circ C$ to $+85^\circ C$         | -4   |            | 4          |         |
|              | Input offset voltage, DGK package only                                                                                     | $V_S = 5$ to $36V$                                                | -3.5 | $\pm 0.37$ | 3.5        |         |
|              |                                                                                                                            | $V_S = 5$ to $36V$ , $T_A = -40^\circ C$ to $+85^\circ C$         | -5   |            | 5          |         |
| $I_B$        | Input bias current                                                                                                         |                                                                   |      | -3.5       | -25        | nA      |
|              |                                                                                                                            | $T_A = -40^\circ C$ to $+85^\circ C$                              |      |            | -50        | nA      |
| $I_{OS}$     | Input offset current                                                                                                       |                                                                   | -10  | $\pm 0.5$  | 10         | nA      |
|              |                                                                                                                            | $T_A = -40^\circ C$ to $+85^\circ C$                              | -25  |            | 25         | nA      |
| $V_{CM}$     | Common mode range <sup>(1)</sup>                                                                                           | $V_S = 3$ to $36V$                                                | (V-) |            | (V+) - 1.5 | V       |
|              |                                                                                                                            | $V_S = 3$ to $36V$ , $T_A = -40^\circ C$ to $+85^\circ C$         | (V-) |            | (V+) - 2.0 | V       |
| $A_{VD}$     | Large signal differential voltage amplification                                                                            | $V_S = 15V$ , $V_O = 1.4V$ to $11.4V$ ;<br>$R_L \geq 15k$ to (V+) | 50   | 200        |            | V/mV    |
| $V_{OL}$     | Low level output Voltage {swing from (V-)}<br>$I_{SINK} \leq 4mA$ , $V_{ID} = -1V$<br>$T_A = -40^\circ C$ to $+85^\circ C$ |                                                                   |      | 110        | 400        | mV      |
|              |                                                                                                                            |                                                                   |      |            | 550        | mV      |
| $I_{OH-LKG}$ | High-level output leakage current                                                                                          | (V+) = $V_O = 5V$ ; $V_{ID} = 1V$                                 |      | 0.1        | 20         | nA      |
|              |                                                                                                                            | (V+) = $V_O = 36V$ ; $V_{ID} = 1V$                                |      | 0.3        | 50         | nA      |
| $I_{OL}$     | Low level output current                                                                                                   | $V_{OL} = 1.5V$ ; $V_{ID} = -1V$ ; $V_S = 5V$                     | 6    | 21         |            | mA      |
| $I_Q$        | Quiescent current (all comparators)                                                                                        | $V_S = 5V$ , no load                                              |      | 400        | 600        | $\mu A$ |
|              |                                                                                                                            | $V_S = 36V$ , no load, $T_A = -40^\circ C$ to $+85^\circ C$       |      | 550        | 800        | $\mu A$ |

- (1) The voltage at either input can not be allowed to go negative by more than 0.3V otherwise output can be incorrect and excessive input current can flow. The upper end of the common-mode voltage range is limited by  $V_{CC} - 2V$ . However only one input needs to be in the valid common mode range, the other input can go up the maximum  $V_{CC}$  level and the comparator provides a proper output state. Either or both inputs can go to maximum  $V_{CC}$  level without damage.

## 5.6 Electrical Characteristics LM2903B

 $V_S = 5V$ ,  $V_{CM} = (V-)$ ;  $T_A = 25^\circ C$  (unless otherwise noted).

| PARAMETER    |                                                                                    | TEST CONDITIONS                                                   | MIN  | TYP        | MAX        | UNIT    |
|--------------|------------------------------------------------------------------------------------|-------------------------------------------------------------------|------|------------|------------|---------|
| $V_{IO}$     | Input offset voltage                                                               | $V_S = 5$ to $36V$                                                | -2.5 | $\pm 0.37$ | 2.5        | mV      |
|              |                                                                                    | $V_S = 5$ to $36V$ , $T_A = -40^\circ C$ to $+125^\circ C$        | -4   |            | 4          |         |
|              | Input offset voltage, DGK package only                                             | $V_S = 5$ to $36V$                                                | -3.5 | $\pm 0.37$ | 3.5        |         |
|              |                                                                                    | $V_S = 5$ to $36V$ , $T_A = -40^\circ C$ to $+125^\circ C$        | -5   |            | 5          |         |
| $I_B$        | Input bias current                                                                 |                                                                   |      | -3.5       | -25        | nA      |
|              |                                                                                    | $T_A = -40^\circ C$ to $+125^\circ C$                             |      |            | -50        | nA      |
| $I_{OS}$     | Input offset current                                                               |                                                                   | -10  | $\pm 0.5$  | 10         | nA      |
|              |                                                                                    | $T_A = -40^\circ C$ to $+125^\circ C$                             | -25  |            | 25         | nA      |
| $V_{CM}$     | Common mode range <sup>(1)</sup>                                                   | $V_S = 3$ to $36V$                                                | (V-) |            | (V+) - 1.5 | V       |
|              |                                                                                    | $V_S = 3$ to $36V$ , $T_A = -40^\circ C$ to $+125^\circ C$        | (V-) |            | (V+) - 2.0 | V       |
| $A_{VD}$     | Large signal differential voltage amplification                                    | $V_S = 15V$ , $V_O = 1.4V$ to $11.4V$ ;<br>$R_L \geq 15k$ to (V+) | 50   | 200        |            | V/mV    |
| $V_{OL}$     | Low level output Voltage {swing from (V-)}<br>$I_{SINK} \leq 4mA$ , $V_{ID} = -1V$ | $T_A = -40^\circ C$ to $+125^\circ C$                             |      | 110        | 400        | mV      |
|              |                                                                                    |                                                                   |      |            | 550        | mV      |
| $I_{OH-LKG}$ | High-level output leakage current                                                  | (V+) = $V_O = 5V$ ; $V_{ID} = 1V$                                 |      | 0.1        | 20         | nA      |
|              |                                                                                    | (V+) = $V_O = 36V$ ; $V_{ID} = 1V$                                |      | 0.3        | 50         | nA      |
| $I_{OL}$     | Low level output current                                                           | $V_{OL} = 1.5V$ ; $V_{ID} = -1V$ ; $V_S = 5V$                     | 6    | 21         |            | mA      |
| $I_Q$        | Quiescent current (all comparators)                                                | $V_S = 5V$ , no load                                              |      | 400        | 600        | $\mu A$ |
|              |                                                                                    | $V_S = 36V$ , no load, $T_A = -40^\circ C$ to $+125^\circ C$      |      | 550        | 800        | $\mu A$ |

- (1) The voltage at either input can not be allowed to go negative by more than 0.3V otherwise output can be incorrect and excessive input current can flow. The upper end of the common-mode voltage range is limited by  $V_{CC} - 2V$ . However only one input needs to be in the valid common mode range, the other input can go up the maximum  $V_{CC}$  level and the comparator provides a proper output state. Either or both inputs can go to maximum  $V_{CC}$  level without damage.

## 5.7 Switching Characteristics LM393B and LM2903B

 $V_S = 5V$ ,  $V_{O\_PULLUP} = 5V$ ,  $V_{CM} = V_S/2$ ,  $C_L = 15pF$ ,  $R_L = 5.1k \text{ Ohm}$ ,  $T_A = 25^\circ C$  (unless otherwise noted).

| PARAMETER      |                                                                              | TEST CONDITIONS                           | MIN | TYP  | MAX | UNIT |
|----------------|------------------------------------------------------------------------------|-------------------------------------------|-----|------|-----|------|
| $t_{response}$ | Propagation delay time, high-to-low; TTL input signal <sup>(1)</sup>         | TTL input with $V_{ref} = 1.4V$           |     | 300  |     | ns   |
| $t_{response}$ | Propagation delay time, high-to-low; Small scale input signal <sup>(1)</sup> | Input overdrive = 5mV, Input step = 100mV |     | 1000 |     | ns   |

- (1) High-to-low and low-to-high refers to the transition at the input.

## 5.8 Electrical Characteristics for LM193, LM293, and LM393 (without A suffix)

at specified free-air temperature,  $V_{CC} = 5V$  (unless otherwise noted)

| PARAMETER                                                | TEST CONDITIONS                                                                   | $T_A$ <sup>(1)</sup>       | LM193 |                        |      | LM293<br>LM393 |                        |      | UNIT    |
|----------------------------------------------------------|-----------------------------------------------------------------------------------|----------------------------|-------|------------------------|------|----------------|------------------------|------|---------|
|                                                          |                                                                                   |                            | MIN   | TYP                    | MAX  | MIN            | TYP                    | MAX  |         |
| $V_{IO}$ Input offset voltage                            | $V_{CC} = 5V$ to $30V$ ,<br>$V_{IC} = V_{ICR}$ min,<br>$V_O = 1.4V$               | $25^\circ C$               |       | 2                      | 5    |                | 2                      | 5    | mV      |
|                                                          |                                                                                   | Full range                 |       |                        | 9    |                |                        | 9    |         |
| $I_{IO}$ Input offset current                            | $V_O = 1.4V$                                                                      | $25^\circ C$               |       | 3                      | 25   |                | 5                      | 50   | nA      |
|                                                          |                                                                                   | Full range                 |       |                        | 100  |                |                        | 250  |         |
| $I_{IB}$ Input bias current                              | $V_O = 1.4V$                                                                      | $25^\circ C$               |       | –25                    | –100 |                | –25                    | –250 | nA      |
|                                                          |                                                                                   | Full range                 |       |                        | –300 |                |                        | –400 |         |
| $V_{ICR}$ Common-mode input-voltage range <sup>(2)</sup> |                                                                                   | $25^\circ C$               |       | 0 to<br>$V_{CC} - 1.5$ |      |                | 0 to<br>$V_{CC} - 1.5$ |      | V       |
|                                                          |                                                                                   | Full range                 |       | 0 to<br>$V_{CC} - 2$   |      |                | 0 to<br>$V_{CC} - 2$   |      |         |
| $A_{VD}$ Large-signal differential-voltage amplification | $V_{CC} = 15V$ ,<br>$V_O = 1.4V$ to $11.4V$ ,<br>$R_L \geq 15k\Omega$ to $V_{CC}$ | $25^\circ C$               |       | 50                     | 200  |                | 50                     | 200  | V/mV    |
| $I_{OH}$ High-level output current                       | $V_{OH} = 5V$ $V_{ID} = 1V$                                                       | $25^\circ C$               |       |                        | 0.1  |                | 0.1                    | 50   | nA      |
|                                                          | $V_{OH} = 30V$ $V_{ID} = 1V$                                                      | Full range                 |       |                        | 1    |                |                        | 1    | $\mu A$ |
| $V_{OL}$ Low-level output voltage                        | $I_{OL} = 4mA$ , $V_{ID} = -1V$                                                   | $25^\circ C$               |       | 150                    | 400  |                | 130                    | 400  | mV      |
|                                                          |                                                                                   | Full range                 |       |                        | 700  |                |                        | 700  |         |
| $I_{OL}$ Low-level output current                        | $V_{OL} = 1.5V$ , $V_{ID} = -1V$                                                  | $25^\circ C$               |       | 6                      |      |                | 6                      |      | mA      |
| $I_{CC}$ Supply current                                  | $R_L = \infty$                                                                    | $V_{CC} = 5V$ $25^\circ C$ |       | 0.8                    | 1    |                | 0.45                   | 1    | mA      |
|                                                          |                                                                                   | $V_{CC} = 30V$ Full range  |       |                        | 2.5  |                | 0.55                   | 2.5  |         |

- (1) Full range (minimum or maximum) for LM193 is  $-55^\circ C$  to  $125^\circ C$ , for LM293 is  $-25^\circ C$  to  $85^\circ C$ , and for LM393 is  $0^\circ C$  to  $70^\circ C$ . All characteristics are measured with zero common-mode input voltage, unless otherwise specified.
- (2) The voltage at either input can not be allowed to go negative by more than  $0.3V$  otherwise output can be incorrect and excessive input current can flow. The upper end of the common-mode voltage range is limited by  $V_{CC} - 2V$ . However only one input needs to be in the valid common mode range, and the other input can go up the maximum  $V_{CC}$  level and the comparator provides a proper output state. Either or both inputs can go to maximum  $V_{CC}$  level without damage.

## 5.9 Electrical Characteristics for LM293A and LM393A

at specified free-air temperature,  $V_{CC} = 5V$  (unless otherwise noted)

| PARAMETER                                                | TEST CONDITIONS                                                                | $T_A$ <sup>(1)</sup> | LM293A<br>LM393A |                        |      | UNIT    |
|----------------------------------------------------------|--------------------------------------------------------------------------------|----------------------|------------------|------------------------|------|---------|
|                                                          |                                                                                |                      | MIN              | TYP                    | MAX  |         |
| $V_{IO}$ Input offset voltage                            | $V_{CC} = 5V$ to $30V$ , $V_O = 1.4V$<br>$V_{IC} = V_{ICR(min)}$               | $25^\circ C$         |                  | 1                      | 2    | mV      |
|                                                          |                                                                                | Full range           |                  |                        | 4    |         |
| $I_{IO}$ Input offset current                            | $V_O = 1.4V$                                                                   | $25^\circ C$         |                  | 5                      | 50   | nA      |
|                                                          |                                                                                | Full range           |                  |                        | 150  |         |
| $I_{IB}$ Input bias current                              | $V_O = 1.4V$                                                                   | $25^\circ C$         |                  | –25                    | –250 | nA      |
|                                                          |                                                                                | Full range           |                  |                        | –400 |         |
| $V_{ICR}$ Common-mode input-voltage range <sup>(2)</sup> |                                                                                | $25^\circ C$         |                  | 0 to<br>$V_{CC} - 1.5$ |      | V       |
|                                                          |                                                                                | Full range           |                  | 0 to<br>$V_{CC} - 2$   |      |         |
| $A_{VD}$ Large-signal differential-voltage amplification | $V_{CC} = 15V$ , $V_O = 1.4V$ to $11.4V$ ,<br>$R_L \geq 15k\Omega$ to $V_{CC}$ | $25^\circ C$         |                  | 50                     | 200  | V/mV    |
| $I_{OH}$ High-level output current                       | $V_{OH} = 5V$ , $V_{ID} = 1V$                                                  | $25^\circ C$         |                  | 0.1                    | 50   | nA      |
|                                                          | $V_{OH} = 30V$ , $V_{ID} = 1V$                                                 | Full range           |                  |                        | 1    | $\mu A$ |
| $V_{OL}$ Low-level output voltage                        | $I_{OL} = 4mA$ , $V_{ID} = -1V$                                                | $25^\circ C$         |                  | 110                    | 400  | mV      |
|                                                          |                                                                                | Full range           |                  |                        | 700  |         |
| $I_{OL}$ Low-level output current                        | $V_{OL} = 1.5V$ , $V_{ID} = -1V$                                               | $25^\circ C$         |                  | 6                      |      | mA      |
| $I_{CC}$ Supply current                                  | $R_L = \infty$                                                                 | $V_{CC} = 5V$        |                  | 0.60                   | 1    | mA      |
|                                                          |                                                                                | $V_{CC} = 30V$       |                  | 0.72                   | 2.5  |         |

- (1) Full range (minimum or maximum) for LM293A is  $-25^\circ C$  to  $85^\circ C$ , and for LM393A is  $0^\circ C$  to  $70^\circ C$ . All characteristics are measured with zero common-mode input voltage, unless otherwise specified.
- (2) The voltage at either input can not be allowed to go negative by more than  $0.3V$  otherwise output can be incorrect and excessive input current can flow. The upper end of the common-mode voltage range is limited by  $V_{CC} - 2V$ . However only one input needs to be in the valid common mode range, and the other input can go up the maximum  $V_{CC}$  level and the comparator provides a proper output state. Either or both inputs can go to maximum  $V_{CC}$  level without damage.

## 5.10 Electrical Characteristics for LM2903, LM2903V, and LM2903AV

at specified free-air temperature,  $V_{CC} = 5V$  (unless otherwise noted)

| PARAMETER        |                                                 | TEST CONDITIONS                                                                                                     | T <sub>A</sub> <sup>(1)</sup> | LM2903, LM2903V               |     |      | LM2903AV                      |     |      | UNIT |
|------------------|-------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|-------------------------------|-------------------------------|-----|------|-------------------------------|-----|------|------|
|                  |                                                 |                                                                                                                     |                               | MIN                           | TYP | MAX  | MIN                           | TYP | MAX  |      |
| V <sub>IO</sub>  | Input offset voltage                            | V <sub>CC</sub> = 5V to MAX <sup>(2)</sup> ,<br>V <sub>O</sub> = 1.4V,<br>V <sub>IC</sub> = V <sub>ICR(min)</sub> , | 25°C                          |                               | 2   | 7    |                               | 1   | 2    | mV   |
|                  |                                                 |                                                                                                                     | Full range                    |                               |     | 15   |                               |     | 4    |      |
| I <sub>IO</sub>  | Input offset current                            | V <sub>O</sub> = 1.4V                                                                                               | 25°C                          |                               | 5   | 50   |                               | 5   | 50   | nA   |
|                  |                                                 |                                                                                                                     | Full range                    |                               |     | 200  |                               |     | 200  |      |
| I <sub>IB</sub>  | Input bias current                              | V <sub>O</sub> = 1.4V                                                                                               | 25°C                          |                               | –25 | –250 |                               | –25 | –250 | nA   |
|                  |                                                 |                                                                                                                     | Full range                    |                               |     | –500 |                               |     | –500 |      |
| V <sub>ICR</sub> | Common-mode input-voltage range <sup>(3)</sup>  |                                                                                                                     | 25°C                          | 0 to<br>V <sub>CC</sub> – 1.5 |     |      | 0 to<br>V <sub>CC</sub> – 1.5 |     |      | V    |
|                  |                                                 |                                                                                                                     | Full range                    | 0 to<br>V <sub>CC</sub> – 2   |     |      | 0 to<br>V <sub>CC</sub> – 2   |     |      |      |
| A <sub>VD</sub>  | Large-signal differential-voltage amplification | V <sub>CC</sub> = 15V, V <sub>O</sub> = 1.4V to 11.4V,<br>R <sub>L</sub> ≥ 15kΩ to V <sub>CC</sub>                  | 25°C                          | 25                            | 100 |      | 25                            | 100 | V/mV |      |
| I <sub>OH</sub>  | High-level output current                       | V <sub>OH</sub> = 5V,                      V <sub>ID</sub> = 1V                                                     | 25°C                          |                               | 0.1 | 50   |                               | 0.1 | 50   | nA   |
|                  |                                                 | V <sub>OH</sub> = V <sub>CC</sub> MAX <sup>(2)</sup> ,        V <sub>ID</sub> = 1V                                  | Full range                    |                               |     | 1    |                               |     | 1    | μA   |
| V <sub>OL</sub>  | Low-level output voltage                        | I <sub>OL</sub> = 4mA,                      V <sub>ID</sub> = –1V,                                                  | 25°C                          |                               | 150 | 400  |                               | 150 | 400  | mV   |
|                  |                                                 |                                                                                                                     | Full range                    |                               |     | 700  |                               |     | 700  |      |
| I <sub>OL</sub>  | Low-level output current                        | V <sub>OL</sub> = 1.5V,                      V <sub>ID</sub> = –1V                                                  | 25°C                          | 6                             |     |      | 6                             |     | mA   |      |
| I <sub>CC</sub>  | Supply current                                  | R <sub>L</sub> = ∞                                                                                                  | V <sub>CC</sub> = 5V          | 25°C                          | 0.8 | 1    | 0.8                           | 1   | mA   |      |
|                  |                                                 |                                                                                                                     | V <sub>CC</sub> = MAX         | Full range                    |     | 2.5  |                               | 2.5 |      |      |

- (1) Full range (minimum or maximum) for LM2903 is  $-40^\circ\text{C}$  to  $125^\circ\text{C}$ . All characteristics are measured with zero common-mode input voltage, unless otherwise specified.
- (2)  $V_{CC} \text{ MAX} = 30V$  for non-V devices and  $32V$  for V-suffix devices.
- (3) The voltage at either input can not be allowed to go negative by more than  $0.3V$  otherwise output can be incorrect and excessive input current can flow. The upper end of the common-mode voltage range is limited by  $V_{CC} - 2V$ . However only one input needs to be in the valid common mode range, the other input can go up the maximum  $V_{CC}$  level and the comparator provides a proper output state. Either or both inputs can go to maximum  $V_{CC}$  level without damage.

## 5.11 Switching Characteristics: LM193, LM239, LM393, LM2903, all 'A' and 'V' versions

$V_{CC} = 5V$ ,  $T_A = 25^\circ\text{C}$

| PARAMETER     | TEST CONDITIONS                                                                              |                                     | TYP | UNIT    |
|---------------|----------------------------------------------------------------------------------------------|-------------------------------------|-----|---------|
| Response time | $R_L$ connected to $5V$ through $5.1k\Omega$ ,<br>$C_L = 15pF$ <sup>(1)</sup> <sup>(2)</sup> | 100mV input step with 5mV overdrive | 1.3 | $\mu s$ |
|               |                                                                                              | TTL-level input step                | 0.3 |         |

- (1)  $C_L$  includes probe and jig capacitance.
- (2) The response time specified is the interval between the input step function and the instant when the output crosses  $1.4V$ .

## 5.12 Typical Characteristics, LMx93x and LM2903x

$T_A = 25^\circ\text{C}$ ,  $V_S = 5\text{V}$ ,  $R_{\text{PULLUP}} = 5.1\text{k}$ ,  $C_L = 15\text{pF}$ ,  $V_{\text{CM}} = 0\text{V}$ ,  $V_{\text{UNDERDRIVE}} = 100\text{mV}$ ,  $V_{\text{OVERDRIVE}} = 100\text{mV}$  unless otherwise noted.




Figure 5-1. Total Supply Current vs. Supply Voltage




Figure 5-2. Total Supply Current vs. Input Voltage at 3V




Figure 5-3. Total Supply Current vs. Input Voltage at 3.3V




Figure 5-4. Total Supply Current vs. Input Voltage at 5V




Figure 5-5. Total Supply Current vs. Input Voltage at 12V




Figure 5-6. Total Supply Current vs. Input Voltage at 36V

## 5.12 Typical Characteristics, LMx93x and LM2903x (continued)

$T_A = 25^\circ\text{C}$ ,  $V_S = 5\text{V}$ ,  $R_{\text{PULLUP}} = 5.1\text{k}$ ,  $C_L = 15\text{pF}$ ,  $V_{\text{CM}} = 0\text{V}$ ,  $V_{\text{UNDERDRIVE}} = 100\text{mV}$ ,  $V_{\text{OVERDRIVE}} = 100\text{mV}$  unless otherwise noted.




Figure 5-7. Input Offset Voltage vs. Temperature at 3V




Figure 5-8. Input Offset Voltage vs. Temperature at 5V




Figure 5-9. Input Offset Voltage vs. Temperature at 12V




Figure 5-10. Input Offset Voltage vs. Temperature at 36V




Figure 5-11. Input Offset Voltage vs. Supply Voltage at  $-40^\circ\text{C}$




Figure 5-12. Input Offset Voltage vs. Supply Voltage at  $25^\circ\text{C}$

## 5.12 Typical Characteristics, LMx93x and LM2903x (continued)

$T_A = 25^\circ\text{C}$ ,  $V_S = 5\text{V}$ ,  $R_{\text{PULLUP}} = 5.1\text{k}$ ,  $C_L = 15\text{pF}$ ,  $V_{\text{CM}} = 0\text{V}$ ,  $V_{\text{UNDERDRIVE}} = 100\text{mV}$ ,  $V_{\text{OVERDRIVE}} = 100\text{mV}$  unless otherwise noted.




Figure 5-13. Input Offset Voltage vs. Supply Voltage at 85°C




Figure 5-14. Input Offset Voltage vs. Supply Voltage at 125°C




Figure 5-15. Input Bias Current vs. Supply Voltage




Figure 5-16. Input Bias Current vs. Input Voltage at 5V




Figure 5-17. Input Bias Current vs. Input Voltage at 12V




Figure 5-18. Input Bias Current vs. Input Voltage at 36V

## 5.12 Typical Characteristics, LMx93x and LM2903x (continued)

$T_A = 25^\circ\text{C}$ ,  $V_S = 5\text{V}$ ,  $R_{\text{PULLUP}} = 5.1\text{k}$ ,  $C_L = 15\text{pF}$ ,  $V_{\text{CM}} = 0\text{V}$ ,  $V_{\text{UNDERDRIVE}} = 100\text{mV}$ ,  $V_{\text{OVERDRIVE}} = 100\text{mV}$  unless otherwise noted.




Figure 5-19. Output Low Voltage vs. Output Sinking Current at 3V




Figure 5-20. Output Low Voltage vs. Output Sinking Current at 5V




Figure 5-21. Output Low Voltage vs. Output Sinking Current at 12V




Figure 5-22. Output Low Voltage vs. Output Sinking Current at 36V




Figure 5-23. Output High Leakage Current vs. Temperature at 5V




Figure 5-24. Output High Leakage Current vs. Temperature at 36V

## 5.12 Typical Characteristics, LMx93x and LM2903x (continued)

$T_A = 25^\circ\text{C}$ ,  $V_S = 5\text{V}$ ,  $R_{\text{PULLUP}} = 5.1\text{k}$ ,  $C_L = 15\text{pF}$ ,  $V_{\text{CM}} = 0\text{V}$ ,  $V_{\text{UNDERDRIVE}} = 100\text{mV}$ ,  $V_{\text{OVERDRIVE}} = 100\text{mV}$  unless otherwise noted.




Figure 5-25. High to Low Propagation Delay vs. Input Overdrive Voltage, 5V




Figure 5-26. Low to High Propagation Delay vs. Input Overdrive Voltage, 5V




Figure 5-27. High to Low Propagation Delay vs. Input Overdrive Voltage, 12V




Figure 5-28. Low to High Propagation Delay vs. Input Overdrive Voltage, 12V




Figure 5-29. High to Low Propagation Delay vs. Input Overdrive Voltage, 36V






Figure 5-30. Low to High Propagation Delay vs. Input Overdrive Voltage, 36V

## 5.12 Typical Characteristics, LMx93x and LM2903x (continued)

$T_A = 25^\circ\text{C}$ ,  $V_S = 5\text{V}$ ,  $R_{\text{PULLUP}} = 5.1\text{k}$ ,  $C_L = 15\text{pF}$ ,  $V_{\text{CM}} = 0\text{V}$ ,  $V_{\text{UNDERDRIVE}} = 100\text{mV}$ ,  $V_{\text{OVERDRIVE}} = 100\text{mV}$  unless otherwise noted.



**Figure 5-31. Response Time for Various Overdrives, High-to-Low Transition**



**Figure 5-32. Response Time for Various Overdrives, Low-to-High Transition**


## 6 Detailed Description

### 6.1 Overview

These dual comparators have the ability to operate up to absolute maximum of 36V (38V for the "B" version) on the supply pin. This device has proven ubiquity and versatility across a wide range of applications. This is due to very wide supply voltages range, low  $I_q$  and fast response of the devices.

The open-collector outputs allow the user to level shift to the desired logic level independent of  $V_{CC}$ , while also enabling AND functionality when multiple outputs are connected together.

### 6.2 Functional Block Diagram



**Figure 6-1. Schematic (Each Comparator)**

### 6.3 Feature Description

The comparator consists of a PNP Darlington pair input, allowing the device to operate with very high gain and fast response with minimal input bias current. The input Darlington pair creates a limit on the input common mode voltage capability, allowing the comparator to accurately function from ground to  $V_{CC} - 2V$  over temperature. A clamp is added around Q3 to mimic the both inputs above input voltage range behavior of the original classic silicon.

The output consists of an open drain NPN (pull-down or low side) transistor. The output NPN sinks current when the negative input voltage is higher than the positive input voltage and the offset voltage. The  $V_{OL}$  is resistive and scales with the output current. Please see the "Output Low Voltage vs. Output Sinking Current" graphs for  $V_{OL}$  values with respect to the output current.

### 6.4 Device Functional Modes

#### 6.4.1 Voltage Comparison

The device operates solely as a voltage comparator, comparing the differential voltage between the positive and negative pins and outputting a logic low or high impedance (logic high with pullup) based on the input differential polarity.

## 7 Application and Implementation

### Note

Information in the following applications sections is not part of the TI component specification, and TI does not warrant its accuracy or completeness. TI's customers are responsible for determining suitability of components for their purposes, as well as validating and testing their design implementation to confirm system functionality.

### 7.1 Application Information

The device is typically used to compare a single signal to a reference or two signals against each other. Many users take advantage of the open drain output to drive the comparison logic output to a logic voltage level to an MCU or logic device. The wide supply range and high voltage capability makes this comparator an excellent choice for level shifting to a higher or lower voltage.

### 7.2 Typical Application




Figure 7-1. Single-Ended and Differential Comparator Configurations

#### 7.2.1 Design Requirements

For this design example, use the parameters listed in Table 7-1 as the input parameters.

Table 7-1. Design Parameters

| DESIGN PARAMETER         | EXAMPLE VALUE       |
|--------------------------|---------------------|
| Input Voltage Range      | 0V to Vsup-2V       |
| Supply Voltage           | 4.5V to VCC maximum |
| Logic Supply Voltage     | 0V to VCC maximum   |
| Output Current (Rpullup) | 1μA to 4mA          |
| Input Overdrive Voltage  | 100mV               |
| Reference Voltage        | 2.5V                |
| Load Capacitance (CL)    | 15pF                |

#### 7.2.2 Detailed Design Procedure

When using the device in a general comparator application, determine the following:

- Input Voltage Range
- Minimum Overdrive Voltage
- Output and Drive Current
- Response Time

##### 7.2.2.1 Input Voltage Range

When choosing the input voltage range, the input common mode voltage range ( $V_{ICR}$ ) must be taken in to account. If temperature operation is below 25°C the  $V_{ICR}$  can range from 0V to  $V_{CC}-2.0V$ . This limits the input

voltage range to as high as  $V_{CC} - 2.0V$  and as low as  $0V$ . Operation outside of this range can yield incorrect comparisons.

The following is a list of input voltage situation and the outcomes:

1. When both  $IN^-$  and  $IN^+$  are both within the common-mode range:
  - a. If  $IN^-$  is higher than  $IN^+$  and the offset voltage, the output is low and the output transistor is sinking current
  - b. If  $IN^-$  is lower than  $IN^+$  and the offset voltage, the output is high impedance and the output transistor is not conducting
2. When  $IN^-$  is higher than common-mode and  $IN^+$  is within common-mode, the output is low and the output transistor is sinking current
3. When  $IN^+$  is higher than common-mode and  $IN^-$  is within common-mode, the output is high impedance and the output transistor is not conducting
4. When  $IN^-$  and  $IN^+$  are both higher than common-mode, see Section 2 of [Application Design Guidelines for LM339, LM393, TL331 Family Comparators Including the New B-versions](#).

#### 7.2.2.2 Minimum Overdrive Voltage

Overdrive Voltage is the differential voltage produced between the positive and negative inputs of the comparator over the offset voltage ( $V_{IO}$ ). To make an accurate comparison the Overdrive Voltage ( $V_{OD}$ ) must be higher than the input offset voltage ( $V_{IO}$ ). Overdrive voltage can also determine the response time of the comparator, with the response time decreasing with increasing overdrive. [Figure 7-2](#) and [Figure 7-3](#) show positive and negative response times with respect to overdrive voltage.

#### 7.2.2.3 Output and Drive Current

Output current is determined by the load/pull-up resistance and logic/pullup voltage. The output current produces a output low voltage ( $V_{OL}$ ) from the comparator. In which  $V_{OL}$  is proportional to the output current. See the *Output Low vs. Sinking Current* graphs in the [Typical Characteristics, LMx93x and LM2903x](#) section to determine  $V_{OL}$  based on the output current.

The output current can also effect the transient response. See [Section 7.2.2.4](#) for more information.


#### 7.2.2.4 Response Time

Response time is a function of input over drive. See [Application Curves](#) for typical response times. The rise and falls times can be determined by the load capacitance ( $C_L$ ), load/pullup resistance ( $R_{PULLUP}$ ) and equivalent collector-emitter resistance ( $R_{CE}$ ).


- The rise time ( $\tau_R$ ) is approximately  $\tau_R = R_{PULLUP} \times C_L$
- The fall time ( $\tau_F$ ) is approximately  $\tau_F = R_{CE} \times C_L$ 
  - $R_{CE}$  can be determine by taking the slope of [Figure 5-20](#) in the linear region at the desired temperature, or by dividing the  $V_{OL}$  by  $I_{out}$

### 7.2.3 Application Curves

The following curves are generated with 5V on  $V_{CC}$  and  $V_{Logic}$ ,  $R_{PULLUP} = 5.1k\Omega$ , and 50pF scope probe.



**Figure 7-2. Response Time for Various Overdrives (Positive Transition)**



**Figure 7-3. Response Time for Various Overdrives (Negative Transition)**

### 7.2.4 Power Supply Recommendations

For fast response and comparison applications with noisy or AC inputs, TI recommends to use a bypass capacitor on the supply pin to reject any variation on the supply voltage. This variation can eat into the input common-mode range of the comparator and create an inaccurate comparison.


### 7.2.5 Layout

#### 7.2.5.1 Layout Guidelines

For accurate comparator applications without hysteresis maintaining a stable power supply with minimized noise and glitches is critical. Best practice is to add a bypass capacitor between the supply voltage and ground. This can be implemented on the positive power supply and negative supply (if available). If a negative supply is not being used, do not put a capacitor between the IC's GND pin and system ground.

Minimize coupling between outputs and inverting inputs to prevent output oscillations. Do not run output and inverting input traces in parallel unless there is a  $V_{CC}$  or GND trace between output and inverting input traces to reduce coupling. When series resistance is added to inputs, place resistor close to the device.

#### 7.2.5.2 Layout Example



**Figure 7-4. LM2903 Layout Example**

## 8 Device and Documentation Support

### 8.1 Receiving Notification of Documentation Updates

To receive notification of documentation updates, navigate to the device product folder on [ti.com](https://www.ti.com). Click on *Notifications* to register and receive a weekly digest of any product information that has changed. For change details, review the revision history included in any revised document.

### 8.2 Support Resources

[TI E2E™ support forums](#) are an engineer's go-to source for fast, verified answers and design help — straight from the experts. Search existing answers or ask your own question to get the quick design help you need.

Linked content is provided "AS IS" by the respective contributors. They do not constitute TI specifications and do not necessarily reflect TI's views; see TI's [Terms of Use](#).

### 8.3 Trademarks

TI E2E™ is a trademark of Texas Instruments.

All trademarks are the property of their respective owners.

### 8.4 Electrostatic Discharge Caution



This integrated circuit can be damaged by ESD. Texas Instruments recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage.

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.

### 8.5 Glossary

[TI Glossary](#) This glossary lists and explains terms, acronyms, and definitions.

## 9 Revision History

NOTE: Page numbers for previous revisions may differ from page numbers in the current version.

| Changes from Revision AG (January 2025) to Revision AH (April 2025)            | Page |
|--------------------------------------------------------------------------------|------|
| • Updated front page <i>Family Comparison Table</i> ESD specs.....             | 1    |
| • Restored missing "P" package column in <i>Thermal Information</i> table..... | 5    |

| Changes from Revision AF (August 2023) to Revision AG (January 2025) | Page |
|----------------------------------------------------------------------|------|
| • Removed legacy device graphs.....                                  | 11   |
| • Updated internal <i>Schematic</i> .....                            | 17   |

| Changes from Revision AE (November 2020) to Revision AF (August 2023) | Page |
|-----------------------------------------------------------------------|------|
| • Added reference to Application Note.....                            | 18   |

| Changes from Revision AD (October 2020) to Revision AE (November 2020)                | Page |
|---------------------------------------------------------------------------------------|------|
| • Corrected Family Comparison Table Offset Voltage units to mV.....                   | 1    |
| • LM393B and LM2903B recommended minimum supply voltage changed to 2V throughout..... | 1    |
| • Added separate offset voltage row for LM393B and LM2903B DGK package.....           | 1    |
| • Changed "B" devices recommended minimum supply voltage to 2V.....                   | 4    |

- 
- Updated "B" device Supply Current vs Supply Voltage Graph for 2V..... 11
- 

#### Changes from Revision AC (February 2020) to Revision AD (October 2020) Page

- Updated the numbering format for tables, figures and cross-references throughout the document..... 1
- 

#### Changes from Revision AB (December 2019) to Revision AC (February 2020) Page

- Changed front page Features, Applications and Description text to highlight B version..... 1
  - Added WSON and SOT-23-8 packages..... 1
  - Added Links to Family Table ..... 1
  - Added DDF and DSG pkgs to Thermal Table..... 5
- 

#### Changes from Revision AA (September 2019) to Revision AB (December 2019) Page

- Changed LM393B and LM2903B from Preview to Active status..... 1
  - Added Family Comparison Table..... 1
- 

#### Changes from Revision Z (October 2017) to Revision AA (September 2019) Page

- Added "B" devices with various text changes throughout data sheet..... 1
  - Deleted from Device Information old LM193 CDIP and LCCC package references and drawings. These are on the LM139-MIL data sheet..... 1
  - Added "B" devices Thermal Information table..... 5
  - Added "B" device electrical tables..... 5
  - Added "B" device graphs ..... 11
- 

## 10 Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser based versions of this data sheet, refer to the left hand navigation.

## PACKAGING INFORMATION

| Orderable part number          | Status<br>(1) | Material type<br>(2) | Package   Pins        | Package qty   Carrier | RoHS<br>(3) | Lead finish/<br>Ball material<br>(4) | MSL rating/<br>Peak reflow<br>(5) | Op temp (°C) | Part marking<br>(6) |
|--------------------------------|---------------|----------------------|-----------------------|-----------------------|-------------|--------------------------------------|-----------------------------------|--------------|---------------------|
| <a href="#">LM193DR</a>        | Active        | Production           | SOIC (D)   8          | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -55 to 125   | LM193               |
| LM193DR.A                      | Active        | Production           | SOIC (D)   8          | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -55 to 125   | LM193               |
| <a href="#">LM193DRG4</a>      | Active        | Production           | SOIC (D)   8          | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -55 to 125   | LM193               |
| LM193DRG4.A                    | Active        | Production           | SOIC (D)   8          | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -55 to 125   | LM193               |
| <a href="#">LM2903AVQDR</a>    | Active        | Production           | SOIC (D)   8          | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | L2903AV             |
| LM2903AVQDR.A                  | Active        | Production           | SOIC (D)   8          | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | L2903AV             |
| <a href="#">LM2903AVQDRG4</a>  | Active        | Production           | SOIC (D)   8          | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | L2903AV             |
| LM2903AVQDRG4.A                | Active        | Production           | SOIC (D)   8          | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | L2903AV             |
| <a href="#">LM2903AVQPWR</a>   | Active        | Production           | TSSOP (PW)   8        | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | (2903AV, L2903AV)   |
| LM2903AVQPWR.A                 | Active        | Production           | TSSOP (PW)   8        | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | (2903AV, L2903AV)   |
| LM2903AVQPWR.B                 | Active        | Production           | TSSOP (PW)   8        | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | (2903AV, L2903AV)   |
| <a href="#">LM2903AVQPWRG4</a> | Active        | Production           | TSSOP (PW)   8        | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | (2903AV, L2903AV)   |
| LM2903AVQPWRG4.A               | Active        | Production           | TSSOP (PW)   8        | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | (2903AV, L2903AV)   |
| LM2903AVQPWRG4.B               | Active        | Production           | TSSOP (PW)   8        | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | (2903AV, L2903AV)   |
| <a href="#">LM2903BIDDFR</a>   | Active        | Production           | SOT-23-THIN (DDF)   8 | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 2903B               |
| LM2903BIDDFR.B                 | Active        | Production           | SOT-23-THIN (DDF)   8 | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 2903B               |
| LM2903BIDDFRG4                 | Active        | Production           | SOT-23-THIN (DDF)   8 | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 2903B               |
| LM2903BIDDFRG4.B               | Active        | Production           | SOT-23-THIN (DDF)   8 | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 2903B               |
| <a href="#">LM2903BIDGKR</a>   | Active        | Production           | VSSOP (DGK)   8       | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 903B                |
| LM2903BIDGKR.A                 | Active        | Production           | VSSOP (DGK)   8       | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 903B                |
| LM2903BIDGKR.B                 | Active        | Production           | VSSOP (DGK)   8       | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 903B                |
| LM2903BIDGKRG4                 | Active        | Production           | VSSOP (DGK)   8       | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 903B                |
| LM2903BIDGKRG4.A               | Active        | Production           | VSSOP (DGK)   8       | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 903B                |
| LM2903BIDGKRG4.B               | Active        | Production           | VSSOP (DGK)   8       | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 903B                |
| <a href="#">LM2903BIDR</a>     | Active        | Production           | SOIC (D)   8          | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | L2903B              |
| LM2903BIDR.A                   | Active        | Production           | SOIC (D)   8          | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | L2903B              |
| LM2903BIDR.B                   | Active        | Production           | SOIC (D)   8          | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | L2903B              |
| LM2903BIDRG4                   | Active        | Production           | SOIC (D)   8          | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | L2903B              |
| LM2903BIDRG4.A                 | Active        | Production           | SOIC (D)   8          | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | L2903B              |

| Orderable part number        | Status<br>(1) | Material type<br>(2) | Package   Pins  | Package qty   Carrier | RoHS<br>(3) | Lead finish/<br>Ball material<br>(4) | MSL rating/<br>Peak reflow<br>(5) | Op temp (°C) | Part marking<br>(6) |
|------------------------------|---------------|----------------------|-----------------|-----------------------|-------------|--------------------------------------|-----------------------------------|--------------|---------------------|
| LM2903BIDRG4.B               | Active        | Production           | SOIC (D)   8    | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | L2903B              |
| <a href="#">LM2903BIDSGR</a> | Active        | Production           | WSON (DSG)   8  | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 903B                |
| LM2903BIDSGR.A               | Active        | Production           | WSON (DSG)   8  | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 903B                |
| LM2903BIDSGR.B               | Active        | Production           | WSON (DSG)   8  | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 903B                |
| LM2903BIDSGRG4               | Active        | Production           | WSON (DSG)   8  | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 903B                |
| LM2903BIDSGRG4.A             | Active        | Production           | WSON (DSG)   8  | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 903B                |
| LM2903BIDSGRG4.B             | Active        | Production           | WSON (DSG)   8  | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 903B                |
| <a href="#">LM2903BIPWR</a>  | Active        | Production           | TSSOP (PW)   8  | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | L2903B              |
| LM2903BIPWR.B                | Active        | Production           | TSSOP (PW)   8  | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | L2903B              |
| <a href="#">LM2903DGKR</a>   | Active        | Production           | VSSOP (DGK)   8 | 2500   LARGE T&R      | Yes         | NIPDAU   SN<br>  NIPDAUAG            | Level-1-260C-UNLIM                | -40 to 125   | (MAP, MAS, MAU)     |
| LM2903DGKR.A                 | Active        | Production           | VSSOP (DGK)   8 | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | (MAP, MAS, MAU)     |
| <a href="#">LM2903DR</a>     | Active        | Production           | SOIC (D)   8    | 2500   LARGE T&R      | Yes         | NIPDAU   SN                          | Level-1-260C-UNLIM                | -40 to 125   | LM2903              |
| LM2903DR.A                   | Active        | Production           | SOIC (D)   8    | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LM2903              |
| <a href="#">LM2903DRG3</a>   | Active        | Production           | SOIC (D)   8    | 2500   LARGE T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -40 to 125   | LM2903              |
| LM2903DRG3.A                 | Active        | Production           | SOIC (D)   8    | 2500   LARGE T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -40 to 125   | LM2903              |
| <a href="#">LM2903P</a>      | Active        | Production           | PDIP (P)   8    | 50   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | -40 to 125   | LM2903P             |
| LM2903P.A                    | Active        | Production           | PDIP (P)   8    | 50   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | -40 to 125   | LM2903P             |
| LM2903P.B                    | Active        | Production           | PDIP (P)   8    | 50   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | -40 to 125   | LM2903P             |
| <a href="#">LM2903PSR</a>    | Active        | Production           | SO (PS)   8     | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | L2903               |
| LM2903PSR.A                  | Active        | Production           | SO (PS)   8     | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | L2903               |
| <a href="#">LM2903PWR</a>    | Active        | Production           | TSSOP (PW)   8  | 2000   LARGE T&R      | Yes         | NIPDAU   SN                          | Level-1-260C-UNLIM                | -40 to 125   | L2903               |
| LM2903PWR.A                  | Active        | Production           | TSSOP (PW)   8  | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | L2903               |
| LM2903PWR.B                  | Active        | Production           | TSSOP (PW)   8  | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | L2903               |
| <a href="#">LM2903PWRG3</a>  | Active        | Production           | TSSOP (PW)   8  | 2000   LARGE T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -40 to 125   | L2903               |
| LM2903PWRG3.A                | Active        | Production           | TSSOP (PW)   8  | 2000   LARGE T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -40 to 125   | L2903               |
| <a href="#">LM2903PWRG4</a>  | Active        | Production           | TSSOP (PW)   8  | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | L2903               |
| LM2903PWRG4.A                | Active        | Production           | TSSOP (PW)   8  | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | L2903               |
| LM2903PWRG4.B                | Active        | Production           | TSSOP (PW)   8  | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | L2903               |
| <a href="#">LM2903QD</a>     | Active        | Production           | SOIC (D)   8    | 75   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 2903Q               |
| LM2903QD.A                   | Active        | Production           | SOIC (D)   8    | 75   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | 2903Q               |

| Orderable part number         | Status<br>(1) | Material type<br>(2) | Package   Pins  | Package qty   Carrier | RoHS<br>(3) | Lead finish/<br>Ball material<br>(4) | MSL rating/<br>Peak reflow<br>(5) | Op temp (°C) | Part marking<br>(6) |
|-------------------------------|---------------|----------------------|-----------------|-----------------------|-------------|--------------------------------------|-----------------------------------|--------------|---------------------|
| <a href="#">LM2903QDRG4</a>   | Obsolete      | Production           | SOIC (D)   8    | -                     | -           | Call TI                              | Call TI                           | -40 to 125   | 2903Q               |
| <a href="#">LM2903VQDR</a>    | Active        | Production           | SOIC (D)   8    | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | L2903V              |
| LM2903VQDR.A                  | Active        | Production           | SOIC (D)   8    | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | L2903V              |
| <a href="#">LM2903VQDRG4</a>  | Obsolete      | Production           | SOIC (D)   8    | -                     | -           | Call TI                              | Call TI                           | -40 to 125   | L2903V              |
| <a href="#">LM2903VQPWR</a>   | Active        | Production           | TSSOP (PW)   8  | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | L2903V              |
| LM2903VQPWR.A                 | Active        | Production           | TSSOP (PW)   8  | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | L2903V              |
| LM2903VQPWR.B                 | Active        | Production           | TSSOP (PW)   8  | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | L2903V              |
| <a href="#">LM2903VQPWRG4</a> | Obsolete      | Production           | TSSOP (PW)   8  | -                     | -           | Call TI                              | Call TI                           | -40 to 125   | L2903V              |
| <a href="#">LM293ADGKR</a>    | Active        | Production           | VSSOP (DGK)   8 | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -25 to 85    | (MDP, MDS, MDU)     |
| LM293ADGKR.A                  | Active        | Production           | VSSOP (DGK)   8 | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -25 to 85    | (MDP, MDS, MDU)     |
| LM293ADGKRG4                  | Active        | Production           | VSSOP (DGK)   8 | 2500   LARGE T&R      | -           | Call TI                              | Call TI                           | -25 to 85    |                     |
| <a href="#">LM293ADR</a>      | Active        | Production           | SOIC (D)   8    | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -25 to 85    | LM293A              |
| LM293ADR.A                    | Active        | Production           | SOIC (D)   8    | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -25 to 85    | LM293A              |
| <a href="#">LM293D</a>        | Obsolete      | Production           | SOIC (D)   8    | -                     | -           | Call TI                              | Call TI                           | -25 to 85    | LM293               |
| <a href="#">LM293DGKR</a>     | Active        | Production           | VSSOP (DGK)   8 | 2500   LARGE T&R      | Yes         | NIPDAU   SN                          | Level-1-260C-UNLIM                | -25 to 85    | (MCP, MCS, MCU)     |
| LM293DGKR.A                   | Active        | Production           | VSSOP (DGK)   8 | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -25 to 85    | (MCP, MCS, MCU)     |
| LM293DGKR.B                   | Active        | Production           | VSSOP (DGK)   8 | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -25 to 85    | (MCP, MCS, MCU)     |
| LM293DGKRG4                   | Active        | Production           | VSSOP (DGK)   8 | 2500   LARGE T&R      | -           | Call TI                              | Call TI                           | -25 to 85    |                     |
| <a href="#">LM293DR</a>       | Active        | Production           | SOIC (D)   8    | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -25 to 85    | LM293               |
| LM293DR.A                     | Active        | Production           | SOIC (D)   8    | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -25 to 85    | LM293               |
| <a href="#">LM293DRG3</a>     | Active        | Production           | SOIC (D)   8    | 2500   LARGE T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -25 to 85    | LM293               |
| LM293DRG3.A                   | Active        | Production           | SOIC (D)   8    | 2500   LARGE T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -25 to 85    | LM293               |
| <a href="#">LM293P</a>        | Active        | Production           | PDIP (P)   8    | 50   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | -25 to 85    | LM293P              |
| LM293P.A                      | Active        | Production           | PDIP (P)   8    | 50   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | -25 to 85    | LM293P              |
| LM293P.B                      | Active        | Production           | PDIP (P)   8    | 50   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | -25 to 85    | LM293P              |
| LM293PE4                      | Active        | Production           | PDIP (P)   8    | 50   TUBE             | -           | Call TI                              | Call TI                           | -25 to 85    |                     |
| <a href="#">LM393ADGKR</a>    | Active        | Production           | VSSOP (DGK)   8 | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | (M8P, M8S, M8U)     |
| LM393ADGKR.A                  | Active        | Production           | VSSOP (DGK)   8 | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | (M8P, M8S, M8U)     |
| LM393ADGKRG4                  | Active        | Production           | VSSOP (DGK)   8 | 2500   LARGE T&R      | -           | Call TI                              | Call TI                           | 0 to 70      |                     |
| <a href="#">LM393ADR</a>      | Active        | Production           | SOIC (D)   8    | 2500   LARGE T&R      | Yes         | NIPDAU   SN                          | Level-1-260C-UNLIM                | 0 to 70      | LM393A              |
| LM393ADR.A                    | Active        | Production           | SOIC (D)   8    | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | LM393A              |

| Orderable part number       | Status<br>(1) | Material type<br>(2) | Package   Pins        | Package qty   Carrier | RoHS<br>(3) | Lead finish/<br>Ball material<br>(4) | MSL rating/<br>Peak reflow<br>(5) | Op temp (°C) | Part marking<br>(6) |
|-----------------------------|---------------|----------------------|-----------------------|-----------------------|-------------|--------------------------------------|-----------------------------------|--------------|---------------------|
| <a href="#">LM393ADRG4</a>  | Obsolete      | Production           | SOIC (D)   8          | -                     | -           | Call TI                              | Call TI                           | 0 to 70      | LM393A              |
| <a href="#">LM393AP</a>     | Active        | Production           | PDIP (P)   8          | 50   TUBE             | Yes         | NIPDAU   SN                          | N/A for Pkg Type                  | 0 to 70      | LM393AP             |
| LM393AP.A                   | Active        | Production           | PDIP (P)   8          | 50   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | 0 to 70      | LM393AP             |
| LM393AP.B                   | Active        | Production           | PDIP (P)   8          | 50   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | 0 to 70      | LM393AP             |
| LM393APE4                   | Active        | Production           | PDIP (P)   8          | 50   TUBE             | -           | Call TI                              | Call TI                           | 0 to 70      |                     |
| <a href="#">LM393APSR</a>   | Active        | Production           | SO (PS)   8           | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | L393A               |
| LM393APSR.A                 | Active        | Production           | SO (PS)   8           | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | L393A               |
| <a href="#">LM393APWR</a>   | Active        | Production           | TSSOP (PW)   8        | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | L393A               |
| LM393APWR.A                 | Active        | Production           | TSSOP (PW)   8        | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | L393A               |
| LM393APWR.B                 | Active        | Production           | TSSOP (PW)   8        | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | L393A               |
| LM393APWRG4                 | Obsolete      | Production           | TSSOP (PW)   8        | -                     | -           | Call TI                              | Call TI                           | 0 to 70      | L393A               |
| <a href="#">LM393BIDDFR</a> | Active        | Production           | SOT-23-THIN (DDF)   8 | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 85    | 393B                |
| LM393BIDDFR.B               | Active        | Production           | SOT-23-THIN (DDF)   8 | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 85    | 393B                |
| LM393BIDDFRG4               | Active        | Production           | SOT-23-THIN (DDF)   8 | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 85    | 393B                |
| LM393BIDDFRG4.B             | Active        | Production           | SOT-23-THIN (DDF)   8 | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 85    | 393B                |
| <a href="#">LM393BIDGKR</a> | Active        | Production           | VSSOP (DGK)   8       | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 85    | 393B                |
| LM393BIDGKR.A               | Active        | Production           | VSSOP (DGK)   8       | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 85    | 393B                |
| LM393BIDGKR.B               | Active        | Production           | VSSOP (DGK)   8       | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 85    | 393B                |
| <a href="#">LM393BIDR</a>   | Active        | Production           | SOIC (D)   8          | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 85    | LM393B              |
| LM393BIDR.A                 | Active        | Production           | SOIC (D)   8          | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 85    | LM393B              |
| LM393BIDR.B                 | Active        | Production           | SOIC (D)   8          | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 85    | LM393B              |
| LM393BIDRG4                 | Active        | Production           | SOIC (D)   8          | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 85    | LM393B              |
| LM393BIDRG4.A               | Active        | Production           | SOIC (D)   8          | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 85    | LM393B              |
| LM393BIDRG4.B               | Active        | Production           | SOIC (D)   8          | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 85    | LM393B              |
| <a href="#">LM393BIDSGR</a> | Active        | Production           | WSON (DSG)   8        | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 85    | 393B                |
| LM393BIDSGR.A               | Active        | Production           | WSON (DSG)   8        | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 85    | 393B                |
| LM393BIDSGR.B               | Active        | Production           | WSON (DSG)   8        | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 85    | 393B                |
| LM393BIDSGRG4               | Active        | Production           | WSON (DSG)   8        | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 85    | 393B                |
| LM393BIDSGRG4.A             | Active        | Production           | WSON (DSG)   8        | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 85    | 393B                |
| LM393BIDSGRG4.B             | Active        | Production           | WSON (DSG)   8        | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 85    | 393B                |
| <a href="#">LM393BIPWR</a>  | Active        | Production           | TSSOP (PW)   8        | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 85    | LM393B              |

| Orderable part number      | Status<br>(1) | Material type<br>(2) | Package   Pins  | Package qty   Carrier | RoHS<br>(3) | Lead finish/<br>Ball material<br>(4) | MSL rating/<br>Peak reflow<br>(5) | Op temp (°C) | Part marking<br>(6) |
|----------------------------|---------------|----------------------|-----------------|-----------------------|-------------|--------------------------------------|-----------------------------------|--------------|---------------------|
| LM393BIPWR.A               | Active        | Production           | TSSOP (PW)   8  | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 85    | LM393B              |
| LM393BIPWR.B               | Active        | Production           | TSSOP (PW)   8  | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 85    | LM393B              |
| <a href="#">LM393DGKR</a>  | Active        | Production           | VSSOP (DGK)   8 | 2500   LARGE T&R      | Yes         | NIPDAU   SN                          | Level-1-260C-UNLIM                | 0 to 70      | (M9P, M9S, M9U)     |
| LM393DGKR.A                | Active        | Production           | VSSOP (DGK)   8 | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | (M9P, M9S, M9U)     |
| LM393DGKRG4                | Active        | Production           | VSSOP (DGK)   8 | 2500   LARGE T&R      | -           | Call TI                              | Call TI                           | 0 to 70      |                     |
| <a href="#">LM393DR</a>    | Active        | Production           | SOIC (D)   8    | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | LM393               |
| LM393DR.A                  | Active        | Production           | SOIC (D)   8    | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | LM393               |
| <a href="#">LM393DRG3</a>  | Active        | Production           | SOIC (D)   8    | 2500   LARGE T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | 0 to 70      | LM393               |
| LM393DRG3.A                | Active        | Production           | SOIC (D)   8    | 2500   LARGE T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | 0 to 70      | LM393               |
| <a href="#">LM393DRG4</a>  | Obsolete      | Production           | SOIC (D)   8    | -                     | -           | Call TI                              | Call TI                           | 0 to 70      | LM393               |
| <a href="#">LM393P</a>     | Active        | Production           | PDIP (P)   8    | 50   TUBE             | Yes         | NIPDAU   SN                          | N/A for Pkg Type                  | 0 to 70      | LM393P              |
| LM393P.A                   | Active        | Production           | PDIP (P)   8    | 50   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | 0 to 70      | LM393P              |
| LM393P.B                   | Active        | Production           | PDIP (P)   8    | 50   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | 0 to 70      | LM393P              |
| <a href="#">LM393PE3</a>   | Active        | Production           | PDIP (P)   8    | 50   TUBE             | Yes         | SN                                   | N/A for Pkg Type                  | 0 to 70      | LM393P              |
| LM393PE3.A                 | Active        | Production           | PDIP (P)   8    | 50   TUBE             | Yes         | SN                                   | N/A for Pkg Type                  | 0 to 70      | LM393P              |
| <a href="#">LM393PE4</a>   | Active        | Production           | PDIP (P)   8    | 50   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | 0 to 70      | LM393P              |
| LM393PE4.A                 | Active        | Production           | PDIP (P)   8    | 50   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | 0 to 70      | LM393P              |
| LM393PE4.B                 | Active        | Production           | PDIP (P)   8    | 50   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | 0 to 70      | LM393P              |
| LM393PS                    | Active        | Production           | SO (PS)   8     | 80   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | L393                |
| LM393PS.A                  | Active        | Production           | SO (PS)   8     | 80   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | L393                |
| <a href="#">LM393PSR</a>   | Active        | Production           | SO (PS)   8     | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | L393                |
| LM393PSR.A                 | Active        | Production           | SO (PS)   8     | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | L393                |
| LM393PSRG4                 | Active        | Production           | SO (PS)   8     | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | L393                |
| <a href="#">LM393PWR</a>   | Active        | Production           | TSSOP (PW)   8  | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | L393                |
| LM393PWR.A                 | Active        | Production           | TSSOP (PW)   8  | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | L393                |
| LM393PWR.B                 | Active        | Production           | TSSOP (PW)   8  | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | L393                |
| <a href="#">LM393PWRG3</a> | Active        | Production           | TSSOP (PW)   8  | 2000   LARGE T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | 0 to 70      | L393                |
| LM393PWRG3.A               | Active        | Production           | TSSOP (PW)   8  | 2000   LARGE T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | 0 to 70      | L393                |
| <a href="#">LM393PWRG4</a> | Active        | Production           | TSSOP (PW)   8  | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | L393                |
| LM393PWRG4.A               | Active        | Production           | TSSOP (PW)   8  | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | L393                |
| LM393PWRG4.B               | Active        | Production           | TSSOP (PW)   8  | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | L393                |

<sup>(1)</sup> **Status:** For more details on status, see our [product life cycle](#).

<sup>(2)</sup> **Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

<sup>(3)</sup> **RoHS values:** Yes, No, RoHS Exempt. See the [TI RoHS Statement](#) for additional information and value definition.

<sup>(4)</sup> **Lead finish/Ball material:** Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

<sup>(5)</sup> **MSL rating/Peak reflow:** The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

<sup>(6)</sup> **Part marking:** There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

**OTHER QUALIFIED VERSIONS OF LM2903, LM2903B, LM293 :**

- Automotive : [LM2903-Q1](#), [LM2903B-Q1](#)
- Enhanced Product : [LM293-EP](#)

NOTE: Qualified Version Definitions:

- Automotive - Q100 devices qualified for high-reliability automotive applications targeting zero defects
- Enhanced Product - Supports Defense, Aerospace and Medical Applications

**TAPE AND REEL INFORMATION**

**QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE**


\*All dimensions are nominal

| Device         | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|----------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| LM193DR        | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| LM193DRG4      | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| LM2903AVQDR    | SOIC         | D               | 8    | 2500 | 330.0              | 12.5               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| LM2903AVQDR    | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| LM2903AVQDR    | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| LM2903AVQDRG4  | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| LM2903AVQPWR   | TSSOP        | PW              | 8    | 2000 | 330.0              | 12.4               | 7.0     | 3.6     | 1.6     | 8.0     | 12.0   | Q1            |
| LM2903AVQPWRG4 | TSSOP        | PW              | 8    | 2000 | 330.0              | 12.4               | 7.0     | 3.6     | 1.6     | 8.0     | 12.0   | Q1            |
| LM2903BIDDFR   | SOT-23-THIN  | DDF             | 8    | 3000 | 180.0              | 8.4                | 3.2     | 3.2     | 1.4     | 4.0     | 8.0    | Q3            |
| LM2903BIDDFRG4 | SOT-23-THIN  | DDF             | 8    | 3000 | 180.0              | 8.4                | 3.2     | 3.2     | 1.4     | 4.0     | 8.0    | Q3            |
| LM2903BIDGKR   | VSSOP        | DGK             | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| LM2903BIDGKR   | VSSOP        | DGK             | 8    | 2500 | 330.0              | 12.4               | 5.3     | 3.4     | 1.4     | 8.0     | 12.0   | Q1            |
| LM2903BIDGKR4  | VSSOP        | DGK             | 8    | 2500 | 330.0              | 12.4               | 5.3     | 3.4     | 1.4     | 8.0     | 12.0   | Q1            |
| LM2903BIDR     | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| LM2903BIDRG4   | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |

| Device         | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|----------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| LM2903BIDSGR   | WSO          | DSG             | 8    | 3000 | 180.0              | 8.4                | 2.3     | 2.3     | 1.15    | 4.0     | 8.0    | Q2            |
| LM2903BIDSGRG4 | WSO          | DSG             | 8    | 3000 | 180.0              | 8.4                | 2.3     | 2.3     | 1.15    | 4.0     | 8.0    | Q2            |
| LM2903BIPWR    | TSSOP        | PW              | 8    | 2000 | 330.0              | 12.4               | 7.0     | 3.6     | 1.6     | 8.0     | 12.0   | Q1            |
| LM2903DGKR     | VSSOP        | DGK             | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| LM2903DR       | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| LM2903DR       | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| LM2903DR       | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| LM2903DRG3     | SOIC         | D               | 8    | 2500 | 330.0              | 12.8               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| LM2903PSR      | SO           | PS              | 8    | 2000 | 330.0              | 16.4               | 8.35    | 6.6     | 2.4     | 12.0    | 16.0   | Q1            |
| LM2903PWR      | TSSOP        | PW              | 8    | 2000 | 330.0              | 12.4               | 7.0     | 3.6     | 1.6     | 8.0     | 12.0   | Q1            |
| LM2903PWRG3    | TSSOP        | PW              | 8    | 2000 | 330.0              | 12.4               | 7.0     | 3.6     | 1.6     | 8.0     | 12.0   | Q1            |
| LM2903PWRG4    | TSSOP        | PW              | 8    | 2000 | 330.0              | 12.4               | 7.0     | 3.6     | 1.6     | 8.0     | 12.0   | Q1            |
| LM2903VQDR     | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| LM2903VQPWR    | TSSOP        | PW              | 8    | 2000 | 330.0              | 12.4               | 7.0     | 3.6     | 1.6     | 8.0     | 12.0   | Q1            |
| LM293ADGKR     | VSSOP        | DGK             | 8    | 2500 | 330.0              | 12.4               | 5.3     | 3.4     | 1.4     | 8.0     | 12.0   | Q1            |
| LM293ADR       | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| LM293ADR       | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| LM293ADR       | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| LM293DGKR      | VSSOP        | DGK             | 8    | 2500 | 330.0              | 12.4               | 5.3     | 3.4     | 1.4     | 8.0     | 12.0   | Q1            |
| LM293DR        | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| LM293DR        | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| LM293DR        | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| LM293DRG3      | SOIC         | D               | 8    | 2500 | 330.0              | 12.8               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| LM393ADGKR     | VSSOP        | DGK             | 8    | 2500 | 330.0              | 12.4               | 5.3     | 3.4     | 1.4     | 8.0     | 12.0   | Q1            |
| LM393ADR       | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| LM393ADR       | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| LM393ADR       | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| LM393APSR      | SO           | PS              | 8    | 2000 | 330.0              | 16.4               | 8.35    | 6.6     | 2.4     | 12.0    | 16.0   | Q1            |
| LM393APWR      | TSSOP        | PW              | 8    | 2000 | 330.0              | 12.4               | 7.0     | 3.6     | 1.6     | 8.0     | 12.0   | Q1            |
| LM393BIDDFR    | SOT-23-THIN  | DDF             | 8    | 3000 | 180.0              | 8.4                | 3.2     | 3.2     | 1.4     | 4.0     | 8.0    | Q3            |
| LM393BIDDFRG4  | SOT-23-THIN  | DDF             | 8    | 3000 | 180.0              | 8.4                | 3.2     | 3.2     | 1.4     | 4.0     | 8.0    | Q3            |
| LM393BIDGKR    | VSSOP        | DGK             | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| LM393BIDR      | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| LM393BIDRG4    | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| LM393BIDSGR    | WSO          | DSG             | 8    | 3000 | 180.0              | 8.4                | 2.3     | 2.3     | 1.15    | 4.0     | 8.0    | Q2            |
| LM393BIDSGRG4  | WSO          | DSG             | 8    | 3000 | 180.0              | 8.4                | 2.3     | 2.3     | 1.15    | 4.0     | 8.0    | Q2            |
| LM393BIPWR     | TSSOP        | PW              | 8    | 2000 | 330.0              | 12.4               | 7.0     | 3.6     | 1.6     | 8.0     | 12.0   | Q1            |
| LM393DGKR      | VSSOP        | DGK             | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| LM393DGKR      | VSSOP        | DGK             | 8    | 2500 | 330.0              | 12.4               | 5.3     | 3.4     | 1.4     | 8.0     | 12.0   | Q1            |
| LM393DR        | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |

| Device     | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| LM393DR    | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| LM393DR    | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| LM393DRG3  | SOIC         | D               | 8    | 2500 | 330.0              | 12.8               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| LM393PSR   | SO           | PS              | 8    | 2000 | 330.0              | 16.4               | 8.35    | 6.6     | 2.4     | 12.0    | 16.0   | Q1            |
| LM393PWR   | TSSOP        | PW              | 8    | 2000 | 330.0              | 12.4               | 7.0     | 3.6     | 1.6     | 8.0     | 12.0   | Q1            |
| LM393PWRG3 | TSSOP        | PW              | 8    | 2000 | 330.0              | 12.4               | 7.0     | 3.6     | 1.6     | 8.0     | 12.0   | Q1            |
| LM393PWRG4 | TSSOP        | PW              | 8    | 2000 | 330.0              | 12.4               | 7.0     | 3.6     | 1.6     | 8.0     | 12.0   | Q1            |

## TAPE AND REEL BOX DIMENSIONS



\*All dimensions are nominal

| Device         | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|----------------|--------------|-----------------|------|------|-------------|------------|-------------|
| LM193DR        | SOIC         | D               | 8    | 2500 | 353.0       | 353.0      | 32.0        |
| LM193DRG4      | SOIC         | D               | 8    | 2500 | 353.0       | 353.0      | 32.0        |
| LM2903AVQDR    | SOIC         | D               | 8    | 2500 | 353.0       | 353.0      | 32.0        |
| LM2903AVQDR    | SOIC         | D               | 8    | 2500 | 340.5       | 338.1      | 20.6        |
| LM2903AVQDR    | SOIC         | D               | 8    | 2500 | 353.0       | 353.0      | 32.0        |
| LM2903AVQDRG4  | SOIC         | D               | 8    | 2500 | 353.0       | 353.0      | 32.0        |
| LM2903AVQPWR   | TSSOP        | PW              | 8    | 2000 | 353.0       | 353.0      | 32.0        |
| LM2903AVQPWRG4 | TSSOP        | PW              | 8    | 2000 | 353.0       | 353.0      | 32.0        |
| LM2903BIDDFR   | SOT-23-THIN  | DDF             | 8    | 3000 | 210.0       | 185.0      | 35.0        |
| LM2903BIDDFRG4 | SOT-23-THIN  | DDF             | 8    | 3000 | 210.0       | 185.0      | 35.0        |
| LM2903BIDGKR   | VSSOP        | DGK             | 8    | 2500 | 353.0       | 353.0      | 32.0        |
| LM2903BIDGKR   | VSSOP        | DGK             | 8    | 2500 | 353.0       | 353.0      | 32.0        |
| LM2903BIDGKRG4 | VSSOP        | DGK             | 8    | 2500 | 353.0       | 353.0      | 32.0        |
| LM2903BIDR     | SOIC         | D               | 8    | 2500 | 353.0       | 353.0      | 32.0        |
| LM2903BIDRG4   | SOIC         | D               | 8    | 2500 | 353.0       | 353.0      | 32.0        |
| LM2903BIDSGR   | WSO          | DSG             | 8    | 3000 | 210.0       | 185.0      | 35.0        |
| LM2903BIDSGRG4 | WSO          | DSG             | 8    | 3000 | 210.0       | 185.0      | 35.0        |
| LM2903BIPWR    | TSSOP        | PW              | 8    | 2000 | 353.0       | 353.0      | 32.0        |

| Device        | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|---------------|--------------|-----------------|------|------|-------------|------------|-------------|
| LM2903DGKR    | VSSOP        | DGK             | 8    | 2500 | 353.0       | 353.0      | 32.0        |
| LM2903DR      | SOIC         | D               | 8    | 2500 | 353.0       | 353.0      | 32.0        |
| LM2903DR      | SOIC         | D               | 8    | 2500 | 340.5       | 338.1      | 20.6        |
| LM2903DR      | SOIC         | D               | 8    | 2500 | 353.0       | 353.0      | 32.0        |
| LM2903DRG3    | SOIC         | D               | 8    | 2500 | 364.0       | 364.0      | 27.0        |
| LM2903PSR     | SO           | PS              | 8    | 2000 | 353.0       | 353.0      | 32.0        |
| LM2903PWR     | TSSOP        | PW              | 8    | 2000 | 353.0       | 353.0      | 32.0        |
| LM2903PWRG3   | TSSOP        | PW              | 8    | 2000 | 364.0       | 364.0      | 27.0        |
| LM2903PWRG4   | TSSOP        | PW              | 8    | 2000 | 353.0       | 353.0      | 32.0        |
| LM2903VQDR    | SOIC         | D               | 8    | 2500 | 353.0       | 353.0      | 32.0        |
| LM2903VQPWR   | TSSOP        | PW              | 8    | 2000 | 353.0       | 353.0      | 32.0        |
| LM293ADGKR    | VSSOP        | DGK             | 8    | 2500 | 353.0       | 353.0      | 32.0        |
| LM293ADR      | SOIC         | D               | 8    | 2500 | 340.5       | 338.1      | 20.6        |
| LM293ADR      | SOIC         | D               | 8    | 2500 | 353.0       | 353.0      | 32.0        |
| LM293ADR      | SOIC         | D               | 8    | 2500 | 353.0       | 353.0      | 32.0        |
| LM293DGKR     | VSSOP        | DGK             | 8    | 2500 | 356.0       | 356.0      | 35.0        |
| LM293DR       | SOIC         | D               | 8    | 2500 | 353.0       | 353.0      | 32.0        |
| LM293DR       | SOIC         | D               | 8    | 2500 | 340.5       | 338.1      | 20.6        |
| LM293DR       | SOIC         | D               | 8    | 2500 | 353.0       | 353.0      | 32.0        |
| LM293DRG3     | SOIC         | D               | 8    | 2500 | 364.0       | 364.0      | 27.0        |
| LM393ADGKR    | VSSOP        | DGK             | 8    | 2500 | 353.0       | 353.0      | 32.0        |
| LM393ADR      | SOIC         | D               | 8    | 2500 | 353.0       | 353.0      | 32.0        |
| LM393ADR      | SOIC         | D               | 8    | 2500 | 353.0       | 353.0      | 32.0        |
| LM393ADR      | SOIC         | D               | 8    | 2500 | 340.5       | 338.1      | 20.6        |
| LM393APSR     | SO           | PS              | 8    | 2000 | 353.0       | 353.0      | 32.0        |
| LM393APWR     | TSSOP        | PW              | 8    | 2000 | 353.0       | 353.0      | 32.0        |
| LM393BIDDFR   | SOT-23-THIN  | DDF             | 8    | 3000 | 210.0       | 185.0      | 35.0        |
| LM393BIDDFRG4 | SOT-23-THIN  | DDF             | 8    | 3000 | 210.0       | 185.0      | 35.0        |
| LM393BIDGKR   | VSSOP        | DGK             | 8    | 2500 | 353.0       | 353.0      | 32.0        |
| LM393BIDR     | SOIC         | D               | 8    | 2500 | 353.0       | 353.0      | 32.0        |
| LM393BIDRG4   | SOIC         | D               | 8    | 2500 | 353.0       | 353.0      | 32.0        |
| LM393BIDSGR   | WSO          | DSG             | 8    | 3000 | 210.0       | 185.0      | 35.0        |
| LM393BIDSGRG4 | WSO          | DSG             | 8    | 3000 | 210.0       | 185.0      | 35.0        |
| LM393BIPWR    | TSSOP        | PW              | 8    | 2000 | 353.0       | 353.0      | 32.0        |
| LM393DGKR     | VSSOP        | DGK             | 8    | 2500 | 353.0       | 353.0      | 32.0        |
| LM393DGKR     | VSSOP        | DGK             | 8    | 2500 | 353.0       | 353.0      | 32.0        |
| LM393DR       | SOIC         | D               | 8    | 2500 | 353.0       | 353.0      | 32.0        |
| LM393DR       | SOIC         | D               | 8    | 2500 | 340.5       | 338.1      | 20.6        |
| LM393DR       | SOIC         | D               | 8    | 2500 | 353.0       | 353.0      | 32.0        |
| LM393DRG3     | SOIC         | D               | 8    | 2500 | 364.0       | 364.0      | 27.0        |
| LM393PSR      | SO           | PS              | 8    | 2000 | 353.0       | 353.0      | 32.0        |
| LM393PWR      | TSSOP        | PW              | 8    | 2000 | 353.0       | 353.0      | 32.0        |
| LM393PWRG3    | TSSOP        | PW              | 8    | 2000 | 364.0       | 364.0      | 27.0        |

---

| Device     | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|------------|--------------|-----------------|------|------|-------------|------------|-------------|
| LM393PWRG4 | TSSOP        | PW              | 8    | 2000 | 353.0       | 353.0      | 32.0        |

**TUBE**


\*All dimensions are nominal

| Device     | Package Name | Package Type | Pins | SPQ | L (mm) | W (mm) | T (μm) | B (mm) |
|------------|--------------|--------------|------|-----|--------|--------|--------|--------|
| LM2903P    | P            | PDIP         | 8    | 50  | 506    | 13.97  | 11230  | 4.32   |
| LM2903P.A  | P            | PDIP         | 8    | 50  | 506    | 13.97  | 11230  | 4.32   |
| LM2903P.B  | P            | PDIP         | 8    | 50  | 506    | 13.97  | 11230  | 4.32   |
| LM2903QD   | D            | SOIC         | 8    | 75  | 505.46 | 6.76   | 3810   | 4      |
| LM2903QD.A | D            | SOIC         | 8    | 75  | 505.46 | 6.76   | 3810   | 4      |
| LM293P     | P            | PDIP         | 8    | 50  | 506    | 13.97  | 11230  | 4.32   |
| LM293P.A   | P            | PDIP         | 8    | 50  | 506    | 13.97  | 11230  | 4.32   |
| LM293P.B   | P            | PDIP         | 8    | 50  | 506    | 13.97  | 11230  | 4.32   |
| LM393AP    | P            | PDIP         | 8    | 50  | 506    | 13.97  | 11230  | 4.32   |
| LM393AP    | P            | PDIP         | 8    | 50  | 506.1  | 9      | 600    | 5.4    |
| LM393AP.A  | P            | PDIP         | 8    | 50  | 506    | 13.97  | 11230  | 4.32   |
| LM393AP.A  | P            | PDIP         | 8    | 50  | 506.1  | 9      | 600    | 5.4    |
| LM393AP.B  | P            | PDIP         | 8    | 50  | 506    | 13.97  | 11230  | 4.32   |
| LM393AP.B  | P            | PDIP         | 8    | 50  | 506.1  | 9      | 600    | 5.4    |
| LM393P     | P            | PDIP         | 8    | 50  | 506.1  | 9      | 600    | 5.4    |
| LM393P     | P            | PDIP         | 8    | 50  | 506    | 13.97  | 11230  | 4.32   |
| LM393P.A   | P            | PDIP         | 8    | 50  | 506.1  | 9      | 600    | 5.4    |
| LM393P.A   | P            | PDIP         | 8    | 50  | 506    | 13.97  | 11230  | 4.32   |
| LM393P.B   | P            | PDIP         | 8    | 50  | 506.1  | 9      | 600    | 5.4    |
| LM393P.B   | P            | PDIP         | 8    | 50  | 506    | 13.97  | 11230  | 4.32   |
| LM393PE3   | P            | PDIP         | 8    | 50  | 506.1  | 9      | 600    | 5.4    |
| LM393PE3.A | P            | PDIP         | 8    | 50  | 506.1  | 9      | 600    | 5.4    |
| LM393PE4   | P            | PDIP         | 8    | 50  | 506    | 13.97  | 11230  | 4.32   |
| LM393PE4.A | P            | PDIP         | 8    | 50  | 506    | 13.97  | 11230  | 4.32   |
| LM393PE4.B | P            | PDIP         | 8    | 50  | 506    | 13.97  | 11230  | 4.32   |
| LM393PS    | PS           | SOP          | 8    | 80  | 530    | 10.5   | 4000   | 4.1    |
| LM393PS.A  | PS           | SOP          | 8    | 80  | 530    | 10.5   | 4000   | 4.1    |



## VSSOP - 1.1 mm max height

[illegible]

TEXAS  
INSTRUMENTS  
www.ti.com

# EXAMPLE BOARD LAYOUT

DGK0008A

™ VSSOP - 1.1 mm max height

SMALL OUTLINE PACKAGE



SOLDER MASK DETAILS

4214862/A 04/2023

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.
7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.
8. Vias are optional depending on application, refer to device data sheet. If any vias are implemented, refer to their locations shown on this view. It is recommended that vias under paste be filled, plugged or tented.
9. Size of metal pad may vary due to creepage requirement.

## EXAMPLE STENCIL DESIGN

DGK0008A

<sup>TM</sup> VSSOP - 1.1 mm max height

SMALL OUTLINE PACKAGE



SOLDER PASTE EXAMPLE  
SCALE: 15X

4214862/A 04/2023

NOTES: (continued)

11. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
12. Board assembly site may have different recommendations for stencil design.


**DDF0008A**



# PACKAGE OUTLINE

## SOT-23-THIN - 1.1 mm max height

PLASTIC SMALL OUTLINE



4222047/E 07/2024

### NOTES:


1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm per side.

# EXAMPLE BOARD LAYOUT



DDF0008A

SOT-23-THIN - 1.1 mm max height

PLASTIC SMALL OUTLINE



LAND PATTERN EXAMPLE  
EXPOSED METAL SHOWN  
SCALE:15X



SOLDER MASK DETAILS

4222047/E 07/2024

NOTES: (continued)


4. Publication IPC-7351 may have alternate designs.
5. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

## EXAMPLE STENCIL DESIGN

DDF0008A

SOT-23-THIN - 1.1 mm max height

PLASTIC SMALL OUTLINE



SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL  
SCALE:15X

4222047/E 07/2024

NOTES: (continued)

6. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
7. Board assembly site may have different recommendations for stencil design.



## PACKAGE OUTLINE

**SOIC - 1.75 mm max height**

SMALL OUTLINE INTEGRATED CIRCUIT




1. Linear dimensions are in inches [millimeters]. Dimensions in parenthesis are for reference only. Controlling dimensions are in inches. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed .006 [0.15] per side.
4. This dimension does not include interlead flash.
5. Reference JEDEC registration MS-012, variation AA.

# EXAMPLE BOARD LAYOUT

D0008A

SOIC - 1.75 mm max height

SMALL OUTLINE INTEGRATED CIRCUIT



4214825/C 02/2019

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.

7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

## EXAMPLE STENCIL DESIGN

D0008A

SOIC - 1.75 mm max height

SMALL OUTLINE INTEGRATED CIRCUIT



SOLDER PASTE EXAMPLE  
BASED ON .005 INCH [0.125 MM] THICK STENCIL  
SCALE:8X

4214825/C 02/2019

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

# MECHANICAL DATA

PS (R-PDSO-G8)

PLASTIC SMALL-OUTLINE PACKAGE




4040063/C 03/03

- NOTES:
- A. All linear dimensions are in millimeters.
  - B. This drawing is subject to change without notice.
  - C. Body dimensions do not include mold flash or protrusion, not to exceed 0,15.

PS (R-PDSO-G8)

PLASTIC SMALL OUTLINE



- NOTES:
- A. All linear dimensions are in millimeters.
  - B. This drawing is subject to change without notice.
  - C. Publication IPC-7351 is recommended for alternate designs.
  - D. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC-7525 for other stencil recommendations.
  - E. Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.

P (R-PDIP-T8)

PLASTIC DUAL-IN-LINE PACKAGE



- NOTES:
- A. All linear dimensions are in inches (millimeters).
  - B. This drawing is subject to change without notice.
  - C. Falls within JEDEC MS-001 variation BA.

## GENERIC PACKAGE VIEW


**DSG 8**

**WSON - 0.8 mm max height**

2 x 2, 0.5 mm pitch

PLASTIC SMALL OUTLINE - NO LEAD

This image is a representation of the package family, actual package may vary.  
Refer to the product data sheet for package details.



4224783/A




# EXAMPLE BOARD LAYOUT


DSG0008A

WSN - 0.8 mm max height

PLASTIC SMALL OUTLINE - NO LEAD



LAND PATTERN EXAMPLE  
SCALE:20X



SOLDER MASK DETAILS

4218900/E 08/2022

NOTES: (continued)


4. This package is designed to be soldered to a thermal pad on the board. For more information, see Texas Instruments literature number SLUA271 ([www.ti.com/lit/slue271](http://www.ti.com/lit/slue271)).
5. Vias are optional depending on application, refer to device data sheet. If any vias are implemented, refer to their locations shown on this view. It is recommended that vias under paste be filled, plugged or tented.

## EXAMPLE STENCIL DESIGN

DSG0008A

WSN - 0.8 mm max height

PLASTIC SMALL OUTLINE - NO LEAD



SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL

EXPOSED PAD 9:  
87% PRINTED SOLDER COVERAGE BY AREA UNDER PACKAGE  
SCALE:25X

4218900/E 08/2022

NOTES: (continued)

6. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.




# EXAMPLE BOARD LAYOUT



PW0008A

TSSOP - 1.2 mm max height

SMALL OUTLINE PACKAGE



LAND PATTERN EXAMPLE  
SCALE:10X



SOLDER MASK DETAILS  
NOT TO SCALE

4221848/A 02/2015

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.


7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

## EXAMPLE STENCIL DESIGN

PW0008A

TSSOP - 1.2 mm max height

SMALL OUTLINE PACKAGE



SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL  
SCALE:10X

4221848/A 02/2015

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

## IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you fully indemnify TI and its representatives against any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to [TI's Terms of Sale](#), [TI's General Quality Guidelines](#), or other applicable terms available either on [ti.com](https://www.ti.com) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products. Unless TI explicitly designates a product as custom or customer-specified, TI products are standard, catalog, general purpose devices.

TI objects to and rejects any additional or different terms you may propose.

Copyright © 2025, Texas Instruments Incorporated

Last updated 10/2025