
www.ti.com

RAD-TOLERANT CLASS V, QUADRUPLE 2-INPUT POSITIVE-NOR GATES

FEATURES

- AC Types Feature 1.5-V to 5.5-V Operation
- Rad-Tolerant: 50 KRad(Si) TID (1)
 - TID Dose Rate < 2 mRad/sec
- QML-V Qualified, SMD 5962-87612

 Radiation tolerance is a typical value based upon initial device qualification. Radiation Lot Acceptance Testing is available contact factory for details.



DESCRIPTION

The <u>'AC02</u> devices contain four independent 2-input NOR gates that perform the Boolean function $Y = \overline{A} \cdot \overline{B}$ or $Y = \overline{A} + \overline{B}$ in positive logic.

ORDERING INFORMATION(1)


| T _A | PACK | ORDERABLE PART NUMBER | TOP-SIDE MARKING | |
|----------------|-------------|-----------------------|---------------------|-----------------|
| –55°C to 125°C | J - package | tubo | 5962-8761203VCA | 5962-8761203VCA |
| -55 C to 125 C | W - package | tube | 5962-8761203VDA | 5962-8761203VDA |

- (1) For the most current package and ordering information, see the Package Option Addendum at the end of this document, or see the TI Web site at www.ti.com.
- (2) Package drawings, standard packing quantities, thermal data, symbolization, and PCB design guidelines are available at www.ti.com/sc/package.

FUNCTION TABLE (EACH GATE)

| INP | UTS | OUTPUT |
|-----|-----|--------|
| Α | В | Y |
| Н | Χ | L |
| Х | Н | L |
| L | L | Н |

LOGIC DIAGRAM (POSITIVE LOGIC)







Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

2B

10



ABSOLUTE MAXIMUM RATINGS(1)

over operating free-air temperature range (unless otherwise noted)

| | | | | MIN | MAX | UNIT |
|------------------|---|-----------------------------|--|-----|------|------|
| V_{CC} | V _{CC} Supply voltage range | | | | 6 | V |
| I _{IK} | Input clamp current ⁽²⁾ | $V_I < 0$ or $V_I > V_{CC}$ | | | ±20 | mA |
| I _{OK} | Output clamp current ⁽²⁾ | V _O < 0 | | | ±50 | mA |
| Io | Continuous output current | $V_O = 0$ to V_{CC} | | | ±50 | mA |
| | Continuous current through V _{CC} or GND | | | | ±100 | mA |
| T _{stg} | Storage temperature range | | | -65 | 150 | = C |

⁽¹⁾ Stresses beyond those listed under absolute maximum ratings may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under recommended operating conditions is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

RECOMMENDED OPERATING CONDITIONS⁽¹⁾

| | | | T _A = 2 | T _A = 25°C | | –55°C TO 125°C | |
|-----------------|------------------------------------|----------------------------------|--------------------|-----------------------|------|-------------------|--------|
| | | | MIN | MAX | MIN | MAX | |
| V_{CC} | Supply voltage | | 1.5 | 5.5 | 1.5 | 5.5 | V |
| | | V _{CC} = 1.5 V | 1.2 | | 1.2 | | |
| V_{IH} | High-level input voltage | $V_{CC} = 3 V$ | 2.1 | | 2.1 | | V |
| | | V _{CC} = 5.5 V | 3.85 | | 3.85 | | |
| | Low-level input voltage | V _{CC} = 1.5 V | | 0.3 | | 0.3 | |
| V_{IL} | | $V_{CC} = 3 V$ | | 0.9 | | 0.9 | V |
| | | $V_{CC} = 5.5 \text{ V}$ | | 1.65 | | 1.65 | |
| VI | Input voltage | | 0 | V_{CC} | 0 | V_{CC} | V |
| Vo | Output voltage | | 0 | V_{CC} | 0 | V_{CC} | V |
| I _{OH} | High-level output current | V _{CC} = 4.5 V to 5.5 V | | -24 | | -24 | mA |
| I _{OL} | Low-level output current | V _{CC} = 4.5 V to 5.5 V | | 24 | | 24 | mA |
| Δt/Δν | Input transition rice or fall rate | V _{CC} = 1.5 V to 3 V | | 50 | | 50 | ns/V |
| ΔΙ/ΔΙ | Input transition rise or fall rate | V _{CC} = 3.6 V to 5.5 V | | 20 | | 20 | 115/ V |

All unused inputs of the device must be held at V_{CC} or GND to ensure proper device operation. Refer to the TI application report, Implications of Slow or Floating CMOS Inputs, literature number SCBA004.

Submit Documentation Feedback

⁽²⁾ The input and output voltage ratings may be exceeded provided the input and output current ratings are observed.



ELECTRICAL CHARACTERISTICS

over operating free-air temperature range (unless otherwise noted)

| PARAMETER | TEST CONDITIONS | | V _{cc} | T _A = 25°C | | −55°C TO 125°C | | UNIT | |
|-----------------|---|---------------------------------|-----------------|-----------------------|------|-------------------|-------|------|--|
| | | | | MIN | MAX | MIN | MAX | | |
| | | | 1.5 V | 1.4 | | 1.4 | | | |
| | | $I_{OH} = -50 \ \mu A$ | 3 V | 2.9 | | 2.9 | | | |
| V | \/ \/ or\/ | | 4.5 V | 4.4 | | 4.4 | | V | |
| V _{OH} | $V_I = V_{IH}$ or V_{IL} | $I_{OH} = -4mA$ | 3 V | 2.58 | | 2.4 | | V | |
| | | $I_{OH} = -24 \text{ mA}$ | 4.5 V | 3.94 | | 3.7 | | | |
| | | $I_{OH} = -50 \text{ mA}^{(1)}$ | 5.5 V | | | 3.85 | | | |
| | V V 22V | | | 1.5 V | | 0.1 | | 0.1 | |
| | | $I_{OL} = 50 \mu A$ | 3 V | | 0.1 | | 0.1 | | |
| V | | | 4.5 V | | 0.1 | | 0.1 | V | |
| V _{OL} | $V_I = V_{IH}$ or V_{IL} | I _{OL} = 12 mA | 3 V | | 0.36 | | 0.5 | V | |
| | | I _{OL} = 24 mA | 4.5 V | | 0.36 | | 0.525 | | |
| | | $I_{OL} = 50 \text{ mA}^{(1)}$ | 5.5 V | | | | 1.65 | | |
| I _I | V _I = V _{CC} or GND | | 5.5 V | | ±0.1 | | ±1 | μΑ | |
| I _{CC} | $V_I = V_{CC}$ or GND, | I _O = 0 | 5.5 V | | 4 | | 80 | μΑ | |
| Cı | | | | | 10 | | 10 | pF | |

⁽¹⁾ Test one output at a time, not exceeding 1-second duration. Measurement is made by forcing indicated current and measuring voltage to minimize power dissipation. Test verifies a minimum 50-Ω transmission-line drive capability at 85°C and 75-Ω transmission-line drive capability at 125°C.



SWITCHING CHARACTERISTICS

over recommended operating free-air temperature range, $V_{CC} = 1.5 \text{ V}$, $C_L = 50 \text{ pF}$ (unless otherwise noted) (see Figure 1)

| PARAMETER | ARAMETER FROM TO (OUTPUT) | | −55°C TO 125°C | UNIT |
|------------------|---------------------------|----------|-------------------|----------|
| | (INFOT) | (001701) | MIN MA | (|
| t _{PLH} | A or B | V | 14 | |
| t _{PHL} | A or B | T T | 14 | ns 4 |

SWITCHING CHARACTERISTICS

over recommended operating free-air temperature range, V_{CC} = 3.3 V ± 0.3 V, C_L = 50 pF (unless otherwise noted) (see Figure 1)

| PARAMETER | FROM (INPUT) | TO (OUTPUT) | –55°C 125 | | UNIT |
|------------------|-----------------|----------------|--------------|------|------|
| | (INFOT) | (001701) | MIN | MAX | |
| t _{PLH} | A or D | V | 4 | 16.1 | 20 |
| t _{PHL} | A or B | Ť | 4 | 16.1 | ns |

SWITCHING CHARACTERISTICS

over recommended operating free-air temperature range, V_{CC} = 5 V ± 0.5 V, C_L = 50 pF (unless otherwise noted) (see Figure 1)

| PARAMETER | FROM | FROM TO 125°C TO 125°C (INPUT) | | | |
|------------------|---------|--------------------------------|-----|------|----|
| | (INFOT) | (001701) | MIN | MAX | |
| t _{PLH} | A or B | V | 2.9 | 11.5 | 20 |
| t _{PHL} | AOIB | ı | 2.9 | 11.5 | ns |

OPERATING CHARACTERISTICS


 $V_{CC} = 5 \text{ V}, T_A = 25^{\circ}\text{C}$

| | PARAMETER | TYP | UNIT |
|----------|-------------------------------|-----|------|
| C_{pd} | Power dissipation capacitance | 55 | pF |

Submit Documentation Feedback



PARAMETER MEASUREMENT INFORMATION



NOTES: A. C_L includes probe and test-fixture capacitance.

VOLTAGE WAVEFORMS

PROPAGATION DELAY AND OUTPUT TRANSITION TIMES

B. Waveform 1 is for an output with internal conditions such that the output is low except when disabled by the output control. Waveform 2 is for an output with internal conditions such that the output is high except when disabled by the output control.

(see Note B)

- C. All input pulses are supplied by generators having the following characteristics: PRR \leq 1 MHz, $Z_O = 50 \Omega$, $t_f = 3$ ns, $t_f = 3$ ns. Phase relationships between waveforms are arbitrary.
- D. For clock inputs, f_{max} is measured with the input duty cycle at 50%.
- E. The outputs are measured one at a time with one input transition per measurement.
- F. t_{PLH} and t_{PHL} are the same as t_{pd} .
- G. t_{PZL} and t_{PZH} are the same as t_{en}.
- H. t_{PLZ} and t_{PHZ} are the same as t_{dis} .

Figure 1. Load Circuit and Voltage Waveforms

Submit Documentation Feedback

VOLTAGE WAVEFORMS

OUTPUT ENABLE AND DISABLE TIMES

≈0 V

www.ti.com 11-Nov-2025

PACKAGING INFORMATION

| Orderable part number | Status | Material type | Package Pins | Package qty Carrier | RoHS | Lead finish/ Ball material | MSL rating/ Peak reflow | Op temp (°C) | Part marking (6) |
|-----------------------|--------|---------------|----------------|-----------------------|------|-------------------------------|----------------------------|--------------|-----------------------------------|
| | (-) | (=) | | | (5) | (4) | (5) | | (-) |
| 5962-8761203VCA | Active | Production | CDIP (J) 14 | 25 TUBE | No | SNPB | N/A for Pkg Type | -55 to 125 | 5962-8761203VC A SNV54AC02J |
| 5962-8761203VCA.A | Active | Production | CDIP (J) 14 | 25 TUBE | No | SNPB | N/A for Pkg Type | -55 to 125 | 5962-8761203VC A SNV54AC02J |
| 5962-8761203VDA | Active | Production | CFP (W) 14 | 25 TUBE | No | SNPB | N/A for Pkg Type | -55 to 125 | 5962-8761203VD A SNV54AC02W |
| 5962-8761203VDA.A | Active | Production | CFP (W) 14 | 25 TUBE | No | SNPB | N/A for Pkg Type | -55 to 125 | 5962-8761203VD A SNV54AC02W |

⁽¹⁾ Status: For more details on status, see our product life cycle.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative

⁽²⁾ Material type: When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

⁽³⁾ RoHS values: Yes, No, RoHS Exempt. See the TI RoHS Statement for additional information and value definition.

⁽⁴⁾ Lead finish/Ball material: Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

⁽⁵⁾ MSL rating/Peak reflow: The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

⁽⁶⁾ Part marking: There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

PACKAGE OPTION ADDENDUM

www.ti.com 11-Nov-2025

and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

OTHER QUALIFIED VERSIONS OF SN54AC02-SP:

Catalog : SN54AC02-DIE

NOTE: Qualified Version Definitions:

Catalog - TI's standard catalog product

PACKAGE MATERIALS INFORMATION

www.ti.com 23-May-2025

TUBE



*All dimensions are nominal

| Device | Package Name | Package Type | Pins | SPQ | L (mm) | W (mm) | T (µm) | B (mm) |
|-------------------|--------------|--------------|------|-----|--------|--------|--------|--------|
| 5962-8761203VDA | W | CFP | 14 | 25 | 506.98 | 26.16 | 6220 | NA |
| 5962-8761203VDA.A | W | CFP | 14 | 25 | 506.98 | 26.16 | 6220 | NA |

W (R-GDFP-F14)

CERAMIC DUAL FLATPACK



NOTES:

- A. All linear dimensions are in inches (millimeters).
- B. This drawing is subject to change without notice.
- C. This package can be hermetically sealed with a ceramic lid using glass frit.
- D. Index point is provided on cap for terminal identification only.
- E. Falls within MIL STD 1835 GDFP1-F14



CERAMIC DUAL IN LINE PACKAGE



Images above are just a representation of the package family, actual package may vary. Refer to the product data sheet for package details.

4040083-5/G





CERAMIC DUAL IN LINE PACKAGE



NOTES:

- 1. All controlling linear dimensions are in inches. Dimensions in brackets are in millimeters. Any dimension in brackets or parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
- 2. This drawing is subject to change without notice.
- 3. This package is hermitically sealed with a ceramic lid using glass frit.
- His package is remitted by sealed with a ceramic its using glass mit.
 Index point is provided on cap for terminal identification only and on press ceramic glass frit seal only.
 Falls within MIL-STD-1835 and GDIP1-T14.



CERAMIC DUAL IN LINE PACKAGE



IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you fully indemnify TI and its representatives against any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale, TI's General Quality Guidelines, or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products. Unless TI explicitly designates a product as custom or customer-specified, TI products are standard, catalog, general purpose devices.

TI objects to and rejects any additional or different terms you may propose.

Copyright © 2025, Texas Instruments Incorporated

Last updated 10/2025