SCBS683H - MARCH 1997 - REVISED OCTOBER 2003


- Support Mixed-Mode Signal Operation (5-V Input and Output Voltages With 3.3-V V<sub>CC</sub>)
- Typical V<sub>OLP</sub> (Output Ground Bounce)
   <0.8 V at V<sub>CC</sub> = 3.3 V, T<sub>A</sub> = 25°C
- Support Unregulated Battery Operation Down to 2.7 V
- I<sub>off</sub> and Power-Up 3-State Support Hot Insertion
- Bus Hold on Data Inputs Eliminates the Need for External Pullup/Pulldown Resistors
- Latch-Up Performance Exceeds 500 mA Per JESD 17
- ESD Protection Exceeds JESD 22
  - 2000-V Human-Body Model (A114-A)
  - 200-V Machine Model (A115-A)

## description/ordering information


These octal flip-flops are designed specifically for low-voltage (3.3-V)  $V_{CC}$  operation, but with the capability to provide a TTL interface to a 5-V system environment.

The eight flip-flops of the 'LVTH374 devices are edge-triggered D-type flip-flops. On the positive transition of the clock (CLK) input, the Q outputs are set to the logic levels set up at the data (D) inputs.

#### SN54LVTH374...J OR W PACKAGE SN74LVTH374...DB, DW, NS, OR PW PACKAGE (TOP VIEW)



## SN54LVTH374 . . . FK PACKAGE (TOP VIEW)



## **ORDERING INFORMATION**

TA	PACK	AGE†	ORDERABLE PART NUMBER	TOP-SIDE MARKING
	0010 014	Tube SN74LVTH374DW		1.VT1107.4
	SOIC - DW	Tape and reel	SN74LVTH374DWR	LVTH374
4000 / 0500	SOP - NS	Tape and reel	SN74LVTH374NSR	LVTH374
–40°C to 85°C	SSOP – DB	Tape and reel	SN74LVTH374DBR	LXH374
	TOOOD DW	Tube	SN74LVTH374PW	1.7/1/07/4
	TSSOP - PW	Tape and reel	SN74LVTH374PWR	LXH374
	CDIP – J	Tube	SNJ54LVTH374J	SNJ54LVTH374J
−55°C to 125°C	CFP – W	Tube	SNJ54LVTH374W	SNJ54LVTH374W
	LCCC - FK	Tube	SNJ54LVTH374FK	SNJ54LVTH374FK

<sup>†</sup> Package drawings, standard packing quantities, thermal data, symbolization, and PCB design guidelines are available at www.ti.com/sc/package.



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.



processing does not necessarily include testing of all pa

SCBS683H - MARCH 1997 - REVISED OCTOBER 2003

## description/ordering information (continued)

A buffered output-enable (OE) input can be used to place the eight outputs in either a normal logic state (high or low logic levels) or the high-impedance state. In the high-impedance state, the outputs neither load nor drive the bus lines significantly. The high-impedance state and increased drive provide the capability to drive bus lines without need for interface or pullup components.

OE does not affect the internal operations of the flip-flops. Old data can be retained or new data can be entered while the outputs are in the high-impedance state.

When  $V_{CC}$  is between 0 and 1.5 V, the devices are in the high-impedance state during power up or power down. However, to ensure the high-impedance state above 1.5 V,  $\overline{OE}$  should be tied to  $V_{CC}$  through a pullup resistor; the minimum value of the resistor is determined by the current-sinking capability of the driver.


Active bus-hold circuitry holds unused or undriven inputs at a valid logic state. Use of pullup or pulldown resistors with the bus-hold circuitry is not recommended.

These devices are fully specified for hot-insertion applications using Ioff and power-up 3-state. The Ioff circuitry disables the outputs, preventing damaging current backflow through the devices when they are powered down. The power-up 3-state circuitry places the outputs in the high-impedance state during power up and power down, which prevents driver conflict.

**FUNCTION TABLE** (each flip-flop)

	INPUTS	OUTPUT	
OE	CLK	Q	
L	<b>↑</b>	Н	Н
L	$\uparrow$	L	L
L	H or L	Χ	$Q_0$
Н	X	Χ	Z

### logic diagram (positive logic)





SCBS683H - MARCH 1997 - REVISED OCTOBER 2003

## absolute maximum ratings over operating free-air temperature range (unless otherwise noted)†

Supply voltage range, V <sub>CC</sub> Input voltage range, V <sub>I</sub> (see Note 1)  Voltage range applied to any output in the high-impedance	
or power-off state, V <sub>O</sub> (see Note 1)	–0.5 V to 7 V
Voltage range applied to any output in the high state, VO (see Note 1)	$-0.5 \text{ V to V}_{CC} + 0.5 \text{ V}$
Current into any output in the low state, IO: SN54LVTH374	96 mA
SN74LVTH374	128 mA
Current into any output in the high state, IO (see Note 2): SN54LVTH374	48 mA
SN74LVTH374	64 mA
Input clamp current, I <sub>IK</sub> (V <sub>I</sub> < 0)	–50 mA
Output clamp current, I <sub>OK</sub> (V <sub>O</sub> < 0)	–50 mA
Package thermal impedance, θ <sub>JA</sub> (see Note 3): DB package	70°C/W
DW package	58°C/W
NS package	60°C/W
PW package	83°C/W
Storage temperature range, T <sub>stg</sub>	

<sup>†</sup> Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

- NOTES: 1. The input and output negative-voltage ratings may be exceeded if the input and output clamp-current ratings are observed.
  - 2. This current flows only when the output is in the high state and  $V_O > V_{CC}$ .
  - 3. The package thermal impedance is calculated in accordance with JESD 51-7.

## recommended operating conditions (see Note 4)

		SN54LV	TH374	SN74LV	TH374	
		MIN	MAX	MIN	MAX	UNIT
Vcc	Supply voltage	2.7	3.6	2.7	3.6	V
V <sub>IH</sub>	High-level input voltage	2		2		V
VIL	Low-level input voltage		0.8		8.0	V
VI	Input voltage		5.5		5.5	V
ІОН	High-level output current		-24		-32	mA
loL	Low-level output current		48		64	mA
Δt/Δν	Input transition rise or fall rate		10		10	ns/V
Δt/ΔV <sub>CC</sub>	Power-up ramp rate	200		200		μs/V
T <sub>A</sub>	Operating free-air temperature	-55	125	-40	85	°C

NOTE 4: All unused control inputs of the device must be held at V<sub>CC</sub> or GND to ensure proper device operation. Refer to the TI application report, *Implications of Slow or Floating CMOS Inputs*, literature number SCBA004.



SCBS683H - MARCH 1997 - REVISED OCTOBER 2003

## electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

VIK         VCC = 2.7 V.         I₁ = -18 mA         — 1.2					SN54	4LVTH37	4	SN74	LVTH37	4		
$V_{OH} = \begin{array}{ c c c c c } \hline V_{CC} & V_$	PARA	METER	TEST CO	ONDITIONS	MIN	TYP†	MAX	MIN	TYP†	MAX	UNIT	
$V_{OH} = \begin{array}{ c c c c c } \hline V_{CC} = 2.7 \ V, & I_{OH} = -8  \text{mA} & 2.4 & 2.4 \\ \hline V_{CC} = 3 \ V & I_{OH} = -24  \text{mA} & 2 \\ \hline I_{OH} = -22  \text{mA} & 2 \\ \hline V_{CC} = 2.7 \ V & I_{OL} = 100  \mu\text{A} & 0.2 & 0.2 \\ \hline I_{OL} = 100  \mu\text{A} & 0.5 & 0.5 \\ \hline V_{CC} = 2.7 \ V & I_{OL} = 16  \text{mA} & 0.4 & 0.4 \\ \hline I_{OL} = 16  \text{mA} & 0.4 & 0.4 & 0.4 \\ \hline I_{OL} = 32  \text{mA} & 0.5 & 0.5 \\ \hline I_{OL} = 48  \text{mA} & 0.55 & 0.5 \\ \hline I_{OL} = 64  \text{mA} & 0.55 & 0.5 \\ \hline V_{CC} = 3.6 \ V, & V_{I} = 0.55 \ V & 10 & 10 \\ \hline Data & V_{CC} = 3.6 \ V, & V_{I} = V_{CC}  \text{or GND} & \pm 1 \\ \hline I_{I} & V_{CC} = 3.6 \ V, & V_{I} = V_{CC}  \text{or GND} & \pm 1 \\ \hline I_{I} & V_{CC} = 3.6 \ V, & V_{I} = 0.8 \ V & 75 & 75 \\ \hline V_{CC} = 3.6 \ V, & V_{I} = 0.8 \ V & 75 & 75 \\ \hline V_{CC} = 3.6 \ V, & V_{I} = 0  \text{to } 3.6 \ V & -75 \\ \hline I_{OZH} & V_{CC} = 3.6 \ V, & V_{O} = 0.5 \ V & -75 \\ \hline I_{OZPU} & V_{CC} = 3.6 \ V, & V_{O} = 0.5 \ V & 0.5 \ V & -5 \\ \hline I_{OZPD} & V_{CC} = 3.6 \ V, & V_{O} = 0.5 \ V & 0.5 \ V & 0.5 \ V_{OE} = 3.6 \ V, & V_{O} = 0.5 \ V & 0.5 \ V_{OE} = 0.5 \ V & 0.5 \ V_{OE} = 3.6 \ V, & V_{O} = 0.5 \ V & 0.5 \ V_{OE} = 3.6 \ V, & V_{O} = 0.5 \ V & 0.5 \ V_{OE} = 3.6 \ V, & V_{O} = 0.5 \ V & 0.5 \ V_{OE} = 3.6 \ V, & V_{O} = 0.5 \ V & 0.5 \ V_{OE} = 3.6 \ V, & V_{O} = 0.5 \ V & 0.5 \ V_{OE} = 3.6 \ V, & V_{O} = 0.5 \ V & 0.5 \ V_{OE} = 3.6 \ V, & V_{O} = 0.5 \ V & 0.5 \ V_{OE} = 3.6 \ V, & V_{O} = 0.5 \ V & 0.5 \ V_{OE} = 3.6 \ V, & V_{O} = 0.5 \ V & 0.5 \ V_{OE} = 3.6 \ V_{OE$	VIK		$V_{CC} = 2.7 \text{ V},$	I <sub>I</sub> = -18 mA			-1.2			-1.2	V	
VoH			$V_{CC} = 2.7 \text{ V to } 3.6 \text{ V},$	$I_{OH} = -100  \mu A$	V <sub>CC</sub> -0.2			V <sub>CC</sub> -0.2				
VCC = 3 V   IOH = -24 mA   2   2   2   2   2   2   2   2   2	V		$V_{CC} = 2.7 V$ ,	$I_{OH} = -8 \text{ mA}$	2.4			2.4			V	
VOL    Voc = 2.7 V   IoL = 100 µA   0.2   0.2   0.2     IoL = 100 µA   0.5   0.5     IoL = 24 mA   0.4   0.4     Voc = 3 V   IoL = 32 mA   0.5   0.5     IoL = 48 mA   0.55   0.55     IoL = 48 mA   0.55   0.55     IoL = 48 mA   0.55   0.55     IoL = 64 mA   0.55   0.55     IoL = 7.5   0.55   0.55     IoL = 8.6 V   VI = VCC   0.5 V   0.5 V     IoL = 8.6 V   VI = VCC   0.5 V   0.5 V     IoL = 8.6 V   VI = 0.8 V   0.55   0.55     IoL = 8.6 V   VI = 0.8 V   0.55   0.55     Iol = 8.6 V   VI = 0.5 V   0.5 V   0.5 V     Iol = 0.5 V	∨ОН		V 2 V	$I_{OH} = -24 \text{ mA}$	2						V	
Vol			vCC = 2 v	$I_{OH} = -32 \text{ mA}$				2				
OL = 24 mA   O.5   O.5     OL = 16 mA   O.4   O.4     OL = 32 mA   O.5   O.5     OL = 48 mA   O.55     OL = 40 m			Vaa - 27V	I <sub>OL</sub> = 100 μA			0.2			0.2		
$V_{CC} = 3 \text{ V} \qquad \begin{array}{ c c c c c c c c c c c c c c c c c c c$			vCC = 2.7 v	I <sub>OL</sub> = 24 mA			0.5			0.5		
VCC = 3 V	Voi			I <sub>OL</sub> = 16 mA			0.4			0.4	V	
IOL = 48 MA	VOL		V 2.V	$I_{OL} = 32 \text{ mA}$			0.5			0.5	V	
			ACC = 2 A	$I_{OL} = 48 \text{ mA}$			0.55					
$   I_{\text{I}}   \begin{array}{ c c c c c } \hline \text{Control} & \text{VCC} = 3.6  \text{V}, & \text{V}_{\text{I}} = \text{VCC} \text{ or GND} & \pm 1 & \pm 1 \\ \hline \text{Data} & \text{Inputs} & \text{VCC} = 3.6  \text{V} & \begin{array}{ c c c c c } \hline \text{V}_{\text{I}} = \text{VCC} & \text{I} & 1 & 1 \\ \hline \text{V}_{\text{I}} = 0 & -5 & -5 & -5 \\ \hline \text{Ioff} & \text{VCC} = 0, & \text{V}_{\text{I}} \text{ or V}_{\text{O}} = 0 \text{ to } 4.5  \text{V} \\ \hline \text{V}_{\text{I}} = 0 & -75 & -75 & -75 \\ \hline \text{V}_{\text{I}} = 2  \text{V} & -75 & -75 & -75 \\ \hline \text{V}_{\text{I}} = 2  \text{V} & -75 & -75 & -75 \\ \hline \text{IOZH} & \text{VCC} = 3.6  \text{V}, & \text{V}_{\text{I}} = 0 \text{ to } 3.6  \text{V} & -75 & -75 \\ \hline \text{IOZPU} & \begin{array}{ c c c c c c c c c c c c c c c c c c c$				$I_{OL} = 64 \text{ mA}$						0.55		
$ \begin{array}{ c c c c c c } \hline I_I & inputs & VCC = 3.6 \ V, & V_I = VCC \ or \ GND & \pm 1 & \pm 1 \\ \hline Data & V_{CC} = 3.6 \ V & V_I = V_{CC} & 1 & 1 & 1 \\ \hline I_{OM} & V_{CC} = 0, & V_{I} \ or \ V_{OC} = 0, & V_{I} \ or \ V_{OC} = 0 \ ot \ 0.5 \ \hline V_{I} = 0 \ ot \ 0.5 \ \hline V_{I} = 0 \ ot \ 0.5 \ \hline V_{I} = 0 \ ot \ 0.5 \ \hline V_{I} = 0 \ ot \ 0.5 \ \hline V_{I} = 0 \ ot \ 0.5 \ \hline V_{I} = 0 \ ot \ 0.5 \ \hline V_{I} = 0 \ ot \ 0.5 \ \hline V_{I} = 0 \ ot \ 0.5 \ \hline V_{I} = 0 \ ot \ 0.5 \ \hline V_{I} = 0 \ ot \ 0.5 \ \hline V_{I} = 0 \ ot \ 0.5 \ \hline V_{I} = 0 \ ot \ 0.5 \ \hline V_{I} = 0 \ ot \ 0.5 \ \hline V_{I} = 0 \ ot \ 0.5 \ \hline V_{I} = 0 \ ot \ 0.5 \ \hline V_{I} = 0 \ ot \ 0.5 \ \hline V_{I} = 0 \ ot \ 0.5 \ ot \ 0.5 \ \hline V_{I} = 0 \ ot \ 0.5 \ ot \ 0.5 \ ot \ 0.5 \ \hline V_{I} = 0 \ ot \ 0.5 \ ot \ 0.$			$V_{CC} = 0 \text{ or } 3.6 \text{ V},$	V <sub>I</sub> = 5.5 V			10			10		
$ \begin{array}{ c c c c c c } \hline & Data & V_{CC} = 3.6 \ V & \hline & V_{I} = V_{CC} & 1 & 1 & 1 \\ \hline & I_{Off} & V_{CC} = 0, & V_{I} \text{ or } V_{O} = 0 \text{ to } 4.5 \ V & & & & & & & & \\ \hline & I_{I(hold)} & Data & V_{CC} = 3 \ V & \hline & V_{I} = 0.8 \ V & \hline & V_{I} = 0 \ V_{I} = 0.8 \ V & \hline & V_{I} = 0 \ V_{I} = 0.8 \ V & \hline & V_{I} = 0 \ V_{I} = 0.8 \ V & \hline & V_{I} = 0 \ V_{I} = 0.8 \ V & \hline & V_{I} = 0 \ V_{I} = 0.8 \ V & \hline & V_{I} = 0 \ V_{I} = 0.8 \ V & \hline & V_{I} = 0 \ V_{I} = 0.8 \ V & \hline & V_{I} = 0 \ V_{I} = 0.8 \ V & \hline & V_{I} = 0 \ V_{I} = 0.8 \ V & \hline & V_{I} = 0 \ V_{I} = 0.8 \ V_{I} = 0.8 \ V_{I} & \hline & V_{I} = 0 \ V_{I} = 0.8 \ V_{I} & \hline & V_{I} = 0 \ V_{I} = 0.5 \ V & V_{I} = 0.5 \ V_{I} = 0.5 \ V & V_{I} = 0.5 \ V_{I} = 0.5 \ V & V_{I} = 0.5 \ V & V_{I} = 0.5 \ V & V_{I} = 0.5 \ V_{I} = 0.5 \ V & V_{I} = 0.5 \ V_{I} = 0.5 \ V & V_{I} = 0.5 \ V_{I} = 0.5 \ V & V_{I} = 0.5 \ V_{I} =$	l <sub>i</sub>		V <sub>CC</sub> = 3.6 V,	$V_I = V_{CC}$ or GND			±1			±1	μА	
Injust	•	Data		VI = VCC			1			1	·	
$   I_{\text{I}(\text{hold})}   \text{Data} \\ \text{inputs}   \text{Data} \\ \text{inputs}   \text{VCC} = 3 \text{ V} \\ \text{V}_{\text{I}} = 2 \text{ V} \\ \text{V}_{\text{I}} = $		inputs	ACC = 3.9 A	V <sub>I</sub> = 0			-5			-5		
$ \begin{array}{ c c c c c } \hline I_{I}(hold) & Data \\ inputs & \hline \\ V_{CC} = 3.6 \text{ V}^{\ddagger}, & V_{I} = 0 \text{ to } 3.6 \text{ V} \\ \hline \\ V_{CC} = 3.6 \text{ V}^{\ddagger}, & V_{I} = 0 \text{ to } 3.6 \text{ V} \\ \hline \\ I_{OZH} & V_{CC} = 3.6 \text{ V}, & V_{O} = 3 \text{ V} \\ \hline \\ I_{OZL} & V_{CC} = 3.6 \text{ V}, & V_{O} = 0.5 \text{ V} \\ \hline \\ I_{OZPU} & \hline \\ \hline \\ V_{CC} = 0 \text{ to } 1.5 \text{ V}, V_{O} = 0.5 \text{ V} \text{ to } 3 \text{ V}, \\ \hline \\ I_{OZPU} & \hline \\ \hline \\ I_{OZPD} & \hline \\ \hline \\ V_{CC} = 1.5 \text{ V to } 0, V_{O} = 0.5 \text{ V to } 3 \text{ V}, \\ \hline \\ \hline \\ I_{OZPD} & \hline \\ \hline \\ V_{CC} = 3.6 \text{ V}, & \hline \\ \hline \\ V_{CC} = 3.6 \text{ V}, & \hline \\ \hline \\ V_{CC} = 3.6 \text{ V}, & \hline \\ \hline \\ V_{CC} = 3.6 \text{ V}, & \hline \\ \hline \\ V_{CC} = 3.6 \text{ V}, & \hline \\ \hline \\ V_{CC} = 3.6 \text{ V}, & \hline \\ \hline \\ V_{CC} = 3.6 \text{ V}, & \hline \\ \hline \\ V_{CC} = 3.6 \text{ V}, & \hline \\ \hline \\ V_{CC} = 3.6 \text{ V}, & \hline \\ \hline \\ V_{CC} = 3.6 \text{ V}, & \hline \\ \hline \\ V_{CC} = 3.6 \text{ V}, & \hline \\ \hline \\ V_{CC} = 3.6 \text{ V}, & \hline \\ \hline \\ \hline \\ V_{CC} = 3.6 \text{ V}, & \hline \\ \hline \\ \hline \\ V_{CC} = 3.6 \text{ V}, & \hline \\ \hline \\ \hline \\ V_{CC} = 3.6 \text{ V}, & \hline \\ \hline$	l <sub>off</sub>		$V_{CC} = 0$ ,	$V_I$ or $V_O = 0$ to 4.5 $V$						±100	μΑ	
$ \begin{array}{ c c c c c c } \hline II(hold) & Data & VI = 2 \ V & -75 & -75 \\ \hline Iozh & V_{CC} = 3.6 \ V^{\ddagger}, & V_{I} = 0 \ to \ 3.6 \ V & 5 & 5 \\ \hline Iozh & V_{CC} = 3.6 \ V, & V_{O} = 3 \ V & 5 & 5 \\ \hline Iozh & V_{CC} = 3.6 \ V, & V_{O} = 0.5 \ V & -5 & -5 \\ \hline Iozh & V_{CC} = 0 \ to \ 1.5 \ V, \ V_{O} = 0.5 \ V \ to \ 3 \ V, & \pm 100^* & \pm 100 \\ \hline Iozh & V_{CC} = 1.5 \ V \ to \ 0, \ V_{O} = 0.5 \ V \ to \ 3 \ V, & \pm 100^* & \pm 100 \\ \hline Iozh & V_{CC} = 3.6 \ V, & Outputs \ high & 0.19 & 0.19 \\ \hline Ioc & V_{CC} = 3.6 \ V, & Outputs \ low & 5 & 5 \\ \hline V_{CC} = 3.6 \ V, & Outputs \ low & 5 & 5 \\ \hline V_{CC} = 3.6 \ V, & Outputs \ low & 5 & 5 \\ \hline V_{CC} = 3.6 \ V, & Outputs \ low & 5 & 5 \\ \hline V_{CC} = 3.6 \ V, & Outputs \ low & 5 & 5 \\ \hline V_{CC} = 3.6 \ V, & Outputs \ low & 5 & 5 \\ \hline V_{CC} = 3.6 \ V, & Outputs \ low & 5 & 5 \\ \hline V_{CC} = 3.6 \ V, & Outputs \ disabled & 0.19 & 0.19 \\ \hline \hline V_{CC} = 3 \ V \ to \ 3.6 \ V, One \ input \ at \ V_{CC} - 0.6 \ V, & 0.3 \\ \hline \end{array}$			Vaa – 2 V	V <sub>I</sub> = 0.8 V	75			75				
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	li(bold)		∧CC = 2 ∧	V <sub>I</sub> = 2 V	-75			-75			μΑ	
$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	·i(riola)	inputs	$V_{CC} = 3.6 V^{\ddagger},$	$V_{I} = 0 \text{ to } 3.6 \text{ V}$							μ	
$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	lozh		V <sub>CC</sub> = 3.6 V,	V <sub>O</sub> = 3 V			5			5	μΑ	
IOZPU $\overline{OE}$ = don't care       ±100         IOZPD $\frac{V_{CC}}{OE}$ = 1.5 V to 0, $V_{O}$ = 0.5 V to 3 V, $\frac{100^{\circ}}{OE}$ = don't care       ±100*         V <sub>CC</sub> = 3.6 V, $\frac{1}{O}$ = 0, $\frac{1}{O}$ = 0.19       0.19         V <sub>CC</sub> = 3.6 V, $\frac{1}{O}$ = 0, $\frac{1}{O}$ = 0.19       0.19         Outputs low $\frac{1}{O}$ = 0.19       0.19         Outputs disabled       0.19	lozL		V <sub>CC</sub> = 3.6 V,	V <sub>O</sub> = 0.5 V			-5			-5	μΑ	
OZPD   OE = don't care	lozpu			0.5 V to 3 V,			±100*			±100	μА	
ICC $\begin{vmatrix} V_{CC} = 3.6 \text{ V}, \\ I_{O} = 0, \\ V_{I} = V_{CC} \text{ or GND} \end{vmatrix}$ Outputs low $\begin{vmatrix} 5 \\ 0.19 \end{vmatrix}$ Outputs disabled 0.19 0.19	lozpd		$\frac{V_{CC}}{OE} = 1.5 \text{ V to } 0, V_{O} = 0$	0.5 V to 3 V,			±100*			±100	μА	
ICC $I_O = 0$ , $V_I = V_{CC}$ or GNDOutputs low55Outputs disabled0.190.19			Vcc = 3.6 V.	Outputs high			0.19			0.19		
$V_I = V_{CC}$ or GND Outputs disabled 0.19 0.19 0.19 $V_{CC} = 3 \text{ V to } 3.6 \text{ V, One input at } V_{CC} - 0.6 \text{ V,}$	ICC		$I_{O} = 0$ ,	Outputs low			5			5	mA	
$\Delta I_{CC}$ $V_{CC} = 3 \text{ V to } 3.6 \text{ V, One input at } V_{CC} - 0.6 \text{ V,}$ 0.2			$V_I = V_{CC}$ or GND	Outputs disabled			0.19			0.19		
Other Inputs at VCC or GND	ΔlCC§		V <sub>CC</sub> = 3 V to 3.6 V, One Other inputs at V <sub>CC</sub> or	e input at V <sub>CC</sub> – 0.6 V, GND		_	0.2			0.2	mA	
C <sub>i</sub> V <sub>I</sub> = 3 V or 0 3	Ci		V <sub>I</sub> = 3 V or 0			3			3		pF	
$C_0$ $V_0 = 3 \text{ V or } 0$ 7			V <sub>O</sub> = 3 V or 0			7			7		pF	

<sup>\*</sup> On products compliant to MIL-PRF-38535, this parameter is not production tested.



<sup>†</sup> All typical values are at  $V_{CC} = 3.3 \text{ V}$ ,  $T_A = 25^{\circ}\text{C}$ .

<sup>‡</sup> This is the bus-hold maximum dynamic current. It is the minimum overdrive current required to switch the input from one state to another.

<sup>§</sup> This is the increase in supply current for each input that is at the specified TTL voltage level, rather than VCC or GND.

SCBS683H - MARCH 1997 - REVISED OCTOBER 2003

## timing requirements over recommended operating free-air temperature range (unless otherwise noted) (see Figure 1)

			SN54L\	/TH374	H374		SN74L\	/TH374		
		V <sub>CC</sub> = 3.3 V ± 0.3 V V <sub>CC</sub> =		= 2.7 V $V_{CC} = 3.3 \text{ V} \pm 0.3 \text{ V}$		3.3 V 3 V	V <sub>CC</sub> = 2.7 V		UNIT	
		MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	
fclock	Clock frequency		150		150		150		150	MHz
t <sub>W</sub>	Pulse duration, CLK high or low	3.3		3.3		3.3		3.3		ns
t <sub>su</sub>	Setup time, data before CLK↑	1.6		2		1.5		2		ns
th	Hold time, data after CLK↑	0.8		0.5		0.8		0		ns

# switching characteristics over recommended ranges of supply voltage and operating free-air temperature, $C_L = 50$ pF (unless otherwise noted) (see Figure 1)


				SN54LVTH374				SN7	74LVTH	374		
PARAMETER FROM (INPUT)		TO (OUTPUT)		$V_{CC}$ = 3.3 V $\pm$ 0.3 V		V <sub>CC</sub> = 2.7 V		$^{\pm}$ 0.3 V $^{\pm}$		V <sub>CC</sub> = 2.7 V		UNIT
			MIN	MAX	MIN	MAX	MIN	TYP <sup>†</sup>	MAX	MIN	MAX	
f <sub>max</sub>			150		150		150			150		MHz
t <sub>PLH</sub>	OL K	_	1	5.1		5.6	1.8	2.9	4.5		5	
t <sub>PHL</sub>	CLK	Q	1.5	5.1		5.2	1.8	2.9	4.2		4.3	ns
<sup>t</sup> PZH	ŌĒ	_	0.8	5.6		6.6	1.3	2.8	4.7		5.6	
tPZL	OE	Q	1.2	5.4		6.2	1.6	3	4.7		5.2	ns
t <sub>PHZ</sub>	ŌĒ	0	1.5	5.6		5.7	1.9	3	4.6	·	4.9	20
t <sub>PLZ</sub>	OE .	Q	0.8	5.2		5.3	2	3.1	4.5	·	4.6	ns

 $<sup>\</sup>overline{\dagger}$  All typical values are at V<sub>CC</sub> = 3.3 V, T<sub>A</sub> = 25°C.



SCBS683H - MARCH 1997 - REVISED OCTOBER 2003

#### PARAMETER MEASUREMENT INFORMATION



NOTES: A. C<sub>1</sub> includes probe and jig capacitance.

- B. Waveform 1 is for an output with internal conditions such that the output is low except when disabled by the output control. Waveform 2 is for an output with internal conditions such that the output is high except when disabled by the output control.
- C. All input pulses are supplied by generators having the following characteristics: PRR  $\leq$  10 MHz,  $Z_Q = 50 \ \Omega$ ,  $t_f \leq$  2.5 ns,  $t_f \leq$  2.5 ns.
- D. The outputs are measured one at a time with one transition per measurement.
- E. All parameters and waveforms are not applicable to all devices.

Figure 1. Load Circuit and Voltage Waveforms



www.ti.com 11-Nov-2025

#### PACKAGING INFORMATION

Orderable part number	Status	Material type	Package   Pins	Package qty   Carrier	RoHS (3)	Lead finish/ Ball material	MSL rating/ Peak reflow	Op temp (°C)	Part marking (6)
						(4)	(5)		
5962-9951001QSA	Active	Production	CFP (W)   20	25   TUBE	No	SNPB	N/A for Pkg Type	-55 to 125	5962-9951001QS A SNJ54LVTH374W
SN74LVTH374DBR	Active	Production	SSOP (DB)   20	2000   LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	LXH374
SN74LVTH374DBR.B	Active	Production	SSOP (DB)   20	2000   LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	LXH374
SN74LVTH374DW	Active	Production	SOIC (DW)   20	25   TUBE	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	LVTH374
SN74LVTH374DW.B	Active	Production	SOIC (DW)   20	25   TUBE	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	LVTH374
SN74LVTH374DWR	Active	Production	SOIC (DW)   20	2000   LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	LVTH374
SN74LVTH374DWR.B	Active	Production	SOIC (DW)   20	2000   LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	LVTH374
SN74LVTH374DWRG4	Active	Production	SOIC (DW)   20	2000   LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	LVTH374
SN74LVTH374DWRG4.B	Active	Production	SOIC (DW)   20	2000   LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	LVTH374
SN74LVTH374NSR	Active	Production	SOP (NS)   20	2000   LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	LVTH374
SN74LVTH374NSR.B	Active	Production	SOP (NS)   20	2000   LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	LVTH374
SN74LVTH374PW	Active	Production	TSSOP (PW)   20	70   TUBE	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	LXH374
SN74LVTH374PW.B	Active	Production	TSSOP (PW)   20	70   TUBE	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	LXH374
SN74LVTH374PWR	Active	Production	TSSOP (PW)   20	2000   LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	LXH374
SN74LVTH374PWR.B	Active	Production	TSSOP (PW)   20	2000   LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	LXH374
SNJ54LVTH374W	Active	Production	CFP (W)   20	25   TUBE	No	SNPB	N/A for Pkg Type	-55 to 125	5962-9951001QS A SNJ54LVTH374W

<sup>(1)</sup> Status: For more details on status, see our product life cycle.

<sup>(2)</sup> Material type: When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

<sup>(3)</sup> RoHS values: Yes, No, RoHS Exempt. See the TI RoHS Statement for additional information and value definition.

<sup>(4)</sup> Lead finish/Ball material: Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

## PACKAGE OPTION ADDENDUM

www.ti.com 11-Nov-2025

(5) MSL rating/Peak reflow: The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

(6) Part marking: There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

#### OTHER QUALIFIED VERSIONS OF SN54LVTH374, SN74LVTH374:

Catalog: SN74LVTH374

Enhanced Product: SN74LVTH374-EP, SN74LVTH374-EP

Military: SN54LVTH374

NOTE: Qualified Version Definitions:

- Catalog TI's standard catalog product
- Enhanced Product Supports Defense, Aerospace and Medical Applications
- Military QML certified for Military and Defense Applications

## **PACKAGE MATERIALS INFORMATION**

www.ti.com 24-Jul-2025

## TAPE AND REEL INFORMATION





	-
A0	Dimension designed to accommodate the component width
В0	Dimension designed to accommodate the component length
K0	Dimension designed to accommodate the component thickness
W	Overall width of the carrier tape
P1	Pitch between successive cavity centers

## QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE



#### \*All dimensions are nominal

Device	Package Type	Package Drawing		SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
SN74LVTH374DBR	SSOP	DB	20	2000	330.0	16.4	8.2	7.5	2.5	12.0	16.0	Q1
SN74LVTH374DWR	SOIC	DW	20	2000	330.0	24.4	10.8	13.3	2.7	12.0	24.0	Q1
SN74LVTH374DWRG4	SOIC	DW	20	2000	330.0	24.4	10.8	13.3	2.7	12.0	24.0	Q1
SN74LVTH374NSR	SOP	NS	20	2000	330.0	24.4	8.4	13.0	2.5	12.0	24.0	Q1
SN74LVTH374PWR	TSSOP	PW	20	2000	330.0	16.4	6.95	7.0	1.4	8.0	16.0	Q1



www.ti.com 24-Jul-2025



#### \*All dimensions are nominal

7 til dillionoriono di o mominar							
Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
SN74LVTH374DBR	SSOP	DB	20	2000	353.0	353.0	32.0
SN74LVTH374DWR	SOIC	DW	20	2000	356.0	356.0	45.0
SN74LVTH374DWRG4	SOIC	DW	20	2000	356.0	356.0	45.0
SN74LVTH374NSR	SOP	NS	20	2000	356.0	356.0	45.0
SN74LVTH374PWR	TSSOP	PW	20	2000	353.0	353.0	32.0

## **PACKAGE MATERIALS INFORMATION**

www.ti.com 24-Jul-2025

## **TUBE**



## \*All dimensions are nominal

Device	Package Name	Package Type	Pins	SPQ	L (mm)	W (mm)	T (µm)	B (mm)
SN74LVTH374DW	DW	SOIC	20	25	507	12.83	5080	6.6
SN74LVTH374DW.B	DW	SOIC	20	25	507	12.83	5080	6.6
SN74LVTH374PW	PW	TSSOP	20	70	530	10.2	3600	3.5
SN74LVTH374PW.B	PW	TSSOP	20	70	530	10.2	3600	3.5

## W (R-GDFP-F20)

## CERAMIC DUAL FLATPACK



- A. All linear dimensions are in inches (millimeters).
- This drawing is subject to change without notice.
- C. This package can be hermetically sealed with a ceramic lid using glass frit.

  D. Index point is provided on cap for terminal identification only.

  E. Falls within Mil—Std 1835 GDFP2—F20







- 1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.

  2. This drawing is subject to change without notice.

  3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not
- exceed 0.15 mm per side.
- 4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.25 mm per side.
- 5. Reference JEDEC registration MO-153.





NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.

7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.





NOTES: (continued)

- 8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
- 9. Board assembly site may have different recommendations for stencil design.







- 1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.

  2. This drawing is subject to change without notice.

  3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not
- exceed 0.15 mm per side.
- 4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.25 mm per side.
- 5. Reference JEDEC registration MO-150.





NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.

7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.





NOTES: (continued)

- 8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
- 9. Board assembly site may have different recommendations for stencil design.



## **MECHANICAL DATA**

## NS (R-PDSO-G\*\*)

## 14-PINS SHOWN

## PLASTIC SMALL-OUTLINE PACKAGE



- A. All linear dimensions are in millimeters.
- B. This drawing is subject to change without notice.
- C. Body dimensions do not include mold flash or protrusion, not to exceed 0,15.





SOIC



- 1. All linear dimensions are in millimeters. Dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.

  2. This drawing is subject to change without notice.

  3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not
- exceed 0.15 mm per side.
- 4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.43 mm per side.
- 5. Reference JEDEC registration MS-013.



SOIC



NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.

7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.



SOIC



NOTES: (continued)

- 8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
- 9. Board assembly site may have different recommendations for stencil design.



## IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you fully indemnify TI and its representatives against any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale, TI's General Quality Guidelines, or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products. Unless TI explicitly designates a product as custom or customer-specified, TI products are standard, catalog, general purpose devices.

TI objects to and rejects any additional or different terms you may propose.

Copyright © 2025, Texas Instruments Incorporated

Last updated 10/2025