

AUDIO CODEC AC'97 VOLTAGE-TRANSLATION TRANSCEIVER

FEATURES


- Voltage-Level Transceiver for Interfacing 1.8 V Audio Codec (AC'97) Controllers With 3.3 V AC'97 Codec Links
- Configurable I/O Switching Levels With Dual-Supply Pins Operating Over Full 1.2-V to 3.6-V Power-Supply Range
- For Low-Power Operation, A and B Ports Are Placed in High-Impedance State When Either Supply Voltage Is Switched Off

PW PACKAGE

- Latch-Up Performance Exceeds 100 mA Per JESD 78, Class II
 SD Protection Exceeds JESD 22
- ESD Protection Exceeds JESD 22
 - 7000-V Human-Body Model (A114-A)
 - 200-V Machine Model (A115-A)
 - 1500-V Charged-Device Model (C101)

(TOP VIEW) DIR2 □ 10 20 □ DIR1 $\stackrel{-}{\equiv} \bar{\mathsf{v}}_{\mathsf{CCB}}$ CCA 💳 19 2 Å4 □□ — В¥́ 18 A5 □□ — B5 17 4 GND □ 5 16 ightharpoons GND **—** В6 A6 □ 6 15 A1 □□ 14 ___ B2 A3 □ 8 13 □ B3 DNU \square 9 12 A2 □ 10 11 □ DIR(345)

RGY PACKAGE (BOTTOM VIEW)



The exposed center pad, if used, must be connected as a secondary ground or left electrically open.

TERMINAL ASSIGNMENTS (20-Ball ZXY Package)

	Α	В	С	D
5	V_{CCA}	DIR2	DIR1	V_{CCB}
4	A5	A4	B4	B5
3	A6	GND	GND	B6
2	А3	A1	B2	B1
1	DNU ⁽¹⁾	A2	DIR(345)	В3

(1) DNU - Do not use; should be left unconnected

DESCRIPTION/ORDERING INFORMATION

The SN74AVC6T622 is a voltage-level transceiver for interfacing 1.8 V audio codec (AC'97) controllers, the audio/analog modem functionality found in personal computers, with 3.3V AC'97 codec links. With the digital switching levels of today's AC'97 codecs lowering to 1.8-V logic levels, the SN74AVC6T622 device can be used to bridge the gap between legacy 3.3-V AC'97 codecs and AC'97 controllers that are now operating at 1.8 V. The 6-bit wide SN74AVC6T622 device complies with the AC'97 electrical interface (both levels and timing) specification.



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.



Two supply-voltage pins allow the A-port and B-port input switching thresholds to be configured separately. The A port is designed to track V_{CCA} , while the B port is designed to track V_{CCB} . V_{CCA} and V_{CCB} can accept any supply voltage from 1.2 V to 3.6 V.

If either V_{CC} is switched off ($V_{CCA} = 0 \text{ V}$ and/or $V_{CCB} = 0 \text{ V}$), all outputs are placed in the high-impedance state to conserve power.

The SN74AVC6T622 is available in two 0.5-mm-pitch ball grid array (BGA) packages. The 20-ball package has dimensions of 3 mm × 2.5 mm, and the 24-ball package measures 3 mm × 3 mm. Memory cards are widely used in mobile phones, PDAs, digital cameras, personal media players, camcorders, set-top boxes, etc. Low static power consumption and small package size make the SN74AVC6T622 an ideal choice for these applications.

ORDERING INFORMATION

T _A	PACKAGE ⁽¹⁾⁽²⁾)	ORDERABLE PART NUMBER	TOP-SIDE MARKING
	QFN – RGY	Reel of 1000	SN74AVC6T622RGYR	WU622
-40°C to 85°C	TSSOP – PW	Reel of 2000	SN74AVC6T622PWR	WU622
	UFBGA – ZXY (Pb-Free)	Reel of 2500	SN74AVC6T622ZXYR	WU622

- (1) Package drawings, thermal data, and symbolization are available at www.ti.com/packaging.
- (2) For the most current package and ordering information, see the Package Option Addendum at the end of this document, or see the TI website at www.ti.com.

REFERENCE DESIGN




Figure 1. Interfacing 1.8 V AC'97 Controllers With 3.3 V AC'97 Controllers



TERMINAL FUNCTIONS

ZXY BALL NO.	RGY, PW PIN NO.	NAME	TYPE	DESCRIPTION
A1	9	DNU		Do not use; leave unconnected
A2	8	А3	I	AC'97 controller SYNC signal
A3	6	A6	I	AC'97 controller BIT_CLK signal
A4	4	A5	- 1	AC'97 controller RESET signal
A5	2	V _{CCA}	Pwr	A-port supply voltage. V _{CCA} powers all A-port I/Os and control pins.
B1	10	A2	0	AC'97 controller SDATA_In0 signal
B2	7	A1	I/O	GPIO to miscellaneous GPIO controller
B3, C3	5, 16	GND	_	Ground
B4	3	A4	I	AC'97 controller SDATA_Out signal
B5	1	DIR2	_	Should be tied to GND
C1	11	DIR(345)	_	Should be tied to V _{CCA}
C2	14	B2	ı	Secondary AC'97 codec SDATA_Out signal
C4	18	B4	0	Secondary AC'97 codec SDATA_In signal
C5	20	DIR1	- 1	Direction control from miscellaneous GPIO controller
D1	12	В3	0	Secondary AC'97 codec SYNC signal
D2	13	B1	0	Optional GPIO signal if A1 is enabled
D3	15	В6	0	Secondary AC'97 codec BIT_CLK_In signal
D4	17	B5	0	Secondary AC'97 codec RESET signal
D5	19	V _{CCB}	Pwr	B-port supply voltage. V _{CCB} powers all B-port I/Os and control pins.



FUNCTION TABLES


CONTROL INPUT DIR2	OUTPUT	OUTPUT CIRCUITS						
	A2	B2	OPERATION					
High	Hi-Z	Enabled	A2 to B2					
Low	Enabled	Hi-Z	B2 to A2					

CONTROL INPUT DIR1	OUTPUT	FUNCTION	
	A1	B1	FUNCTION
High	Hi-Z	Enabled	A1 to B1
Low	Enabled	Hi-Z	B1 to A1

CONTROL INPUT	OUTPUT	FUNCTION	
DIR(345)	A3, A4, A5	B3, B4, B5	FUNCTION
			A3 to B3
High	Hi-Z	Enabled	A4 to B4
			A5 to B5
			B3 to A3
Low	Enabled	Hi-Z	B4 to A4
			B5 to A5



LOGIC DIAGRAM (POSITIVE LOGIC)





ABSOLUTE MAXIMUM RATINGS(1)

over operating free-air temperature range (unless otherwise noted)

			MIN	MAX	UNIT
V _{CCA} V _{CCB}	Supply voltage range		-0.5	4.6	٧
		I/O ports (A port)	-0.5	4.6	
V_{I}	Input voltage range (2)	I/O ports (B port)	-0.5	4.6	V
		Control inputs	-0.5	4.6	
\/	Voltage range applied to any output	A port	-0.5	4.6	V
Vo	in the high-impedance or power-off state (2)	B port	-0.5	4.6	V
\/	Valtage range applied to any output in the high or law state (2)(3)	A port	-0.5	$-0.5 V_{CCA} + 0.5$	
Vo	Voltage range applied to any output in the high or low state (2)(3)	B port	-0.5	V _{CCB} + 0.5	V
I _{IK}	Input clamp current	V _I < 0		-50	mA
I _{OK}	Output clamp current	V _O < 0		-50	mA
Io	Continuous output current	·		±50	mA
	Continuous current through V _{CCA} , V _{CCB} , or GND			±100	mA
		PW package ⁽⁴⁾		83	
θ_{JA}	Package thermal impedance	RGY package (5)		37	°C/W
		ZXY package ⁽⁴⁾		193	
T _{stg}	Storage temperature range		-65	150	°C

⁽¹⁾ Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability. The input voltage and output negative-voltage ratings may be exceeded if the input and output current ratings are observed.

The output positive-voltage rating may be exceeded up to 4.6 V maximum if the output current rating is observed.

The package thermal impedance is calculated in accordance with JESD 51-7.

The package thermal impedance is calculated in accordance with JESD 51-5.



RECOMMENDED OPERATING CONDITIONS(1)(2)(3)

			V _{CCI}	V _{cco}	MIN	MAX	UNIT
V _{CCA}	Supply voltage				1.2	3.6	V
V_{CCB}	Supply voltage				1.2	3.6	V
			1.2 V to 1.95 V		V _{CCI} × 0.65		
V_{IH}	High-level input voltage	All inputs (4)	1.95 V to 2.7 V		1.7		V
			2.7 V to 3.6 V		2		
			1.2 V to 1.95 V			V _{CCI} × 0.35	
V_{IL}	Low-level input voltage	All inputs ⁽⁴⁾	1.95 V to 2.7 V			0.7	V
			2.7 V to 3.6 V			0.8	
VI	Input voltage	Control inputs			0	3.6	V
		Active state			0	V _{CCO}	
$V_{I/O}$	Input/output voltage	3-state			0	3.6	V
				1.2 V		-1	
				1.4 V to 1.6 V		-1	
I _{OH}	High-level output current	(A port)		1.65 V to 1.95 V		-2	mA
				2.3 V to 2.7 V		-4	
				3 V to 3.6 V		-8	
				1.2 V		1	
				1.4 V to 1.6 V		1	
I_{OL}	Low-level output current ((A port)		1.65 V to 1.95 V		2	mA
				2.3 V to 2.7 V		4	
				3 V to 3.6 V		8	
				1.2 V		-1	
				1.4 V to 1.6 V		-2	
I_{OH}	High-level output current	(B port)		1.65 V to 1.95 V		-4	mA
				2.3 V to 2.7 V		-8	
				3 V to 3.6 V		-16	
				1.2 V		1	
				1.4 V to 1.6 V		2	
I_{OL}	Low-level output current ((B port)		1.65 V to 1.95 V		4	mA
				2.3 V to 2.7 V		8	
				3 V to 3.6 V		16	
Δt/Δν	Input transition rise or fall rate					5	ns/V
T _A	Operating free-air temper	ature			-40	85	°C

⁽²⁾

 V_{CCI} is the V_{CC} associated with the input port. V_{CCO} is the V_{CC} associated with the output port. All unused data inputs of the device must be held at V_{CCI} or GND to ensure proper device operation. Refer to the TI application report, *Implications of Slow or Floating CMOS Inputs*, literature number SCBA004. DIR2, DIR1, and DIR(345) are referenced to V_{CCA} .



ELECTRICAL CHARACTERISTICS(1)(2)

over recommended operating free-air temperature range (unless otherwise noted)

В4	DAMETED	TEST CON	DITIONS	V	V	T _A =	= 25°C		LINUT		
PA	RAMETER	TEST CON	DITIONS	V _{CCA}	V _{CCB}		TYP ⁽³⁾	MAX	UNIT		
		$I_{OH} = -100 \mu A$		1.2 V to 3.6 V	1.2 V to 3.6 V	V _{CCO} - 0.2					
		1 4 4		1.2 V	1.2 V		1.1				
.,	A t	$I_{OH} = -1 \text{ mA}$	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	1.4 V	1.4 V	1.05					
V _{OH}	A port	$I_{OH} = -2 \text{ mA}$	$V_I = V_{IH}$	1.65 V	1.65 V	1.2			V		
		$I_{OH} = -4 \text{ mA}$		2.3 V	2.3 V	1.75					
		$I_{OH} = -8 \text{ mA}$		3 V	3 V	2.3					
		I _{OL} = 100 μA		1.2 V to 3.6 V	1.2 V to 3.6 V			0.2			
		1 4 1		1.2 V	1.2 V		0.07				
.,	At	$I_{OL} = 1 \text{ mA}$., .,	1.4 V	1.4 V			0.35	.,		
V_{OL}	A port	I _{OL} = 2 mA	$V_I = V_{IL}$	1.65 V	1.65 V			0.45	V		
		I _{OL} = 4 mA		2.3 V	2.3 V			0.55			
		I _{OL} = 8 mA		3 V	3 V			0.7			
		$I_{OH} = -100 \mu A$		1.2 V to 3.6 V	1.2 V to 3.6 V	V _{CCO} - 0.2					
		$I_{OH} = -1 \text{ mA}$		1.2 V	1.2 V		1.1				
		$I_{OH} = -2 \text{ mA}$		1.4 V	1.4 V	1.05			V		
V_{OH}	B port	$I_{OH} = -4 \text{ mA}$	$V_I = V_{IH}$	1.65 V	1.65 V	1.2					
		$I_{OH} = -8 \text{ mA}$		2.3 V	2.3 V	1.75					
		I _{OH} = -16 mA		3 V	3 V	2.3					
		I _{OL} = 100 μA		1.2 V to 3.6 V	1.2 V to 3.6 V			0.2			
		I _{OL} = 1 mA		1.2 V	1.2 V		0.07	-			
		I _{OL} = 2 mA		1.4 V	1.4 V			0.35			
V_{OL}	B port	I _{OL} = 4 mA	$V_I = V_{IL}$	1.65 V	1.65 V			0.45	V		
		I _{OL} = 8 mA		2.3 V	2.3 V			0.55			
		I _{OL} = 16 mA		3 V	3 V			0.7			
I _I	Control inputs	$V_I = V_{CCA}$ or GND		1.2 V to 3.6 V	1.2 V to 3.6 V			±1	μΑ		
				0 V	0 V to 3.6 V			±5	±5		
l _{off}	A or B port	V_I or $V_O = 0$ to 3.6 V		0 V to 3.6 V	0 V			±5	μΑ		
I _{OZ} ⁽⁴⁾	A or B port	$V_O = V_{CCO}$ or GND, $V_I = V_{CCI}$ or GND	See function table for input states when outputs are Hi Z	3.6 V	3.6 V			±5	μА		
			I	1.2 V to 3.6 V	1.2 V to 3.6 V			10	-		
I_{CCA}		$V_I = V_{CCI}$ or GND,	$I_O = 0$	3.6 V	0 V			10	μΑ		
				0 V	3.6 V			-1			
				1.2 V to 3.6 V	1.2 V to 3.6 V			10			
I _{CCB}		$V_I = V_{CCI}$ or GND,	$I_{O} = 0$	3.6 V	0 V			-1	μΑ		
				0 V	3.6 V			10			
I _{CCA} +	I _{CCB}	$V_I = V_{CCI}$ or GND,	I _O = 0	1.2 V to 3.6 V	1.2 V to 3.6 V			15	μΑ		
C _i	Control inputs	V _I = V _{CCA} or GND	· ·	1.8 V	3 V		1.5	2	pF		
- 1	Clock input			1.0 V			۲'				
_	A port	$V_O = V_{CCA}$ or GND					2.5	3			
C_{io}	B port	$V_O = V_{CCB}$ or GND		1.8 V	3 V		pF				

 $[\]begin{array}{ll} \hbox{(1)} & V_{CCO} \text{ is the } V_{CC} \text{ associated with the output port.} \\ \hbox{(2)} & V_{CCI} \text{ is the } V_{CC} \text{ associated with the input port.} \\ \hbox{(3)} & \text{All typical values are at } T_A = 25^{\circ}\text{C.} \\ \hbox{(4)} & \text{For I/O ports, the parameter } I_{OZ} \text{ includes the input leakage current.} \\ \end{array}$



OUTPUT SLEW RATES(1)

over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER	FROM	то	$V_{CCA} = 1.8 \text{ V} \pm 0.15$ $V_{CCB} = 3 \text{ V} \pm 0.3 \text{ V}$	V, ' UNIT
			MIN M	AX
t _r	10%	90%	;	3 ⁽²⁾ ns
t _f	90%	10%	;	3 ⁽²⁾ ns

- (1) Values are characterized, but not production tested.
- (2) Using $C_L = 15 \text{ pF}$ on the B side and $C_L = 7 \text{ pF}$ on the A side

TYPICAL SWITCHING CHARACTERISTICS

 $T_A = 25$ °C, $V_{CCA} = 1.2 \text{ V (see Figure 2)}$

PARAMETER	FROM	TO (OUTPUT)	V _{CCB} = 1.2 V	V _{CCB} = 1.5 V	V _{CCB} = 1.8 V	V _{CCB} = 2.5 V	V _{CCB} = 3 V	V _{CCB} = 3.3 V	UNIT
	(INPUT)	(OUTPUT)	TYP	TYP	TYP	TYP	TYP	TYP	
	Α	В	3.8	3	2.6	2.5	2.5	2.6	
	В	Α	4.6	4.2	4	3.9	3.9	3.8	
t _{pd}	A6	В6	3.8	3	2.6	2.5	2.5	2.6	ns
	A2	B2	3.8	3	2.6	2.5	2.5	2.6	
	B2	A2	4.6	4.2	4	3.9	3.9	3.8	
t _{en} ⁽¹⁾	DIR	В	4.8	4	3.7	3.4	3.4	3.4	20
len (*/		Α	4.5	4.4	5	5.4	5.4	5.4	ns
. (1)	515	В	6.3	5.2	5.6	4.8	4.8	6.1	
$t_{dis}^{(1)}$	DIR	Α	4.8	4.6	5.3	5.4	5.4	5.3	ns

⁽¹⁾ DIR refers to DIR2, DIR1, and DIR(345).

SWITCHING CHARACTERISTICS

over recommended operating free-air temperature range, $V_{CCA} = 1.5 \text{ V} \pm 0.1 \text{ V}$ (see Figure 2)

PARAMETER	FROM				FROM (INPUT)	TO (OUTPUT	V _{CCB} = 1.2 V	V _{CCB} = ± 0.7	1.5 V 1 V	V _{CCB} = ± 0.1	1.8 V 5 V	V _{CCB} = ± 0.2		V _{CCB} :		V _{CCB} = ± 0.3		UNIT
	(INFUT))	TYP	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX					
	Α	В	3.4	1.1	5.6	1	4.8	1	3.9	0.9	3.9	0.9	3.8					
	В	Α	3.8	1.4	6	1.3	5.6	1.3	5.2	0.5	5.2	0.3	5.2					
t _{pd}	A6	B6	3.4	1.1	5.6	1	4.8	1	3.9	0.9	3.9	0.9	3.8	ns				
	A2	B2	3.4	1.1	5.6	1	4.8	1	3.9	0.9	3.9	0.9	3.8					
	B2	A2	3.8	1.4	6	1.3	5.6	1.3	5.2	0.5	5.2	0.3	5.2					
t _{en} ⁽¹⁾	DIR	В	4	1.3	7.7	1.1	6.9	0.8	6.1	8.0	6	0.8	5.9					
len`′	DIK	Α	3.5	1.4	7	1.5	7.4	1.7	8.2	1.7	8.2	1.7	7.7	ns				
t _{dis} (1)	DID	В	5.7	1.9	8.9	2.1	10.4	1.8	8.7	1.7	8.5	2.4	11.4					
^L dis`′	DIR	Α	3.4	1.2	7	1.2	6.8	1.2	6.9	1.2	6.5	1.2	6.6	ns				

(1) DIR refers to DIR2, DIR1, and DIR(345).



SWITCHING CHARACTERISTICS

over recommended operating free-air temperature range, $V_{CCA} = 1.8 \text{ V} \pm 0.15 \text{ V}$ (see Figure 2)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	V _{CCB} = 1.2 V	V _{CCB} = ± 0.		V _{CCB} = ± 0.1		V _{CCB} = ± 0.2		V _{CCB} = ± 0.3				UNIT
	(INFOI)	(001701)	TYP	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MIN MAX 0.7 3.1 0.2 4.3 0.7 3.1 0.7 3.1 0.2 4.3 0.7 4.8 1.4 5.3 2.2 8.2	
	Α	В	3.2	1	5.2	0.8	4.4	0.7	3.5	0.6	3.4	0.7	3.1	
	В	Α	3.4	1.1	5.2	1	4.8	0.9	4.3	0.3	4.3	0.2	4.3	
t _{pd}	A6	B6	3.2	1	5.2	0.8	4.4	0.7	3.5	0.6	3.4	0.7	3.1	ns
ч рd	A2	B2	3.2	1	5.2	0.8	4.4	0.7	3.5	0.6	3.4	0.7	3.1	
	B2	A2	3.4	1.1	5.2	1	4.8	0.9	4.3	0.3	4.3	0.2	4.3	
t _{en} ⁽¹⁾	DIR	В	3.5	1.2	6.8	0.9	6	0.7	5.1	0.7	5	0.7	4.8	20
len`´	DIK	Α	2.9	1.1	4.7	1.1	5.2	1.4	5.1	1.4	5.1	1.4	5.3	ns
t _{dis} (1)	DIR	В	5.3	1.6	8.4	2	9.5	1.6	8.2	1.4	8.1	2.2	8.2	5
^L dis` ′	DIK	Α	3.6	1.3	7.7	1.2	7.9	1.3	7.5	1.3	7.5	1.3	7.6	ns

⁽¹⁾ DIR refers to DIR2, DIR1, and DIR(345).

SWITCHING CHARACTERISTICS

over recommended operating free-air temperature range, $V_{CCA} = 2.5 \text{ V} \pm 0.2 \text{ V}$ (see Figure 2)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	V _{CCB} = 1.2 V	V _{CCB} = ± 0.1		V _{CCB} = ± 0.1		V _{CCB} = ± 0.2		V _{CCB} :		V _{CCB} = ± 0.3		UNIT
	(INFUT)	(OUTPUT)	TYP	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	
	Α	В	3	0.8	4.7	0.7	3.8	0.6	2.9	0.4	2.7	0.5	2.5	
	В	Α	3	0.9	4.4	0.7	3.9	0.6	3.3	0.3	3.2	0.3	3.2	
t _{pd}	A6	B6	3	0.8	4.7	0.7	3.8	0.6	2.9	0.4	2.7	0.5	2.5	ns
	A2	B2	3	0.8	4.7	0.7	3.8	0.6	2.9	0.4	2.7	0.5	2.5	
	B2	A2	3	0.9	4.4	0.7	3.9	0.6	3.3	0.3	3.2	0.3	3.2	
t _{en} ⁽¹⁾	DIR	В	3.1	1	5.7	0.8	4.8	0.5	3.9	0.5	3.7	0.5	3.6	20
len` ′	DIK	Α	2.2	0.7	3.5	0.6	4.3	1.2	4.4	0.7	4.6	0.4	4.7	ns
+	DIR	В	4.6	1.4	7.6	1.8	8.4	1.3	7.2	1.3	7.1	2	7.5	20
t _{dis}	DIK	Α	2.6	0.9	5.6	0.9	5.4	1	5.5	0.9	5.5	0.9	5.8	ns

⁽¹⁾ DIR refers to DIR2, DIR1, and DIR(345).



SWITCHING CHARACTERISTICS

over recommended operating free-air temperature range, $V_{CCA} = 3.3 \text{ V} \pm 0.3 \text{ V}$ (see Figure 2)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	V _{CCB} = 1.2 V	V _{CCB} = ± 0.7		V _{CCB} = ± 0.1		V _{CCB} = ± 0.2		V _{CCB} : ± 0.3		V _{CCB} = ± 0.3		UNIT
	(INFUI)	(OUTPUT)	TYP	MIN	MAX									
	Α	В	2.8	0.8	4.5	0.6	3.6	0.4	2.7	0.4	2.7	0.3	2.3	
	В	Α	2.9	0.8	4.3	0.6	3.7	0.5	3	0.5	3	0.1	2.7	
t _{pd}	A6	B6	2.8	0.8	4.5	0.6	3.6	0.4	2.7	0.4	2.7	0.3	2.3	ns
	A2	B2	2.8	0.8	4.5	0.6	3.6	0.4	2.7	0.4	2.7	0.3	2.3	
	B2	A2	2.9	0.8	4.3	0.6	3.7	0.5	3	0.5	3	0.1	2.7	
₊ (1)	DIB	В	3	1	5.1	0.6	4.3	0.5	3.4	0.5	3.4	0.4	3	20
t _{en} ⁽¹⁾	DIR	Α	2	0.6	3.1	0.6	5.4	0.7	5.4	0.7	5.4	0.5	5.4	ns
t _{dis} (1)	DIR	В	4.4	1.4	7.4	1.8	8.3	1.2	7	1.2	7	2	7.3	20
^l dis ()	אוט	Α	3.7	1.5	8.1	1.5	7.9	1.5	7.9	1.5	7.9	1.5	8	ns

⁽¹⁾ DIR refers to DIR2, DIR1, and DIR(345).

TYPICAL FREQUENCY AND OUTPUT SKEW

 $T_A = 25$ °C, $V_{CCA} = 1.2$ V (see Figure 2)

DAD	AMETER	FROM	то	V _{CCB} = 1.2 V	V _{CCB} = 1.5 V	V _{CCB} = 1.8 V	V _{CCB} = 2.5 V	V _{CCB} = 3 V	V _{CCB} = 3.3 V	UNIT
FARA	AIVIETER	(INPUT)	(OUTPUT)	TYP	TYP	TYP	TYP	TYP	TYP	UNIT
	Clock	A6	B6	95	95	95	95	95	95	
t _{max}	Data	Α	В	95	95	95	95	95	95	MHz
	Dala	В	Α	95	95	95	95	95	95	
t _{sk(o)}	Channel- to- channel	А	В	0.5	0.4	0.4	0.3	0.5	0.5	ns

MAXIMUM FREQUENCY AND OUTPUT SKEW

over recommended operating free-air temperature range, $V_{CCA} = 1.5 \text{ V} \pm 0.1 \text{ V}$ (see Figure 2)

PAF	PARAMETER	FROM (INPUT)	TO	V _{CCB} = 1.2 V	V _{CCB} = ± 0.1		V _{CCB} = ± 0.1		V _{CCB} = ± 0.2		V _{CCB}	= 3 V 3 V	V _{CCB} = ± 0.3		UNIT
		(INFUI)	(OUTPUT)	TYP	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	
	Clock	A6	B6	95	95		95		95		95		95		
f_{max}	Data	Α	В	95	95		95		95		95		95		MHz
	Data	В	Α	95	95		95		95		95		95		
t _{sk(o)}	Channel- to- channel	DIR	В	0.3		0.3		0.3		0.3		0.5		0.4	ns

MAXIMUM FREQUENCY AND OUTPUT SKEW

over recommended operating free-air temperature range, $V_{CCA} = 1.8 \text{ V} \pm 0.15 \text{ V}$ (see Figure 2)

PAF	RAMETER	FROM (INPUT)	TO (OUTPUT)	V _{CCB} = 1.2 V	V _{CCB} = ± 0.1		V _{CCB} = ± 0.1		V _{CCB} = ± 0.2		V _{CCB} ± 0.	= 3 V 3 V	V _{CCB} = ± 0.		UNIT
		(INFUI)	(OUTFUT)	TYP	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	
	Clock	A6	B6	95	95		95		95		95		95		
f _{max}	Dete	Α	В	95	95		95		95		95		95		MHz
	Data	В	Α	95	95		95		95		95		95		
t _{sk(o)}	Channel- to- channel	DIR	В	0.3		0.3		0.3		0.3		0.5		0.3	ns

Copyright © 2008–2009, Texas Instruments Incorporated

Submit Documentation Feedback



MAXIMUM FREQUENCY AND OUTPUT SKEW

over recommended operating free-air temperature range, V_{CCA} = 2.5 V ± 0.2 V (see Figure 2)

PAF	RAMETER	FROM (INPUT)	TO (OUTPUT)	V _{CCB} = 1.2 V	V _{CCB} = ± 0.1		V _{CCB} = ± 0.1		V _{CCB} = ± 0.2		V _{CCB}		V _{CCB} = ± 0.		UNIT
		(INFUT)	(OUIFUI)	TYP	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	
	Clock	A6	B6	95	95		95		95		95		95		
f_{max}	Data	Α	В	95	95		95		95		95		95		MHz
	Data	В	Α	95	95		95		95		95		95		
t _{sk(o)}	Channel- to- channel	DIR	В	0.3		0.3		0.3		0.2		0.6		0.3	ns

MAXIMUM FREQUENCY AND OUTPUT SKEW

over recommended operating free-air temperature range, V_{CCA} = 3.3 V \pm 0.3 V (see Figure 2)

PAF	RAMETER	FROM (INPUT)	TO (OUTPUT)	V _{CCB} = 1.2 V	V _{CCB} = ± 0.1		V _{CCB} = ± 0.1		V _{CCB} = ± 0.2			= 3 V .3 V	V _{CCB} = ± 0.		UNIT
		(INFUT)	(OUIFUI)	TYP	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	
	Clock	A6	B6	95	95		95		95		95		95		
f_{max}	Data	Α	В	95	95		95		95		95		95		MHz
	Data	В	Α	95	95		95		95		95		95		
t _{sk(o)}	Channel- to- channel	DIR	В	0.3		0.3		0.4		0.3		0.6		0.4	ns

Submit Documentation Feedback



OPERATING CHARACTERISTICS


 $T_A = 25$ °C

PARA	AMETER	TEST CONDITIONS	V _{CCA} = V _{CCB} = 1.2 V	$V_{CCA} = V_{CCB} = 1.5 V$	$V_{CCA} = V_{CCB} = 1.8 V$	$V_{CCA} = V_{CCB} = 2.5 V$	$V_{CCA} = V_{CCB} = 3 V$ TYP	V _{CCA} = V _{CCB} = 3.3 V	UNIT
C (1)	A-port input, B-port output B-port input	$C_{L} = 0,$ f = 10 MHz,	1.9	2	2.1	2.4	2.7	2.9	n=
OpdA ` /	B-port input, A-port output	$t_r = t_f = 1 \text{ ns}$	4.4	4.5	4.6	4.7	4.8	4.9	pF
C _{pdB} ⁽¹⁾	A-port input, B-port output	$C_L = 0$,	5.3	5.4	5.4	5.7	5.8	5.9	, E
OpdB ('')	B-port input, A-port output	f = 10 MHz, $t_r = t_f = 1 \text{ ns}$	0.3	0.3	0.4	0.5	0.6	0.6	pF

⁽¹⁾ Power dissipation capacitance per transceiver




PARAMETER MEASUREMENT INFORMATION



TEST	S1
t _{pd}	Open
t _{PLZ} /t _{PZL}	2×V _{CCO}
t _{PHZ} /t _{PZH}	GND

V _{cco}	CL	R _L	V _{TP}
1.5 V \pm 0.1 V	15 pF	2 k Ω	0.1 V
1.8 V \pm 0.15 V	15 pF	2 k Ω	0.15 V
2.5 V \pm 0.2 V	15 pF	2 k Ω	0.15 V
3.3 V \pm 0.3 V	15 pF	2 k Ω	0.3 V



- NOTES: A. C_L includes probe and jig capacitance.
 - B. Waveform 1 is for an output with internal conditions such that the output is low, except when disabled by the output control. Waveform 2 is for an output with internal conditions such that the output is high, except when disabled by the output control.
 - C. All input pulses are supplied by generators having the following characteristics: PRR \leq 10 MHz, $Z_0 = 50 \Omega$, $dv/dt \geq 1 V/ns$.
 - D. The outputs are measured one at a time, with one transition per measurement.
 - E. t_{PLZ} and t_{PHZ} are the same as t_{dis}.
 - F. t_{PZL} and t_{PZH} are the same as t_{en}.
 - G. t_{PLH} and t_{PHL} are the same as t_{pd} .
 - H. V_{CCI} is the V_{CC} associated with the input port.
 - I. V_{CCO} is the V_{CC} associated with the output port.

Figure 2. Load Circuit and Voltage Waveforms

www.ti.com

11-Nov-2025

PACKAGING INFORMATION

Orderable part number	Status	Material type	Package Pins	Package qty Carrier	RoHS	Lead finish/	MSL rating/	Op temp (°C)	Part marking
	(1)	(2)			(3)	Ball material	Peak reflow		(6)
						(4)	(5)		
SN74AVC6T622PWR	Active	Production	TSSOP (PW) 20	2000 LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	WU622
SN74AVC6T622PWR.B	Active	Production	TSSOP (PW) 20	2000 LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	WU622
SN74AVC6T622RGYR	Active	Production	VQFN (RGY) 20	3000 LARGE T&R	Yes	NIPDAU	Level-2-260C-1 YEAR	-40 to 85	WU622
SN74AVC6T622RGYR.B	Active	Production	VQFN (RGY) 20	3000 LARGE T&R	Yes	NIPDAU	Level-2-260C-1 YEAR	-40 to 85	WU622

⁽¹⁾ Status: For more details on status, see our product life cycle.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

⁽²⁾ Material type: When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

⁽³⁾ RoHS values: Yes, No, RoHS Exempt. See the TI RoHS Statement for additional information and value definition.

⁽⁴⁾ Lead finish/Ball material: Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

⁽⁵⁾ MSL rating/Peak reflow: The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

⁽⁶⁾ Part marking: There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

PACKAGE MATERIALS INFORMATION

www.ti.com 24-Jul-2025

TAPE AND REEL INFORMATION





A0	Dimension designed to accommodate the component width
В0	Dimension designed to accommodate the component length
K0	Dimension designed to accommodate the component thickness
W	Overall width of the carrier tape
P1	Pitch between successive cavity centers

QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE



*All dimensions are nominal

Device	Package Type	Package Drawing		SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
SN74AVC6T622PWR	TSSOP	PW	20	2000	330.0	16.4	6.95	7.0	1.4	8.0	16.0	Q1
SN74AVC6T622RGYR	VQFN	RGY	20	3000	330.0	12.4	3.71	4.71	1.1	8.0	12.0	Q1

www.ti.com 24-Jul-2025



*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
SN74AVC6T622PWR	TSSOP	PW	20	2000	353.0	353.0	32.0
SN74AVC6T622RGYR	VQFN	RGY	20	3000	353.0	353.0	32.0

3.5 x 4.5, 0.5 mm pitch

PLASTIC QUAD FGLATPACK - NO LEAD

This image is a representation of the package family, actual package may vary. Refer to the product data sheet for package details.





PLASTIC QUAD FLATPACK - NO LEAD



NOTES:

- 1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
 2. This drawing is subject to change without notice.
- 3. The package thermal pad must be soldered to the printed circuit board for thermal and mechanical performance.



PLASTIC QUAD FLATPACK - NO LEAD



NOTES: (continued)

- 4. This package is designed to be soldered to a thermal pad on the board. For more information, see Texas Instruments literature number SLUA271 (www.ti.com/lit/slua271).
- Vias are optional depending on application, refer to device data sheet. If any vias are implemented, refer to their locations shown on this view. It is recommended that vias under paste be filled, plugged or tented.



PLASTIC QUAD FLATPACK - NO LEAD



NOTES: (continued)

6. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.





SMALL OUTLINE PACKAGE



NOTES:

- 1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.

 2. This drawing is subject to change without notice.

 3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not
- exceed 0.15 mm per side.
- 4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.25 mm per side.
- 5. Reference JEDEC registration MO-153.



SMALL OUTLINE PACKAGE



NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.

7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.



SMALL OUTLINE PACKAGE



NOTES: (continued)

- 8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
- 9. Board assembly site may have different recommendations for stencil design.



IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you fully indemnify TI and its representatives against any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale, TI's General Quality Guidelines, or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products. Unless TI explicitly designates a product as custom or customer-specified, TI products are standard, catalog, general purpose devices.

TI objects to and rejects any additional or different terms you may propose.

Copyright © 2025, Texas Instruments Incorporated

Last updated 10/2025