









SN74AVC8T245-Q1 SCES785E - DECEMBER 2008 - REVISED NOVEMBER 2023

SN74AVC8T245-Q1 Automotive 8-Bit Dual-Supply Bus Transceiver With Configurable Voltage Translation and 3-State Outputs

1 Features

- Qualified for automotive applications
- AEC Q100 test guidance with the following results:
 - Device temperature grade 1: –40°C to +125°C ambient operating temperature range
 - Device HBM ESD Classification Level H2
 - Device CDM ESD Classification Level C3B
- Control inputs V_{IH} and V_{IL} levels are referenced to V_{CCA} voltage
- V_{CC} isolation feature if either V_{CC} input is at GND, all I/O ports are in the high-impedance state
- I_{off} supports partial power-down-mode operation
- Fully configurable dual-rail design allows each port to operate over the full 1.4-V to 3.6-V powersupply range
- I/Os are 4.6-V tolerant
- Maximum data rates:
 - 170Mbps (V_{CCA} < 1.8 V or V_{CCB} < 1.8 V)
 - 320Mbps (V_{CCA} ≥ 1.8 V and V_{CCB} ≥ 1.8 V)
- Latch-up performance exceeds 100 mA per JESD 78, Class II

2 Applications

- **Telematics**
- Cluster
- Head unit
- Navigation systems

3 Description

The SN74AVC8T245-Q1 is an 8-bit noninverting bus transceiver that uses two separate configurable power-supply rails. The SN74AVC8T245-Q1 operation is optimal with V_{CCA} and V_{CCB} set at 1.4 V to 3.6 V. It is operational with V_{CCA} and V_{CCB} as low as 1.2 V. The A port is designed to track V_{CCA}. V_{CCA} accepts any supply voltage from 1.2 V to 3.6 V. The B port is designed to track V_{CCB}. V_{CCB} accepts any supply voltage from 1.2 V to 3.6 V. This allows for universal low-voltage bidirectional translation between any of the 1.2-V, 1.5-V, 1.8-V, 2.5-V, and 3.3-V voltage nodes.

The SN74AVC8T245-Q1 design enables asynchronous communication between data buses. The device transmits data from the A bus to the B bus or from the B bus to the A bus, depending on the logic level at the direction-control (DIR) input. One can use the output-enable (\overline{OE}) input to disable the outputs so the buses are effectively isolated.

In the SN74AVC8T245-Q1 design, V_{CCA} supplies the control pins (DIR and \overline{OE}).

This device specification covers partial-power-down applications using Ioff. The Ioff circuitry disables the outputs when the device is powered down. This inhibits current backflow into the device which prevents damage to the device.


The V_{CC} isolation feature allows both ports to be in the high-impedance state if either V_{CC} input is at GND.

To put the device in the high-impedance state during power up or power down, tie \overline{OE} to V_{CC} through a pullup resistor; the current-sinking capability of the driver determines the minimum value of the resistor.

Package Information

PART NUMBER	PACKAGE ⁽¹⁾	PACKAGE SIZE ⁽²⁾
SN74AVC8T245-Q1	RHL (VQFN, 24)	5.5 mm × 3.5 mm
3N74AVC01243-Q1	PW (TSSOP, 24)	7.8 mm × 6.4 mm

- (1) For more information, see Section 11.
- The package size (length × width) is a nominal value and includes pins, where applicable.



Logic Diagram (Positive Logic)




Table of Contents

1 Features1	7 Detailed Description	17
2 Applications 1	7.1 Overview	17
3 Description1	7.2 Functional Block Diagram	
4 Pin Configuration and Functions3	7.3 Feature Description	
5 Specifications 4	7.4 Device Functional Modes	
5.1 Absolute Maximum Ratings4	8 Application and Implementation	18
5.2 ESD Ratings4	8.1 Application Information	18
5.3 Recommended Operating Conditions5	8.2 Typical Application	
5.4 Thermal Information6	8.3 Power Supply Recommendations	
5.5 Electrical Characteristics6	8.4 Layout	20
5.6 Switching Characteristics: V _{CCA} = 1.2 V7	9 Device and Documentation Support	2
5.7 Switching Characteristics: V _{CCA} = 1.5 V ± 0.1 V8	9.1 Documentation Support	2
5.8 Switching Characteristics: V _{CCA} = 1.8 V ± 0.15 V9	9.2 Receiving Notification of Documentation Updates	2
5.9 Switching Characteristics: V _{CCA} = 2.5 V ± 0.2 V10	9.3 Support Resources	2
5.10 Switching Characteristics: V _{CCA} = 3.3 V ± 0.3 V10	9.4 Trademarks	2
5.11 Operating Characteristics12	9.5 Electrostatic Discharge Caution	2
5.12 Typical Total Static Current Consumption (I _{CCA}	9.6 Glossary	2
+ I _{CCB})13	10 Revision History	2
5.13 Typical Characteristics14	11 Mechanical, Packaging, and Orderable	
6 Parameter Measurement Information16	Information	22



4 Pin Configuration and Functions






Figure 4-2. PW Package, 24-Pin TSSOP (Top View)

Figure 4-1. RHL Package, 24-Pin VQFN (Top View)

Table 4-1. Pin Functions

	PIN		TYPE ⁽¹⁾	DESCRIPTION
NAME	VQFN	TSSOP	ITPE	DESCRIPTION
A1	3	3	I/O	Input/output A1. Referenced to V _{CCA} .
A2	4	4	I/O	Input/output A2. Referenced to V _{CCA} .
A3	5	5	I/O	Input/output A3. Referenced to V _{CCA} .
A4	6	6	I/O	Input/output A4. Referenced to V _{CCA} .
A5	7	7	I/O	Input/output A5. Referenced to V _{CCA} .
A6	8	8	I/O	Input/output A6. Referenced to V _{CCA} .
A7	9	9	I/O	Input/output A7. Referenced to V _{CCA} .
A8	10	10	I/O	Input/output A8. Referenced to V _{CCA} .
B1	21	21	I/O	Input/output B1. Referenced to V _{CCB} .
B2	20	20	I/O	Input/output B2. Referenced to V _{CCB} .
B3	19	19	I/O	Input/output B3. Referenced to V _{CCB} .
B4	18	18	I/O	Input/output B4. Referenced to V _{CCB} .
B5	17	17	I/O	Input/output B5. Referenced to V _{CCB} .
B6	16	16	I/O	Input/output B6. Referenced to V _{CCB} .
B7	15	15	I/O	Input/output B7. Referenced to V _{CCB} .
B8	14	14	I/O	Input/output B8. Referenced to V _{CCB} .
DIR	2		I	Direction-control input for 1 ports
GND	12, 13	11, 12, 13	_	Ground
OE	22	22	I	3-state output-mode enable. Pull \overline{OE} high to place '2' outputs in 3-state mode. Referenced to V_{CCA} .
V _{CCA}	1	1	_	A-port power supply voltage. 1.2 V ≤ V _{CCA} ≤ 3.6 V
V _{CCB}	23, 24	23, 24	_	B-port power supply voltage. 1.2 V ≤ V _{CCB} ≤ 3.6 V
Thermal pa	d		_	The exposed thermal pad must be connected as a secondary GND or be left electrically open.

(1) I = input, O = output



5 Specifications

5.1 Absolute Maximum Ratings

over operating free-air temperature range (unless otherwise noted)(1)

			MIN	MAX	UNIT
V_{CCA}	Supply voltage		-0.5	4.6	V
V _{CCB}	Supply voltage		-0.5	4.0	V
	·	I/O ports (A port)	-0.5	4.6	V
VI	Input voltage ⁽²⁾	I/O ports (B port)	-0.5	4.6	V
		Control inputs	-0.5	4.6	٧
	Voltage range	A port	-0.5	4.6	٧
Vo	applied to any output in the high-impedance or power-off state ⁽²⁾	B port	-0.5	4.6	V
	Voltage range	A port	-0.5	(V _{CCA} + 0.5)	V
Vo	applied to any output in the high or low state ⁽²⁾ (3)	B port	-0.5	(V _{CCB} + 0.5)	٧
I _{IK}	Input clamp current	V _I < 0		-50	mA
I _{OK}	Output clamp current	V _O < 0		-50	mA
Io	Continuous output of	current		±50	mA
	Continuous current	through V _{CCA} , V _{CCB} , or GND		±100	mA
TJ	Junction temperatur	e		150	°C
T _{stg}	Storage temperature	9	– 65	150	°C

⁽¹⁾ Stresses beyond those listed under *Absolute Maximum Ratings* may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under *Recommended Operating Conditions* is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

5.2 ESD Ratings

			VALUE	UNIT
V	Electrostatic	Human-body model (HBM), per AEC Q100-002 Classification Level H2 ⁽¹⁾	±2000	V
V _(ESD)	discharge	Charged-device model (CDM), per AEC Q100-011 Classification Level C3B	±750	v

(1) AEC Q100-002 indicates that HBM stressing shall be in accordance with the ANSI/ESDA/JEDEC JS-001 specification.

Submit Document Feedback

Copyright © 2023 Texas Instruments Incorporated

⁽²⁾ The device withstands voltages in excess of input voltage and output negative-voltage ratings while operating within the input and output current ratings.

⁽³⁾ The device withstands voltages in excess of the output positive-voltage rating up to 4.6 V maximum while operating within the output current rating.



5.3 Recommended Operating Conditions

See (1) (2) (3)

			V _{CCI}	V _{cco}	MIN	MAX	UNIT
V _{CCA}	Supply voltage				1.2	3.6	V
V _{CCB}	Supply voltage				1.2	3.6	V
			1.2 V to 1.95 V		V _{CCI} × 0.65		
V_{IH}	High-level input voltage	Data inputs	1.95 V to 2.7 V		1.6		V
	voltago		2.7 V to 3.6 V		2		
			1.2 V to 1.95 V			V _{CCI} × 0.35	
V_{IL}	Low-level input voltage	Data inputs	1.95 V to 2.7 V			0.7	V
	voltage		2.7 V to 3.6 V			0.8	
High lovel input			1.2 V to 1.95 V		V _{CCA} × 0.65		
V_{IH}	High-level input voltage	DIR (referenced to V _{CCA})	1.95 V to 2.7 V		1.6		V
	voltage	(referenced to V _{GCA})	2.7 V to 3.6 V		2		
			1.2 V to 1.95 V			V _{CCA} × 0.35	
V_{IL}	/	DIR (referenced to V _{CCA})	1.95 V to 2.7 V			0.7	V
		(referenced to VCCA)	2.7 V to 3.6 V			0.8	
VI	Input voltage				0	3.6	V
	Outrout walterns	Active state			0	V _{cco}	V
Vo	Output voltage	3-state			0	3.6	V
				1.2 V		-3	
				1.4 V to 1.6 V		-6	
I _{OH}	High-level output curr	ent		1.65 V to 1.95 V		-8	mA
				2.3 V to 2.7 V		-9	
				3 V to 3.6 V		-12	
				1.2 V		3	
				1.4 V to 1.6 V		6	
I _{OL}	Low-level output curre	ent		1.65 V to 1.95 V		8	mA
				2.3 V to 2.7 V		9	
				3 V to 3.6 V		12	
Δt / Δν	Input transition rise or	fall rate				5	ns / V
T _A	Operating free-air ten	nperature			-40	125	°C

 $[\]begin{split} &V_{CCI} \text{ is the } V_{CC} \text{ associated with the input port.} \\ &V_{CCO} \text{ is the } V_{CC} \text{ associated with the output port.} \end{split}$ (2)

Hold all unused data inputs of the device at V_{CCI} or GND for proper device operation. See the TI application report, *Implications of Slow or Floating CMOS Inputs*, SCBA004.



5.4 Thermal Information

		SN74AVC	8T245-Q1	
	THERMAL METRIC	RHL (VQFN)	PW (TSSOP)	UNIT
		24 PINS	24 PINS	
$R_{\theta JA}$	Junction-to-ambient thermal resistance	36.8	93.1	°C/W
R ₀ JC(top)	Junction-to-case (top) thermal resistance	32.5	36.7	°C/W
$R_{\theta JB}$	Junction-to-board thermal resistance	15.7	48.4	°C/W
ΨЈТ	Junction-to-top characterization parameter	0.7	93.1	°C/W
ΨЈВ	Junction-to-board characterization parameter	15.6	48.0	°C/W
R _{θJC(bot)}	Junction-to-case (bottom) thermal resistance	5.6	N/A	°C/W

5.5 Electrical Characteristics

over recommended operating free-air temperature range (unless otherwise noted)(2) (1)

	PARAMETER	TEST COI	NDITIONS	V _{CCA}	V _{CCB}	T _A	MIN	TYP	MAX	UNIT
		I _{OH} = -100 μA		1.2 V to 3.6 V	1.2 V to 3.6 V	T _A = -40°C to +125°C	V _{CCO} - 0.2			
		I _{OH} = -3 mA	I _{OH} = -3 mA	1.2 V	1.2 V	T _A = 25°C		0.95		
		I _{OH} = -6 mA		1.4 V	1.4 V	T _A = -40°C to +125°C	1			
V _{OH}		I _{OH} = -8 mA	$V_I = V_{IH}$	1.65 V	1.65 V	T _A = -40°C to +125°C	1.2			V
		I _{OH} = -9 mA		2.3 V	2.3 V	T _A = -40°C to +125°C	1.75			
		I _{OH} = -12 mA		3 V	3 V	T _A = -40°C to +125°C	2.3			
		Ι _{ΟL} = 100 μΑ		1.2 V to 3.6 V	1.2 V to 3.6 V	T _A = -40°C to +125°C			0.2	
		I _{OL} = 3 mA		1.2 V	1.2 V	T _A = 25°C		0.15		
		I _{OL} = 6 mA		1.4 V	1.4 V	T _A = -40°C to +125°C			0.35	
V _{OL}		I _{OL} = 8 mA	$V_I = V_{IL}$	1.65 V	1.65 V	T _A = -40°C to +125°C			0.45	V
		I _{OL} = 9 mA		2.3 V	2.3 V	T _A = -40°C to +125°C			0.55	
		I _{OL} = 12 mA		3 V	3 V	T _A = -40°C to +125°C			0.7	
L	Control inputs	$V_1 = V_{CCA}$ or GND		1.2 V to 3.6 V	1.2 V to 3.6 V	T _A = 25°C		±0.02 5	±0.25	μA
l _l	Control inputs	AI - ACCV OL GIAD		1.2 V to 3.0 V	1.2 V to 3.0 V	T _A = -40°C to +125°C			±1	μΑ
						T _A = 25°C		±0.1	±1	
	A or B port	$V_1 \text{ or } V_0 = 0 \text{ to } 3.6 \text{ V}$		0 V	0 V to 3.6 V	T _A = -40°C to +125°C			±5	
l _{off}	A OI B POIL	V ₁ OI V ₀ = 0 to 3.6 V				T _A = 25°C		±0.1	±1	μA
				0 V to 3.6 V	0 V	T _A = -40°C to +125°C			±5	
		$V_O = V_{CCO}$ or GND,				T _A = 25°C		±0.5	±2.5	
I _{OZ} (3)	A or B port	$V_I = V_{CCI}$ or GND, $\overline{OE} = V_{IH}$		3.6 V	3.6 V	T _A = -40°C to +125°C			±5	μΑ

Submit Document Feedback

Copyright © 2023 Texas Instruments Incorporated

5.5 Electrical Characteristics (continued)

over recommended operating free-air temperature range (unless otherwise noted)(2) (1)

	PARAMETER	TEST CONDITIONS	V _{CCA}	V _{CCB}	TA	MIN	TYP	MAX	UNIT
			1.2 V to 3.6 V	1.2 V to 3.6 V	T _A = -40°C to +125°C			15	
Icca		$V_{I} = V_{CCI}$ or $GND^{(3)}$, $I_{O} = 0$	0 V	3.6 V	T _A = -40°C to +125°C			-2	μA
			3.6 V	0 V	T _A = -40°C to +125°C			15	
			1.2 V to 3.6 V	1.2 V to 3.6 V	T _A = -40°C to +125°C			15	
I _{CCB}		$V_I = V_{CCI}$ or $GND^{(3)}$, $I_O = 0$	0 V	3.6 V	T _A = -40°C to +125°C			15	μA
			3.6 V	0 V	T _A = -40°C to +125°C			-2	
I _{CCA} +	Іссв	V _I = V _{CCI} or GND, I _O = 0	1.2 V to 3.6 V	1.2 V to 3.6 V	T _A = -40°C to +125°C			25	μA
Ci	Control inputs	V _I = 3.3 V or GND	3.3 V	3.3 V	T _A = 25°C		3.5		pF
C _{io}	A or B port	V _O = 3.3 V or GND	3.3 V	3.3 V	T _A = 25°C		6		pF

- (2)
- V_{CCI} is the V_{CC} associated with the input port. V_{CCO} is the V_{CC} associated with the output port. For I/O ports, the parameter I_{OZ} includes the input leakage current.

5.6 Switching Characteristics: $V_{CCA} = 1.2 \text{ V}$

over recommended operating free-air temperature range, V_{CCA} = 1.2 V (see Figure 6-1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	V _{CCB}	TYP	UNIT
			V _{CCB} = 1.2 V	3.1	
			V _{CCB} = 1.5 V	2.6	
t _{PLH} , t _{PHL}	A	В	V _{CCB} = 1.8 V	2.5	ns
			V _{CCB} = 2.5 V	3	
			V _{CCB} = 3.3 V	3.5	
			V _{CCB} = 1.2 V	3.1	
			V _{CCB} = 1.5 V	2.7	
t _{PLH} , t _{PHL}	В	В А	V _{CCB} = 1.8 V	2.5	ns
			V _{CCB} = 2.5 V	2.4	
			V _{CCB} = 3.3 V	2.3	
			V _{CCB} = 1.2 V		
			V _{CCB} = 1.5 V		
t _{PZH} , t _{PZL}	ŌĒ	A	V _{CCB} = 1.8 V	5.3	ns
			V _{CCB} = 2.5 V		
			V _{CCB} = 3.3 V		
			V _{CCB} = 1.2 V	5.1	
			V _{CCB} = 1.5 V	4	
t _{PZH} , t _{PZL}	ŌĒ	В	V _{CCB} = 1.8 V	3.5	ns
			V _{CCB} = 2.5 V	3.2	
			V _{CCB} = 3.3 V	3.1	

5.6 Switching Characteristics: V_{CCA} = 1.2 V (continued)

over recommended operating free-air temperature range, V_{CCA} = 1.2 V (see Figure 6-1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	V _{CCB}	TYP	UNIT
			V _{CCB} = 1.2 V		
			V _{CCB} = 1.5 V		
t _{PHZ} , t _{PLZ}	ŌĒ	Α	V _{CCB} = 1.8 V	4.8	ns
			V _{CCB} = 2.5 V		
			V _{CCB} = 3.3 V		
			V _{CCB} = 1.2 V	4.7	
			V _{CCB} = 1.5 V	4	
t _{PHZ} , t _{PLZ}	ŌĒ	В	V _{CCB} = 1.8 V	4.1	ns
			V _{CCB} = 2.5 V	4.3	
			V _{CCB} = 3.3 V	5.1	

5.7 Switching Characteristics: $V_{CCA} = 1.5 V \pm 0.1 V$

over recommended operating free-air temperature range, V_{CCA} = 1.5 V ± 0.1 V (see Figure 6-1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	V _{CCB}	MIN	TYP	MAX	UNIT
			V _{CCB} = 1.2 V		3.1		
			V _{CCB} = 1.5 V ± 0.1 V	0.5		14.7	
t _{PLH} , t _{PHL}	Α	В	V _{CCB} = 1.8 V ± 0.15 V	0.5		13.3	ns
			V _{CCB} = 2.5 V ± 0.2 V	0.5		13.9	
			V _{CCB} = 3.3 V ± 0.3 V	0.5		17.2	
			V _{CCB} = 1.2 V		3.1		
			V _{CCB} = 1.5 V ± 0.1 V	0.5		14.7	
t _{PLH} , t _{PHL}	В	A	V _{CCB} = 1.8 V ± 0.15 V	0.5		14.2	ns
			V _{CCB} = 2.5 V ± 0.2 V	0.5		13.5	
			V _{CCB} = 3.3 V ± 0.3 V	0.5		13.2	
			V _{CCB} = 1.2 V		5.3		
			V _{CCB} = 1.5 V ± 0.1 V	0.5		20.5	ns
t _{PZH} , t _{PZL}	ŌĒ	Ē A	V _{CCB} = 1.8 V ± 0.15 V	0.5		20.5	
			V _{CCB} = 2.5 V ± 0.2 V	0.5		20.5	
			$V_{CCB} = 3.3 \text{ V} \pm 0.3 \text{ V}$	0.5		20.5	
			V _{CCB} = 1.2 V		5.1		
			V _{CCB} = 1.5 V ± 0.1 V	0.5		18.6	
t _{PZH} , t _{PZL}	ŌĒ	В	V _{CCB} = 1.8 V ± 0.15 V	0.5		17.7	ns
			V _{CCB} = 2.5 V ± 0.2 V	0.5		15.1	
			$V_{CCB} = 3.3 \text{ V} \pm 0.3 \text{ V}$	0.5		14.4	
			V _{CCB} = 1.2 V		4.8		
			V _{CCB} = 1.5 V ± 0.1 V	0.5		20.3	ns
t _{PHZ} , t _{PLZ}	ŌĒ	Α	V _{CCB} = 1.8 V ± 0.15 V	0.5		20.3	
			V _{CCB} = 2.5 V ± 0.2 V	0.5		20.3	
			V _{CCB} = 3.3 V ± 0.3 V	0.5		20.3	

Product Folder Links: SN74AVC8T245-Q1

ubmit Document Feedback



5.7 Switching Characteristics: $V_{CCA} = 1.5 \text{ V} \pm 0.1 \text{ V}$ (continued)

over recommended operating free-air temperature range, V_{CCA} = 1.5 V \pm 0.1 V (see Figure 6-1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	V _{CCB}	MIN	TYP MAX	UNIT
	ŌĒ		V _{CCB} = 1.2 V		4.7	
		В	V _{CCB} = 1.5 V ± 0.1 V	0.5	20.0	
t _{PHZ} , t _{PLZ}			V _{CCB} = 1.8 V ± 0.15 V	0.5	18.6	ns
			V _{CCB} = 2.5 V ± 0.2 V	0.5	17.9	
			V _{CCB} = 3.3 V ± 0.3 V	0.5	18.9	

5.8 Switching Characteristics: $V_{CCA} = 1.8 \text{ V} \pm 0.15 \text{ V}$

over recommended operating free-air temperature range, V_{CCA} = 1.8 V ± 0.15 V (see Figure 6-1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	V _{CCB}	MIN	TYP	MAX	UNIT
			V _{CCB} = 1.2 V		2.5		
			V _{CCB} = 1.5 V ± 0.1 V	0.5		14.2	
t _{PLH} , t _{PHL}	Α	В	V _{CCB} = 1.8 V ± 0.15 V	0.5		13.0	ns
			V _{CCB} = 2.5 V ± 0.2 V	0.5		12.3	
			$V_{CCB} = 3.3 \text{ V} \pm 0.3 \text{ V}$	0.5		12.1	
			V _{CCB} = 1.2 V		2.5		
			V _{CCB} = 1.5 V ± 0.1 V	0.5		13.3	
PLH, tPHL	В	Α	V _{CCB} = 1.8 V ± 0.15 V	0.5		13.0	ns
			V _{CCB} = 2.5 V ± 0.2 V	0.5		12.1	
			$V_{CCB} = 3.3 \text{ V} \pm 0.3 \text{ V}$	0.5		11.8	
			V _{CCB} = 1.2 V		3		ns
	ŌĒ	A	V _{CCB} = 1.5 V ± 0.1 V	0.5		17.2	
PZH, tPZL			V _{CCB} = 1.8 V ± 0.15 V	0.5		17.2	
			V _{CCB} = 2.5 V ± 0.2 V	0.5		17.2	
			$V_{CCB} = 3.3 \text{ V} \pm 0.3 \text{ V}$	0.5		17.2	
			V _{CCB} = 1.2 V		4.6		
	ŌĒ		V _{CCB} = 1.5 V ± 0.1 V	0.5		19.6	ns
PZH, tPZL		В	V _{CCB} = 1.8 V ± 0.15 V	0.5		17.0	
			V _{CCB} = 2.5 V ± 0.2 V	0.5		14.2	
			$V_{CCB} = 3.3 \text{ V} \pm 0.3 \text{ V}$	0.5		13.2	
			V _{CCB} = 1.2 V		2.8		
			V _{CCB} = 1.5 V ± 0.1 V	0.5		17.7	
e _{PHZ} , t _{PLZ}	ŌĒ	A	V _{CCB} = 1.8 V ± 0.15 V	0.5		17.7	ns
			V _{CCB} = 2.5 V ± 0.2 V	0.5		17.7	
			V _{CCB} = 3.3 V ± 0.3 V	0.5		17.7	
			V _{CCB} = 1.2 V		3.9		
			V _{CCB} = 1.5 V ± 0.1 V	0.5		18.9	ns
PHZ, tPLZ	ŌĒ	В	V _{CCB} = 1.8 V ± 0.15 V	0.5		17.3	
			V _{CCB} = 2.5 V ± 0.2 V	0.5		15.8	
			V _{CCB} = 3.3 V ± 0.3 V	0.5		15.4	



5.9 Switching Characteristics: $V_{CCA} = 2.5 V \pm 0.2 V$

over recommended operating free-air temperature range, V_{CCA} = 2.5 V \pm 0.2 V (see Figure 6-1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	V _{CCB}	MIN	TYP	MAX	UNIT
			V _{CCB} = 1.2 V		2.4		
			V _{CCB} = 1.5 V ± 0.1 V	0.5		13.5	
t _{PLH} , t _{PHL}	Α	В	V _{CCB} = 1.8 V ± 0.15 V	0.5		12.1	ns
			V _{CCB} = 2.5 V ± 0.2 V	0.5		10.7	
			V _{CCB} = 3.3 V ± 0.3 V	0.5		10.2	
			V _{CCB} = 1.2 V		3		
			V _{CCB} = 1.5 V ± 0.1 V	0.5		13.9	
t _{PLH} , t _{PHL}	В	Α	V _{CCB} = 1.8 V ± 0.15 V	0.5	,	12.3	ns
			V _{CCB} = 2.5 V ± 0.2 V	0.5	,	10.7	
			V _{CCB} = 3.3 V ± 0.3 V	0.5	,	10.4	
		ŌE A	V _{CCB} = 1.2 V		2.2		
	ŌĒ		V _{CCB} = 1.5 V ± 0.1 V	0.5		13.7	ns
t _{PZH} , t _{PZL}			V _{CCB} = 1.8 V ± 0.15 V	0.5		13.7	
			V _{CCB} = 2.5 V ± 0.2 V	0.5		13.7	
			V _{CCB} = 3.3 V ± 0.3 V	0.5	,	13.7	
	ŌĒ		V _{CCB} = 1.2 V		4.5		ns
			V _{CCB} = 1.5 V ± 0.1 V	0.5		19.1	
t _{PZH} , t _{PZL}		В	V _{CCB} = 1.8 V ± 0.15 V	0.5	,	16.5	
			V _{CCB} = 2.5 V ± 0.2 V	0.5	,	13.3	
			V _{CCB} = 3.3 V ± 0.3 V	0.5		12.3	
			V _{CCB} = 1.2 V		1.8		
			V _{CCB} = 1.5 V ± 0.1 V	0.5		14.2	
t _{PHZ} , t _{PLZ}	ŌĒ	Α	V _{CCB} = 1.8 V ± 0.15 V	0.5	,	14.2	ns
			V _{CCB} = 2.5 V ± 0.2 V	0.5	,	14.2	
			V _{CCB} = 3.3 V ± 0.3 V	0.5	,	14.2	
			V _{CCB} = 1.2 V		3.6		
			V _{CCB} = 1.5 V ± 0.1 V	0.5		17.7	
t _{PHZ} , t _{PLZ}	ŌĒ	В	V _{CCB} = 1.8 V ± 0.15 V	0.5		16.3	ns
			V _{CCB} = 2.5 V ± 0.2 V	0.5		14.2	
			V _{CCB} = 3.3 V ± 0.3 V	0.5		12.1	

5.10 Switching Characteristics: V_{CCA} = 3.3 V ± 0.3 V

over recommended operating free-air temperature range, V_{CCA} = 3.3 V \pm 0.3 V (see Figure 6-1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	V _{CCB}	MIN	TYP	MAX	UNIT
	А	В	V _{CCB} = 1.2 V		2.3		
			V _{CCB} = 1.5 V ± 0.1 V	0.5		13.2	
t _{PLH} , t _{PHL}			V _{CCB} = 1.8 V ± 0.15 V	0.5	-	11.1	ns
			V _{CCB} = 2.5 V ± 0.2 V	0.5		10.4	
			V _{CCB} = 3.3 V ± 0.3 V	0.5		9.7	

Product Folder Links: SN74AVC8T245-Q1



5.10 Switching Characteristics: $V_{CCA} = 3.3 \text{ V} \pm 0.3 \text{ V}$ (continued)

over recommended operating free-air temperature range, V_{CCA} = 3.3 V \pm 0.3 V (see Figure 6-1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	V _{CCB}	MIN	TYP	MAX	UNIT	
			V _{CCB} = 1.2 V		3.5			
			V _{CCB} = 1.5 V ± 0.1 V	0.5		17.2		
t _{PLH} , t _{PHL}	В	A	V _{CCB} = 1.8 V ± 0.15 V	0.5		12.1	ns	
			V _{CCB} = 2.5 V ± 0.2 V	0.5		10.2		
			V _{CCB} = 3.3 V ± 0.3 V	0.5		9.7		
			V _{CCB} = 1.2 V		2			
			V _{CCB} = 1.5 V ± 0.1 V	0.5		12.3		
t _{PZH} , t _{PZL}	ŌĒ	Α	V _{CCB} = 1.8 V ± 0.15 V	0.5		12.3	ns	
			V _{CCB} = 2.5 V ± 0.2 V	0.5		12.3		
			V _{CCB} = 3.3 V ± 0.3 V	0.5		12.3		
		В	V _{CCB} = 1.2 V		4.5			
	ŌĒ		V _{CCB} = 1.5 V ± 0.1 V	0.5		18.9		
t _{PZH} , t _{PZL}			V _{CCB} = 1.8 V ± 0.15 V	0.5		16.1	ns	
			V _{CCB} = 2.5 V ± 0.2 V	0.5		13.2		
			V _{CCB} = 3.3 V ± 0.3 V	0.5		12.3		
			V _{CCB} = 1.2 V		1.7			
			V _{CCB} = 1.5 V ± 0.1 V	0.5		12.3		
t _{PHZ} , t _{PLZ}	ŌĒ	A	V _{CCB} = 1.8 V ± 0.15 V	0.5		12.3	ns	
			V _{CCB} = 2.5 V ± 0.2 V	0.5		12.3		
			$V_{CCB} = 3.3 \text{ V} \pm 0.3 \text{ V}$	0.5		12.3		
			V _{CCB} = 1.2 V		3.4			
			V _{CCB} = 1.5 V ± 0.1 V	0.5		17.4		
t _{PHZ} , t _{PLZ}	ŌĒ	В	V _{CCB} = 1.8 V ± 0.15 V	0.5		15.8	ns	
			V _{CCB} = 2.5 V ± 0.2 V	0.5		13.7		
			V _{CCB} = 3.3 V ± 0.3 V	0.5		12.6		



5.11 Operating Characteristics

 $T_A = 25^{\circ}C$

$T_A = 25^\circ$	PARAMETE	iR .	TEST CONDITIONS	V _{CCA}	TYP	UNIT
				V _{CCA} = V _{CCB} = 1.2 V		
			C _L = 0,	V _{CCA} = V _{CCB} = 1.5 V	1	
		Outputs enabled	f = 10 MHz,	V _{CCA} = V _{CCB} = 1.8 V		
		Chabled	$t_r = t_f = 1 \text{ ns}$	V _{CCA} = V _{CCB} = 2.5 V		
	A to D			V _{CCA} = V _{CCB} = 3.3 V		
	A to B			V _{CCA} = V _{CCB} = 1.2 V		
			$C_L = 0$,	V _{CCA} = V _{CCB} = 1.5 V		
		Outputs disabled	f = 10 MHz,	V _{CCA} = V _{CCB} = 1.8 V	1	
		disabled	$t_r = t_f = 1 \text{ ns}$	V _{CCA} = V _{CCB} = 2.5 V		
C (1)				V _{CCA} = V _{CCB} = 3.3 V		
C _{pdA} (1)				V _{CCA} = V _{CCB} = 1.2 V	12	- pF
			$C_1 = 0$,	V _{CCA} = V _{CCB} = 1.5 V	12	1
		Outputs enabled	f = 10 MHz,	V _{CCA} = V _{CCB} = 1.8 V	12	-
		eliabled	$t_r = t_f = 1 \text{ ns}$	V _{CCA} = V _{CCB} = 2.5 V	13	-
				V _{CCA} = V _{CCB} = 3.3 V	14	-
	B to A	Outputs disabled	$C_L = 0,$ f = 10 MHz, $t_r = t_f = 1 \text{ ns}$	V _{CCA} = V _{CCB} = 1.2 V	1	
				V _{CCA} = V _{CCB} = 1.5 V		
				V _{CCA} = V _{CCB} = 1.8 V		
				V _{CCA} = V _{CCB} = 2.5 V		
				V _{CCA} = V _{CCB} = 3.3 V		
			$C_L = 0,$ f = 10 MHz, $t_r = t_f = 1 \text{ ns}$	V _{CCA} = V _{CCB} = 1.2 V	12	
		Outputs enabled		V _{CCA} = V _{CCB} = 1.5 V	12	
				V _{CCA} = V _{CCB} = 1.8 V	12	
				V _{CCA} = V _{CCB} = 2.5 V	13	
				V _{CCA} = V _{CCB} = 3.3 V	14	
	A to B		C _L = 0,	V _{CCA} = V _{CCB} = 1.2 V		
				V _{CCA} = V _{CCB} = 1.5 V		
		Outputs disabled	f = 10 MHz,	V _{CCA} = V _{CCB} = 1.8 V	1	
		disabled	$t_r = t_f = 1 \text{ ns}$	V _{CCA} = V _{CCB} = 2.5 V		
(1)				V _{CCA} = V _{CCB} = 3.3 V		_
C _{pdB} (1)				V _{CCA} = V _{CCB} = 1.2 V		- pF
			$C_L = 0$,	V _{CCA} = V _{CCB} = 1.5 V		
		Outputs enabled	f = 10 MHz,	V _{CCA} = V _{CCB} = 1.8 V	1	
		enabled	$t_r = t_f = 1 \text{ ns}$	V _{CCA} = V _{CCB} = 2.5 V		
	D. A. A.			V _{CCA} = V _{CCB} = 3.3 V		
	B to A			V _{CCA} = V _{CCB} = 1.2 V		1
			$C_L = 0$,	V _{CCA} = V _{CCB} = 1.5 V		
		Outputs disabled	f = 10 MHz,	V _{CCA} = V _{CCB} = 1.8 V	1	
		uisabicu	$t_r = t_f = 1 \text{ ns}$	V _{CCA} = V _{CCB} = 2.5 V		
				$V_{CCA} = V_{CCB} = 3.3 \text{ V}$		

(1) Power dissipation capacitance per transceiver

Submit Document Feedback

Copyright © 2023 Texas Instruments Incorporated



5.12 Typical Total Static Current Consumption ($I_{CCA} + I_{CCB}$)

V	V _{CCA}						
V _{CCB}	0 V	1.2 V	1.5 V	1.8 V	2.5 V	3.3 V	UNIT
0 V	0	<0.5	<0.5	<0.5	<0.5	<0.5	μΑ
1.2 V	<0.5	<1	<1	<1	<1	1	μΑ
1.5 V	<0.5	<1	<1	<1	<1	1	μΑ
1.8 V	<0.5	<1	<1	<1	<1	<1	μA
2.5 V	<0.5	1	<1	<1	<1	<1	μA
3.3 V	<0.5	1	<1	<1	<1	<1	μA



5.13 Typical Characteristics

 $T_A = 25^{\circ}C$




Figure 5-1. Typical Propagation Delay (A to B) vs Load Capacitance




Figure 5-2. Typical Propagation Delay (A to B) vs Load Capacitance




Figure 5-3. Typical Propagation Delay (A to B) vs Load Capacitance




Figure 5-4. Typical Propagation Delay (A to B) vs Load Capacitance




Figure 5-5. Typical Propagation Delay (A to B) vs Load Capacitance




Figure 5-6. Typical Propagation Delay (A to B) vs Load Capacitance

5.13 Typical Characteristics (continued)

 $T_A = 25^{\circ}C$




Figure 5-7. Typical Propagation Delay (A to B) vs Load Capacitance




Figure 5-8. Typical Propagation Delay (A to B) vs Load Capacitance




Figure 5-9. Typical Propagation Delay (A to B) vs Load Capacitance




Figure 5-10. Low-Level Output Voltage (V_{OL}) vs Low-Level Current (I_{OL})





Figure 5-11. High-Level Output Voltage (V_{OH}) vs High-Level Current (I_{OH})



 V_{CCA}


6 Parameter Measurement Information




TEST	S 1
t _{pd}	Open
t _{PLZ} /t _{PZL}	2 × V _{CCO}
t _{PHZ} /t _{PZH}	GND


LOAD CIRCUIT

V _{cco}	CL	R _L	V _{TP}
1.2 V	15 pF	2 k Ω	0.1 V
1.5 V ± 0.1 V	15 pF	2 k Ω	0.1 V
1.8 V ± 0.15 V	15 pF	2 k Ω	0.15 V
2.5 V ± 0.2 V	15 pF	2 k Ω	0.15 V
3.3 V ± 0.3 V	15 pF	2 k Ω	0.3 V





ENABLE AND DISABLE TIMES



NOTES: A. C_L includes probe and jig capacitance.

B. Waveform 1 is for an output with internal conditions such that the output is low except when disabled by the output control. Waveform 2 is for an output with internal conditions such that the output is high, except when disabled by the output control.

Output

- C. All input pulses are supplied by generators having the following characteristics: PRR ≤ 10 MHz, Z_Ω= 50Ω, dv/dt ≥ 1 V/ns.
- D. The outputs are measured one at a time, with one transition per measurement.
- E. t_{PLZ} and t_{PHZ} are the same as t_{dis} .
- F. t_{PZL} and t_{PZH} are the same as t_{en} .
- $\begin{array}{ll} \text{G.} & t_{PLH} \text{ and } t_{PHL} \text{ are the same as } t_{pd}. \\ \text{H.} & V_{CCI} \text{ is the } V_{CC} \text{ associated with the input port.} \end{array}$
- I. V_{CCO} is the V_{CC} associated with the output port.

Figure 6-1. Load Circuit and Voltage Waveforms

7 Detailed Description

7.1 Overview

The SN74AVC8T245-Q1 is an 8-bit, dual-supply noninverting bidirectional voltage level translation device. V_{CCA} supports the Ax pins and control pins (DIR and \overline{OE}), and V_{CCB} supports the Bx pins. The A port can accept I/O voltages ranging from 1.2 V to 3.6 V, while the B port can accept I/O voltages from 1.2 V to 3.6 V. A high on DIR allows data transmission from Ax to Bx and a low on DIR allows data transmission from Bx to Ax when \overline{OE} is set to low. When \overline{OE} is set to high, both Ax and Bx pins are in the high-impedance state.

7.2 Functional Block Diagram




Figure 7-1. Logic Diagram (Positive Logic)

7.3 Feature Description

7.3.1 Fully Configurable Dual-Rail Design

Both V_{CCA} and V_{CCB} can be supplied at any voltage between 1.2 V and 3.6 V; thus, making the device an excellent choice for translating between any of the low voltage nodes (1.2 V, 1.8 V, 2.5 V, and 3.3 V).

7.3.2 Supports High Speed Translation

The SN74AVC8T245-Q1 device can support high data rate applications. The translated signal data rate can be up to 380Mbps when the signal is translated from 1.8 V to 3.3 V.

7.3.3 I_{off} Supports Partial-Power-Down Mode Operation

loff prevents backflow current by disabling I/O output circuits when the device is in partial-power-down mode.

7.4 Device Functional Modes

Table 7-1 lists the functional modes of the device.

Table 7-1. Function Table (Each 8-Bit Section)

INP	UTS	OPERATION
ŌĒ	DIR	OPERATION
L	L	B data to A bus
L	Н	A data to B bus
Н	Х	All outputs Hi-



8 Application and Implementation

Note

Information in the following applications sections is not part of the TI component specification, and TI does not warrant its accuracy or completeness. TI's customers are responsible for determining suitability of components for their purposes, as well as validating and testing their design implementation to confirm system functionality.

8.1 Application Information

The SN74AVC8T245-Q1 device can be used in level-translation applications for interfacing devices or systems operating at different interface voltages with one another. The SN74AVC8T245-Q1 device is an excellent choice for applications where a push-pull driver is connected to the data I/Os. The maximum data rate can be up to 320Mbps when the device translates a signal from 1.8 V to 3.3 V.

8.2 Typical Application




Figure 8-1. Typical Application Diagram

Submit Document Feedback

Copyright © 2023 Texas Instruments Incorporated



8.2.1 Design Requirements

Table 8-1 lists the parameters for this design example.

Table 8-1. Design Parameters

DESIGN PARAMETER	EXAMPLE VALUE
Input voltage range	1.2 V
Output voltage range	3.3 V

8.2.2 Detailed Design Procedure

To begin the design process, determine the following:

- · Input voltage range
 - Use the supply voltage of the device that is driving the SN74AVC8T245-Q1 device to determine the input voltage range. For a valid logic high, the value must exceed the V_{IH} of the input port. For a valid logic low, the value must be less than the V_{IL} of the input port. For this example, the input voltage is 1.2 V.
- · Output voltage range
 - Use the supply voltage of the device that the SN74AVC8T245-Q1 device is driving to determine the output voltage range. For this example, the output voltage is 3.3 V.

8.2.3 Application Curve




Figure 8-2. Translation Up (1.2 V to 3.3 V) at 2.5 MHz

8.3 Power Supply Recommendations

The SN74AVC8T245-Q1 device uses two separate configurable power-supply rails: V_{CCA} and V_{CCB} . V_{CCA} accepts any supply voltage from 1.2 V to 3.6 V, and V_{CCB} accepts any supply voltage from 1.2 V to 3.6 V. The A port and B port are designed to track V_{CCA} and V_{CCB} respectively, allowing for low-voltage bidirectional translation between any of the 1.2-V, 1.5-V, 1.8-V, 2.5-V, and 3.3-V voltage nodes.

 V_{CCA} supplies the output-enable (\overline{OE}) input circuit in this design; when the \overline{OE} input is high, all outputs are placed in the high-impedance state. To put the outputs in the high-impedance state during power up or power down, the \overline{OE} input pin must be tied to V_{CCA} through a pullup resistor and must not be enabled until V_{CCA} and V_{CCB} are fully ramped and stable. The current-sinking capability of the driver determines the minimum value of the pullup resistor to V_{CCA} .



8.4 Layout

8.4.1 Layout Guidelines

For device reliability, it is recommended to follow common printed-circuit board layout guidelines:

- Use bypass capacitors on power supplies.
- Use short trace lengths to avoid excessive loading.
- Place pads on the signal paths for loading capacitors or pullup resistors to adjust signal rise and fall times, depending on the system requirements.

8.4.2 Layout Example






Figure 8-3. SN74AVC8T245-Q1 Layout Diagram

Submit Document Feedback

Copyright © 2023 Texas Instruments Incorporated



9 Device and Documentation Support

9.1 Documentation Support

9.1.1 Related Documentation

For related documentation see the following:

- Texas Instruments, Implications of Slow or Floating CMOS Inputs Application Note
- Texas Instruments, Understanding and Interpreting Standard-Logic Data Sheets Application Note
- Texas Instruments, Introduction to Logic Application Note
- Texas Instruments, Voltage Translation Between 3.3-V, 2.5-V, 1.8-V, and 1.5-V Logic Standards Application Note
- Texas Instruments, AVC Advanced Very-Low-Voltage CMOS Logic Data Book User's Guide

9.2 Receiving Notification of Documentation Updates

To receive notification of documentation updates, navigate to the device product folder on ti.com. Click on *Notifications* to register and receive a weekly digest of any product information that has changed. For change details, review the revision history included in any revised document.

9.3 Support Resources

TI E2E[™] support forums are an engineer's go-to source for fast, verified answers and design help — straight from the experts. Search existing answers or ask your own question to get the quick design help you need.

Linked content is provided "AS IS" by the respective contributors. They do not constitute TI specifications and do not necessarily reflect TI's views; see TI's Terms of Use.

9.4 Trademarks

TI E2E™ is a trademark of Texas Instruments.

All trademarks are the property of their respective owners.

9.5 Electrostatic Discharge Caution



This integrated circuit can be damaged by ESD. Texas Instruments recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage.

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.

9.6 Glossary

TI Glossary

This glossary lists and explains terms, acronyms, and definitions.

10 Revision History

NOTE: Page numbers for previous revisions may differ from page numbers in the current version.

С	hanges from Revision D (October 2017) to Revision E (November 2023)	Page
•	Updated the numbering format for tables, figures, and cross-references throughout the document	1
•	Updated the thermal information for the RHL package and updated the information for the PW package	
С	hanges from Revision C (March 2016) to Revision D (October 2017)	Page
•	Added Junction temperature, T _J in <i>Absolute Maximum Ratings</i> table	4
•	Deleted 2DIR and 2 OE from Overview	17
С	hanges from Revision B (December 2012) to Revision C (January 2016)	Page
•	Added ESD Ratings table, Feature Description section, Device Functional Modes, Application and	
	Implementation section, Power Supply Recommendations section, Layout section, Device and	
	Documentation Support section, and Mechanical, Packaging, and Orderable Information section	1
•	Deleted Ordering Information table	1

Copyright © 2023 Texas Instruments Incorporated



Changes from Revision A (June 2011) to Revision B (December 2012)	Page
Added bullets to the Features list	
Added Pin Functions table to the data sheet	3
 Deleted θ_{JA} row from Absolute Maximum Ratings table 	4
Changed ESD ratings	
Added Thermal Information table	
• Added Figure 7-10 and Figure 7-11 to the <i>Typical Characteristics</i> section .	

11 Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

Product Folder Links: SN74AVC8T245-Q1

www.ti.com 9-Nov-2025

PACKAGING INFORMATION

Orderable part number	Status	Material type	Package Pins	Package qty Carrier	RoHS	Lead finish/ Ball material	MSL rating/ Peak reflow	Op temp (°C)	Part marking (6)
		()			(-/	(4)	(5)		(-,
CAVC8T245QRHLRQ1	Active	Production	VQFN (RHL) 24	1000 LARGE T&R	Yes	NIPDAU	Level-2-260C-1 YEAR	-40 to 125	WE245Q
CAVC8T245QRHLRQ1.A	Active	Production	VQFN (RHL) 24	1000 LARGE T&R	Yes	NIPDAU	Level-2-260C-1 YEAR	-40 to 125	WE245Q
CAVC8T245QRHLRQ1.B	Active	Production	VQFN (RHL) 24	1000 LARGE T&R	Yes	NIPDAU	Level-2-260C-1 YEAR	-40 to 125	WE245Q
SN74AVC8T245QPWRQ1	Active	Production	TSSOP (PW) 24	2000 LARGE T&R	Yes	NIPDAU	Level-3-260C-168 HR	-40 to 125	WE245Q
SN74AVC8T245QPWRQ1.A	Active	Production	TSSOP (PW) 24	2000 LARGE T&R	Yes	NIPDAU	Level-3-260C-168 HR	-40 to 125	WE245Q
SN74AVC8T245QPWRQ1.B	Active	Production	TSSOP (PW) 24	2000 LARGE T&R	Yes	NIPDAU	Level-3-260C-168 HR	-40 to 125	WE245Q

⁽¹⁾ Status: For more details on status, see our product life cycle.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

⁽²⁾ Material type: When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

⁽³⁾ RoHS values: Yes, No, RoHS Exempt. See the TI RoHS Statement for additional information and value definition.

⁽⁴⁾ Lead finish/Ball material: Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

⁽⁵⁾ MSL rating/Peak reflow: The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

⁽⁶⁾ Part marking: There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

PACKAGE OPTION ADDENDUM

www.ti.com 9-Nov-2025

OTHER QUALIFIED VERSIONS OF SN74AVC8T245-Q1:

● Catalog : SN74AVC8T245

NOTE: Qualified Version Definitions:

Catalog - TI's standard catalog product

PACKAGE MATERIALS INFORMATION

www.ti.com 14-Nov-2025

TAPE AND REEL INFORMATION





A0	Dimension designed to accommodate the component width
В0	Dimension designed to accommodate the component length
K0	Dimension designed to accommodate the component thickness
W	Overall width of the carrier tape
P1	Pitch between successive cavity centers

QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE



*All dimensions are nominal

Device	Package Type	Package Drawing		SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
CAVC8T245QRHLRQ1	VQFN	RHL	24	1000	330.0	12.4	3.8	5.8	1.2	8.0	12.0	Q1
SN74AVC8T245QPWRQ1	TSSOP	PW	24	2000	330.0	16.4	6.95	8.3	1.6	8.0	16.0	Q1

www.ti.com 14-Nov-2025



*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
CAVC8T245QRHLRQ1	VQFN	RHL	24	1000	367.0	367.0	35.0
SN74AVC8T245QPWRQ1	TSSOP	PW	24	2000	353.0	353.0	32.0



SMALL OUTLINE PACKAGE



NOTES:

- 1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.

 2. This drawing is subject to change without notice.

 3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not
- exceed 0.15 mm per side.
- 4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.25 mm per side.
- 5. Reference JEDEC registration MO-153.



SMALL OUTLINE PACKAGE



NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.

7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.



SMALL OUTLINE PACKAGE




NOTES: (continued)

- 8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
- 9. Board assembly site may have different recommendations for stencil design.



PLASTIC QUAD FLATPACK- NO LEAD




NOTES:

- All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
- 2. This drawing is subject to change without notice.
- 3. The package thermal pad must be soldered to the printed circuit board for optimal thermal and mechanical performance.



PLASTIC QUAD FLATPACK- NO LEAD




NOTES: (continued)

- 4. This package is designed to be soldered to a thermal pad on the board. For more information, see Texas Instruments literature number SLUA271 (www.ti.com/lit/slua271).
- 5. Vias are optional depending on application, refer to device data sheet. If any vias are implemented, refer to their locations shown on this view. It is recommended that vias under paste be filled, plugged or tented.



PLASTIC QUAD FLATPACK- NO LEAD



NOTES: (continued)

6. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.



IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you fully indemnify TI and its representatives against any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale, TI's General Quality Guidelines, or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products. Unless TI explicitly designates a product as custom or customer-specified, TI products are standard, catalog, general purpose devices.

TI objects to and rejects any additional or different terms you may propose.

Copyright © 2025, Texas Instruments Incorporated

Last updated 10/2025