

The SN54F299 is obsolete and no longer supplied.

SN54F299, SN74F299 8-BIT UNIVERSAL SHIFT/STORAGE REGISTERS WITH 3-STATE OUTPUTS

SDFS071B – MARCH 1987 – REVISED APRIL 2004


- **Four Modes of Operation:**
 - Hold (Store)
 - Shift Right
 - Shift Left
 - Load Data
- **Operates With Outputs Enabled or at High Impedance**
- **3-State Outputs Drive Bus Lines Directly**
- **Can Be Cascaded for N-Bit Word Lengths**
- **Direct Overriding Clear**
- **Applications:**
 - Stacked or Pushdown Registers
 - Buffer Storage
 - Accumulator Registers

description/ordering information


These 8-bit universal shift/storage registers feature multiplexed I/O ports to achieve full 8-bit data handling in a single 20-pin package. Two function-select (S_0, S_1) inputs and two output-enable ($\overline{OE1}, \overline{OE2}$) inputs can be used to choose the modes of operation listed in the function table.

Synchronous parallel loading is accomplished by taking both S_0 and S_1 high. This places the 3-state outputs in a high-impedance state and permits data that is applied on the I/O ports to be clocked into the register. Reading out of the register can be accomplished while the outputs are enabled in any mode. Clearing occurs when the clear (\overline{CLR}) input is low. Taking either $\overline{OE1}$ or $\overline{OE2}$ high disables the outputs but has no effect on clearing, shifting, or storage of data.

SN54F299 . . . J PACKAGE
SN74F299 . . . DW, N, OR NS PACKAGE
(TOP VIEW)



SN54F299 . . . FK PACKAGE
(TOP VIEW)



ORDERING INFORMATION

| T_A | PACKAGE† | | ORDERABLE PART NUMBER | TOP-SIDE MARKING |
|-------------|-----------|--------------|-----------------------|------------------|
| 0°C to 70°C | PDIP – N | Tube of 20 | SN74F299N | SN74F299N |
| | SOIC – DW | Tube of 25 | SN74F299DW | F299 |
| | | Reel of 2000 | SN74F299DWR | |
| | SOP – NS | Reel of 2000 | SN74F299NSR | 74F299 |

† Package drawings, standard packing quantities, thermal data, symbolization, and PCB design guidelines are available at www.ti.com/sc/package.



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

**TEXAS
INSTRUMENTS**

POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

Copyright © 2004, Texas Instruments Incorporated

SN54F299, SN74F299

8-BIT UNIVERSAL SHIFT/STORAGE REGISTERS

WITH 3-STATE OUTPUTS

SDFS071B – MARCH 1987 – REVISED APRIL 2004

The SN54F299 is obsolete and no longer supplied.


FUNCTION TABLE

| MODE | INPUTS | | | | | | | | I/O PORTS | | | | | | | | OUTPUTS | |
|-------------|--------|----|----|------|------|-----|----|----|------------------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|
| | CLR | S1 | S0 | OE1† | OE2† | CLK | SL | SR | A/Q _A | B/Q _B | C/Q _C | D/Q _D | E/Q _E | F/Q _F | G/Q _G | H/Q _H | Q _A ' | Q _H ' |
| Clear | L | X | L | L | L | X | X | X | L | L | L | L | L | L | L | L | L | L |
| | L | L | X | L | L | X | X | X | L | L | L | L | L | L | L | L | L | L |
| | L | H | H | X | X | X | X | X | X | X | X | X | X | X | X | X | L | L |
| Hold | H | L | L | L | L | X | X | X | Q _{A0} | Q _{B0} | Q _{C0} | Q _{D0} | Q _{E0} | Q _{F0} | Q _{G0} | Q _{H0} | Q _{A0} | Q _{H0} |
| | H | X | X | L | L | L | X | X | Q _{A0} | Q _{B0} | Q _{C0} | Q _{D0} | Q _{E0} | Q _{F0} | Q _{G0} | Q _{H0} | Q _{A0} | Q _{H0} |
| Shift Right | H | L | H | L | L | ↑ | X | H | H | Q _{An} | Q _{Bn} | Q _{Cn} | Q _{Dn} | Q _{En} | Q _{Fn} | Q _{Gn} | H | Q _{Gn} |
| | H | L | H | L | L | ↑ | X | L | L | Q _{An} | Q _{Bn} | Q _{Cn} | Q _{Dn} | Q _{En} | Q _{Fn} | Q _{Gn} | L | Q _{Gn} |
| Shift Left | H | H | L | L | L | ↑ | H | X | Q _{Bn} | Q _{Cn} | Q _{Dn} | Q _{En} | Q _{Fn} | Q _{Gn} | Q _{Hn} | H | Q _{Bn} | H |
| | H | H | L | L | L | ↑ | L | X | Q _{Bn} | Q _{Cn} | Q _{Dn} | Q _{En} | Q _{Fn} | Q _{Gn} | Q _{Hn} | L | Q _{Bn} | L |
| Load | H | H | H | X | X | ↑ | X | X | a | b | c | d | e | f | g | h | a | h |

NOTE: a . . . h = the level of the steady-state input at inputs A through H, respectively. This data is loaded into the flip-flops while the flip-flop outputs are isolated from the I/O terminals.

† When one or both output-enable inputs are high, the eight I/O terminals are disabled to the high-impedance state; however, sequential operation or clearing of the register is not affected.

logic diagram (positive logic)



‡ I/O ports not shown: B/Q_B (13), C/Q_C (6), D/Q_D (14), E/Q_E (5), F/Q_F (15), and G/Q_G (4).

The SN54F299 is obsolete and no longer supplied.

SN54F299, SN74F299 8-BIT UNIVERSAL SHIFT/STORAGE REGISTERS WITH 3-STATE OUTPUTS

SDFS071B – MARCH 1987 – REVISED APRIL 2004

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)[†]

| | |
|--|--------------------|
| Supply voltage range, V_{CC} | –0.5 V to 7 V |
| Input voltage range, V_I (see Note 1) | –1.2 V to 7 V |
| Input current range | –30 mA to 5 mA |
| Voltage range applied to any output in the disabled or power-off state | –0.5 V to 5.5 V |
| Voltage range applied to any output in the high state | –0.5 V to V_{CC} |
| Current into any output in the low state: Q_A' or Q_H' | 40 mA |
| SN54F299 (Q_A thru Q_H) | 40 mA |
| SN74F299 (Q_A thru Q_H) | 48 mA |
| Package thermal impedance, θ_{JA} (see Note 2): DW package | 58°C/W |
| N package | 69°C/W |
| NS package | 60°C/W |
| Storage temperature range, T_{stg} | –65°C to 150°C |

[†] Stresses beyond those listed under “absolute maximum ratings” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

- NOTES: 1. The input voltage ratings may be exceeded provided the input current ratings are observed.
2. The package thermal impedance is calculated in accordance with JESD 51-7.

recommended operating conditions (see Note 3)

| | | SN54F299 | | | SN74F299 | | | UNIT |
|----------|--------------------------------|----------|-----|------------------|----------|-----|------------------|------|
| | | MIN | NOM | MAX | MIN | NOM | MAX | |
| V_{CC} | Supply voltage | 4.5 | 5 | 5.5 | 4.5 | 5 | 5.5 | V |
| V_{IH} | High-level input voltage | 2 | | | 2 | | | V |
| V_{IL} | Low-level input voltage | | | 0.8 | | | 0.8 | V |
| I_{IK} | Input clamp current | | | –18 | | | –18 | mA |
| I_{OH} | High-level output current | | | Q_A' or Q_H' | | | Q_A' or Q_H' | mA |
| | | | | Q_A thru Q_H | | | Q_A thru Q_H | |
| I_{OL} | Low-level output current | | | Q_A' or Q_H' | | | Q_A' or Q_H' | mA |
| | | | | Q_A thru Q_H | | | Q_A thru Q_H | |
| T_A | Operating free-air temperature | –55 | | 125 | 0 | | 70 | °C |

NOTE 3: All unused inputs of the device must be held at V_{CC} or GND to ensure proper device operation. Refer to the TI application report, *Implications of Slow or Floating CMOS Inputs*, literature number SCBA004.

SN54F299, SN74F299

8-BIT UNIVERSAL SHIFT/STORAGE REGISTERS

WITH 3-STATE OUTPUTS

SDFS071B – MARCH 1987 – REVISED APRIL 2004

The SN54F299 is obsolete and no longer supplied.

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

| PARAMETER | | TEST CONDITIONS | | SN54F299 | | | SN74F299 | | | UNIT |
|-------------------|--------------------------------------|--|--------------------------|----------|-------|-------|----------|-------|-----|------|
| | | | | MIN | TYP† | MAX | MIN | TYP† | MAX | |
| V _{IK} | | V _{CC} = 4.5 V, I _I = − 18 mA | | − 1.2 | | | − 1.2 | | | V |
| V _{OH} | Q _A ' or Q _H ' | V _{CC} = 4.5 V | I _{OH} = − 1 mA | 2.5 | 3.4 | | 2.5 | 3.4 | | V |
| | Q _A thru Q _H | | I _{OH} = − 1 mA | 2.5 | 3.4 | | 2.5 | 3.4 | | |
| | | | I _{OH} = − 3 mA | 2.4 | 3.3 | | 2.4 | 3.3 | | |
| | Any output | V _{CC} = 4.75 V, I _{OH} = − 1 mA to − 3 mA | | | | 2.7 | | | | |
| V _{OL} | Q _A ' or Q _H ' | V _{CC} = 4.5 V | I _{OL} = 20 mA | 0.3 | 0.5 | | 0.3 | 0.5 | | V |
| | Q _A thru Q _H | | I _{OL} = 20 mA | 0.3 | 0.5 | | | | | |
| | | | I _{OL} = 24 mA | | | | 0.35 | 0.5 | | |
| I _I | A thru H | V _{CC} = 5.5 V | V _I = 5.5 V | 1 | | | 1 | | | mA |
| | Any other | | V _I = 7 V | 0.1 | | | 0.1 | | | |
| I _{IH} ‡ | A thru H | V _{CC} = 5.5 V, V _I = 2.7 V | | 70 | | | 70 | | | μA |
| | Any other | | 20 | | | 20 | | | | |
| I _{IL} ‡ | A thru H | V _{CC} = 5.5 V, V _I = 0.5 V | | − 0.65 | | | − 0.65 | | | mA |
| | S0 or S1 | | − 1.2 | | | − 1.2 | | | | |
| | Any other | | − 0.6 | | | − 0.6 | | | | |
| | | | | | | | | | | |
| I _{OS} § | | V _{CC} = 5.5 V, V _O = 0 | | − 60 | − 150 | | − 60 | − 150 | | mA |
| I _{CC} | | V _{CC} = 5.5 V, See Note 4 | | 68 | 95 | | 68 | 95 | | mA |

† All typical values are at $V_{CC} = 5\text{ V}$, $T_A = 25^\circ\text{C}$.

‡ For I/O ports (Q_A thru Q_H), the parameters I_{IH} and I_{IL} include the off-state output current.

§ Not more than one output should be shorted at a time, and the duration of the short circuit should not exceed one second.

NOTE 4: I_{CC} is measured with $\overline{OE}1$, $\overline{OE}2$, and CLK at 4.5 V.

timing requirements over recommended ranges of supply voltage and operating free-air temperature (unless otherwise noted)

| | | | | V _{CC} = 5 V, T _A = 25°C | | SN54F299 | | SN74F299 | | UNIT | | | |
|--------------------|--|--|--|---|-------------|----------|-----|----------|-----|------|----|----|----|
| | | | | 'F299 | | | | | | | | | |
| | | | | MIN | MAX | MIN | MAX | MIN | MAX | | | | |
| f _{clock} | Clock frequency | | | 70 | | 65 | | 70 | | MHz | | | |
| t _w | Pulse duration | | CLK high or low | | 7 | | 8 | | 7 | | ns | | |
| | | | CLR low | | 7 | | 8 | | 7 | | | | |
| t _{su} | Setup time before CLK↑ | S0 or S1 | | High or low | | 8.5 | | 9.5 | | 8.5 | | ns | |
| | | A/Q _A thru H/Q _H , SR, or SL | | High or low | | 5.5 | | 6.5 | | 5.5 | | | |
| | Inactive-state setup time before CLK↑¶ | CLR | | High | | 7 | | 13 | | 7 | | | |
| t _h | Hold time after CLK↑ | | S0 or S1 | | High or low | | 0 | | 0 | | 0 | | ns |
| | | | A/Q _A thru H/Q _H , SR, or SL | | High or low | | 2 | | 2 | | 2 | | |

† Inactive-state setup time also is referred to as recovery time.



POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

The SN54F299 is obsolete and no longer supplied.

SN54F299, SN74F299 8-BIT UNIVERSAL SHIFT/STORAGE REGISTERS WITH 3-STATE OUTPUTS

SDFS071B – MARCH 1987 – REVISED APRIL 2004

switching characteristics (see Figure 1)

| PARAMETER | FROM (INPUT) | TO (OUTPUT) | V _{CC} = 5 V, C _L = 50 pF, R _L = 500 Ω, T _A = 25°C | | | V _{CC} = 4.5 V to 5.5 V, C _L = 50 pF, R _L = 500 Ω, T _A = MIN to MAX† | | | | UNIT |
|------------------|--|--------------------------------------|---|------|-----|---|------|----------|------|------|
| | | | 'F299 | | | SN54F299 | | SN74F299 | | |
| | | | MIN | TYP | MAX | MIN | MAX | MIN | MAX | |
| f _{max} | | | 70 | 100 | | 65 | | 70 | | MHz |
| t _{PLH} | CLK | Q _A ' or Q _H ' | 3.2 | 6.6 | 9 | 2.7 | 10.5 | 3.2 | 10 | ns |
| t _{PHL} | | | 2.7 | 6.1 | 8.5 | 2.2 | 10 | 2.7 | 9.5 | |
| t _{PLH} | CLK | Q _A thru Q _H | 3.2 | 6.6 | 9 | 2.7 | 11 | 3.2 | 10 | ns |
| t _{PHL} | | | 4.2 | 8.1 | 11 | 3.7 | 12.5 | 4.2 | 12 | |
| t _{PHL} | $\overline{\text{CLR}}$ | Q _A ' or Q _H ' | 3.7 | 7.1 | 9.5 | 3.2 | 11.5 | 3.7 | 10.5 | ns |
| | | Q _A thru Q _H | 5.7 | 10.6 | 14 | 5 | 15.5 | 5.7 | 15 | |
| t _{PZH} | $\overline{\text{OE1}}$ or $\overline{\text{OE2}}$ | Q _A thru Q _H | 2.7 | 5.6 | 8 | 2.2 | 10.5 | 2.7 | 9 | ns |
| t _{PZL} | | | 3.2 | 6.6 | 10 | 2.7 | 12 | 3.2 | 11 | |
| t _{PHZ} | $\overline{\text{OE1}}$ or $\overline{\text{OE2}}$ | Q _A thru Q _H | 1.7 | 4.1 | 6 | 1.7 | 9 | 1.7 | 7 | ns |
| t _{PLZ} | | | 1.2 | 3.6 | 5.5 | 1.2 | 7.5 | 1.2 | 6.5 | |

† For conditions shown as MIN or MAX, use the appropriate value specified under recommended operating conditions.



SN54F299, SN74F299


8-BIT UNIVERSAL SHIFT/STORAGE REGISTERS

WITH 3-STATE OUTPUTS

SDFS071B – MARCH 1987 – REVISED APRIL 2004

The SN54F299 is obsolete and no longer supplied.

PARAMETER MEASUREMENT INFORMATION



- NOTES: A. C_L includes probe and jig capacitance.
- B. Waveform 1 is for an output with internal conditions such that the output is low, except when disabled by the output control. Waveform 2 is for an output with internal conditions such that the output is high, except when disabled by the output control.
- C. All input pulses are supplied by generators having the following characteristics: $PRR \leq 1$ MHz, $Z_O = 50 \Omega$, $t_r \leq 2.5$ ns, $t_f \leq 2.5$ ns, duty cycle = 50%.
- D. The outputs are measured one at a time, with one input transition per measurement.

Figure 1. Load Circuit and Voltage Waveforms

PACKAGING INFORMATION

| Orderable part number | Status (1) | Material type (2) | Package Pins | Package qty Carrier | RoHS (3) | Lead finish/ Ball material (4) | MSL rating/ Peak reflow (5) | Op temp (°C) | Part marking (6) |
|-----------------------------|---------------|----------------------|----------------|-----------------------|-------------|--------------------------------------|-----------------------------------|--------------|---------------------|
| SN74F299DW | Obsolete | Production | SOIC (DW) 20 | - | - | Call TI | Call TI | 0 to 70 | F299 |
| SN74F299DWR | Active | Production | SOIC (DW) 20 | 2000 LARGE T&R | Yes | NIPDAU | Level-1-260C-UNLIM | 0 to 70 | F299 |
| SN74F299DWR.A | Active | Production | SOIC (DW) 20 | 2000 LARGE T&R | Yes | NIPDAU | Level-1-260C-UNLIM | 0 to 70 | F299 |
| SN74F299N | Active | Production | PDIP (N) 20 | 20 TUBE | Yes | NIPDAU | N/A for Pkg Type | 0 to 70 | SN74F299N |
| SN74F299N.A | Active | Production | PDIP (N) 20 | 20 TUBE | Yes | NIPDAU | N/A for Pkg Type | 0 to 70 | SN74F299N |
| SN74F299NS.A | Active | Production | SOP (NS) 20 | 40 TUBE | Yes | NIPDAU | Level-1-260C-UNLIM | 0 to 70 | 74F299 |

⁽¹⁾ **Status:** For more details on status, see our [product life cycle](#).

⁽²⁾ **Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

⁽³⁾ **RoHS values:** Yes, No, RoHS Exempt. See the [TI RoHS Statement](#) for additional information and value definition.

⁽⁴⁾ **Lead finish/Ball material:** Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

⁽⁵⁾ **MSL rating/Peak reflow:** The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

⁽⁶⁾ **Part marking:** There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

TAPE AND REEL INFORMATION



*All dimensions are nominal

| Device | Package Type | Package Drawing | Pins | SPQ | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|-------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| SN74F299DWR | SOIC | DW | 20 | 2000 | 330.0 | 24.4 | 10.8 | 13.3 | 2.7 | 12.0 | 24.0 | Q1 |

TAPE AND REEL BOX DIMENSIONS



*All dimensions are nominal

| Device | Package Type | Package Drawing | Pins | SPQ | Length (mm) | Width (mm) | Height (mm) |
|-------------|--------------|-----------------|------|------|-------------|------------|-------------|
| SN74F299DWR | SOIC | DW | 20 | 2000 | 356.0 | 356.0 | 45.0 |

TUBE



*All dimensions are nominal

| Device | Package Name | Package Type | Pins | SPQ | L (mm) | W (mm) | T (μm) | B (mm) |
|--------------|--------------|--------------|------|-----|--------|--------|--------|--------|
| SN74F299N | N | PDIP | 20 | 20 | 506 | 13.97 | 11230 | 4.32 |
| SN74F299N.A | N | PDIP | 20 | 20 | 506 | 13.97 | 11230 | 4.32 |
| SN74F299NS.A | NS | SOP | 20 | 40 | 530 | 10.5 | 4000 | 4.1 |

MECHANICAL DATA

NS (R-PDSO-G**)

PLASTIC SMALL-OUTLINE PACKAGE

14-PINS SHOWN



- NOTES:
- A. All linear dimensions are in millimeters.
 - B. This drawing is subject to change without notice.
 - C. Body dimensions do not include mold flash or protrusion, not to exceed 0,15.

N (R-PDIP-T**)

16 PINS SHOWN

PLASTIC DUAL-IN-LINE PACKAGE



| PINS ** DIM | 14 | 16 | 18 | 20 |
|---------------------|------------------|------------------|------------------|------------------|
| A MAX | 0.775 (19,69) | 0.775 (19,69) | 0.920 (23,37) | 1.060 (26,92) |
| A MIN | 0.745 (18,92) | 0.745 (18,92) | 0.850 (21,59) | 0.940 (23,88) |
| MS-001 VARIATION | AA | BB | AC | AD |




4040049/E 12/2002

NOTES:

- A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
-  Falls within JEDEC MS-001, except 18 and 20 pin minimum body length (Dim A).
 The 20 pin end lead shoulder width is a vendor option, either half or full width.

DW0020A**PACKAGE OUTLINE****SOIC - 2.65 mm max height**

SOIC

**NOTES:**

1. All linear dimensions are in millimeters. Dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm per side.
4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.43 mm per side.
5. Reference JEDEC registration MS-013.

DW0020A

SOIC - 2.65 mm max height

SOIC



LAND PATTERN EXAMPLE
SCALE:6X



SOLDER MASK DETAILS

4220724/A 05/2016

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.
7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

EXAMPLE STENCIL DESIGN

DW0020A

SOIC - 2.65 mm max height

SOIC



SOLDER PASTE EXAMPLE
BASED ON 0.125 mm THICK STENCIL
SCALE:6X

4220724/A 05/2016

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you fully indemnify TI and its representatives against any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to [TI's Terms of Sale](#), [TI's General Quality Guidelines](#), or other applicable terms available either on [ti.com](https://www.ti.com) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products. Unless TI explicitly designates a product as custom or customer-specified, TI products are standard, catalog, general purpose devices.

TI objects to and rejects any additional or different terms you may propose.

Copyright © 2025, Texas Instruments Incorporated

Last updated 10/2025