- Programmable Look-Ahead Up/Down Binary Counters
- Fully Synchronous Operation for Counting and Programming
- Internal Look-Ahead for Fast Counting
- · Carry Output for n-Bit Cascading
- Fully Independent Clock Circuit


description

These synchronous presettable counters feature an internal carry look-ahead for cascading in high speed counting applications. The 'LS169B and 'S169 are 4-bit binary counters. Synchronous operation is provided by having all flip-flops clocked simultaneously so that the outputs change coincident with each other when so instructed by the countenable inputs and internal gating. This mode of operation helps eliminate the output counting spikes that are normally associated with asynchronous (ripple-clock) counters. A buffered clock input triggers the four master-slave flip-flops on the rising (positive-going) edge of the clock waveform.

These counters are fully programmable; that is the outputs may each be preset to either level. The load input circuitry allows loading with the carry-enable output of cascaded counters. As loading is synchronous, setting up a low level at the load input disables the counter and causes the outputs to agree with the data inputs after the next clock pulse.

SN54LS169B, SN54S169 . . . J OR W PACKAGE SN74LS169B, SN74S169 . . . D OR N PACKAGE (TOP VIEW) U₁6∐Vcc U/D∏1 15 RCO CLK 2 $A \square 3$ 14 □ QA В 🛛 4 13 🛮 QB 12 QC C∐5 D [] € 11 🗌 QD 10 ENT ENP 7 9 LOAD GND ∐8

SN54LS169B, SN54S169 . . . FK PACKAGE (TOP VIEW)




NC-No internal connection

TYPE	''''	MAXIMUM REQUENCY	TYPICAL POWER
	COUNTING	COUNTING DOWN	DISSIPATION
'LS169B	35MHz	35MHz	100mW
'S169	70MHz	500mW	

The carry look-ahead circuitry provides for cascading counters for n-bit synchronous applications without additional gating. Instrumental in accomplishing this function are two count-enable inputs and a carry output. Both count enable inputs (ENP, ENT) must be low to count. The direction of the count is determined by the level of the up/down input. When the input is high, the counter counts up; when low, it counts down. Input ENT is fed forward to enable the carry output. The carry output thus enabled will produce a low-level output pulse with a duration approximately equal to the high portion of the QA output when counting up and approximately equal to the low portion of the QA output when counting down. This low-level overflow carry pulse can be used to enable successive cascaded stages. Transitions at the ENP or ENT inputs are allowed regardless of the level of the clock input. All inputs are diode-clamped to minimize transmission-line effects, thereby simplifying system design.

These counters feature a fully independent clock circuit. Changes at control inputs ($\overline{\text{ENP}}$, $\overline{\text{ENT}}$, $\overline{\text{LOAD}}$, $\overline{\text{U/D}}$) that will modify the operating mode have no effect until clocking occurs. The function of the counter (whether enabled, disabled, loading, or counting) will be dictated solely by the conditions meeting the stable setup and hold times.


logic symbol[†]



 † This symbol is in accordance with ANSI/IEEE Std. 91-1984 and IEC Publication 617-12. Pin numbers shown are for D, J, N, and W packages.




logic diagram (positive logic)



Pin numbers shown are for D, J, N, and W packages.

logic diagram (positive logic)




Pin numbers shown are for D, J, N, and W packages.



typical load, count, and inhibit sequences


Illustrated below is the following sequence:

- 1. Load (preset) to binary thirteen.
- 2. Count up to fourteen, fifteen (maximum), zero, one, and two.
- 3. Inhibit
- 4. Count down to one, zero (minimum), fifteen, fourteen, and thirteen





schematics of inputs and outputs



absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

Supply voltage, VCC (see Note 1)		7 V
Input voltage		7 V
Operating free-air temperature range	: SN54LS169B	$ 55^{\circ}$ C to 125° C
	SN74LS169B	0°C to 70°C
Storage temperature range		65° C to 150° C

NOTE 1: Voltage values are with respect to network ground terminal.

recommended operating conditions

				SI	154LS1	69B	SN	174LS16	59B	UNIT
				MIN	NOM	MAX	MIN	NOM	MAX	ONT
Vcc	Supply voltage			4.5	5	5.5	4.75	5	5.25	V
VIH	High-level-input voltage	2			2			V		
VIL	Low-level input voltage					0.7			8.0	V
ЮН	High-level output current		RCO			- 0.4			- 0.4	mA
0			Any Q			- 1.2			- 1.2	mA
loL	Low-level output current		RCO			4			8	mA
·OL			Any Q			12			24	mA
fclock	Clock frequency			0		20	0		20	MHz
tw(clock)	Width of clock pulse (high or low) (see Figure 1)		25			25			ns
		Data inputs	A, B, C, D	30			30]
		ENP or ENT		30			30			ns
t _{su}	Setup time, (see Figure 1)	Load		35			35] '''
			35			35				
th	Hold time at any input with respect to clock (see Figure 1)						0			ns
TA	Operating free-air temperature			- 55		125	0		70	°c

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

					SN	154LS16	9B	SN	174LS16	59B	UNIT
PARAMETER		TEST COND	ITIONS		MIN	TYP‡	MAX	MIN	TYP‡	MAX	GINET
VIK	V _{CC} = MIN,	I ₁ = - 18 mA					– 1.5			– 1. 5	V
	V _{CC} = MIN,	V _{IH} = 2 V,	RCO	I _{OH} = - 0.4 mA	2.5	3.4		2.7	3.4		V
Vон	VIL = MAX		Any Q	I _{OH} = - 1.2 mA	2.4	3.2		2.4	3.2		
			RCO	IOH = 4 mA		0.25	0.4		0.25	0.4	
	V _{CC} = MIN,	V _{IH} = 2 V,	RCO	I _{OL} = 8 mA					0.35	0.5] _v
VOL	VIL = MAX			I _{OL} = 12 mA		0.25	0.4		0.25	0.4]
			Any Q	I _{OL} = 24 mA					0.35	0.5]
Iį	V _{CC} = MAX,	V _I = 7 V	-				0.1			0.1	mA
ПН	V _{CC} = MAX,	V ₁ = 2.7 V					20			20	μА
			U/D, LC	AD, ENP, CLK			- 0.2			- 0.2	^
IL	V _{CC} = MAX,	V ₁ = 0.4 V	All othe				- 0.4			- 0.4	mA
			RCO		- 20		- 100	- 20		- 100	
los§	V _{CC} = MAX,	VO = 0 V	Any Q		- 30		- 130	- 30		- 130	mA
lcc	V _{CC} = MAX,	See Note 2	1			28	45		28	45	mA

[†]For conditions shown as MIN or MAX, use the appropriate value specified under recommended operating conditions.

switching characteristics, $V_{CC} = 5 \text{ V}$, $T_A = 25^{\circ}\text{C}$ (see note 3)

	FROM	то	7707.001	DIE10110		'LS169	В	UNIT
PARAMETER¶	(INPUT)	(OUTPUT)	TEST CON	DITIONS	MIN	TYP	MAX	UNII
fmax					20	35		MHz
^t PLH	01.14	RCO				26	40	ns
tPHL tPHL	CLK	HCO HCO				17	25	115
^t PLH	ENT	RCO	D - 010	045 -5		15	25	ns
tPHL	ENI	HCO	$R_L = 2 k\Omega$,	C _L = 15 pF		11	20	'''
^t PLH		700				23	35	
^t PHL	U/Ω	RCO				15	25	ns
^t PLH						16	25	
tPHL	CLK	Any Q	R _L = 667 Ω,	C _L = 45 pF		17	25	ns

[¶] Propagation delay time from up/down to ripple carry must be measured with the counter at either a minimum or a maximum count. As the logic level of the up/down input is changed, the ripple carry output will follow. If the count is minimum (0), the ripple carry output transistion will be in phase. If the count is maximum (15), the ripple carry output will be out of phase.

NOTE 3: Load circuits and voltage waveforms are shown in Section 1.




 $[\]ddagger$ All typical values are at V_{CC} = 5 V, T_A = 25°C. § Not more than one output should be shorted at a time, and duration of the short-circuit should not exceed one second.


NOTE 2: ICC is measured after applying a momentary 4.5 V, then ground, to the clock input with all other inputs grounded and the outputs

SYNCHRONOUS 4-BIT UP/DOWN BINARY COUNTERS

SDLS134 - OCTOBER 1976 - REVISED MARCH 1988

schematics of inputs and outputs





absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

Supply voltage, VCC (See Note 4)
Input voltage 5.5 V
Interemitter voltage (see Note 5)
Operating free-air temperature range: SN54S169 (see Note 6)55°C to 125°C
SN74S169 0°C to 70°C
Storage temperature range

recommended operating conditions

		S	N54S1	69	S	N74S1	69	LIBUT
		MIN	NOM	MAX	MIN	NOM	MAX	UNIT
Supply voltage, V _{CC}		4.5	5	5.5	4.75	5	5.25	٧
High-level output current, IOH				- 1			- 1	mA
Low-level output current, IQL				20			20	mA
Clock frequency, fclock		0		40	0		40	MHz
Width of clock pulse, tw(clock) (high	or low) (see Figure 1)	10			10			ns
	Data inputs A, B, C, D	4			4			_
·	ENP or ENT	14			14			ns
Setup time,t _{SU} (see Figure 1)	Load	9			6] ""
	U/D	20			20			
Hold time at any input with respect to	clock, t _w (see Figure 1)	1			1			ns
Operating free-air temperature, TA (se		- 55		125	0		70	°C

NOTES: 4. Voltage values, except interemitter voltage, are with respect to network ground terminal.

- 5. This is the voltage between two emitters of a multiple-emitter transistor. For these circuits, this rating applies between the count enable inputs $\overline{\text{ENP}}$ and $\overline{\text{ENT}}$.
- 6. A SN54S169 in the W package operating at free-air temperatures above 91 °C requires a heat sink that provides a thermal resistance from case to free-air, $R_{\theta CA}$, of not more than 26 °C/W.



electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

			unizione t	S	N54S1	39	S	39	UNIT	
PARAMETER		TEST CO	NDITIONS [†]	MIN	TYP‡	MAX	MIN	TYP [‡]	MAX	CIVIT
V _{IH} High-level input voltage				2			2			V
V _{IL} Low-level input voltage						0.8			0.8	٧
VIK Input clamp voltage		V _{CC} = MIN,	$I_{J} = -18 \text{ mA}$			-1.2			-1.2	V
V _{OH} High-level output voltage		$V_{CC} = MIN,$ $V_{IL} = 0.8 V,$	$V_{IH} = 2 V$, $I_{OH} = -1 \text{ mA}$	2.5	3.4		2.7	3.4		٧
V _{OL} Low-level output voltage		$V_{CC} = MIN,$ $V_{IL} = 0.8 V,$	V _{IH} = 2 V, I _{OL} = 20 mA			0.5			0.5	٧
I Input current at maximum inpu	it voltage	V _{CC} = MAX,	V ₁ = 5.5 V			1			1	mA
	ENT					100			100	
IH High-level input current	Load	V _{CC} = MAX,	$V_i = 2.7 V$	- 10		- 200	- 10		- 200	μΑ
	Other inputs					50			50	
ENT		.,	V 05V			-4			-4	mA
IL Low-level input current Other inputs		$V_{CC} = MAX,$	V _I = 0.5 V			- 2			- 2	111/4
IOS Short-circuit output current§		V _{CC} = MAX,		- 40		- 100	- 40		- 100	mΑ
ICC Supply current		V _{CC} = MAX,	See Note 2		100	160		100	160	mA

[†] For conditions shown as MIN or MAX, use the appropriate value specified under recommended operating conditions.

NOTE 2: ICC is measured after applying a momentary 4.5 V, then ground, to the clock input with all other inputs grounded and the outputs open.

switching characteristics, VCC = 5 V, TA = 25°C

ď	FROM	то		U	/D = H	IGH	U/	D = L(w	UNIT
PARAMETER¶	(INPUT)	(OUTPUT)	TEST CONDITIONS	MIN	TYP	MAX	MIN	TYP	MAX	ONT
f _{max}				40	70		40	55		MHz
tPLH .	01.14	500	1		14	21		14	21	ns
tPHL.	CLK	RCO	0 15-5		20	28		20	28	113
t _{PLH}	01.14		$C_L = 15 \mathrm{pF},$ $R_L = 280 \Omega,$		8	15		8	15	ns
tPHL	CLK	Any Q	See Figures 2 and 3		11	15		11	15] '''
tPLH		===	and Note 3		7.5	11		6	12	ns
tPHL	ENT	RCO			15	22		15	25] ""
tPLH♦			1		9	15		8	15	
tpHL≎	U/ <u>D</u>	RCO			10	15		16	22	ns

 $¹_{t_{max}} = maximum clock frequency$

Propagation delay time from up/down to ripple carry must be measured with the counter at either a minimum or a maximum count. As the logic level of the up/down input is changed, the ripple carry output will follow. If the count is minimum (0), the ripple carry output transition will be in phase. If the count is maximum (15 for 'S169), the ripple carry output will be out of phase.

NOTE 3: Load circuits and voltage waveforms are shown in Section 1.




 $^{^{\}ddagger}$ All typical values are at V_{CC} = 5 V, T_A = 25 °C.

[§] Not more than one output should be shorted at a time, and duration of the short-circuit should not exceed one second.

tpLH = propagation delay time, low-to-high-level output

tpHL = propagation delay time, high-to-low-level output


PARAMETER MEASUREMENT INFORMATION



NOTES: A. The input pulses are supplied by a generator having the following characteristics: PRR \leq 1 MHz, duty cycle \leq 50%, $Z_{out} \approx$ 50 Ω ; for 'LS169B, $t_r \leq$ 15 ns; $t_f \leq$ 6 ns, and for 'S169, $t_r \leq$ 2.5 ns, $t_f \leq$ 2.5 ns.

B. For 'LS169B, V_{ref} = 1.3 V; for 'S168 and 'S169, V_{ref} = 1.5 V.

FIGURE 1-PULSE WIDTHS, SETUP TIMES, HOLD TIMES




NOTES: A. The input pulses are supplied by a generator having the following characteristics: PRR \leq MHz, duty cycle \leq 50%, Z_{out} \approx 50 Ω ; for 'LS169B, t_r \leq 15 ns, t_f \leq 5 ns; and for 'S169, t_r \leq 2.5 ns.

- B. tpLH and tpHL from enable T input to ripple carry output assume that the counter is at the maximum count, all Q outputs high.
- C. For 'LS169B, $V_{ref} = 1.3 \text{ V}$; for 'S169, $V_{ref} = 1.5 \text{ V}$.
- D. Propagation delay time from up/down to ripple carry must be measured with the counter at either a minimum or a maximum count. As the logic level of the up/down input is changed, the ripple carry output will follow. If the count is minimum (0) the ripple carry output transition will be in phase. If the count is maximum (15), the ripple carry output will be out of phase.

FIGURE 2-PROPAGATION DELAY TIMES TO CARRY OUTPUT



PARAMETER MEASUREMENT INFORMATION



UP-COUNT VOLTAGE WAVEFORMS

NOTES: A. The input pulses are supplied by a generator having the following characteristics: PRR ≤ 1 MHz, duty cycle ≤50%, $Z_{out} \approx 50~\Omega$; for 'LS169B, $t_r \leq 15$ ns; $t_f \leq 6$ ns, and 'S169, $t_r \leq 2.5$ ns, $t_f \leq 2.5$ ns. Vary PRR to measure f_{max} .

- B. Outputs Q_D and carry are tested at t_{n+16} , where t_n is the bit-time when all outputs are low. C. For 'LS169B, $V_{ref}=1.3$ V; for 'S169, $V_{ref}=1.5$ V.

FIGURE 3-PROPAGATION DELAY TIMES FROM CLOCK



www.ti.com

14-Oct-2025

PACKAGING INFORMATION

Orderable part number	Status (1)	Material type	Package Pins	Package qty Carrier	RoHS (3)	Lead finish/ Ball material	MSL rating/ Peak reflow	Op temp (°C)	Part marking (6)
80018022A	Active	Production	LCCC (FK) 20	55 TUBE	No	SNPB	N/A for Pkg Type	-55 to 125	80018022A SNJ54LS 169BFK
8001802EA	Active	Production	CDIP (J) 16	25 TUBE	No	SNPB	N/A for Pkg Type	-55 to 125	8001802EA SNJ54LS169BJ
8001802EA	Active	Production	CDIP (J) 16	25 TUBE	No	SNPB	N/A for Pkg Type	-55 to 125	8001802EA SNJ54LS169BJ
8001802FA	Active	Production	CFP (W) 16	25 TUBE	No	SNPB	N/A for Pkg Type	-55 to 125	8001802FA SNJ54LS169BW
8001802FA	Active	Production	CFP (W) 16	25 TUBE	No	SNPB	N/A for Pkg Type	-55 to 125	8001802FA SNJ54LS169BW
SN54LS169BJ	Active	Production	CDIP (J) 16	25 TUBE	No	SNPB	N/A for Pkg Type	-55 to 125	SN54LS169BJ
SN54LS169BJ	Active	Production	CDIP (J) 16	25 TUBE	No	SNPB	N/A for Pkg Type	-55 to 125	SN54LS169BJ
SN54LS169BJ.A	Active	Production	CDIP (J) 16	25 TUBE	No	SNPB	N/A for Pkg Type	-55 to 125	SN54LS169BJ
SN54LS169BJ.A	Active	Production	CDIP (J) 16	25 TUBE	No	SNPB	N/A for Pkg Type	-55 to 125	SN54LS169BJ
SN54S169J	Active	Production	CDIP (J) 16	25 TUBE	No	SNPB	N/A for Pkg Type	-55 to 125	SN54S169J
SN54S169J	Active	Production	CDIP (J) 16	25 TUBE	No	SNPB	N/A for Pkg Type	-55 to 125	SN54S169J
SN54S169J.A	Active	Production	CDIP (J) 16	25 TUBE	No	SNPB	N/A for Pkg Type	-55 to 125	SN54S169J
SN54S169J.A	Active	Production	CDIP (J) 16	25 TUBE	No	SNPB	N/A for Pkg Type	-55 to 125	SN54S169J
SN74LS169BD	Active	Production	SOIC (D) 16	40 TUBE	Yes	NIPDAU	Level-1-260C-UNLIM	0 to 70	LS169B
SN74LS169BD	Active	Production	SOIC (D) 16	40 TUBE	Yes	NIPDAU	Level-1-260C-UNLIM	0 to 70	LS169B
SN74LS169BD.A	Active	Production	SOIC (D) 16	40 TUBE	Yes	NIPDAU	Level-1-260C-UNLIM	0 to 70	LS169B
SN74LS169BD.A	Active	Production	SOIC (D) 16	40 TUBE	Yes	NIPDAU	Level-1-260C-UNLIM	0 to 70	LS169B
SN74LS169BN	Active	Production	PDIP (N) 16	25 TUBE	Yes	NIPDAU	N/A for Pkg Type	0 to 70	SN74LS169BN
SN74LS169BN	Active	Production	PDIP (N) 16	25 TUBE	Yes	NIPDAU	N/A for Pkg Type	0 to 70	SN74LS169BN
SN74LS169BN.A	Active	Production	PDIP (N) 16	25 TUBE	Yes	NIPDAU	N/A for Pkg Type	0 to 70	SN74LS169BN
SN74LS169BN.A	Active	Production	PDIP (N) 16	25 TUBE	Yes	NIPDAU	N/A for Pkg Type	0 to 70	SN74LS169BN
SNJ54LS169BFK	Active	Production	LCCC (FK) 20	55 TUBE	No	SNPB	N/A for Pkg Type	-55 to 125	80018022A SNJ54LS 169BFK





www.ti.com 14-Oct-2025

Orderable part number	Status	Material type	Package Pins	Package qty Carrier	RoHS (3)	Lead finish/ Ball material	MSL rating/ Peak reflow	Op temp (°C)	Part marking (6)
SNJ54LS169BFK	Active	Production	LCCC (FK) 20	55 TUBE	No	SNPB	N/A for Pkg Type	-55 to 125	80018022A SNJ54LS 169BFK
SNJ54LS169BFK.A	Active	Production	LCCC (FK) 20	55 TUBE	No	SNPB	N/A for Pkg Type	-55 to 125	80018022A SNJ54LS 169BFK
SNJ54LS169BFK.A	Active	Production	LCCC (FK) 20	55 TUBE	No	SNPB	N/A for Pkg Type	-55 to 125	80018022A SNJ54LS 169BFK
SNJ54LS169BJ	Active	Production	CDIP (J) 16	25 TUBE	No	SNPB	N/A for Pkg Type	-55 to 125	8001802EA SNJ54LS169BJ
SNJ54LS169BJ	Active	Production	CDIP (J) 16	25 TUBE	No	SNPB	N/A for Pkg Type	-55 to 125	8001802EA SNJ54LS169BJ
SNJ54LS169BJ.A	Active	Production	CDIP (J) 16	25 TUBE	No	SNPB	N/A for Pkg Type	-55 to 125	8001802EA SNJ54LS169BJ
SNJ54LS169BJ.A	Active	Production	CDIP (J) 16	25 TUBE	No	SNPB	N/A for Pkg Type	-55 to 125	8001802EA SNJ54LS169BJ
SNJ54LS169BW	Active	Production	CFP (W) 16	25 TUBE	No	SNPB	N/A for Pkg Type	-55 to 125	8001802FA SNJ54LS169BW
SNJ54LS169BW	Active	Production	CFP (W) 16	25 TUBE	No	SNPB	N/A for Pkg Type	-55 to 125	8001802FA SNJ54LS169BW
SNJ54LS169BW.A	Active	Production	CFP (W) 16	25 TUBE	No	SNPB	N/A for Pkg Type	-55 to 125	8001802FA SNJ54LS169BW
SNJ54LS169BW.A	Active	Production	CFP (W) 16	25 TUBE	No	SNPB	N/A for Pkg Type	-55 to 125	8001802FA SNJ54LS169BW
SNJ54S169J	Active	Production	CDIP (J) 16	25 TUBE	No	SNPB	N/A for Pkg Type	-55 to 125	SNJ54S169J
SNJ54S169J	Active	Production	CDIP (J) 16	25 TUBE	No	SNPB	N/A for Pkg Type -55 to 125		SNJ54S169J
SNJ54S169J.A	Active	Production	CDIP (J) 16	25 TUBE	No	SNPB	N/A for Pkg Type	-55 to 125	SNJ54S169J
SNJ54S169J.A	Active	Production	CDIP (J) 16	25 TUBE	No	SNPB	N/A for Pkg Type	-55 to 125	SNJ54S169J

⁽¹⁾ Status: For more details on status, see our product life cycle.

⁽²⁾ Material type: When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

PACKAGE OPTION ADDENDUM

www.ti.com 14-Oct-2025

- (3) RoHS values: Yes, No, RoHS Exempt. See the TI RoHS Statement for additional information and value definition.
- (4) Lead finish/Ball material: Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.
- (5) MSL rating/Peak reflow: The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.
- (6) Part marking: There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

OTHER QUALIFIED VERSIONS OF SN54LS169B, SN74LS169B:

Catalog: SN74LS169B

Military: SN54LS169B

NOTE: Qualified Version Definitions:

- Catalog TI's standard catalog product
- Military QML certified for Military and Defense Applications



www.ti.com 23-May-2025

PACKAGE MATERIALS INFORMATION

TUBE



*All dimensions are nominal

Device	Package Name	Package Type	Pins	SPQ	L (mm)	W (mm)	T (µm)	B (mm)
80018022A	FK	LCCC	20	55	506.98	12.06	2030	NA
8001802FA	W	CFP	16	25	506.98	26.16	6220	NA
SN74LS169BD	D	SOIC	16	40	507	8	3940	4.32
SN74LS169BD.A	D	SOIC	16	40	507	8	3940	4.32
SN74LS169BN	N	PDIP	16	25	506	13.97	11230	4.32
SN74LS169BN	N	PDIP	16	25	506	13.97	11230	4.32
SN74LS169BN.A	N	PDIP	16	25	506	13.97	11230	4.32
SN74LS169BN.A	N	PDIP	16	25	506	13.97	11230	4.32
SNJ54LS169BFK	FK	LCCC	20	55	506.98	12.06	2030	NA
SNJ54LS169BFK.A	FK	LCCC	20	55	506.98	12.06	2030	NA
SNJ54LS169BW	W	CFP	16	25	506.98	26.16	6220	NA
SNJ54LS169BW.A	W	CFP	16	25	506.98	26.16	6220	NA

D (R-PDS0-G16)

PLASTIC SMALL OUTLINE



NOTES:

- A. All linear dimensions are in inches (millimeters).
- B. This drawing is subject to change without notice.
- Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.006 (0,15) each side.
- Body width does not include interlead flash. Interlead flash shall not exceed 0.017 (0,43) each side.
- E. Reference JEDEC MS-012 variation AC.



W (R-GDFP-F16)

CERAMIC DUAL FLATPACK



NOTES:

- A. All linear dimensions are in inches (millimeters).
- B. This drawing is subject to change without notice.
- C. This package can be hermetically sealed with a ceramic lid using glass frit.
- D. Index point is provided on cap for terminal identification only.
- E. Falls within MIL STD 1835 GDFP2-F16



8.89 x 8.89, 1.27 mm pitch

LEADLESS CERAMIC CHIP CARRIER

This image is a representation of the package family, actual package may vary. Refer to the product data sheet for package details.



INSTRUMENTS www.ti.com

14 LEADS SHOWN



NOTES:

- A. All linear dimensions are in inches (millimeters).
- B. This drawing is subject to change without notice.
- C. This package is hermetically sealed with a ceramic lid using glass frit.
- D. Index point is provided on cap for terminal identification only on press ceramic glass frit seal only.
- E. Falls within MIL STD 1835 GDIP1-T14, GDIP1-T16, GDIP1-T18 and GDIP1-T20.

N (R-PDIP-T**)

PLASTIC DUAL-IN-LINE PACKAGE

16 PINS SHOWN



NOTES:

- A. All linear dimensions are in inches (millimeters).
- B. This drawing is subject to change without notice.
- Falls within JEDEC MS-001, except 18 and 20 pin minimum body length (Dim A).
- The 20 pin end lead shoulder width is a vendor option, either half or full width.



IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATA SHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

TI objects to and rejects any additional or different terms you may have proposed.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265 Copyright © 2025. Texas Instruments Incorporated