
SCLS498A - MAY 2003 - REVISED MAY 2004

- Controlled Baseline
  - One Assembly/Test Site, One Fabrication Site
- Extended Temperature Performance of -40°C to 105°C
- Enhanced Diminishing Manufacturing Sources (DMS) Support
- Enhanced Product-Change Notification
- Qualification Pedigree†
- Typical V<sub>OLP</sub> (Output Ground Bounce)
   <0.8 V at V<sub>CC</sub> = 3.3 V, T<sub>A</sub> = 25°C
- Typical V<sub>OHV</sub> (Output V<sub>OH</sub> Undershoot)
   >2.3 V at V<sub>CC</sub> = 3.3 V, T<sub>A</sub> = 25°C
- Supports Mixed-Mode Voltage Operation on All Ports
- Schmitt-Trigger Circuitry on A, B, and CLR Inputs for Slow Input Transition Rates

T Component qualification in accordance with JEDEC and industry standards to ensure reliable operation over an extended temperature range. This includes, but is not limited to, Highly Accelerated Stress Test (HAST) or biased 85/85, temperature cycle, autoclave or unbiased HAST, electromigration, bond intermetallic life, and mold compound life. Such qualification testing should not be viewed as justifying use of this component beyond specified performance and environmental limits.

- Edge Triggered From Active-High or Active-Low Gated Logic Inputs
- I<sub>off</sub> Supports Partial-Power-Down Mode Operation
- Retriggerable for Very Long Output Pulses, Up To 100% Duty Cycle
- Overriding Clear Terminates Output Pulse
- Glitch-Free Power-Up Reset on Outputs
- ESD Protection Exceeds JESD 22
  - 2000-V Human-Body Model (A114-A)
  - 200-V Machine Model (A115-A)
  - 1000-V Charged-Device Model (C101)



### description/ordering information

The SN74LV123A is a dual retriggerable monostable multivibrator designed for 2-V to 5.5-V V<sub>CC</sub> operation.

This edge-triggered multivibrator features output pulse-duration control by three methods. In the first method, the  $\overline{A}$  input is low, and the B input goes high. In the second method, the B input is high, and the  $\overline{A}$  input goes low. In the third method, the  $\overline{A}$  input is low, the B input is high, and the clear  $(\overline{CLR})$  input goes high.

The output pulse duration is programmable by selecting external resistance and capacitance values. The external timing capacitor must be connected between  $C_{ext}$  and  $R_{ext}/C_{ext}$  (positive) and an external resistor connected between  $R_{ext}/C_{ext}$  and  $V_{CC}$ . To obtain variable pulse durations, connect an external variable resistance between  $R_{ext}/C_{ext}$  and  $V_{CC}$ . The output pulse duration also can be reduced by taking  $\overline{CLR}$  low.

Pulse triggering occurs at a particular voltage level and is not directly related to the transition time of the input pulse. The  $\overline{A}$ , B, and  $\overline{CLR}$  inputs have Schmitt triggers with sufficient hysteresis to handle slow input transition rates with jitter-free triggering at the outputs.

#### ORDERING INFORMATION

TA	PACKAGE‡		ORDERABLE PART NUMBER	TOP-SIDE MARKING
-40°C to 105°C	TSSOP - PW	Tape and reel	SN74LV123ATPWREP	L123AEP

<sup>‡</sup> Package drawings, standard packing quantities, thermal data, symbolization, and PCB design guidelines are available at www.ti.com/sc/package.



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.



SCLS498A - MAY 2003 - REVISED MAY 2004

### description/ordering information (continued)

Once triggered, the basic pulse duration can be extended by retriggering the gated low-level-active  $(\overline{A})$  or high-level-active (B) input. Pulse duration can be reduced by taking  $\overline{CLR}$  low. The input/output timing diagram illustrates pulse control by retriggering the inputs and early clearing.

During power up, Q outputs are in the low state, and  $\overline{Q}$  outputs are in the high state. The outputs are glitch free, without applying a reset pulse.


This device is fully specified for partial-power-down applications using I<sub>off</sub>. The I<sub>off</sub> circuitry disables the outputs, preventing damaging current backflow through the device when it is powered down.

FUNCTION TABLE (each multivibrator)

	(500.		, ato.,			
	INPUTS	OUTPUTS				
CLR			Q	Q		
L	Х	Х	L	Н		
Х	Н	X	∟†	H <sup>†</sup>		
Х	Χ	L	L†	H <sup>†</sup>		
Н	L	$\uparrow$	л	Т		
Н	$\downarrow$	Н	Л	T		
1	L	Н	л	T		


<sup>†</sup> These outputs are based on the assumption that the indicated steady-state conditions at the A and B inputs have been set up long enough to complete any pulse started before the setup.

## logic diagram, each multivibrator (positive logic)



SCLS498A - MAY 2003 - REVISED MAY 2004

## input/output timing diagram



## absolute maximum ratings over operating free-air temperature (unless otherwise noted)†

Supply voltage range, V <sub>CC</sub> –0	).5 V to 7 V
Input voltage range, V <sub>I</sub> (see Note 1)	).5 V to 7 V
Voltage range applied to any output in the high-impedance	
or power-off state, V <sub>O</sub> (see Note 1)	).5 V to 7 V
Output voltage range in high or low state, VO (see Notes 1 and 2)	'CC + 0.5 V
Output voltage range in power-off state, V <sub>O</sub> (see Note 1)	).5 V to 7 V
Input clamp current, $I_{IK}$ ( $V_I < 0$ )	–20 mA
Output clamp current, $I_{OK}$ ( $V_O < 0$ )	–50 mA
Continuous output current, $I_O$ ( $V_O = 0$ to $V_{CC}$ )	±25 mA
Continuous current through V <sub>CC</sub> or GND	±50 mA
Package thermal impedance, $\theta_{JA}$ (see Note 3)	. 113°C/W
Storage temperature range, T <sub>stg</sub> 65°	C to 150°C

<sup>†</sup> Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

- NOTES: 1. The input and output negative-voltage ratings may be exceeded if the input and output current ratings are observed.
  - 2. This value is limited to 5.5 V maximum.
  - 3. The package thermal impedance is calculated in accordance with JESD 51-7.



SCLS498A - MAY 2003 - REVISED MAY 2004

## recommended operating conditions (see Note 4)

			MIN	MAX	UNIT
Vcc	Supply voltage		2	5.5	V
		V <sub>CC</sub> = 2 V	1.5		
.,	LPak Lavel Secret vellage	$V_{CC} = 2.3 \text{ V to } 2.7 \text{ V}$	V <sub>CC</sub> ×0.7		] ,,
$V_{IH}$	High-level input voltage	V <sub>CC</sub> = 3 V to 3.6 V	V <sub>CC</sub> ×0.7		V
		$V_{CC} = 4.5 \text{ V to } 5.5 \text{ V}$	V <sub>CC</sub> × 0.7		
		V <sub>CC</sub> = 2 V		0.5	
Mar	Laur laural imputuralta ma	$V_{CC} = 2.3 \text{ V to } 2.7 \text{ V}$		$V_{CC} \times 0.3$	V
VIL	Low-level input voltage	$V_{CC} = 3 \text{ V to } 3.6 \text{ V}$		$V_{CC} \times 0.3$	V
		$V_{CC} = 4.5 \text{ V to } 5.5 \text{ V}$		$V_{CC} \times 0.3$	
VI	Input voltage		0	5.5	V
VO	Output voltage		0	Vcc	V
		V <sub>CC</sub> = 2 V		-50	μΑ
1	High-level output current	$V_{CC} = 2.3 \text{ V to } 2.7 \text{ V}$		-2	
ЮН		$V_{CC} = 3 \text{ V to } 3.6 \text{ V}$		-6	mA
		$V_{CC} = 4.5 \text{ V to } 5.5 \text{ V}$		-12	
		V <sub>CC</sub> = 2 V		50	μΑ
	Lave been autout comment	$V_{CC} = 2.3 \text{ V to } 2.7 \text{ V}$		2	
lOL	Low-level output current	$V_{CC} = 3 \text{ V to } 3.6 \text{ V}$		6	mA
		$V_{CC} = 4.5 \text{ V to } 5.5 \text{ V}$		12	
-	Fortunal distance states	V <sub>CC</sub> = 2 V	5k		
R <sub>ext</sub>	External timing resistance	V <sub>CC</sub> ≥ 3 V	1k		Ω
C <sub>ext</sub>	External timing capacitance		No res	triction	pF
$\Delta t/\Delta V_{CC}$	Power-up ramp rate		1		ms/V
T <sub>A</sub>	Operating free-air temperature		-40	105	°C

NOTE 4: All unused inputs of the device must be held at V<sub>CC</sub> or GND to ensure proper device operation. Refer to the TI application report, Implications of Slow or Floating CMOS Inputs, literature number SCBA004.



SCLS498A - MAY 2003 - REVISED MAY 2004

## electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

P/	ARAMETER	TEST CONDITIONS		Vcc	MIN	TYP	MAX	UNIT	
		$I_{OH} = -50 \mu\text{A}$		2 V to 5.5 V	V <sub>CC</sub> -0.1				
		I <sub>OH</sub> = −2 mA		2.3 V	2			٧	
VOH		I <sub>OH</sub> = -6 mA		3 V	2.48				
		I <sub>OH</sub> = −12 mA		4.5 V	3.8				
		I <sub>OL</sub> = 50 μA		2 V to 5.5 V			0.1		
V		DL = 2 mA		2.3 V			0.4	.,	
VOL		I <sub>OL</sub> = 6 mA	3 V			0.44	V		
		I <sub>OL</sub> = 12 mA		4.5 V			0.55		
	R <sub>ext</sub> /C <sub>ext</sub> †	V <sub>I</sub> = 5.5 V or GND		2 V to 5.5 V			±2.5		
lį.		V <sub>I</sub> = 5.5 V or GND		0			±1	μΑ	
	A, B, and CLR			0 to 5.5 V			±1		
Icc	Quiescent	$V_I = V_{CC}$ or GND,	= 0	5.5 V			20	μΑ	
				3 V			280		
ICC	Active state (per circuit)	$V_I = V_{CC}$ or GND,		4.5 V			650	μΑ	
(per eneutr)		$R_{\text{ext}}/C_{\text{ext}} = 0.5 \text{ VCC}$		5.5 V			975	ı	
l <sub>off</sub>		$V_I$ or $V_O = 0$ to 5.5 V		0			5	μΑ	
_		V V ~ CND		3.3 V		1.9			
Ci		$V_I = V_{CC}$ or GND		5 V		1.9		pF	

<sup>†</sup> This test is performed with the terminal in the off-state condition.

## timing requirements over recommended operating free-air temperature range, $V_{CC}$ = 3.3 V $\pm$ 0.3 V (unless otherwise noted) (see Figure 1)

		TEOT 00	TEST CONDITIONS			T <sub>A</sub> = 25°C				
		TEST CC	SNOTTIONS	MIN	TYP	MAX	MIN	MAX	UNIT	
	Pulse	CLR			5			5		
t <sub>W</sub>	duration	A or B trigger	]		5			5		ns
	Duda a matria man Cara		5 416	C <sub>ext</sub> = 100 pF	‡	76		‡		ns
trr	Pulse retrigger time	$R_{ext} = 1 k\Omega$	$C_{ext} = 0.01 \mu F$	‡	1.8		‡		μS	

<sup>‡</sup> See retriggering data in the *application information* section.

## timing requirements over recommended operating free-air temperature range, $V_{CC}$ = 5 V $\pm$ 0.5 V (unless otherwise noted) (see Figure 1)

		TEOT 00	TEST CONDITIONS			T <sub>A</sub> = 25°C				
		TEST CC	SNOTTIONS	MIN	TYP	MAX	MIN	MAX	UNIT	
	Pulse	CLR			5			5		
t <sub>W</sub>	duration	A or B trigger	]		5			5		ns
	Date and decrease the co		D 410	C <sub>ext</sub> = 100 pF	‡	59		‡		ns
trr	Pulse retrigger time		$R_{ext} = 1 k\Omega$	$C_{ext} = 0.01  \mu F$	‡	1.5		‡		μS

<sup>‡</sup> See retriggering data in the application information section.



SCLS498A - MAY 2003 - REVISED MAY 2004

## switching characteristics over recommended operating free-air temperature range, $V_{CC}$ = 3.3 V $\pm$ 0.3 V (unless otherwise noted) (see Figure 1)

DADAMETED	FROM	то	TEST	T,	չ = 25°C	;	B. A.I.N.I	MAY	
PARAMETER	(INPUT)	(OUTPUT)	CONDITIONS	MIN	TYP	MAX	MIN	MAX	UNIT
	A or B	Q or Q			11.8	24.1	1	27.5	
<sup>t</sup> pd	CLR	Q or $\overline{\mathbb{Q}}$	C <sub>L</sub> = 50 pF		10.5	19.3	1	22	ns
	CLR trigger	Q or $\overline{\mathbb{Q}}$			12.3	25.9	1	29.5	
			$C_L = 50 \text{ pF},$ $C_{ext} = 28 \text{ pF},$ $R_{ext} = 2 \text{ k}\Omega$		182	240		300	ns
t <sub>W</sub> †		Q or $\overline{\mathbb{Q}}$	$C_L = 50 \text{ pF},$ $C_{\text{ext}} = 0.01 \mu\text{F},$ $R_{\text{ext}} = 10 k\Omega$	90	100	110	90	110	μs
			$C_L$ = 50 pF, $C_{ext}$ = 0.1 $\mu$ F, $R_{ext}$ = 10 k $\Omega$	0.9	1	1.1	0.9	1.1	ms
Δt <sub>W</sub> ‡			C <sub>L</sub> = 50 pF		±1				%

## switching characteristics over recommended operating free-air temperature range, $V_{CC}$ = 5 V $\pm$ 0.5 V (unless otherwise noted) (see Figure 1)

	•	, ,							
DADAMETED	FROM	то	TEST	T,	չ = 25°C	;	MINI	MAY	UNIT
PARAMETER	(INPUT)	(OUTPUT)	CONDITIONS	MIN	TYP	MAX	MIN	MAX	UNIT
	A or B	Q or Q			8.3	14	1	16	
<sup>t</sup> pd	CLR	Q or Q	C <sub>L</sub> = 50 pF		7.4	11.4	1	13	ns
	CLR trigger	Q or $\overline{\mathbb{Q}}$			8.7	14.9	1	17	
			$C_L = 50 \text{ pF},$ $C_{ext} = 28 \text{ pF},$ $R_{ext} = 2 \text{ k}\Omega$		167	200		240	ns
t <sub>W</sub> †		Q or $\overline{\overline{Q}}$	$C_L$ = 50 pF, $C_{ext}$ = 0.01 μF, $R_{ext}$ = 10 kΩ	90	100	110	90	110	μS
			$C_L$ = 50 pF, $C_{ext}$ = 0.1 μF, $R_{ext}$ = 10 kΩ	0.9	1	1.1	0.9	1.1	ms
$_{\Delta t_{W}}$ ‡					±1				%

 $<sup>\</sup>dagger t_W = Duration of pulse at Q and <math>\overline{Q}$  outputs

## operating characteristics, T<sub>A</sub> = 25°C

	PARAMETER	TEST CO	NDITIONS	VCC	TYP	UNIT
_	Davies discination consistence	$C_L = 50 \text{ pF},$	f 40 MH-	3.3 V	44	pF
Cpd	Power dissipation capacitance		f = 10 MHz	5 V	49	




<sup>†</sup>  $t_W$  = Duration of pulse at Q and  $\overline{Q}$  outputs ‡  $\Delta t_W$  = Output pulse-duration variation (Q and  $\overline{Q}$ ) between circuits in same package

 $<sup>^{\</sup>ddagger}\Delta t_W = \text{Output pulse-duration variation (Q and } \overline{Q})$  between circuits in same package

SCLS498A - MAY 2003 - REVISED MAY 2004

#### PARAMETER MEASUREMENT INFORMATION




NOTES: A. C<sub>L</sub> includes probe and jig capacitance.


- B. All input pulses are supplied by generators having the following characteristics: PRR  $\leq$  1 MHz,  $Z_O = 50 \Omega$ ,  $t_f = 3 \text{ ns}$ .
- C. The outputs are measured one at a time, with one input transition per measurement.


Figure 1. Load Circuit and Voltage Waveforms


### APPLICATION INFORMATION<sup>†</sup>











<sup>†</sup>Operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied.



11-Nov-2025 www.ti.com

#### PACKAGING INFORMATION

Orderable part number	Status	Material type	Package   Pins	Package qty   Carrier	<b>RoHS</b> (3)	Lead finish/ Ball material	MSL rating/ Peak reflow	Op temp (°C)	Part marking (6)
SN74LV123ATPWREP	Active	Production	TSSOP (PW)   16	2000   LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	L123AEP
SN74LV123ATPWREP.A	Active	Production	TSSOP (PW)   16	2000   LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	L123AEP
V62/03661-01XE	Active	Production	TSSOP (PW)   16	2000   LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	L123AEP

<sup>(1)</sup> Status: For more details on status, see our product life cycle.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

#### OTHER QUALIFIED VERSIONS OF SN74LV123A-EP:

Catalog: SN74LV123A

<sup>(2)</sup> Material type: When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

<sup>(3)</sup> RoHS values: Yes, No, RoHS Exempt. See the TI RoHS Statement for additional information and value definition.

<sup>(4)</sup> Lead finish/Ball material: Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

<sup>(5)</sup> MSL rating/Peak reflow: The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

<sup>(6)</sup> Part marking: There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

## PACKAGE OPTION ADDENDUM

www.ti.com 11-Nov-2025

Automotive : SN74LV123A-Q1

NOTE: Qualified Version Definitions:

- Catalog TI's standard catalog product
- Automotive Q100 devices qualified for high-reliability automotive applications targeting zero defects

## **PACKAGE MATERIALS INFORMATION**

www.ti.com 24-Jul-2025

### TAPE AND REEL INFORMATION





	Dimension designed to accommodate the component width
В0	Dimension designed to accommodate the component length
K0	Dimension designed to accommodate the component thickness
W	Overall width of the carrier tape
P1	Pitch between successive cavity centers

#### QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE



#### \*All dimensions are nominal

Device	Package Type	Package Drawing		SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
SN74LV123ATPWREP	TSSOP	PW	16	2000	330.0	12.4	6.9	5.6	1.6	8.0	12.0	Q1

## **PACKAGE MATERIALS INFORMATION**

www.ti.com 24-Jul-2025



### \*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)	
SN74LV123ATPWREP	TSSOP	PW	16	2000	353.0	353.0	32.0	

#### IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you fully indemnify TI and its representatives against any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale, TI's General Quality Guidelines, or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products. Unless TI explicitly designates a product as custom or customer-specified, TI products are standard, catalog, general purpose devices.

TI objects to and rejects any additional or different terms you may propose.

Copyright © 2025, Texas Instruments Incorporated

Last updated 10/2025