TLV1543C, TLV1543I, TLV1543M 3.3-V 10-BIT ANALOG-TO-DIGITAL CONVERTERS WITH SERIAL CONTROL AND 11 ANALOG INPUTS


SLAS072E - DECEMBER 1992 - REVISED JANUARY 2004

- 3.3-V Supply Operation
- 10-Bit-Resolution A/D Converter
- 11 Analog Input Channels
- Three Built-In Self-Test Modes
- Inherent Sample and Hold
- Total Unadjusted Error . . . ±1 LSB Max
- On-Chip System Clock
- End-of-Conversion (EOC) Output
- Pin Compatible With TLC1543
- CMOS Technology

description

The TLV1543C, TLV1543I, and TLV1543M are CMOS 10-bit, switched-capacitor, successive-approximation, analog-to-digital converters. These devices have three inputs and a 3-state output [chip select (CS), input-output clock (I/O CLOCK), address input (ADDRESS), and data output (DATA OUT)] that provide a direct 4-wire interface to the serial port of a host processor. The devices allow high-speed data transfers from the host.

In addition to a high-speed A/D converter and versatile control capability, these devices have an on-chip 14-channel multiplexer that can select any one of 11 analog inputs or any one of three internal self-test voltages. The sample-and-hold



function is automatic. At the end of A/D conversion, the end-of-conversion (EOC) output goes high to indicate that conversion is complete. The converter incorporated in the devices features differential high-impedance reference inputs that facilitate ratiometric conversion, scaling, and isolation of analog circuitry from logic and supply noise. A switched-capacitor design allows low-error conversion over the full operating free-air temperature range.

The TLV1543C is characterized for operation from 0° C to 70° C. The TLV1543I is characterized for industrial temperature range of -40° C to 85° C. The TLV1543M is characterized for operation over the full military temperature range of -55° C to 125° C.

AVAILABLE OPTIONS

			P/	ACKAGE				
TA	SMALL SMALL OUTLINE OUTLINE (DB) (DW)		OUTLINE CHIP CARRIER CERAMIC DII		OUTLINE OUTLINE CHIP CARRIER CERAMIC DIP		PLASTIC DIP (N)	PLASTIC CHIP CARRIER (FN)
0°C to 70°C	TLV1543CDB	TLV1543CDW	_	_	TLV1543CN	TLV1543CFN		
-40°C to 85°C	TLV1543IDB	_	_	_	_	_		
-55°C to 125°C	_	_	TLV1543MFK	TLV1543MJ	_	_		




Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.



TLV1543C, TLV1543I, TLV1543M 3.3-V 10-BIT ANALOG-TO-DIGITAL CONVERTERS WITH SERIAL CONTROL AND 11 ANALOG INPUTS

SLAS072E - DECEMBER 1992 - REVISED JANUARY 2004


functional block diagram



typical equivalent inputs

INPUT CIRCUIT IMPEDANCE DURING SAMPLING MODE

INPUT CIRCUIT IMPEDANCE DURING HOLD MODE





Terminal Functions

TERM	INAL		
NAME	NO.	1/0	DESCRIPTION
ADDRESS	17	I	Serial address. A 4-bit serial address selects the desired analog input or test voltage that is to be converted next. The address data is presented with the MSB first and is shifted in on the first four rising edges of I/O CLOCK. After the four address bits have been read into the address register, ADDRESS is ignored for the remainder of the current conversion period.
A0-A10	1–9, 11, 12	I	Analog signal. The 11 analog inputs are applied to A0 – A10 and are internally multiplexed. The driving source impedance should be less than or equal to 1 k Ω .
<u>cs</u>	15	I	Chip select. A high-to-low transition on $\overline{\text{CS}}$ resets the internal counters and controls and enables DATA OUT, ADDRESS, and I/O CLOCK within a maximum of a setup time plus two falling edges of the internal system clock. A low-to-high transition disables ADDRESS and I/O CLOCK within a setup time plus two falling edges of the internal system clock.
DATA OUT	16	0	The 3-state serial output for the A/D conversion result. DATA OUT is in the high-impedance state when $\overline{\text{CS}}$ is high and active when $\overline{\text{CS}}$ is low. With a valid chip select, DATA OUT is removed from the high-impedance state and is driven to the logic level corresponding to the MSB value of the previous conversion result. The next falling edge of I/O CLOCK drives DATA OUT to the logic level corresponding to the next most significant bit, and the remaining bits are shifted out in order with the LSB appearing on the ninth falling edge of I/O CLOCK. On the tenth falling edge of I/O CLOCK, DATA OUT is driven to a low logic level so that serial interface data transfers of more than ten clocks produce zeroes as the unused LSBs.
EOC	19	0	End of conversion. EOC goes from a high- to a low- logic level on the trailing edge of the tenth I/O CLOCK and remains low until the conversion is complete and data are ready for transfer.
GND	10	I	The ground return terminal for the internal circuitry. Unless otherwise noted, all voltage measurements are with respect to GND.
I/O CLOCK	18	I	Input/output clock. I/O CLOCK receives the serial I/O CLOCK input and performs the following four functions: 1) It clocks the four input address bits into the address register on the first four rising edges of I/O CLOCK with the multiplex address available after the fourth rising edge. 2) On the fourth falling edge of I/O CLOCK, the analog input voltage on the selected multiplex input begins charging the capacitor array and continues to do so until the tenth falling edge of I/O CLOCK. 3) It shifts the nine remaining bits of the previous conversion data out on DATA OUT. 4) It transfers control of the conversion to the internal state controller on the falling edge of the tenth clock.
REF+	14	I	The upper reference voltage value (nominally V _{CC}) is applied to REF+. The maximum input voltage range is determined by the difference between the voltage applied to REF+ and the voltage applied to the REF-terminal.
REF-	13	ı	The lower reference voltage value (nominally ground) is applied to REF –.
V _{CC}	20	I	Positive supply voltage

detailed description

With chip select (CS) inactive (high), the ADDRESS and I/O CLOCK inputs are initially disabled and DATA OUT is in the high-impedance state. When the serial interface takes CS active (low), the conversion sequence begins with the enabling of I/O CLOCK and ADDRESS and the removal of DATA OUT from the high-impedance state. The host then provides the 4-bit channel address to ADDRESS and the I/O CLOCK sequence to I/O CLOCK. During this transfer, the host serial interface also receives the previous conversion result from DATA OUT. I/O CLOCK receives an input sequence that is between 10 and 16 clocks long from the host. The first four I/O clocks load the address register with the 4-bit address on ADDRESS selecting the desired analog channel and the next six clocks providing the control timing for sampling the analog input.



TLV1543C, TLV1543I, TLV1543M 3.3-V 10-BIT ANALOG-TO-DIGITAL CONVERTERS WITH SERIAL CONTROL AND 11 ANALOG INPUTS

SLAS072E - DECEMBER 1992 - REVISED JANUARY 2004

detailed description (continued)

There are six basic serial interface timing modes that can be used with the device. These modes are determined by the speed of I/O CLOCK and the operation of \overline{CS} as shown in Table 1. These modes are (1) a fast mode with a 10-clock transfer and \overline{CS} inactive (high) between conversion cycles, (2) a fast mode with a 10-clock transfer and \overline{CS} active (low) continuously, (3) a fast mode with an 11- to 16-clock transfer and \overline{CS} inactive (high) between conversion cycles, (4) a fast mode with a 16-bit transfer and \overline{CS} active (low) continuously, (5) a slow mode with an 11- to 16-clock transfer and \overline{CS} inactive (high) between conversion cycles, and (6) a slow mode with a 16-clock transfer and \overline{CS} active (low) continuously.

The MSB of the previous conversion appears on DATA OUT on the falling edge of \overline{CS} in mode 1, mode 3, and mode 5, on the rising edge of EOC in mode 2 and mode 4, and following the 16th clock falling edge in mode 6. The remaining nine bits are shifted out on the next nine falling edges of I/O CLOCK. Ten bits of data are transmitted to the host through DATA OUT. The number of serial clock pulses used also depends on the mode of operation, but a minimum of ten clock pulses is required for conversion to begin. On the 10th clock falling edge, the EOC output goes low and returns to the high logic level when conversion is complete and the result can be read by the host. On the 10th clock falling edge, the internal logic takes DATA OUT low to ensure that the remaining bit values are zero if the I/O CLOCK transfer is more than ten clocks long.

Table 1 lists the operational modes with respect to the state of \overline{CS} , the number of I/O serial transfer clocks that can be used, and the timing edge on which the MSB of the previous conversion appears at the output.

MODES		cs	NO. OF I/O CLOCKS	MSB AT DATA OUT	TIMING DIAGRAM
	Mode 1	High between conversion cycles	10	CS falling edge	Figure 9
Foot Manda	Mode 2	Low continuously	10	EOC rising edge	Figure 10
Fast Modes	Mode 3	High between conversion cycles	11 to 16‡	CS falling edge	Figure 11
	Mode 4	Low continuously	16 [‡]	EOC rising edge	Figure 12
Slow Modos	Mode 5	High between conversion cycles	11 to 16 [‡]	CS falling edge	Figure 13
Slow Modes	Mode 6	Low continuously	16 [‡]	16th clock falling edge	Figure 14

Table 1. Mode Operation

fast modes

The device is in a fast mode when the serial I/O CLOCK data transfer is completed before the conversion is completed. With a 10-clock serial transfer, the device can only run in a fast mode since a conversion does not begin until the falling edge of the 10th I/O CLOCK.

mode 1: fast mode, CS inactive (high) between conversion cycles, 10-clock transfer

In this mode, $\overline{\text{CS}}$ is inactive (high) between serial I/O CLOCK transfers and each transfer is ten clocks long. The falling edge of $\overline{\text{CS}}$ begins the sequence by removing DATA OUT from the high-impedance state. The rising edge of $\overline{\text{CS}}$ ends the sequence by returning DATA OUT to the high-impedance state within the specified delay time. Also, the rising edge of $\overline{\text{CS}}$ disables the I/O CLOCK and ADDRESS terminals within a setup time plus two falling edges of the internal system clock.

mode 2: fast mode, CS active (low) continuously, 10-clock transfer

In this mode, \overline{CS} is active (low) between serial I/O CLOCK transfers and each transfer is ten clocks long. After the initial conversion cycle, \overline{CS} is held active (low) for subsequent conversions; the rising edge of EOC then begins each sequence by removing DATA OUT from the low logic level, allowing the MSB of the previous conversion to appear immediately on this output.



[†]These edges also initiate serial-interface communication.

[‡] No more than 16 clocks should be used.

TLV1543C, TLV1543I, TLV1543M 3.3-V 10-BIT ANALOG-TO-DIGITAL CONVERTERS WITH SERIAL CONTROL AND 11 ANALOG INPUTS

SLAS072E - DECEMBER 1992 - REVISED JANUARY 2004

mode 3: fast mode, CS inactive (high) between conversion cycles, 11- to 16-clock transfer

In this mode, \overline{CS} is inactive (high) between serial I/O CLOCK transfers and each transfer can be 11 to 16 clocks long. The falling edge of \overline{CS} begins the sequence by removing DATA OUT from the high-impedance state. The rising edge of \overline{CS} ends the sequence by returning DATA OUT to the high-impedance state within the specified delay time. Also, the rising edge of \overline{CS} disables the I/O CLOCK and ADDRESS terminals within a setup time plus two falling edges of the internal system clock.

mode 4: fast mode, CS active (low) continuously, 16-clock transfer

In this mode, \overline{CS} is active (low) between <u>serial I/O CLOCK</u> transfers and each transfer must be exactly 16 clocks long. After the initial conversion cycle, \overline{CS} is held active (low) for subsequent conversions; the rising edge of EOC then begins each sequence by removing DATA OUT from the low logic level, allowing the MSB of the previous conversion to appear immediately on this output.

slow modes

In a slow mode, the conversion is completed before the serial I/O CLOCK data transfer is completed. A slow mode requires a minimum 11-clock transfer into I/O CLOCK, and the rising edge of the eleventh clock must occur before the conversion period is complete; otherwise, the device loses synchronization with the host serial interface, and $\overline{\text{CS}}$ has to be toggled to initialize the system. The eleventh rising edge of the I/O CLOCK must occur within 9.5 μ s after the tenth I/O clock falling edge.

mode 5: slow mode, CS inactive (high) between conversion cycles, 11- to 16-clock transfer

In this mode, \overline{CS} is inactive (high) between serial I/O CLOCK transfers and each transfer can be 11 to 16 clocks long. The falling edge of \overline{CS} begins the sequence by removing DATA OUT from the high-impedance state. The rising edge of \overline{CS} ends the sequence by returning DATA OUT to the high-impedance state within the specified delay time. Also, the rising edge of \overline{CS} disables the I/O CLOCK and ADDRESS terminals within a setup time plus two falling edges of the internal system clock.

mode 6: slow mode, CS active (low) continuously, 16-clock transfer

In this mode, \overline{CS} is active (low) between serial I/O CLOCK transfers and each transfer must be exactly 16 clocks long. After the initial conversion cycle, \overline{CS} is held active (low) for subsequent conversions. The falling edge of the sixteenth I/O CLOCK then begins each sequence by removing DATA OUT from the low state, allowing the MSB of the previous conversion to appear immediately at DATA OUT. The device is then ready for the next 16-clock transfer initiated by the serial interface.

address bits

The 4-bit analog channel-select address for the next conversion cycle is presented to the ADDRESS terminal (MSB first) and is clocked into the address register on the first four leading edges of I/O CLOCK. This address selects one of 14 inputs (11 analog inputs or 3 internal test inputs).

analog inputs and test modes

The 11 analog inputs and the 3 internal test inputs are selected by the 14-channel multiplexer according to the input address as shown in Tables 2 and 3. The input multiplexer is a break-before-make type to reduce input-to-input noise injection resulting from channel switching.

Sampling of the analog input starts on the falling edge of the fourth I/O CLOCK, and sampling continues for six I/O CLOCK periods. The sample is held on the falling edge of the tenth I/O CLOCK. The three test inputs are applied to the multiplexer, sampled, and converted in the same manner as the external analog inputs.



Table 2. Analog-Channel-Select Address

ANALOG INPUT SELECTED	VALUE SHIFTED INTO ADDRESS INPUT					
SELECTED	BINARY	HEX				
A0	0000	0				
A1	0001	1				
A2	0010	2				
А3	0011	3				
A4	0100	4				
A5	0101	5				
A6	0110	6				
A7	0111	7				
A8	1000	8				
A9	1001	9				
A10	1010	А				

Table 3. Test-Mode-Select Address

INTERNAL SELF-TEST VOLTAGE SELECTED†	VALUE SHIFTE ADDRESS II	_	OUTPUT RESULT (HEX)‡
VOLIAGE SELECTED	BINARY	HEX	` ,
$\frac{V_{ref} + -V_{ref}}{2}$	1011	В	200
V _{ref} –	1100	С	000
V _{ref+}	1101	D	3FF

[†] V_{ref+} is the voltage applied to the REF+ input, and V_{ref-} is the voltage applied to the REF- input.

converter and analog input

The CMOS threshold detector in the successive-approximation conversion system determines each bit by examining the charge on a series of binary-weighted capacitors (see Figure 1). In the first phase of the conversion process, the analog input is sampled by closing the S_C switch and all S_T switches simultaneously. This action charges all the capacitors to the input voltage.

In the next phase of the conversion process, all S_T and S_C switches are opened and the threshold detector begins identifying bits by identifying the charge (voltage) on each capacitor relative to the reference (REF $_-$) voltage. In the switching sequence, ten capacitors are examined separately until all ten bits are identified and the charge-convert sequence is repeated. In the first step of the conversion phase, the threshold detector looks at the first capacitor (weight = 512). Node 512 of this capacitor is switched to the REF $_+$ voltage, and the equivalent nodes of all the other capacitors on the ladder are switched to REF $_-$. If the voltage at the summing node is greater than the trip point of the threshold detector (approximately one-half the V_{CC} voltage), a bit 0 is placed in the output register and the 512-weight capacitor is switched to REF $_-$. If the voltage at the summing node is less than the trip point of the threshold detector, a bit 1 is placed in the register and the 512-weight capacitor remains connected to REF $_+$ through the remainder of the successive-approximation process. The process is repeated for the 256-weight capacitor, the 128-weight capacitor, and so forth down the line until all bits are counted.

With each step of the successive-approximation process, the initial charge is redistributed among the capacitors. The conversion process relies on charge redistribution to count and weigh the bits from MSB to LSB.



[‡] The output results shown are the ideal values and vary with the reference stability and with internal offsets.




Figure 1. Simplified Model of the Successive-Approximation System

chip-select operation

The trailing edge of \overline{CS} starts all modes of operation, and \overline{CS} can abort a conversion sequence in any mode. A high-to-low transition on \overline{CS} within the specified time during an ongoing cycle aborts the cycle, and the device returns to the initial state (the contents of the output data register remain at the previous conversion result). Exercise care to prevent \overline{CS} from being taken low close to completion of conversion because the output data can be corrupted.

reference voltage inputs

There are two reference inputs used with these devices: REF+ and REF-. These voltage values establish the upper and lower limits of the analog input to produce a full-scale and zero-scale reading respectively. The values of REF+, REF-, and the analog input should not exceed the positive supply or be lower than GND consistent with the specified absolute maximum ratings. The digital output is at full scale when the input signal is equal to or higher than REF+ and at zero when the input signal is equal to or lower than REF-.

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)[†]

Supply voltage range, V _{CC} (see Note 1): TLV1543C/TLV1543I	0.5 V to 6.5 V
TLV1543M	0.5 V to 6 V
Input voltage range, V _I (any input)	$-0.3 \text{ V to V}_{CC} + 0.3 \text{ V}$
Output voltage range, VO	0.3 V to V _{CC} + 0.3 V
Positive reference voltage, V _{ref+}	V _{CC} + 0.1 V
Negative reference voltage, V _{ref}	–0.1 V
Peak input current (any input), I _(p-p)	±20 mA
Peak total input current (all inputs), Ip	±30 mA
Operating free-air temperature range, TA: TLV1543C	
TLV1543I	–40°C to 85°C
TLV1543M	–55°C to 125°C
Storage temperature range, T _{stq}	–65°C to 150°C
Lead temperature 1,6 mm (1/16 inch) from the case for 10 seconds	

[†] Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

NOTE 1: All voltage values are with respect to digital ground with REF - and GND wired together (unless otherwise noted).



TLV1543C, TLV1543I, TLV1543M 3.3-V 10-BIT ANALOG-TO-DIGITAL CONVERTERS WITH SERIAL CONTROL AND 11 ANALOG INPUTS

SLAS072E - DECEMBER 1992 - REVISED JANUARY 2004

recommended operating conditions

			MIN	NOM	MAX	UNIT
Own book to we M	TLV1543C/TLV1543I		3	3.3	5.5	V
Supply voltage, V _{CC}	TLV1543M		3	3.3	3.6	V
Positive reference voltage, V _{ref+} (see Note 2)				Vcc		V
Negative reference voltage, V _{ref} (see Note 2)				0		V
Differential reference voltage, V _{ref+} - V _{ref-} (see	2.5	Vcc	V _{CC} +0.2	V		
Analog input voltage (see Note 2)	Prential reference voltage, $V_{ref+} - V_{ref-}$ (see Note 2) Independent voltage (see Note 2) Independent voltage (see Note 2) Independent voltage, V_{IH} Independent voltage,				Vcc	V
	TLV1543C/TLV1543I	V _{CC} = 3 V to 5.5 V	2			V
High-level control input voltage, V _{IH}	TLV1543M	V _{CC} = 3 V to 3.6 V	2			V
	TLV1543C/TLV1543I	V _{CC} = 3 V to 5.5 V			0.6	V
Low-level control input voltage, V _{IL}	TLV1543M	V _{CC} = 3 V to 3.6 V			0.8	V
Setup time, address bits at data input before I/O	CLOCK↑, t _{SU(A)} (see Fi	gure 4)	100			ns
Hold time, address bits after I/O CLOCK↑, th(A)	(see Figure 4)		0			ns
Hold time, CS low after last I/O CLOCK↓, th(CS)			0			ns
Setup time, CS low before clocking in first addre	ss bit, t _{su(CS)} (see Note	3)	1.425			μs
	TLV1543C/TLV1543I		0		1.1	
Clock frequency at I/O CLOCK (see Note 4)	TLV1543M	TLV1543M				MHz
Pulse duration, I/O CLOCK high, t _{w(H_I/O)}			190			ns
Pulse duration, I/O CLOCK low, tw(L_I/O)			190			ns
Transition time, I/O CLOCK, t _{t(I/O)} (see Note 5)					1	μs
Transition time, ADDRESS and CS, t _{t(CS)}					10	μs
	TLV1543C	0		70	°C	
Operating free-air temperature, TA	TLV1543I				85	30
ansition time, I/O CLOCK low, $t_{W(L_I/O)}$ ansition time, I/O CLOCK, $t_{t(I/O)}$ (see Note 5) ansition time, ADDRESS and \overline{CS} , $t_{t(CS)}$	TLV1543M		-55		125	°C

- NOTES: 2. Analog input voltages greater than that applied to REF+ convert as all ones (1111111111), while input voltages less than that applied to REF- convert as all zeros (0000000000).
 - 3. To minimize errors caused by noise at \overline{CS} , the internal circuitry waits for a setup time plus two falling edges of the internal system clock after \overline{CS} ↓ before responding to control input signals. No attempt should be made to clock in an address until the minimum \overline{CS} setup time has elapsed.
 - For 11- to 16-bit transfers, after the tenth I/O CLOCK falling edge (≤ 2 V), at least one I/O clock rising edge (≥ 2 V) must occur within 9.5 µs.
 - 5. This is the time required for the clock input signal to fall from V_{IL}max or to rise from V_{IL}max to V_{IL}max to V_{IL}max. In the vicinity of normal room temperature, the devices function with input clock transition time as slow as 1 μs for remote data-acquisition applications where the sensor and the A/D converter are placed several feet away from the controlling microprocessor.



TLV1543C, TLV1543I, TLV1543M 3.3-V 10-BIT ANALOG-TO-DÍGITAL CONVERTERS WITH SERIAL CONTROL AND 11 ANALOG INPUTS SLAS072E - DECEMBER 1992 - REVISED JANUARY 2004

electrical characteristics over recommended operating free-air temperature range, V_{CC} = V_{ref+} = 3 V to 5.5 V, I/O CLOCK frequency = 1.1 MHz for the TLV1543C, and TLV1543I V_{CC} = V_{ref+} = 3 V to 3.6 V, I/O CLOCK frequency = 2.1 MHz for the TLV1543M (unless otherwise noted)

	PARAMETER	l	TEST CONI	DITIONS	MIN	TYP [†]	MAX	UNIT
		TI) (45 400 /TI) (45 40)	$V_{CC} = 3 V$,	$I_{OH} = -1.6 \text{ mA}$	2.4			V
,,	V Likele lavial avitavit valtana	TLV1543C/TLV1543I	$V_{CC} = 3 \text{ V to } 5.5 \text{ V},$	I _{OH} = 20 μA	V _{CC} -0.1			V
VOH	Hign-level output voltage	TI \ /4.5.400.4	$V_{CC} = 3 V$,	$I_{OH} = -1.6 \text{ mA}$	2.4			V
	L Low-level output voltage Off-state (high-impedance-simple description of the content of the complex current of the current of the complex current of the complex current of the cu	TLV1543M	$V_{CC} = 3 \text{ V to } 3.6 \text{ V},$	I _{OH} = 20 μA	V _{CC} -0.1			V
		TLV1543C/TLV1543I	$V_{CC} = 3 V$,	$I_{OL} = 1.6 \text{ mA}$			0.4	V
,	Lave laved autout valeage	1LV1543C/1LV1543I	$V_{CC} = 3 \text{ V to } 5.5 \text{ V},$	I _{OL} = 20 μA			0.1	V
VOL		TI \ /4.5.400.4	$V_{CC} = 3 V$,	$I_{OL} = 1.6 \text{ mA}$			0.4	V
		TLV1543M	$V_{CC} = 3 \text{ V to } 3.6 \text{ V},$	$I_{OL} = 20 \mu A$			0.1	V
	Off state (Islands laws a days as at	1-2	$V_O = V_{CC}$	CS at V _{CC}			10	
IOZ	IOZ Off-state (high-impedance-state) output curr		$V_{O} = 0,$	CS at V _{CC}			-10	μΑ
lн	High-level input current		$V_I = V_{CC}$			0.005	2.5	μΑ
I _I L	Low-level input current		V _I = 0			-0.005	-2.5	μΑ
ICC	Operating supply current		CS at 0 V			0.8	2.5	mA
			Selected channel at Unselected channel			1		
	Selected channel leakage cur	Selected channel at Unselected channel	,			-1	μА	
	Maximum static analog refere	$V_{ref+} = V_{CC}$	$V_{ref-} = GND$			10	μΑ	
	Input capacitance, Analog	TLV1543C/TLV1543I		·		7	60	
C.	inputs	TLV1543M				7	60	pF
Ci	Input capacitance, Control	TLV1543C/TLV1543I		·		5	60	n.E
	inputs	TLV1543M				5	60	pF

 $[\]uparrow$ All typical values are at V_{CC} = 5 V, T_A = 25°C.



TLV1543C, TLV1543I, TLV1543M 3.3-V 10-BIT ANALOG-TO-DIGITAL CONVERTERS WITH SERIAL CONTROL AND 11 ANALOG INPUTS

SLAS072E - DECEMBER 1992 - REVISED JANUARY 2004

operating characteristics over recommended operating free-air temperature range, $V_{CC} = V_{ref+} = 3$ V to 5.5 V, I/O CLOCK frequency = 1.1 MHz for the TLV1543C, and TLV1543I $V_{CC} = V_{ref+} = 3$ V to 3.6 V, I/O CLOCK frequency = 2.1 MHz for the TLV1543M

	PARAMETER	TEST CONDITIONS	MIN	TYP [†]	MAX	UNIT
	Linearity error (see Note 6)				±1	LSB
	Zero error (see Note 7)				±1	LSB
	Full-scale error (see Note 7)				±1	LSB
	Total unadjusted error (see Note 8)				±1	LSB
		ADDRESS = 1011		512		
	Self-test output code (see Table 3 and Note 9)	ADDRESS = 1100		0		1
		ADDRESS = 1101		1023		1
^t c(1)	Conversion time	See Figures 9-14			21	μs
^t c(2)	Total cycle time (access, sample, and conversion)	See Figures 9-14 and Note 10			21 +10 I/O CLOCK periods	μs
^t (acq)	Channel acquisition time (sample)	See Figures 9-14 and Note 10			6	I/O CLOCK periods
t_V	Valid time, DATA OUT remains valid after I/O CLOCK↓	See Figure 6	10			ns
td(I/O-DATA)	Delay time, I/O CLOCK↓ to DATA OUT valid	See Figure 6			240	ns
td(I/O-EOC)	Delay time, tenth I/O CLOCK↓ to EOC↓	See Figure 7		70	240	ns
td(EOC-DATA)	Delay time, EOC↑ to DATA OUT (MSB)	See Figure 8			100	ns
tPZH, tPZL	Enable time, CS↓ to DATA OUT (MSB driven)	See Figure 3			1.3	μs
^t PHZ ^{, t} PLZ	Disable time, CS↑ to DATA OUT (high impedance)	See Figure 3			150	ns
tr(EOC)	Rise time, EOC	See Figure 8			300	ns
^t f(EOC)	Fall time, EOC	See Figure 7			300	ns
^t r(bus)	Rise time, data bus	See Figure 6			300	ns
tf(bus)	Fall time, data bus	See Figure 6			300	ns
td(I/O-CS)	Delay time, tenth I/O CLOCK↓ to $\overline{\text{CS}}$ ↓ to abort conversion (see Note 11)				9	μs

[†] All typical values are at $T_A = 25$ °C.

NOTES: 6. Linearity error is the maximum deviation from the best straight line through the A/D transfer characteristics.

- 7. Zero-scale error is the difference between 0000000000 and the converted output for zero input voltage; full-scale error is the difference between 1111111111 and the converted output for full-scale input voltage.
- 8. Total unadjusted error comprises linearity, zero-scale, and full-scale errors.
- 9. Both the input address and the output codes are expressed in positive logic.
- 10. I/O CLOCK period = 1/(I/O CLOCK frequency) (see Figure 6).
- 11. Any transitions of \overline{CS} are recognized as valid only if the level is maintained for a setup time plus two falling edges of the internal clock (1.425 μs) after the transition.



PARAMETER MEASUREMENT INFORMATION





Figure 2. Load Circuits






Figure 3. DATA OUT to Hi-Z Voltage Waveforms

Figure 4. ADDRESS Setup Voltage Waveforms




Figure 5. CS and I/O CLOCK Voltage Waveforms

PARAMETER MEASUREMENT INFORMATION




Figure 6. DATA OUT and I/O CLOCK Voltage Waveforms




Figure 7. I/O CLOCK and EOC Voltage Waveforms






Figure 8. EOC and DATA OUT Voltage Waveforms





NOTE A: To minimize errors caused by noise at \overline{CS} , the internal circuitry waits for a setup time plus two falling edges of the internal system clock after \overline{CS} ↓ before responding to control input signals. No attempt should be made to clock in an address until the minimum \overline{CS} setup time has elapsed.


Figure 9. Timing for 10-Clock Transfer Using CS



NOTE A: To minimize errors caused by noise at \overline{CS} , the internal circuitry waits for a setup time plus two falling edges of the internal system clock after \overline{CS} ↓ before responding to control input signals. No attempt should be made to clock in an address until the minimum \overline{CS} setup time has elapsed.


Figure 10. Timing for 10-Clock Transfer Not Using CS





- NOTES: A. To minimize errors caused by noise at \overline{CS} , the internal circuitry waits for a set up time plus two falling edges of the internal system clock after \overline{CS} ↓ before responding to control input signals. No attempt should be made to clock in an address until the minimum \overline{CS} setup time has elapsed.
 - B. A low-to-high transition of $\overline{\text{CS}}$ disables ADDRESS and the I/O CLOCK within a maximum of a setup time plus two falling edges of the internal system clock.


Figure 11. Timing for 11- to 16-Clock Transfer Using CS (Serial Transfer Interval Shorter Than Conversion)



- NOTES: A. The first I/O CLOCK must occur after the rising edge of EOC.
 - B. A low-to-high transition of $\overline{\text{CS}}$ disables ADDRESS and the I/O CLOCK within a maximum of a setup time plus two falling edges of the internal system clock.


Figure 12. Timing for 16-Clock Transfer Not Using CS (Serial Transfer Interval Shorter Than Conversion)





- NOTES: A. To minimize errors caused by noise at \overline{CS} , the internal circuitry waits for a set up time plus two falling edges of the internal system clock after \overline{CS} ↓ before responding to control input signals. No attempt should be made to clock in an address until the minimum chip \overline{CS} setup time has elapsed.
 - B. The eleventh rising edge of the I/O CLOCK sequence must occur before the conversion is complete to prevent losing serial interface synchronization.

Figure 13. Timing for 11- to 16-Clock Transfer Using CS (Serial Transfer Interval Longer Than Conversion)




- NOTES: A. The eleventh rising edge of the I/O CLOCK sequence must occur before the conversion is complete to prevent losing serial interface synchronization.
 - B. The I/O CLOCK sequence is exactly 16 clock pulses long.

Figure 14. Timing for 16-Clock Transfer Not Using CS (Serial Transfer Interval Longer Than Conversion)



APPLICATION INFORMATION



- NOTES: A. This curve is based on the assumption that V_{ref+} and V_{ref-} have been adjusted so that the voltage at the transition from digital 0 to 1 (V_{ZT}) is 0.0024 V and the transition to full scale (V_{FT}) is 4.908 V. 1 LSB = 4.8 mV.
 - B. The full-scale value (VFS) is the step whose nominal midstep value has the highest absolute value. The zero-scale value (VZS) is the step whose nominal midstep value equals zero.

Figure 15. Ideal Conversion Characteristics




Figure 16. Serial Interface



APPLICATION INFORMATION

simplified analog input analysis

Using the equivalent circuit in Figure 17, the time required to charge the analog input capacitance from 0 to V_S within 1/2 LSB can be derived as follows:

The capacitance charging voltage is given by

$$V_{C} = V_{S} \left(1 - e^{-t_{C}/R_{t}C_{i}} \right)$$
 (1)

Where:

$$R_t = R_s + r_i$$

The final voltage to 1/2 LSB is given by

$$V_C (1/2 LSB) = V_S - (V_S/2048)$$
 (2)

Equating equation 1 to equation 2 and solving for time t_C gives

$$V_S - (V_S/2048) = V_S \left(1 - e^{-t_C/R_tC_i}\right)$$
 (3)

and


$$t_{c} (1/2 LSB) = R_{t} \times C_{j} \times \ln(2048)$$

$$\tag{4}$$

Therefore, with the values given the time for the analog input signal to settle is

$$t_{\rm C} (1/2 \text{ LSB}) = (R_{\rm S} + 1 \text{ k}\Omega) \times 60 \text{ pF} \times \ln(2048)$$
 (5)

This time must be less than the converter sample time shown in the timing diagrams.



V_I = Input Voltage at A0-A10

V_S = External Driving Source Voltage

R_S = Source Resistance

r_i = Input Resistance

C_i = Input Capacitance

- Noise and distortion for the source must be equivalent to the resolution of the converter.
- R_S must be real at the input frequency.

Figure 17. Equivalent Input Circuit Including the Driving Source



[†] Driving source requirements:

www.ti.com 11-Nov-2025

PACKAGING INFORMATION

Orderable part number	Status	Material type	Package Pins	Package qty Carrier	RoHS	Lead finish/ Ball material	MSL rating/ Peak reflow	Op temp (°C)	Part marking (6)
	()	()			(-7	(4)	(5)		(-)
TLV1543CDB	Active	Production	SSOP (DB) 20	70 TUBE	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	TV1543
TLV1543CDB.A	Active	Production	SSOP (DB) 20	70 TUBE	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	TV1543
TLV1543CDBR	Active	Production	SSOP (DB) 20	2000 LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-	TV1543
TLV1543CDBR.A	Active	Production	SSOP (DB) 20	2000 LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	TV1543
TLV1543CDW	Active	Production	SOIC (DW) 20	25 TUBE	Yes	NIPDAU	Level-1-260C-UNLIM	-	TLV1543C
TLV1543CDW.A	Active	Production	SOIC (DW) 20	25 TUBE	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	TLV1543C
TLV1543CDWR	Active	Production	SOIC (DW) 20	2000 LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-	TLV1543C
TLV1543CDWR.A	Active	Production	SOIC (DW) 20	2000 LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	TLV1543C
TLV1543CFN	Obsolete	Production	PLCC (FN) 20	-	-	Call TI	Call TI	-	TLV1543C
TLV1543CN	Active	Production	PDIP (N) 20	20 TUBE	Yes	NIPDAU	N/A for Pkg Type	-	TLV1543CN
TLV1543CN.A	Active	Production	PDIP (N) 20	20 TUBE	Yes	NIPDAU	N/A for Pkg Type	-40 to 85	TLV1543CN
TLV1543IDB	Active	Production	SSOP (DB) 20	70 TUBE	Yes	NIPDAU	Level-1-260C-UNLIM	-	TY1543
TLV1543IDB.A	Active	Production	SSOP (DB) 20	70 TUBE	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	TY1543
TLV1543IDBR	Active	Production	SSOP (DB) 20	2000 LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-	TY1543
TLV1543IDBR.A	Active	Production	SSOP (DB) 20	2000 LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	TY1543

⁽¹⁾ Status: For more details on status, see our product life cycle.

⁽²⁾ Material type: When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

⁽³⁾ RoHS values: Yes, No, RoHS Exempt. See the TI RoHS Statement for additional information and value definition.

⁽⁴⁾ Lead finish/Ball material: Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

⁽⁵⁾ MSL rating/Peak reflow: The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

⁽⁶⁾ Part marking: There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.



PACKAGE OPTION ADDENDUM

www.ti.com 11-Nov-2025

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

PACKAGE MATERIALS INFORMATION

www.ti.com 23-May-2025

TAPE AND REEL INFORMATION





A0	Dimension designed to accommodate the component width
В0	Dimension designed to accommodate the component length
K0	Dimension designed to accommodate the component thickness
W	Overall width of the carrier tape
P1	Pitch between successive cavity centers

QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE



*All dimensions are nominal

Device	Package Type	Package Drawing		SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
TLV1543CDBR	SSOP	DB	20	2000	330.0	16.4	8.2	7.5	2.5	12.0	16.0	Q1
TLV1543CDWR	SOIC	DW	20	2000	330.0	24.4	10.8	13.3	2.7	12.0	24.0	Q1
TLV1543IDBR	SSOP	DB	20	2000	330.0	16.4	8.2	7.5	2.5	12.0	16.0	Q1



www.ti.com 23-May-2025



*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
TLV1543CDBR	SSOP	DB	20	2000	350.0	350.0	43.0
TLV1543CDWR	SOIC	DW	20	2000	350.0	350.0	43.0
TLV1543IDBR	SSOP	DB	20	2000	350.0	350.0	43.0

PACKAGE MATERIALS INFORMATION

www.ti.com 23-May-2025

TUBE



*All dimensions are nominal

Device	Package Name	Package Type	Pins	SPQ	L (mm)	W (mm)	T (µm)	B (mm)
TLV1543CDB	DB	SSOP	20	70	530	10.5	4000	4.1
TLV1543CDB.A	DB	SSOP	20	70	530	10.5	4000	4.1
TLV1543CDW	DW	SOIC	20	25	506.98	12.7	4826	6.6
TLV1543CDW.A	DW	SOIC	20	25	506.98	12.7	4826	6.6
TLV1543CN	N	PDIP	20	20	506	13.97	11230	4.32
TLV1543CN.A	N	PDIP	20	20	506	13.97	11230	4.32
TLV1543IDB	DB	SSOP	20	70	530	10.5	4000	4.1
TLV1543IDB.A	DB	SSOP	20	70	530	10.5	4000	4.1



SMALL OUTLINE PACKAGE



NOTES:

- 1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.

 2. This drawing is subject to change without notice.

 3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not
- exceed 0.15 mm per side.
- 4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.25 mm per side.
- 5. Reference JEDEC registration MO-150.



SMALL OUTLINE PACKAGE



NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.

7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.




SMALL OUTLINE PACKAGE



NOTES: (continued)

- 8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
- 9. Board assembly site may have different recommendations for stencil design.






Images above are just a representation of the package family, actual package may vary. Refer to the product data sheet for package details.

4040005-2/C








NOTES:

- 1. All linear dimensions are in inches. Any dimensions in brackets are in millimeters. Any dimensions in parenthesis are for reference only. Controlling dimensions are in inches. Dimensioning and tolerancing per ASME Y14.5M.
- 2. This drawing is subject to change without notice.
- 3. Dimension does not include mold protrusion. Maximum allowable mold protrusion .01 in [0.25 mm] per side. 4. Reference JEDEC registration MS-018.






NOTES: (continued)

- 5. Publication IPC-7351 may have alternate designs.
- 6. Solder mask tolerances between and around signal pads can vary based on board fabrication site.





NOTES: (continued)

- Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
- 8. Board assembly site may have different recommendations for stencil design.



N (R-PDIP-T**)

PLASTIC DUAL-IN-LINE PACKAGE

16 PINS SHOWN



NOTES:

- A. All linear dimensions are in inches (millimeters).
- B. This drawing is subject to change without notice.
- Falls within JEDEC MS-001, except 18 and 20 pin minimum body length (Dim A).
- The 20 pin end lead shoulder width is a vendor option, either half or full width.





SOIC



NOTES:

- 1. All linear dimensions are in millimeters. Dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.

 2. This drawing is subject to change without notice.

 3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not
- exceed 0.15 mm per side.
- 4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.43 mm per side.
- 5. Reference JEDEC registration MS-013.



SOIC



NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.

7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.



SOIC



NOTES: (continued)

- 8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
- 9. Board assembly site may have different recommendations for stencil design.



IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you fully indemnify TI and its representatives against any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale, TI's General Quality Guidelines, or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products. Unless TI explicitly designates a product as custom or customer-specified, TI products are standard, catalog, general purpose devices.

TI objects to and rejects any additional or different terms you may propose.

Copyright © 2025, Texas Instruments Incorporated

Last updated 10/2025