

TLV2711 Advanced, Rail-to-Rail, Micropower, Single, LinCMOS™ **Operational Amplifier**

1 Features

- Output swing includes both supply rails
- Low noise: $50 \text{nV}/\sqrt{\text{Hz}}$ (typ at f = 1kHz)
- Low input bias current: 1pA (typ)
- Very low power: 11µA per channel (typ)
- Common-mode input voltage range includes negative rail
- Wide supply voltage range: 2.7V to 10V
- Available in the SOT-23 package

2 Description

The TLV2711 is a single low-voltage operational amplifier available in a 5-pin SOT-23 package. This device consumes only 11µA (typ) of supply current, which is useful for battery-powered applications. Looking at the following plot, the TLV2711 has a 3V noise level of $50\text{nV}/\sqrt{\text{Hz}}$ at 1kHz. The device exhibits rail-to-rail output performance for increased dynamic range in single- or split-supply applications.

The TLV2711, exhibiting high input impedance and low noise, is an excellent choice for small-signal conditioning for high-impedance sources, such as piezoelectric transducers. As a result of the micropower dissipation levels combined with the 3V operation, these devices work well in hand-held monitoring and remote-sensing applications.

In addition, the rail-to-rail output feature with single or split supplies makes this family a great choice when interfacing with analog-to-digital converters (ADCs).

With a total area of 5.6mm², the SOT-23 package only requires one-third the board space of the standard 8-pin SOIC package. This ultra-small package allows designers to place single amplifiers very close to the signal source, minimizing noise pickup from long PCB traces.

Package Information


PART NUMBER	PACKAGE ⁽¹⁾	PACKAGE SIZE ⁽²⁾				
TLV2711	DBV (SOT-23, 5)	2.9mm × 2.8mm				

- (1) For all available packages, see Section 9.
- (2) The package size (length × width) is a nominal value and includes pins, where applicable.

Device Information

T _A	V _{IO} max AT	PACKAGED DEVICES	SYMBOL
	25 C	SOT-23 (DBV) ⁽¹⁾	
0°C to 70°C	3mV	TLV2711CDBV	VAJC
-40°C to +85°C	3mV	TLV2711IDBV	VAJI

DBV package available in tape and reel only.




Equivalent Input Noise Voltage vs Frequency



Table of Contents

1 Features1	5 Typical Characteristics
2 Description1	
3 Pin Configuration and Functions2	6.1 Application Information
4 Specifications3	7 Device and Documentation Support14
4.1 Absolute Maximum Ratings3	7.1 Receiving Notification of Documentation Updates14
4.2 Dissipation Rating Table	· · · · · · · · · · · · · · · · · · ·
4.3 Recommended Operating Conditions3	7.3 Trademarks14
4.4 Electrical Characteristics, V _{DD} = 3 V4	
4.5 Operating Characteristics, V _{DD} = 3 V5	
4.6 Electrical Characteristics, V _{DD} = 5 V5	
4.7 Operating Characteristics, V _{DD} = 5 V6	

3 Pin Configuration and Functions



DBV Package (Top View)

4 Specifications

4.1 Absolute Maximum Ratings

over operating free-air temperature range (unless otherwise noted)(1)

			MIN	MAX	UNIT
V_{DD}	Supply voltage ⁽²⁾			12	V
V _{ID}	Differential input voltage ⁽³⁾			±V _{DD}	V
VI	Input voltage range (any input)(2)				
I _I	Input current (each input)		±5	mA	
	Duration of short-circuit current at (or less that	uration of short-circuit current at (or less than) 25°C ⁽⁴⁾			
	Continuous total power dissipation		See Dissipation Rat	ing Table	
_		TLV2711C	0	70	°C
T _A	Operating free-air temperature range	TLV2711I	-40	85	C
T _{stg}	Storage temperature range	-65	150	°C	
	Lead temperature 1,6 mm (1/16 inch) from ca DBV package		260	°C	

⁽¹⁾ Stresses beyond those listed under Absolute Maximum Ratings may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under Recommended Operating Conditions is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

4.2 Dissipation Rating Table

PACKAGE	T _A ≤ 25 ° C	DERATING FACTOR	T _A = 70 °C	T _A = 85 °C
	POWER RATING	ABOVE T _A = 25°C	POWER RATING	POWER RATING
DBV	150 mW	1.2 mW/°C	96 mW	78 mW

4.3 Recommended Operating Conditions

		TLV2	711C	TLV2	UNIT	
		MIN	MAX	MIN	MAX	UNII
V_{DD}	Supply voltage ⁽¹⁾	2.7	10	2.7	10	V
VI	Input voltage	V _{DD}	V _{DD+} – 1.3	V_{DD-}	V _{DD} + – 1.3	V
V _{IC}	Common-mode input voltage	V _{DD}	V _{DD+} – 1.3	V_{DD-}	V _{DD} + – 1.3	V
T _A	Operating free-air temperature	0	70	-40	85	°C

(1) All voltage values, except differential voltages, are with respect to V_{DD}_.

²⁾ All voltage values, except differential voltages, are with respect to V_{DD}-.

⁽³⁾ Differential voltages are at the noninverting input with respect to the inverting input. Excessive current flows when input is brought below V_{DD} = 0.3 V.

⁽⁴⁾ Short-circuit to ground. Limit temperature, supply voltages, or both to not exceed the maximum dissipation rating.



4.4 Electrical Characteristics, $V_{DD} = 3 V$

at specified free-air temperature, V_{DD} = 3 V (unless otherwise noted)

	DADAMETED	TEST CONDITIONS	T _A (1)	TL	V2711C		Т	LV2711I		LINUT	
	PARAMETER	IESI COND	IIIONS	IA (1)	MIN	TYP	MAX	MIN	TYP	MAX	UNIT
V _{IO}	Input offset voltage					0.4	3		0.4	3	mV
$\alpha_{ m VIO}$	Temperature coefficient of input offset voltage	V+-+15V V	$V_{DD} \pm = \pm 1.5 \text{ V}, V_{O} = 0 \text{ V}, V_{IC} = 0 \text{ V},$			1			1		μV/°C
I _{IO}	Input offset current ⁽²⁾	$R_{\rm S} = 50 \Omega$		25°C		0.5	60		0.5	60	
10	input onset current			Full range			150			150	pА
I _{IB}	Input bias current ⁽²⁾			25°C			60			60	p/ t
чв	input bias current			Full range		1	150		1	150	
V _{ICR}	Common-mode input	 V _{IO} ≤ 5 mV, R _S = 50	0	25°C	0 to 2	-0.3 to 2.2		0 to 2	-0.3 to 2.2		٧
VICR	voltage range	V O = 0 III V , I \(\frac{1}{2} = 0 \)	22	Full range	0 to 1.7			0 to 1.7			v
	I _{OH} = -100 μA			25°C		2.94			2.94		
V _{OH}	High-level output voltage	I _{OH} = -250 μA		25°C		2.85			2.85		V
	3	ΙΟΗ - 250 μΑ		Full range	2.6			2.6			
	L laval autout	V_{IC} = 1.5 V, I_{OL} = 50 μ	ıA	25°C		15			15		
V _{OL}	Low-level output voltage	V _{IC} = 1.5 V, I _{OL} = 500 μA		25°C		150			150		mV
	_			Full range			500			500	
	Large-signal differential voltage	erential voltage $V_{IC} = 1.5 \text{ V},$	$R_L = 10 \text{ k}\Omega^{(3)}$	25°C	3	7		3	7		
A_{VD}			_	Full range	1			1			V/mV
	amplification	-	$R_L = 1 M\Omega^{(3)}$	25°C		600			600		
r _{i(d)}	Differential input resistance			25°C		10 ¹²			10 ¹²		Ω
r _{i(c)}	Common-mode input resistance			25°C		10 ¹²			10 ¹²		Ω
c _{i(c)}	Common-mode input capacitance	f = 10 kHz		25°C		5			5		pF
z _O	Open-loop output impedance	f = 7 kHz, A _V = 1		25°C		5			5		kΩ
CMDD	Common-mode	V _{IC} = 0 to 1.7 V, R _S =	50 Ω	25°C	59	83		59	83		٩D
CMRR	rejection ratio	V _O = 1.5 V			58			58			dB
	Supply voltage	V _{DD} = 2.7 V to 8 V, no	load	25°C	70	95		70	95		
k _{SVR}	rejection ratio (ΔV _{DD} /ΔV _{IO})	$V_{DD} = 2.7 \text{ V to 8 V, 110 load}$ $V_{IC} = V_{DD} / 2,$		Full range	70			70			dB
I _{DD}	Supply current	y current V _O = 1.5 V, no load		25°C		11	25		11	25	μA
-טט	Supply current $V_0 = 1.5 \text{ V, no load}$		Full range			30			30	Γ'`	

 ⁽¹⁾ Full range for the TLV2711C is 0°C to 70°C. Full range for the TLV2711I is – 40°C to +85°C.
 (2) Specified by characterization.

Copyright © 2025 Texas Instruments Incorporated Product Folder Links: TLV2711

⁽³⁾ Referenced to 1.5 V.



4.5 Operating Characteristics, $V_{DD} = 3 V$

at specified free-air temperature, V_{DD} = 3 V (unless otherwise noted)

	PARAMETER	TEST CONDITIONS	T _A (1)	TI	LV2711C	;	Т	LV2711I		UNIT
	PARAWETER	TEST CONDITIONS	'A	MIN	TYP	MAX	MIN	TYP	MAX	
		V _O = 1.1 V to 1.9 V,	25°C	0.01	0.025		0.01	0.025		
SR	Slew rate at unity gain	$R_L = 10 \text{ k}\Omega^{(2)}, C_L = 100 \text{ pF}^{(2)}$	Full range	0.005			0.005		V/µs	V/µs
V _n	Equivalent input noise	f = 10 Hz	25°C		80			80		nV/√ Hz
V _n	voltage	f= 1 kHz	25°C		50			50		110/ 1112
V	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 1 Hz	25°C		660			660		nV
V _{N(PP)}		f = 0.1 Hz to 10 Hz	25°C		880			880		117
In	Equivalent input noise current		25°C		0.6			0.6		fA/√Hz
	Gain-bandwidth product	f = 10 kHz, $R_L = 10 \text{ k}\Omega^{(2)}, C_L = 100 \text{ pF}^{(2)}$	25°C		56			56		kHz
B _{OM}	Maximum output-swing bandwidth	$V_{O(PP)} = 1 \text{ V, } A_V = 1,$ $R_L = 10 \text{ k}\Omega^{(2)}, C_L = 100 \text{ pF}^{(2)}$	25°C		7			7		kHz
фт	Phase margin at unity gain	$R_L = 10 \text{ k}\Omega^{(2)}, C_L = 100 \text{ pF}^{(2)}$	25°C		56°			56°		
	Gain margin		25°C		20			20		dB

⁽¹⁾ Full range for the TLV2711C is 0°C to 70°C. Full range for the TLV2711I is – 40°C to +85°C.

4.6 Electrical Characteristics, $V_{DD} = 5 V$

at specified free-air temperature, V_{DD} = 5 V (unless otherwise noted)

	PARAMETER	TEST COND	NITIONS	T _A (1)	TL	V2711C		1	TLV2711I		UNIT
	PARAMETER	TEST CONL	JITIONS	I A	MIN	TYP	MAX	MIN	TYP	MAX	UNII
V _{IO}	Input offset voltage					0.45	3		0.45	3	mV
α_{VIO}	Temperature coefficient of input offset voltage	V _{DD ±} = ±2.5 V, V _O =	0 V V.a = 0 V	Full range		0.5			0.5		μV/°C
l	Input offset current ⁽²⁾	$R_S = 50 \Omega$	0 v, v _{IC} – 0 v,	25°C		0.5	60		0.5	60	pА
I _{IO}				Full range			150			150	þΑ
	Input bias current ⁽²⁾			25°C		1	60		1	60	pА
I _{IB}	input bias current		I				150			150	PΑ
V	Common-mode input voltage range	$ V_{IO} \le 5 \text{ mV}, R_S = 50 \Omega$		25°C	0 to 4	-0.3 to 4.2		0 to 4	-0.3 to 4.2		V
V _{ICR}				Full range	0 to 3.5			0 to 3.5			
		I _{OH} = -100 μA		25°C		4.95			4.95		
V _{OH}	High-level output voltage	I _{OH} = 250 μA		25°C		4.875			4.875		V
	voltage			Full range	4.6			4.6			
		V _{IC} = 2.5 V, I _{OL} = 50 I	μA	25°C		12			12		
VoL	Low-level output voltage	V - 2 5 V I - 500) A	25°C		120		,	120		mV
	voltage	$V_{IC} = 2.5 \text{ V}, I_{OL} = 500 \mu\text{A}$		Full range			500			500	
	Large-signal		D = 40 kO(3)	25°C	6	12		6	12		
A _{VD}	°	erential voltage $V_{IC} = 2.5 \text{ V},$ $V_{C} = 1 \text{ V to } 4 \text{ V}$	Full range	3			3	- 1		V/mV	
			$R_L = 1 M\Omega^{(3)}$	25°C		800			800		

Copyright © 2025 Texas Instruments Incorporated

⁽²⁾ Referenced to 1.5 V.

4.6 Electrical Characteristics, V_{DD} = 5 V (continued)

at specified free-air temperature, V_{DD} = 5 V (unless otherwise noted)

	PARAMETER	TEST CONDITIONS	T _A (1)	TL	V2711C		TI	V2711I		UNIT	
	FARAMETER	TEST CONDITIONS	'A	MIN	TYP	MAX	MIN	TYP	MAX	ONII	
r _{i(d)}	Differential input resistance		25°C		10 ¹²			10 ¹²		Ω	
r _{i(c)}	Common-mode input resistance		25°C		10 ¹²			10 ¹²		Ω	
c _{i(c)}	Common-mode input capacitance	f = 10 kHz	25°C		5			5		pF	
z _O	Open-loop output impedance	f = 7 kHz, A _V = 1	25°C		5			5		kΩ	
CMRR	Common-mode	$V_{IC} = 0 \text{ to } 2.7 \text{ V}, R_S = 50 \Omega,$	25°C	70	83		70	83		dB	
CIVIKK	rejection ratio	V _O = 2.5 V	Full range	70			70			dB	
	Supply voltage	V _{DD} = 4.4 V to 8 V, no load,	25°C	80	95		80	95			
k _{SVR}	rejection ratio (ΔV _{DD} /ΔV _{IO})	$V_{IC} = V_{DD} / 2$,	Full range	80			80			dB	
1	Supply current	$V_O = 2.5 \text{ V}, \text{ no load}$	25°C		13	25		13	25		
I _{DD}	Supply current		Full range			30			30	μA	

- (1) Full range for the TLV2711C is 0°C to 70°C. Full range for the TLV2711I is 40°C to +85°C.
- (2) Specified by characterization.
- (3) Referenced to 2.5 V.

4.7 Operating Characteristics, $V_{DD} = 5 V$

at specified free-air temperature, V_{DD} = 5 V (unless otherwise noted)

	PARAMETER TEST CONDITIONS		T _A (1)	Т	LV2711C		T	LV2711I		UNIT	
	PARAMETER	TEST CONDITIONS	IA'	MIN	TYP	MAX	MIN	TYP	MAX	ONII	
	Slew rate at unity gain	$R_L = 10 \text{ k}\Omega^{(2)}, C_L = 100 \text{ pF}^{(2)}$	25°C	0.01	0.025		0.01	0.025			
SR			Full range	0.005			0.005			V/µs	
V _n	Equivalent input	f = 10 Hz	25°C		72			72		nV/√ Hz	
V n	noise voltage	f = 1 kHz	25°C		50			50		110/ 1112	
	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 1 Hz	25°C		600			600			
V _{N(PP)}		f = 0.1 Hz to 10 Hz	25°C		800			800		nV	
In	Equivalent input noise current		25°C		0.6			0.6		fA/√ Hz	
	Gain-bandwidth product	f = 10 kHz, R _L = 10 kΩ ⁽²⁾ , C _L = 100 pF ⁽²⁾	25°C		65			65		kHz	
B _{OM}	Maximum output- swing bandwidth	$V_{O(PP)} = 2 \text{ V, } A_V = 1,$ $R_L = 10 \text{ k}\Omega^{(2)}, C_L = 100 \text{ pF}^{(2)}$	25°C		7			7		kHz	
φ _m	Phase margin at unity gain	$R_L = 10 \text{ k}\Omega^{(2)}, C_L = 100 \text{ pF}^{(2)}$	25°C		60°			60°			
	Gain margin		25°C		22			22		dB	

- (1) Full range for the TLV2711C is 0°C to 70°C. Full range for the TLV2711I is -40°C to +85°C.
- (2) Referenced to 2.5 V.

Product Folder Links: TLV2711

5 Typical Characteristics

data at high and low temperatures applicable only within rated operating free-air temperature ranges of the various devices




Figure 5-5. Input Bias and Input Offset Currents vs Free-Air **Temperature**

Free-Air Temperature − °C

Figure 5-6. High-Level Output Voltage vs High-Level Output Current

400

 \mid IOH \mid – High-Level Output Current – μ A Load referenced to 1.5 V

600

800

200

25

125



data at high and low temperatures applicable only within rated operating free-air temperature ranges of the various devices




Figure 5-7. Low-Level Output Voltage vs Low-Level Output Current




Figure 5-8. Low-Level Output Voltage vs Low-Level Output Current




Figure 5-9. High-Level Output Voltage vs High-Level Output Current





Figure 5-10. Low-Level Output Voltage vs Low-Level Output Current



for V_{DD} = 5 V, load referenced to 2.5 V

Figure 5-11. Maximum Peak-to-Peak Output Voltage vs Frequency




Figure 5-12. Output Voltage vs Differential Input Voltage

Submit Document Feedback

Copyright © 2025 Texas Instruments Incorporated

data at high and low temperatures applicable only within rated operating free-air temperature ranges of the various devices





Figure 5-13. Output Voltage vs Differential Input Voltage



For V_{DD} = 3 V, load referenced to 1.5 V, for V_{DD} = 5 V, load referenced to 2.5 V

Figure 5-14. Differential Voltage Amplification vs Load Resistance




Figure 5-15. Large-Signal Differential Voltage Amplification and Phase Margin vs Frequency




Figure 5-16. Large-Signal Differential Voltage Amplification and Phase Margin vs Frequency




Figure 5-17. Large-Signal Differential Voltage Amplification vs Free-Air Temperature





Figure 5-18. Large-Signal Differential Voltage Amplification vs Free-Air Temperature




data at high and low temperatures applicable only within rated operating free-air temperature ranges of the various devices





Submit Document Feedback

Copyright © 2025 Texas Instruments Incorporated

data at high and low temperatures applicable only within rated operating free-air temperature ranges of the various devices







0.66

0.64

10

 $\label{eq:t-Time-mus} \text{Load referenced to 1.5 V}$

30

40

50

Figure 5-26. Inverting Small-Signal Pulse Response




Figure 5-27. Voltage-Follower Small-Signal Pulse Response

20




Figure 5-29. Equivalent Input Noise Voltage vs Frequency

Figure 5-28. Voltage-Follower Small-Signal Pulse Response





Figure 5-30. Input Noise Voltage Over a 10-Second Period

Copyright © 2025 Texas Instruments Incorporated



data at high and low temperatures applicable only within rated operating free-air temperature ranges of the various devices



6 Application and Implementation

Note

Information in the following applications sections is not part of the TI component specification, and TI does not warrant its accuracy or completeness. TI's customers are responsible for determining suitability of components for their purposes, as well as validating and testing their design implementation to confirm system functionality.

6.1 Application Information

6.1.1 Driving Large Capacitive Loads

The TLV2711 is designed to drive larger capacitive loads than most CMOS operational amplifiers. Figure 5-31 illustrate the ability to drive loads up to 600 pF while maintaining good phase margins (R_{null} = 0 Ω).

A smaller series resistor (R_{null}) at the output of the device (see Figure 6-1) improves the gain and phase margins when driving large capacitive loads. The addition of this series resistor has two effects. The first effect is that the series resistor adds a zero to the transfer function. The second effect is that the series resistor reduces the frequency of the pole associated with the output load in the transfer function.

The zero introduced to the transfer function is equal to the series resistance times the load capacitance. To calculate the improvement in phase margin, use Equation 1.

$$\Delta \phi_{m1} = \tan^{-1} \left(2 \times \pi \times \text{UGBW} \times R_{\text{null}} \times C_{\text{L}} \right) \tag{1}$$

where

- $\Delta \phi_{m1}$ = Improvement in phase margin
- UGBW = Unity-gain bandwidth frequency
- R_{null} = Output series resistance
- C_I = Load capacitance




Figure 6-1. Series-Resistance Circuit

6.1.2 Driving Heavy DC Loads

The TLV2711 is designed to provide better sinking and sourcing output currents than previous CMOS rail-to-rail output devices. This device is specified to sink 500 μ A and source 250 μ A at V_{DD} = 3 V and V_{DD} = 5 V at a maximum quiescent I_{DD} of 25 μ A. These specifications provide a greater than 90% power efficiency.

When driving heavy dc loads, such as 10 k Ω , the positive edge under slewing conditions can experience some distortion; see also Figure 5-23. This condition is affected by three factors:

- Where the load is referenced. When the load is referenced to either rail, this condition does not occur. The
 distortion occurs only when the output signal swings through the point where the load is referenced. Figure
 5-24 illustrates two 10-kΩ load conditions. The first load condition shows the distortion seen for a 10-kΩ load
 tied to 2.5 V. The third load condition shows no distortion for a 10-kΩ load tied to 0 V.
- Load resistance. As the load resistance increases, the distortion seen on the output decreases. Figure 5-24 illustrates the difference seen on the output for a 10-k Ω load and a 100-k Ω load with both tied to 2.5 V.
- Input signal edge rate. Faster input edge rates for a step input result in more distortion than with slower input edge rates.

Copyright © 2025 Texas Instruments Incorporated



7 Device and Documentation Support

TI offers an extensive line of development tools. Tools and software to evaluate the performance of the device, generate code, and develop solutions are listed below.

7.1 Receiving Notification of Documentation Updates

To receive notification of documentation updates, navigate to the device product folder on ti.com. Click on *Notifications* to register and receive a weekly digest of any product information that has changed. For change details, review the revision history included in any revised document.

7.2 Support Resources

TI E2E™ support forums are an engineer's go-to source for fast, verified answers and design help — straight from the experts. Search existing answers or ask your own question to get the quick design help you need.

Linked content is provided "AS IS" by the respective contributors. They do not constitute TI specifications and do not necessarily reflect TI's views; see TI's Terms of Use.

7.3 Trademarks

TI E2E™ is a trademark of Texas Instruments.

All trademarks are the property of their respective owners.

7.4 Electrostatic Discharge Caution



This integrated circuit can be damaged by ESD. Texas Instruments recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage.

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.

7.5 Glossary

TI Glossary

This glossary lists and explains terms, acronyms, and definitions.

8 Revision History

NOTE: Page numbers for previous revisions may differ from page numbers in the current version.

CI	hanges from Revision A (March 2001) to Revision B (June 2025)	Page
•	Updated the numbering format for tables, figures, and cross-references throughout the document	1
•	Updated Features	1
•	Deleted references to TLV2711Y chip form device and associated equivalent schematic	1
•	Deleted Output current, Total current into V _{DD+} and out of V _{DD} from Absolute Maximum Ratings	3
•	Deleted Input offset voltage long term drift and table note 4 from both Electrical Characteristics	4
•	Added table note for Input offset current and Input bias current to both Electrical Charateristics	4
•	Changed Z_O from 200Ω to $5k\Omega$ in both <i>Electrical Charateristics</i>	4
•	Changed CMRR minimum at T _A = 25°C from 65 dB to 59 dB	4
•	Changed CMRR minimum at T _A = Full range from 60 dB to 58 dB	4
•	Changed kSVR minimum at T _A = 25°C and T _A = Full range from 80 dB to 70 dB	4
•	Changed Equivalent input noise voltage for f = 1 kHz from 22 nV/√Hz to 50 nV/√Hz	5
•	Updated note 1 to correct temperature ranges for both device versions in both Operating Characteristic	ics <mark>5</mark>
•	Updated table note 3 to show correct reference voltage	5
•	Changed Equivalent input noise voltage for f = 1 kHz from 21 nV/√Hz to 50 nV/√Hz	<mark>6</mark>
•	Updated table note 2 to show correct reference voltage	6
•	Deleted Figures 4, 5, 9, 10, 17, 18, 26-32, 34, 45, 47-49, 51, and 52	<mark>7</mark>
	Updated Figure 4-36 and 4-38; previously Figures 44 and 50	
•	Updated Applications information on driving large capacitive loads	13

Product Folder Links: TLV2711



9 Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

Copyright © 2025 Texas Instruments Incorporated

www.ti.com 25-Oct-2025

PACKAGING INFORMATION

Orderable part number	Status	Material type	Package Pins	Package qty Carrier	RoHS	Lead finish/			Part marking
	(1)	(2)			(3)	Ball material	Peak reflow		(6)
						(4)	(5)		
TLV2711CDBVR	Active	Production	SOT-23 (DBV) 5	3000 LARGE T&R	Yes	NIPDAU SN	Level-1-260C-UNLIM	0 to 70	VAJC
TLV2711CDBVR.A	Active	Production	SOT-23 (DBV) 5	3000 LARGE T&R	Yes	SN	Level-1-260C-UNLIM	0 to 70	VAJC
TLV2711CDBVT	Active	Production	SOT-23 (DBV) 5	250 SMALL T&R	Yes	NIPDAU SN	Level-1-260C-UNLIM	-	VAJC
TLV2711CDBVT.A	Active	Production	SOT-23 (DBV) 5	250 SMALL T&R	Yes	SN	Level-1-260C-UNLIM	-40 to 85	VAJC
TLV2711IDBVR	Active	Production	SOT-23 (DBV) 5	3000 LARGE T&R	Yes	NIPDAU SN	Level-1-260C-UNLIM	-40 to 85	VAJI
TLV2711IDBVR.A	Active	Production	SOT-23 (DBV) 5	3000 LARGE T&R	Yes	SN	Level-1-260C-UNLIM	-40 to 85	VAJI
TLV2711IDBVT	Active	Production	SOT-23 (DBV) 5	250 SMALL T&R	Yes	NIPDAU SN	Level-1-260C-UNLIM	-	VAJI
TLV2711IDBVT.A	Active	Production	SOT-23 (DBV) 5	250 SMALL T&R	Yes	SN	Level-1-260C-UNLIM	-40 to 85	VAJI
TLV2711IDBVTG4	Active	Production	SOT-23 (DBV) 5	250 SMALL T&R	-	Call TI	Call TI	See TLV2711IDBVT	

⁽¹⁾ Status: For more details on status, see our product life cycle.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative

⁽²⁾ Material type: When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

⁽³⁾ RoHS values: Yes, No. RoHS Exempt. See the TI RoHS Statement for additional information and value definition.

⁽⁴⁾ Lead finish/Ball material: Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

⁽⁵⁾ MSL rating/Peak reflow: The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

⁽⁶⁾ Part marking: There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.



PACKAGE OPTION ADDENDUM

www.ti.com 25-Oct-2025

and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

PACKAGE MATERIALS INFORMATION

www.ti.com 1-Nov-2025

TAPE AND REEL INFORMATION





A0	Dimension designed to accommodate the component width
В0	Dimension designed to accommodate the component length
K0	Dimension designed to accommodate the component thickness
W	Overall width of the carrier tape
P1	Pitch between successive cavity centers

QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE



*All dimensions are nominal

Device	Package Type	Package Drawing		SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
TLV2711CDBVR	SOT-23	DBV	5	3000	180.0	8.4	3.2	3.2	1.4	4.0	8.0	Q3
TLV2711CDBVT	SOT-23	DBV	5	250	180.0	8.4	3.2	3.2	1.4	4.0	8.0	Q3
TLV2711IDBVR	SOT-23	DBV	5	3000	180.0	8.4	3.2	3.2	1.4	4.0	8.0	Q3
TLV2711IDBVT	SOT-23	DBV	5	250	180.0	8.4	3.2	3.2	1.4	4.0	8.0	Q3

www.ti.com 1-Nov-2025



*All dimensions are nominal

7 till dillitoriolorio di o riorriiridi								
Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)	
TLV2711CDBVR	SOT-23	DBV	5	3000	210.0	185.0	35.0	
TLV2711CDBVT	SOT-23	DBV	5	250	210.0	185.0	35.0	
TLV2711IDBVR	SOT-23	DBV	5	3000	210.0	185.0	35.0	
TLV2711IDBVT	SOT-23	DBV	5	250	210.0	185.0	35.0	



SMALL OUTLINE TRANSISTOR



NOTES:

- 1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
 2. This drawing is subject to change without notice.
 3. Reference JEDEC MO-178.

- 4. Body dimensions do not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.25 mm per side.
- 5. Support pin may differ or may not be present.



SMALL OUTLINE TRANSISTOR



NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.

7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.



SMALL OUTLINE TRANSISTOR



NOTES: (continued)

- 8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
- 9. Board assembly site may have different recommendations for stencil design.



IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you fully indemnify TI and its representatives against any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale, TI's General Quality Guidelines, or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products. Unless TI explicitly designates a product as custom or customer-specified, TI products are standard, catalog, general purpose devices.

TI objects to and rejects any additional or different terms you may propose.

Copyright © 2025, Texas Instruments Incorporated

Last updated 10/2025