

TPD4E001 Low-Capacitance 4-Channel ESD-Protection for High-Speed Data **Interfaces**

1 Features

- IEC 61000-4-2 ESD Protection (Level 4)
 - ±8kV Contact Discharge
 - ±15kV Air-Gap Discharge
- 5.5A Peak Pulse Current (8/20µs Pulse)
- IO Capacitance: 1.5pF (Typical)
- Low Leakage Current: 1nA (Maximum)
- Low Supply Current: 1nA
- 0.9V to 5.5V Supply-Voltage Range
- Space-Saving DRL, DBV, DCK, DPK, and DRS Package Options
- Alternate 2, 3, 6-Channel options Available: TPD2E001, TPD3E001, TPD6E001

2 Applications

- **USB 2.0**
- Ethernet
- FireWire™ Serial Bus
- **LVDS**
- **SVGA Video Connections**
- Glucose Meters

3 Description


The TPD4E001 is a four-channel Transient Voltage Suppressor (TVS) based Electrostatic Discharge (ESD) protection diode array. The TPD4E001 is rated to dissipate ESD strikes at the maximum level specified in the IEC 61000-4-2 international standard (Level 4). This device has a 1.5pF IO capacitance per channel, making it ideal for use in high-speed data IO interfaces. The ultra low leakage current (< 1nA maximum) is suitable for precision analog measurements in applications like glucose meters and heart rate monitors.

The TPD4E001 is available in DRL(SOT), DBV (SOT-23), DCK (SC-70), DRS (QFN), and DPK (PUSON) packages and is specified for -40°C to +85°C operation. See also the TPD4E1U06DCKR and TPD4E1U06DBVR which are p2p compatible with the TPD4E001DCKR and TPD4E001DBVR. These devices offer higher IEC protection, lower capacitance, lower clamping voltage, and eliminate the input capacitor requirement.

Package Information

PART NUMBER	PACKAGE (1)	BODY SIZE (NOM)						
	SOT (6)	1.60mm × 1.20mm						
	301 (6)	2.90mm × 1.60mm						
TPD4E001	SC70 (6)	2.00mm × 1.25mm						
	USON (6)	1.60mm × 1.60mm						
	SON (6)	3.00mm × 3.00mm						

For all available packages, see the orderable addendum at the end of the data sheet.



Application Schematic



Table of Contents

1 Features1	7 Application and Implementation
2 Applications1	
3 Description1	
4 Pin Configuration and Functions3	
Pin Functions3	8.1 Layout Guidelines
5 Specifications4	8.2 Layout Example10
5.1 Absolute Maximum Ratings4	9 Device and Documentation Support1
5.2 ESD Ratings—JEDEC Specification4	9.1 Third-Party Products Disclaimer1
5.3 ESD Ratings—IEC Specification4	9.2 Documentation Support1
5.4 Recommended Operating Conditions4	9.3 Receiving Notification of Documentation Updates 1
5.5 Thermal Information5	9.4 Support Resources1
5.6 Electrical Characteristics5	9.5 Trademarks11
5.7 Typical Characteristics6	9.6 Electrostatic Discharge Caution1
6 Detailed Description7	9.7 Glossary11
6.1 Overview7	10 Revision History 1
6.2 Functional Block Diagram7	11 Mechanical, Packaging, and Orderable
6.3 Feature Description7	
6.4 Device Functional Modes7	



4 Pin Configuration and Functions




Figure 4-1. DRL Package 6-Pin SOT Top View




Figure 4-2. DBV or DCK Package 6-Pin SOT or SC70 Top View




Figure 4-3. DRS Package 6-Pin SON Top View




Figure 4-4. DPK Package 6-Pin USON Top View




Figure 4-5. TPD4E001R DBV Package 6-Pin SOT Top View

Pin Functions

	PIN	ı		I/O	DESCRIPTION	
NAME	DRS, DRL, DPK	DBV, DCK	TPD4E001R	1/0	DESCRIPTION	
GND	3	2	5	_	Ground	
	1	1	1			
IOx	2	3	3	I	l	ESD-protected channel
IOX	4	4	4			і Езр-р
	5	6	6			
V _{CC}	6	5	2	I	Power-supply input. Bypass V _{CC} to GND with a 0.1-μF ceramic capacitor	
Exposed thermal pad (DRS package only)			_	Exposed thermal pad. Connect to GND or leave floating		



5 Specifications

5.1 Absolute Maximum Ratings

over operating free-air temperature range (unless otherwise noted)(1)

			MIN	MAX	UNIT
V _{CC}			-0.3	7	V
V _{I/O}	IO voltage tolerance		-0.3	V _{CC} + 0.3	V
I _(Surge)	IEC 61000-4-5 peak pulse curre	nt (T _P = 8/20µs), IOx pins		5.5	Α
P _(Surge)	IEC 61000-4-5 peak pulse power	er (T _P = 8/20µs), IOx pins		100	W
TJ	Junction temperature			150	°C
	Bump temperature (soldering)	Infrared (15s)		220	°C
	bump temperature (soldering)	Vapor phase (60s)		215	
	Lead temperature (soldering, 10	s)		300	°C
T _{stg}	Storage temperature		-65	150	°C

⁽¹⁾ Stresses beyond those listed under Absolute Maximum Ratings may cause permanent damage to the device. These are stress ratings only, which do not imply functional operation of the device at these or any other conditions beyond those indicated under Recommended Operating Conditions. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

5.2 ESD Ratings—JEDEC Specification

				VALUE	UNIT
TPD4E0	01 in DRS, DRL, and DPK I	Packages			
		Human-body model (HBM), per ANSI/ESDA/	All pins except 1, 2, 4, and 5	±2000	
V _(ESD)	Electrostatic discharge	JEDEC JS-001 ⁽¹⁾	Pins 1, 2, 4, and 5	±15000	V
(ESD)		Charged-device model (CDM), per JEDEC specification JESD22-C101 ⁽²⁾	All pins	±1000	
TPD4E0	01 in DBV and DCK Packag	ges			
		Human-body model (HBM), per ANSI/ESDA/	All pins except 1, 3, 4, and 6	±2000	
V _(ESD)	Electrostatic discharge	JEDEC JS-001 ⁽¹⁾	Pins 1, 3, 4, and 6	, 4, and 6 ±2000 ±15000 ±1000	
- (LSD)		Charged-device model (CDM), per JEDEC specification JESD22-C101 ⁽²⁾	All pins		-

- (1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process.
- (2) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process.

5.3 ESD Ratings—IEC Specification

				VALUE	UNIT		
TPD4E001 in DRS, DRL, and DPK Packages							
V _(ESD) Electrostatic disch	Clastrostatia diasharas	IEC 61000-4-2 contact discharge	All pins	±8000	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \		
	Electrostatic discharge	IEC 61000-4-2 air-gap discharge All pins		±15000	, v		
TPD4E001 in DBV and DCK Packages							
V Floatrootatic discharge		IEC 61000-4-2 contact discharge	All pins	±8000	\ \/		
V _(ESD)	Electrostatic discharge	IEC 61000-4-2 air-gap discharge	All pins	±15000]		

5.4 Recommended Operating Conditions

over operating free-air temperature range (unless otherwise noted)

			MIN	MAX	UNIT
T _A	Operating free-air temperature		-40	85	°C
	Operating voltage	V _{CC} pin	0.9	5.5	V
	Operating voltage	IO1, IO2 pins	0	V _{CC}	V



5.5 Thermal Information

				TPD4E001			
THERMAL METRIC(1)		THERMAL METRIC ⁽¹⁾ DRL (SOT)		DBV (SOT) DCK (SC70)		DRS (SON)	UNIT
		6 PINS	6 PINS	6 PINS	6 PINS	6 PINS	
R _{θJA}	Junction-to-ambient thermal resistance	226.4	259.7	251.1	247.6	91.9	°C/W
R _{0JC(top)}	Junction-to-case (top) thermal resistance	90.3	186.5	88.1	124.8	106.9	°C/W
R _{θJB}	Junction-to-board thermal resistance	61.2	107.6	54.8	204.2	64.8	°C/W
ΨЈТ	Junction-to-top characterization parameter	6.7	71.4	1.7	19.2	10.2	°C/W
ΨЈВ	Junction-to-board characterization parameter	61	107.1	54.1	209.3	64.9	°C/W
R _{0JC(bot)}	Junction-to-case (bottom) thermal resistance	N/A	N/A	N/A	N/A	29.9	°C/W

⁽¹⁾ For more information about traditional and new thermal metrics, see the Semiconductor and IC Package Thermal Metrics application

5.6 Electrical Characteristics


over operating free-air temperature range (unless otherwise noted), V_{CC} = 5 V \pm 10%

	PARAMETER	TEST CON	IDITIONS	MIN	TYP ⁽¹⁾	MAX	UNIT
V _{CC}	Supply voltage			0.9		5.5	V
I _{CC}	Supply current				1	100	nA
V _F	Diode forward voltage	I _F = 10mA		0.65		0.95	V
V_{BR}	Breakdown Voltage	I _{BR} = 10mA	!				V
		T _A = 25°C, ±15kV HBM,	Positive transients			0.95 V V V CC + 25 -25 VCC + 60 -60 VCC + 100 -100	
	I _F = 10A	Negative transients			-25		
	±8kV contact discharge (IEC 61000-4-2), I _F = 24A Negative	±8kV contact discharge	Positive transients			V _{CC} + 60	
			Negative transients			-60	
V _C		Positive transients			V _{CC} + 100	V	
		#15kV air-gap discharge (IEC 61000-4-2), $I_F = 45A$ Surge strike on IO pin, GND pin grounded, $I_{PP} = 5A$, $8/20\mu s^{(2)}$ Negative transients	Negative transients			-100	
				17			
V_{RWM}	Reverse stand-off voltage	IO pin to GND pin				5.5	V
I _{I/O}	Channel leakage current	V _{i/o} = GND to V _{CC}				±1	nA
C _{I/O}	Channel input capacitance	$V_{CC} = 5V$, bias of $V_{CC}/2$; $f = 10$)MHz		1.5		pF

Typical values are at V_{CC} = 5V and T_A = 25°C. Non-repetitive current pulse 8/20µs exponentially decaying waveform according to ICE61000-4-5.



5.7 Typical Characteristics




6 Detailed Description

6.1 Overview

The TPD4E001 is a four-channel transient voltage suppressor (TVS) based ESD protection diode array. The TPD4E001 is rated to dissipate ESD strikes at the maximum level specified in the IEC 61000-4-2 international standard (Level 4). This device has a 1.5pF IO capacitance per channel, making it ideal for use in high-speed data IO interfaces. The ultra-low leakage current (<1nA maximum) is suitable for precision analog measurements in applications like glucose meters and heart rate monitors.

6.2 Functional Block Diagram



6.3 Feature Description

The TPD4E001 is a uni-directional ESD protection device with low capacitance. The device is constructed with a central ESD clamp that features two hiding diodes per line to reduce the capacitive loading. This central ESD clamp is also connected to V_{CC} to provide protection for the V_{CC} line. Each IO line is rated to dissipate ESD strikes above the maximum level specified in the IEC 61000-4-2 level 4 international standard. The TPD4E001's low loading capacitance makes it ideal for protection high-speed signal terminals.

6.4 Device Functional Modes

The TPD4E001 is a passive-integrated circuit that activates whenever voltages above V_{BR} or below the lower diodes $V_{forward}$ (-0.6V) are present upon the circuit being protected. During ESD events, voltages as high as $\pm 15 \text{kV}$ can be directed to ground and V_{CC} via the internal diode network. Once the voltages on the protected lines fall below the trigger voltage of the TPD4E001 (usually within 10s of nano-seconds) the device reverts back to a high-impedance state.

7 Application and Implementation

Note

Information in the following applications sections is not part of the TI component specification, and TI does not warrant its accuracy or completeness. TI's customers are responsible for determining suitability of components for their purposes. Customers should validate and test their design implementation to confirm system functionality.

7.1 Application Information

The TPD4E001 is a diode array type Transient Voltage Suppressor (TVS) which is typically used to provide a path to ground for dissipating ESD events on hi-speed signal lines between a human interface connector and a system. As the current from ESD passes through the TVS, only a small voltage drop is present across the diode. This is the voltage presented to the protected IC. The low $R_{\rm DYN}$ of the triggered TVS holds this voltage, $V_{\rm CLAMP}$, to a tolerable level to the protected IC.

7.2 Typical Application




Figure 7-1. Typical Application Schematic

7.2.1 Design Requirements

For this design example, a single TPD4E001 is used to protect all the pins of two USB2.0 connectors.

Given the USB application, the following parameters in Table 7-1 are known.

 DESIGN PARAMETER
 VALUE

 Signal range on IO1, IO2, IO3, and IO4
 0V to 3.6V

 Signal voltage range on V_{CC}
 0V to 5.25V

 Operating Frequency
 240MHz

Table 7-1. Design Parameters

7.2.2 Detailed Design Procedure

When placed near the USB connectors, the TPD4E001 ESD solution offers little or no signal distortion during normal operation due to low IO capacitance and ultra-low leakage current specifications. The TPD4E001 ensures that the core circuitry is protected and the system is functioning properly in the event of an ESD strike. For proper operation, the following layout/ design guidelines must be followed:

1. Place the TPD4E001 solution close to the connectors. This allows the TPD4E001 to take away the energy associated with ESD strike before it reaches the internal circuitry of the system board.

- 2. Place a $0.1\mu F$ capacitor very close to the V_{CC} pin. This limits any momentary voltage surge at the IO pin during the ESD strike event.
- 3. Ensure that there is enough metallization for the V_{CC} and GND loop. During normal operation, the TPD4E001 consumes nA leakage current. But during the ESD event, V_{CC} and GND may see 15A to 30A of current, depending on the ESD level. Sufficient current path enables safe discharge of all the energy associated with the ESD strike.
- 4. Leave the unused IO pins floating. In this example of protecting two USB ports, none of the IO pins are left unused.
- 5. The V_{CC} pin can be connected in two different ways:
 - a. If the V_{CC} pin is connected to the system power supply, the TPD4E001 works as a transient suppressor for any signal swing above V_{CC} + V_F . A 0.1 μ F capacitor on the device V_{CC} pin is recommended for ESD bypass.
 - b. If the V_{CC} pin is not connected to the system power supply, the TPD4E001 can tolerate higher signal swing in the range up to 10V. Please note that a 0.1µF capacitor is still recommended at the V_{CC} pin for ESD bypass.

7.2.3 Application Curve

Figure 7-2 is a capture of the voltage clamping waveform of TPD4E001DRL on IO3 during an 8kV Contact IEC61000-4-2 ESD strike.




Figure 7-2. TPD4E001DRL IEC61000-4-2 Voltage Clamp Waveform 8kV Contact

Power Supply Recommendations

This device is a passive ESD protection device so there is no need to power it. Take care to make sure that the maximum voltage specifications for each pin are not violated.

8 Layout

8.1 Layout Guidelines

- The optimum placement is as close to the connector as possible.
 - EMI during an ESD event can couple from the trace being struck to other nearby unprotected traces, resulting in early system failures.
 - The PCB designer needs to minimize the possibility of EMI coupling by keeping any unprotected traces away from the protected traces which are between the TVS and the connector.
- Route the protected traces as straight as possible.
- Eliminate any sharp corners on the protected traces between the TVS and the connector by using rounded corners with the largest radii possible.
 - Electric fields tend to build up on corners, increasing EMI coupling.



8.2 Layout Example

The following is a layout example for protecting two interface ports with the TPD4E001. One example is two USB 2.0 ports, as was discussed in the *Section 7* section. For the USB 2.0 example, IO1 and IO2 is D+ and D-, respectively, of USB port 1. IO3 and IO4 is D- and D+, respectively, of USB port 2.




Figure 8-1. Routing With DRL Package



9 Device and Documentation Support

9.1 Third-Party Products Disclaimer

TI'S PUBLICATION OF INFORMATION REGARDING THIRD-PARTY PRODUCTS OR SERVICES DOES NOT CONSTITUTE AN ENDORSEMENT REGARDING THE SUITABILITY OF SUCH PRODUCTS OR SERVICES OR A WARRANTY, REPRESENTATION OR ENDORSEMENT OF SUCH PRODUCTS OR SERVICES, EITHER ALONE OR IN COMBINATION WITH ANY TI PRODUCT OR SERVICE.

9.2 Documentation Support

9.2.1 Related Documentation

For related documentation see the following:

- Texas Instruments, Reading and Understanding an ESD Protection Datasheet
- Texas Instruments, ESD Layout Guide

9.3 Receiving Notification of Documentation Updates

To receive notification of documentation updates, navigate to the device product folder on ti.com. In the upper right corner, click on *Alert me* to register and receive a weekly digest of any product information that has changed. For change details, review the revision history included in any revised document.

9.4 Support Resources

TI E2E[™] support forums are an engineer's go-to source for fast, verified answers and design help — straight from the experts. Search existing answers or ask your own question to get the quick design help you need.

Linked content is provided "AS IS" by the respective contributors. They do not constitute TI specifications and do not necessarily reflect TI's views; see TI's Terms of Use.

9.5 Trademarks

FireWire[™] is a trademark of Apple Inc.

TI E2E[™] is a trademark of Texas Instruments.

All trademarks are the property of their respective owners.

9.6 Electrostatic Discharge Caution



This integrated circuit can be damaged by ESD. Texas Instruments recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage.

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.

9.7 Glossary

TI Glossary

This glossary lists and explains terms, acronyms, and definitions.

10 Revision History

NOTE: Page numbers for previous revisions may differ from page numbers in the current version.

Changes from Revision O (July 2019) to Revision P (January 2025)	Page
Removed DPK2 package from pin out drawings	3
Changes from Revision N (March 2018) to Revision O (July 2019)	Page
Added TPD4E001R DBV Package image and updated Pin Funtions table	3



С	hanges from Revision M (May 2017) to Revision N (March 2018)	Page
•	TPD4E001DBVR Device Marking changed from NFY to NFYF	13
_		_
С	hanges from Revision L (May 2016) to Revision M (May 2017)	Page
•	Updated Pin Functions table and DCK2 Package image	
• —	Updated 'Surge Protection" to "IEC Specification" in Section 5.3 table	4
С	hanges from Revision K (January 2015) to Revision L (May 2016)	Page
•	Added frequency test condition to Channel input capacitance in the Electrical Characteristics table	
•	Added Community Resources	
С	hanges from Revision J (December 2013) to Revision K (October 2014)	Page
•	Added Pin Configuration and Functions section, ESD Ratings table, Feature Description section, Dev Functional Modes, Application and Implementation section, Power Supply Recommendations section, Section, Device and Documentation Support section, and Mechanical, Packaging, and Orderable Information	n, Layout ormation
С	hanges from Revision I (September 2012) to Revision J (November 2013)	
• -	Updated DescriptionRemoved Ordering Information table	
С	hanges from Revision H (August 2012) to Revision I (September 2012)	Page
•	Added DCK2 package to pin out drawings	
•	Updated Electrical Characteristics table	5
С	hanges from Revision G (December 2011) to Revision H ()	Page
•	Updated TOP-SIDE MARKING column in ORDERING INFORMATION table	
С	hanges from Revision F (May 2011) to Revision G (December 2011)	Page
•	Updated document formatting	
•	Added DPK (PUSON) package and package information	
C	hanges from Revision E (April 2011) to Revision F (May 2011)	Page
<u>-</u>	Added Peak Pulse Waveform Graph to Typical Operating Characteristics	
С	hanges from Revision C (April 2007) to Revision D (December 2010)	Page
•	Added DBV (SOT-23) package and package information	



11 Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

www.ti.com

7-Nov-2025

PACKAGING INFORMATION

Orderable part number	Status (1)	Material type	Package Pins	Package qty Carrier	RoHS (3)	Lead finish/ Ball material	MSL rating/ Peak reflow	Op temp (°C)	Part marking (6)
TPD4E001DBVR	Active	Production	SOT-23 (DBV) 6	3000 LARGE T&R	Yes	NIPDAU SN	Level-1-260C-UNLIM	-40 to 85	(NFY5, NFYF) (NFYP, NFYS)
TPD4E001DBVR.B	Active	Production	SOT-23 (DBV) 6	3000 LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	(NFY5, NFYF) (NFYP, NFYS)
TPD4E001DCKR	Active	Production	SC70 (DCK) 6	3000 LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	(2CF, 2CR) (2CP, 2CP) 2CH
TPD4E001DCKR.B	Active	Production	SC70 (DCK) 6	3000 LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	(2CF, 2CR) (2CP, 2CP) 2CH
TPD4E001DCKRG4	Active	Production	SC70 (DCK) 6	3000 LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	2CF 2CP
TPD4E001DCKRG4.B	Active	Production	SC70 (DCK) 6	3000 LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	2CF 2CP
TPD4E001DPKR	Active	Production	USON (DPK) 6	5000 LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	2C7
TPD4E001DPKR.B	Active	Production	USON (DPK) 6	5000 LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	2C7
TPD4E001DPKRG4	Active	Production	USON (DPK) 6	5000 LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	2C7
TPD4E001DPKRG4.B	Active	Production	USON (DPK) 6	5000 LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	2C7
TPD4E001DPKT	Active	Production	USON (DPK) 6	250 SMALL T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	2C7
TPD4E001DPKT.B	Active	Production	USON (DPK) 6	250 SMALL T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	2C7
TPD4E001DRLR	Active	Production	SOT-5X3 (DRL) 6	4000 LARGE T&R	Yes	NIPDAU NIPDAUAG	Level-1-260C-UNLIM	-40 to 85	(2C7, 2CR) (2CG, 2CH)
TPD4E001DRLR.B	Active	Production	SOT-5X3 (DRL) 6	4000 LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	(2C7, 2CR) (2CG, 2CH)
TPD4E001DRLRG4	Active	Production	SOT-5X3 (DRL) 6	4000 LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	(2C7, 2CR) (2CG, 2CH)
TPD4E001DRSR	Active	Production	SON (DRS) 6	1000 LARGE T&R	Yes	NIPDAU	Level-2-260C-1 YEAR	-40 to 85	ZWM
TPD4E001DRSR.B	Active	Production	SON (DRS) 6	1000 LARGE T&R	Yes	NIPDAU	Level-2-260C-1 YEAR	-40 to 85	ZWM
TPD4E001DRSRG4	Active	Production	SON (DRS) 6	1000 LARGE T&R	Yes	NIPDAU	Level-2-260C-1 YEAR	-40 to 85	ZWM
TPD4E001DRSRG4.B	Active	Production	SON (DRS) 6	1000 LARGE T&R	Yes	NIPDAU	Level-2-260C-1 YEAR	-40 to 85	ZWM
TPD4E001RDBVR	Active	Production	SOT-23 (DBV) 6	3000 LARGE T&R	Yes	SN	Level-1-260C-UNLIM	-40 to 85	NRYF
TPD4E001RDBVR.B	Active	Production	SOT-23 (DBV) 6	3000 LARGE T&R	Yes	SN	Level-1-260C-UNLIM	-40 to 85	NRYF

PACKAGE OPTION ADDENDUM

www.ti.com 7-Nov-2025

- (1) Status: For more details on status, see our product life cycle.
- (2) Material type: When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.
- (3) RoHS values: Yes, No, RoHS Exempt. See the TI RoHS Statement for additional information and value definition.
- (4) Lead finish/Ball material: Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.
- (5) MSL rating/Peak reflow: The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.
- (6) Part marking: There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

OTHER QUALIFIED VERSIONS OF TPD4E001:

Automotive : TPD4E001-Q1

NOTE: Qualified Version Definitions:


• Automotive - Q100 devices qualified for high-reliability automotive applications targeting zero defects



www.ti.com 23-Jul-2025

TAPE AND REEL INFORMATION





A0	Dimension designed to accommodate the component width
В0	Dimension designed to accommodate the component length
K0	Dimension designed to accommodate the component thickness
W	Overall width of the carrier tape
P1	Pitch between successive cavity centers

QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE



*All dimensions are nominal

Device	Package Type	Package Drawing		SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
TPD4E001DBVR	SOT-23	DBV	6	3000	178.0	9.0	3.23	3.17	1.37	4.0	8.0	Q3
TPD4E001DCKR	SC70	DCK	6	3000	178.0	9.0	2.4	2.5	1.2	4.0	8.0	Q3
TPD4E001DCKRG4	SC70	DCK	6	3000	178.0	9.0	2.4	2.5	1.2	4.0	8.0	Q3
TPD4E001DPKR	USON	DPK	6	5000	180.0	9.5	1.75	1.75	0.7	4.0	8.0	Q2
TPD4E001DPKRG4	USON	DPK	6	5000	180.0	9.5	1.75	1.75	0.7	4.0	8.0	Q2
TPD4E001DPKT	USON	DPK	6	250	180.0	9.5	1.75	1.75	0.7	4.0	8.0	Q2
TPD4E001DRLR	SOT-5X3	DRL	6	4000	180.0	8.4	2.0	1.8	0.75	4.0	8.0	Q3
TPD4E001DRSR	SON	DRS	6	1000	330.0	12.4	3.3	3.3	1.1	8.0	12.0	Q2
TPD4E001DRSRG4	SON	DRS	6	1000	330.0	12.4	3.3	3.3	1.1	8.0	12.0	Q2
TPD4E001RDBVR	SOT-23	DBV	6	3000	178.0	9.0	3.23	3.17	1.37	4.0	8.0	Q3



www.ti.com 23-Jul-2025



*All dimensions are nominal

7 til dilliciololio ale Homiliai								
Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)	
TPD4E001DBVR	SOT-23	DBV	6	3000	180.0	180.0	18.0	
TPD4E001DCKR	SC70	DCK	6	3000	180.0	180.0	18.0	
TPD4E001DCKRG4	SC70	DCK	6	3000	180.0	180.0	18.0	
TPD4E001DPKR	USON	DPK	6	5000	184.0	184.0	19.0	
TPD4E001DPKRG4	USON	DPK	6	5000	184.0	184.0	19.0	
TPD4E001DPKT	USON	DPK	6	250	184.0	184.0	19.0	
TPD4E001DRLR	SOT-5X3	DRL	6	4000	210.0	185.0	35.0	
TPD4E001DRSR	SON	DRS	6	1000	353.0	353.0	32.0	
TPD4E001DRSRG4	SON	DRS	6	1000	353.0	353.0	32.0	
TPD4E001RDBVR	SOT-23	DBV	6	3000	180.0	180.0	18.0	





NOTES:

- 1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.

 2. This drawing is subject to change without notice.

 3. Body dimensions do not include mold flash or protrusion. Mold flash and protrusion shall not exceed 0.15 per side.

 4. Falls within JEDEC MO-203 variation AB.





NOTES: (continued)

5. Publication IPC-7351 may have alternate designs.

6. Solder mask tolerances between and around signal pads can vary based on board fabrication site.






NOTES: (continued)

- 7. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
- 8. Board assembly site may have different recommendations for stencil design.



DRS (S-PWSON-N6)

PLASTIC SMALL OUTLINE NO-LEAD



- NOTES: All linear dimensions are in millimeters. Dimensioning and tolerancing per ASME Y14.5M-1994.
 - This drawing is subject to change without notice.

 - SON (Small Outline No—Lead) package configuration.
 The package thermal pad must be soldered to the board for thermal and mechanical performance.
 - See the additional figure in the Product Data Sheet for details regarding the exposed thermal pad features and dimensions.



DRS (S-PWSON-N6)


PLASTIC SMALL OUTLINE NO-LEAD

THERMAL INFORMATION

This package incorporates an exposed thermal pad that is designed to be attached directly to an external heatsink. The thermal pad must be soldered directly to the printed circuit board (PCB). After soldering, the PCB can be used as a heatsink. In addition, through the use of thermal vias, the thermal pad can be attached directly to the appropriate copper plane shown in the electrical schematic for the device, or alternatively, can be attached to a special heatsink structure designed into the PCB. This design optimizes the heat transfer from the integrated circuit (IC).

For information on the Quad Flatpack No-Lead (QFN) package and its advantages, refer to Application Report, QFN/SON PCB Attachment, Texas Instruments Literature No. SLUA271. This document is available at www.ti.com.

The exposed thermal pad dimensions for this package are shown in the following illustration.



Bottom View

Exposed Thermal Pad Dimensions


4207663/E 07/11

NOTE: All linear dimensions are in millimeters



DRS (S-PWSON-N6)

PLASTIC SMALL OUTLINE NO-LEAD



NOTES:

- A. All linear dimensions are in millimeters.
- B. This drawing is subject to change without notice.
- C. Publication IPC-7351 is recommended for alternate designs.
- D. This package is designed to be soldered to a thermal pad on the board. Refer to Application Note, QFN/SON PCB Attachment, Texas Instruments Literature No. SLUA271, and also the Product Data Sheets for specific thermal information, via requirements, and recommended board layout. These documents are available at www.ti.com https://www.ti.com.
- E. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC 7525 for stencil design considerations.
- F. Customers should contact their board fabrication site for solder mask tolerances.





PLASTIC SMALL OUTLINE



NOTES:

- 1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.

 2. This drawing is subject to change without notice.

 3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not
- exceed 0.15 mm per side.
 4. Reference JEDEC registration MO-293 Variation UAAD



PLASTIC SMALL OUTLINE



NOTES: (continued)

- 5. Publication IPC-7351 may have alternate designs.
- 6. Solder mask tolerances between and around signal pads can vary based on board fabrication site.7. Land pattern design aligns to IPC-610, Bottom Termination Component (BTC) solder joint inspection criteria.



PLASTIC SMALL OUTLINE



NOTES: (continued)

- 8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
- 9. Board assembly site may have different recommendations for stencil design.







NOTES:

- 1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.

 2. This drawing is subject to change without notice.

 3. Body dimensions do not include mold flash or protrusion. Mold flash and protrusion shall not exceed 0.25 per side.

- 4. Leads 1,2,3 may be wider than leads 4,5,6 for package orientation.
- 5. Refernce JEDEC MO-178.





NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.

7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.






NOTES: (continued)

- 8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
- 9. Board assembly site may have different recommendations for stencil design.



DPK (S-PUSON-N6)

PLASTIC SMALL OUTLINE NO-LEAD




 A. All linear dimensions are in millimeters. Dimensioning and tolerancing per ASME Y14.5M-1994.
 B. This drawing is subject to change without notice. NOTES:



DPK (S-PUSON-N6)

PLASTIC SMALL OUTLINE NO-LEAD



- NOTES: A. All linear dimensions are in millimeters.
 - B. This drawing is subject to change without notice.
 - C. Publication IPC-7351 is recommended for alternate designs.
 - D. Customers should contact their board fabrication site for minimum solder mask web tolerances between signal pads.
 - E. Maximum stencil thickness 0,127 mm (5 mils). All linear dimensions are in millimeters.
 - F. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC 7525 for stencil design considerations.
 - G. Side aperture dimensions over-print land for acceptable area ratio > 0.66. Customer may reduce side aperture dimensions if stencil manufacturing process allows for sufficient release at smaller opening.



IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you fully indemnify TI and its representatives against any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale, TI's General Quality Guidelines, or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products. Unless TI explicitly designates a product as custom or customer-specified, TI products are standard, catalog, general purpose devices.

TI objects to and rejects any additional or different terms you may propose.

Copyright © 2025, Texas Instruments Incorporated

Last updated 10/2025