











**TPS7A8101** 

SBVS179B - DECEMBER 2011 - REVISED AUGUST 2015

# TPS7A8101 Low-Noise, Wide-Bandwidth, High PSRR, Low-Dropout 1-A Linear Regulator

#### **Features**

- Low-Dropout 1-A Regulator with Enable
- Adjustable Output Voltage: 0.8 V to 6 V
- Wide-Bandwidth High PSRR:
  - 80 dB at 1 kHz
  - 60 dB at 100 kHz
  - 54 dB at 1 MHz
- Low Noise: 23.5 µV<sub>RMS</sub> typical (100 Hz to 100 kHz)
- Stable with a 4.7-µF Capacitance
- **Excellent Load and Line Transient Response**
- 3% Overall Accuracy (Over Load, Line, Temperature)
- Overcurrent and Overtemperature Protection
- Very Low Dropout: 170 mV Typical at 1 A
- Package: 3-mm × 3-mm SON-8

# **Applications**

- Telecom Infrastructure
- Audio
- High-Speed I/F (PLL and VCO)

# 3 Description

The TPS7A8101 low-dropout linear regulator (LDO) offers very good performance in noise and powersupply rejection ratio (PSRR) at the output. This LDO uses an advanced BiCMOS process and a PMOSFET pass device to achieve very low noise, excellent transient response, and excellent PSRR performance.

The TPS7A8101 device is stable with a 4.7-µF ceramic output capacitor, and uses a precision voltage reference and feedback loop to achieve a worst-case accuracy of 3% over all load, line, process, and temperature variations.


This device is fully specified over the temperature range of  $T_J = -40$ °C to 125°C and is offered in a 3mm x 3-mm, SON-8 package with a thermal pad.

# **Device Information**<sup>(1)</sup>

PART NUMBER	PACKAGE	BODY SIZE (NOM)
TPS7A8101	SON (8)	3.00 mm × 3.00 mm

(1) For all available packages, see the orderable addendum at the end of the data sheet.

## Typical Application Circuit





# **Table of Contents**

1	Features 1		8.1 Application Information	
2	Applications 1	•	8.2 Typical Application	
3	Description 1	9	Power Supply Recommendations	15
4	Revision History2	10	Layout	16
5	Pin Configuration and Functions 3		10.1 Layout Guidelines	16
6	Specifications4		10.2 Layout Example	16
	6.1 Absolute Maximum Ratings		10.3 Thermal Protection	16
	6.2 ESD Ratings		10.4 Power Dissipation	17
	6.3 Recommended Operating Conditions		10.5 Estimating Junction Temperature	17
	6.4 Thermal Information	11	Device and Documentation Support	19
	6.5 Electrical Characteristics		11.1 Device Support	19
	6.6 Typical Characteristics		11.2 Documentation Support	19
7	Detailed Description		11.3 Community Resources	19
•	7.1 Overview		11.4 Trademarks	
	7.2 Functional Block Diagram		11.5 Electrostatic Discharge Caution	19
	•		11.6 Glossary	
	7.3 Feature Description	12	Mechanical, Packaging, and Orderable	
			Information	19
8	Application and Implementation 13			

# 4 Revision History

NOTE: Page numbers for previous revisions may differ from page numbers in the current version.

## Changes from Revision A (April 2012) to Revision B

**Page** 

Added ESD Ratings table, Feature Description section, Device Functional Modes, Application and Implementation section, Power Supply Recommendations section, Layout section, Device and Documentation Support section, and Mechanical, Packaging, and Orderable Information section

# Changes from Original (December 2011) to Revision A


Page

Submit Documentation Feedback



# 5 Pin Configuration and Functions

# DRB PACKAGE 8-Pin SON With Exposed Thermal Pad Top View



#### **Pin Functions**

P	IN	1/0	DESCRIPTION				
NAME	NO.	I/O	DESCRIPTION				
EN	5	I	Driving this pin high turns on the regulator. Driving this pin low puts the regulator into shutdown mode. Refer to the <i>Shutdown</i> section for more details. EN must not be left floating and can be connected to IN if not used.				
FB	3	ı	This pin is the input to the control-loop error amplifier and is used to set the output voltage of the device.				
GND	4, pad	_	Ground				
7			Hazagulatad isaut aunah				
IIN	IN 8		nregulated input supply				
NR	6	_	Connect an external capacitor between this pin and ground to reduce output noise to very low levels. The capacitor also slows down the V <sub>OUT</sub> ramp (RC softstart).				
OUT	1	0	Decider output A 4.7 up or lover consister of any time is required for stability				
OUT	2	O	Regulator output. A 4.7-μF or larger capacitor of any type is required for stability.				

Copyright © 2011–2015, Texas Instruments Incorporated



# **Specifications**

# 6.1 Absolute Maximum Ratings

Over operating free-air temperature range (unless otherwise noted). (1)

		MIN	MAX	UNIT
Voltage	IN	-0.3	7	
	FB, NR	-0.3	3.6	V
	EN	-0.3	$V_{IN} + 0.3^{(2)}$	V
	OUT	-0.3	7	
Current	OUT	Interna	Internally Limited	
Temperature	Operating virtual junction, T <sub>J</sub>	-55	150	°C
	Storage, T <sub>stg</sub>	-55	150	°C

<sup>(1)</sup> Stresses beyond those listed under Absolute Maximum Ratings may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated is not implied. Exposure to absolutemaximum-rated conditions for extended periods my affect device reliability.  $V_{EN}$  absolute maximum rating is  $V_{IN} + 0.3 \text{ V}$  or +7 V, whichever is smaller.

# 6.2 ESD Ratings

			VALUE	UNIT
		Human body model (HBM), per ANSI/ESDA/JEDEC JS-001, all pins <sup>(1)</sup>	±2000	
V <sub>(ESD)</sub>	Electrostatic discharge	Charged device model (CDM), per JEDEC specification JESD22-C101, all pins (2)	±500	V

JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process.

# 6.3 Recommended Operating Conditions

Over operating free-air temperature range (unless otherwise noted)

		MIN	MAX	UNIT				
$V_{I}$	Input voltage	2.2	6.5	V				
Io	Output current	0	1	Α				
T <sub>A</sub>	Operating free air temperature	-40	125	°C				

#### 6.4 Thermal Information

		TPS7A8101	
	THERMAL METRIC <sup>(1)</sup>	DRV (SON)	UNIT
		8 PINS	
$R_{\theta JA}$	Junction-to-ambient thermal resistance	47.8	°C/W
$R_{\theta JC(top)}$	Junction-to-case (top) thermal resistance	53.9	°C/W
$R_{\theta JB}$	Junction-to-board thermal resistance	23.4	°C/W
Ψлт	Junction-to-top characterization parameter	1	°C/W
ΨЈВ	Junction-to-board characterization parameter	23.5	°C/W
R <sub>0</sub> JC(bot)	Junction-to-case (bottom) thermal resistance	7.4	°C/W

For more information about traditional and new thermal metrics, see the Semiconductor and IC Package Thermal Metrics application report, SPRA953.

Product Folder Links: TPS7A8101

JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process.



# 6.5 Electrical Characteristics

Over the operating temperature range of  $T_J = -40^{\circ}\text{C}$  to +125°C,  $V_{IN} = V_{OUT(TYP)} + 0.5$  V or 2.2 V (whichever is greater),  $I_{OUT} = 1$  mA,  $V_{EN} = 2.2$  V,  $C_{OUT} = 4.7$   $\mu\text{F}$ ,  $C_{NR} = 0.01$   $\mu\text{F}$ , and  $C_{BYPASS} = 0$   $\mu\text{F}$ , unless otherwise noted. TPS7A8101 is tested at  $V_{OUT} = 0.8$  V and  $V_{OUT} = 6$  V. Typical values are at  $T_J = 25^{\circ}\text{C}$ .

	PARAMETER	TEST CONDIT	TIONS	MIN	TYP	MAX	UNIT
V <sub>IN</sub>	Input voltage range <sup>(1)</sup>			2.2		6.5	V
V <sub>NR</sub>	Internal reference			0.79	0.8	0.81	V
	Output voltage range			0.8		6	V
V <sub>OUT</sub>	Out 1 (2)	$V_{OUT} + 0.5 \text{ V} \le V_{IN} \le 6 \text{ V}, V_{IN} \ge 100 \text{ mA} \le I_{OUT} \le 500 \text{ mA}, 0^{\circ}\text{C}$		-2%		2%	
	Output accuracy <sup>(2)</sup>	$V_{OUT} + 0.5 \text{ V} \le V_{IN} \le 6.5 \text{ V}, V_{II}$ 100 mA $\le I_{OUT} \le 1 \text{ A}$	<sub>N</sub> ≥ 2.2 V,	-3%	±0.3%	3%	
$\Delta V_{O(\Delta VI)}$	Line regulation	$V_{OUT(NOM)} + 0.5 \text{ V} \le V_{IN} \le 6.5 \text{ V}$ $I_{OUT} = 100 \text{ mA}$	V, V <sub>IN</sub> ≥ 2.2 V,		150		μV/V
$\Delta V_{O(\Delta IL)}$	Load regulation	100 mA ≤ I <sub>OUT</sub> ≤ 1 A			2		μV/mA
		$V_{OUT} + 0.5 \text{ V} \le V_{IN} \le 6.5 \text{ V}, V_{II}$ $I_{OUT} = 500 \text{ mA}, V_{FB} = \text{GND or}$				250	
$V_{DO}$	Dropout voltage <sup>(3)</sup>	$V_{OUT} + 0.5 \text{ V} \le V_{IN} \le 6.5 \text{ V}, V_{II}$ $I_{OUT} = 750 \text{ mA}, V_{FB} = \text{GND or}$				350	mV
		$V_{OUT} + 0.5 \text{ V} \le V_{IN} \le 6.5 \text{ V}, V_{II}$ $I_{OUT} = 1 \text{ A}, V_{FB} = \text{GND or } V_{SN}$				500	
I <sub>LIM</sub>	Output current limit	$V_{OUT} = 0.85 \times V_{OUT(NOM)}, V_{IN} \ge$	$V_{OUT} = 0.85 \times V_{OUT(NOM)}, V_{IN} \ge 3.3 \text{ V}$			2000	mA
	Cround pin ourrent	I <sub>OUT</sub> = 1 mA		60	100		
I <sub>GND</sub>	Ground pin current	I <sub>OUT</sub> = 1 A				350	μA
I <sub>SHDN</sub>	Shutdown current (I <sub>GND</sub> )	$V_{EN} \le 0.4 \text{ V}, V_{IN} \ge 2.2 \text{ V}, R_L = 0^{\circ}\text{C} \le T_J \le 85^{\circ}\text{C}$		0.2	2	μA	
I <sub>FB</sub>	Feedback pin current	V <sub>IN</sub> = 6.5 V, V <sub>FB</sub> = 0.8 V			0.02	1	μA
FB			f = 100 Hz		80		
			f = 1 kHz		82		dB
PSRR	Power-supply rejection ratio	$V_{IN} = 4.3 \text{ V}, V_{OUT} = 3.3 \text{ V}, $ $I_{OUT} = 750 \text{ mA}$	f = 10 kHz		78		
		1001 = 700 1117	f = 100 kHz		60		
			f = 1 MHz		54		
V <sub>n</sub>	Output noise voltage	$BW = 100 \text{ Hz to } 100 \text{ kHz}, \\ V_{IN} = 3.8 \text{ V}, V_{OUT} = 3.3 \text{ V}, \\ I_{OUT} = 100 \text{ mA}, C_{NR} = C_{BYPASS}$	<sub>S</sub> = 470 nF		23.5		$\mu V_{RMS}$
V	Enable high (enabled)	$2.2 \text{ V} \le \text{V}_{\text{IN}} \le 3.6 \text{ V}, \text{R}_{\text{L}} = 1 \text{ k}\Omega$	!	1.2			V
$V_{EN(HI)}$	Enable high (enabled)	$3.6 \text{ V} < \text{V}_{\text{IN}} \le 6.5 \text{ V}, \text{ R}_{\text{L}} = 1 \text{ k}\Omega$	)	1.35			V
V <sub>EN(LO)</sub>	Enable low (shutdown)	$R_L = 1 k\Omega$		0		0.4	V
I <sub>EN(HI)</sub>	Enable pin current, enabled	V <sub>IN</sub> = V <sub>EN</sub> = 6.5 V			0.02	1	μΑ
t <sub>STR</sub>	Start-up time	$V_{OUT(NOM)} = 3.3 \text{ V}, V_{OUT} = 0\% \text{ to } 90\%  V_{OUT(NOM)}, \\ R_L = 3.3 \text{ k}\Omega, C_{OUT} = 10  \mu\text{F}, C_{NR} = 470 \text{ nF}$			80		ms
UVLO	Undervoltage lockout	$V_{IN}$ rising, $R_L = 1 \text{ k}\Omega$	1.86	2	2.10	V	
UVLU	Hysteresis	$V_{IN}$ falling, $R_L = 1 \text{ k}\Omega$			75		mV
_	The area of about 1	Shutdown, temperature increa	asing		160		°C
T <sub>SD</sub>	Thermal shutdown temperature	Reset, temperature decreasin		140		°C	
TJ	Operating junction temperature			-40		125	°C

<sup>(1)</sup> Minimum  $V_{IN} = V_{OUT} + V_{DO}$  or 2.2 V, whichever is greater.


Product Folder Links: TPS7A8101

 <sup>(1)</sup> Willimit V<sub>IN</sub> = V<sub>OUT</sub> + V<sub>DO</sub> of 2.2 V, Whichever is greater.
 (2) The TPS7A8101 does not include external resistor tolerances and it is not tested at this condition: V<sub>OUT</sub> = 0.8 V, 4.5V ≤ V<sub>IN</sub> ≤ 6.5 V, and 750 mA ≤ I<sub>OUT</sub> ≤ 1 A because the power dissipation is greater than the maximum rating of the package.
 (3) V<sub>DO</sub> is not measured for fixed output voltage devices with V<sub>OUT</sub> < 1.7 V because minimum V<sub>IN</sub> = 2.2 V.



# 6.6 Typical Characteristics


At  $V_{Onom} = 3.3 \text{ V}$ ,  $V_I = V_{Onom} + 0.5 \text{ V}$  or 2.2 V (whichever is greater),  $I_O = 100 \text{ mA}$ ,  $V_{(EN)} = V_I$ ,  $C_{(IN)} = 1 \text{ }\mu\text{F}$ ,  $C_{(OUT)} = 4.7 \text{ }\mu\text{F}$ , and  $C_{(NR)} = 0.01 \text{ }\mu\text{F}$ ; all temperature values refer to  $T_J$ , unless otherwise noted.





# **Typical Characteristics (continued)**

At  $V_{Onom}$  = 3.3 V,  $V_I$  =  $V_{Onom}$  + 0.5 V or 2.2 V (whichever is greater),  $I_O$  = 100 mA,  $V_{(EN)}$  =  $V_I$ ,  $C_{(IN)}$  = 1  $\mu$ F,  $C_{(OUT)}$  = 4.7  $\mu$ F, and  $C_{(NR)}$  = 0.01  $\mu$ F; all temperature values refer to  $T_J$ , unless otherwise noted.




Copyright © 2011–2015, Texas Instruments Incorporated

Submit Documentation Feedback

# TEXAS INSTRUMENTS

# **Typical Characteristics (continued)**


At  $V_{Onom}$  = 3.3 V,  $V_I$  =  $V_{Onom}$  + 0.5 V or 2.2 V (whichever is greater),  $I_O$  = 100 mA,  $V_{(EN)}$  =  $V_I$ ,  $C_{(IN)}$  = 1  $\mu$ F,  $C_{(OUT)}$  = 4.7  $\mu$ F, and  $C_{(NR)}$  = 0.01  $\mu$ F; all temperature values refer to  $T_J$ , unless otherwise noted.





# **Typical Characteristics (continued)**

At  $V_{Onom}$  = 3.3 V,  $V_I$  =  $V_{Onom}$  + 0.5 V or 2.2 V (whichever is greater),  $I_O$  = 100 mA,  $V_{(EN)}$  =  $V_I$ ,  $C_{(IN)}$  = 1  $\mu$ F,  $C_{(OUT)}$  = 4.7  $\mu$ F, and  $C_{(NR)}$  = 0.01  $\mu$ F; all temperature values refer to  $T_J$ , unless otherwise noted.



Copyright © 2011–2015, Texas Instruments Incorporated

(RMS noise (100 Hz to 100 kHz))


Submit Documentation Feedback

(RMS noise (100 Hz to 100 kHz))

# TEXAS INSTRUMENTS

# **Typical Characteristics (continued)**

At  $V_{Onom}$  = 3.3 V,  $V_I$  =  $V_{Onom}$  + 0.5 V or 2.2 V (whichever is greater),  $I_O$  = 100 mA,  $V_{(EN)}$  =  $V_I$ ,  $C_{(IN)}$  = 1  $\mu$ F,  $C_{(OUT)}$  = 4.7  $\mu$ F, and  $C_{(NR)}$  = 0.01  $\mu$ F; all temperature values refer to  $T_J$ , unless otherwise noted.



Submit Documentation Feedback

Copyright © 2011–2015, Texas Instruments Incorporated



# 7 Detailed Description

#### 7.1 Overview

The TPS7A8101 device belongs to a family of new-generation LDO regulators that use innovative circuitry to achieve wide bandwidth and high loop gain, resulting in extremely high PSRR (over a 1-MHz range) even with very low headroom ( $V_I - V_O$ ). A noise-reduction capacitor ( $C_{(NR)}$ ) at the NR pin and a bypass capacitor ( $C_{(BYPASS)}$ ) decrease noise generated by the bandgap reference to improve PSRR, while a quick-start circuit fast-charges the noise-reduction capacitor. This family of regulators offers sub-bandgap output voltages, current limit, and thermal protection, and is fully specified from  $-40^{\circ}$ C to  $125^{\circ}$ C.

# 7.2 Functional Block Diagram




Figure 30. Functional Block Diagram

#### 7.3 Feature Description

#### 7.3.1 Internal Current Limit

The TPS7A8101 internal current limit helps protect the regulator during fault conditions. During current limit, the output sources a fixed amount of current that is largely independent of output voltage. For reliable operation, the device should not be operated in a current limit state for extended periods of time.

The PMOS pass element in the TPS7A8101 has a built-in body diode that conducts current when the voltage at OUT exceeds the voltage at IN. This current is not limited, so if extended reverse voltage operation is anticipated, external limiting may be appropriate.

#### 7.3.2 Shutdown

The enable pin (EN) is active high and is compatible with standard and low voltage, TTL-CMOS levels. When shutdown capability is not required, EN can be connected to IN.

Copyright © 2011–2015, Texas Instruments Incorporated

Submit Documentation Feedback



# Feature Description (continued)

#### 7.3.3 Start-Up

Through a lower resistance, the bandgap reference can quickly charge the noise reduction capacitor ( $C_{NR}$ ). The TPS7A8101 has a *quick-start* circuit to quickly charge  $C_{NR}$ , if present; see the . At start-up, this quick-start switch is closed, with only 33 k $\Omega$  of resistance between the bandgap reference and the NR pin. The quick-start switch opens approximately 100 ms after any device enabling event, and the resistance between the bandgap reference and the NR pin becomes higher in value (approximately 250 k $\Omega$ ) to form a very good low-pass (RC) filter. This low-pass filter achieves very good noise reduction for the reference voltage.

Inrush current can be a problem in many applications. The 33-k $\Omega$  resistance during the start-up period is intentionally put there to slow down the reference voltage ramp up, thus reducing the inrush current. For example, the capacitance of connecting the recommended  $C_{NR}$  value of 0.47  $\mu$ F along with the 33-k $\Omega$  resistance causes approximately 80-ms RC delay. Start-up time with the other  $C_{NR}$  values can be calculated as:

$$t_{STR}$$
 (s) = 170,000 x  $C_{NR}$  (F) (1)

Although the noise reduction effect is nearly saturated at 0.47  $\mu$ F, connecting a  $C_{NR}$  value greater than 0.47  $\mu$ F can help reduce noise slightly more; however, start-up time will be extremely long because the quick-start switch opens after approximately 100 ms. That is, if  $C_{NR}$  is not fully charged during this 100-ms period,  $C_{NR}$  finishes charging through a higher resistance of 250  $k\Omega$ , and takes much longer to fully charge.

A low leakage C<sub>NR</sub> should be used; most ceramic capacitors are suitable.

## 7.3.4 Undervoltage Lock-Out (UVLO)

The TPS7A8101 uses an undervoltage lock-out circuit to keep the output shut off until the internal circuitry is operating properly. The UVLO circuit has a de-glitch feature so that it typically ignores undershoot transients on the input if they are less than 50-us duration.

#### 7.4 Device Functional Modes

Driving the EN pin over 1.2 V for  $V_I$  from 2.2 V to 3.6 V or 1.35 V for  $V_I$  from 3.6 V to 6.5 V turns on the regulator. Driving the EN pin below 0.4 V causes the regulator to enter shutdown mode.

In shutdown, the current consumption of the device is reduced to 0.02  $\mu A$  typically.

12 *Sub* 

Submit Documentation Feedback

Copyright © 2011–2015, Texas Instruments Incorporated



# 8 Application and Implementation

#### NOTE

Information in the following applications sections is not part of the TI component specification, and TI does not warrant its accuracy or completeness. TI's customers are responsible for determining suitability of components for their purposes. Customers should validate and test their design implementation to confirm system functionality.

## 8.1 Application Information

The TPS7A8101 belongs to a family of new generation LDO regulators that use innovative circuitry to achieve wide bandwidth and high loop gain, resulting in extremely high PSRR (over a 1-MHz range) at very low headroom ( $V_{IN} - V_{OUT}$ ). A noise reduction capacitor ( $C_{NR}$ ) at the NR pin and a bypass capacitor ( $C_{BYPASS}$ ) bypass noise generated by the bandgap reference to improve PSRR, while a quick-start circuit fast-charges the noise reduction capacitor. This family of regulators offers sub-bandgap output voltages, current limit, and thermal protection, and is fully specified from  $-40^{\circ}$ C to  $125^{\circ}$ C.

#### 8.1.1 Recommended Component Values

**Table 1. Recommended Capacitor Values** 

SYMBOL	NAME	VALUE	
C <sub>IN</sub>	Input capacitor		
C <sub>OUT</sub>	Output capacitor	10 μF	
C <sub>NR</sub>	C <sub>NR</sub> Noise reduction capacitor between NR and GND		
C <sub>BYPASS</sub>	Noise reduction capacitor across R <sub>1</sub>	470 nF	

Table 2. Recommended Feedback Resistor Values for Common Output Voltages

V <sub>OUT</sub>	R <sub>1</sub>	R <sub>2</sub>
0.8 V	0 Ω (Short)	10 kΩ
1 V	2.49 kΩ	10 kΩ
1.2 V	4.99 kΩ	10 kΩ
1.5 V	8.87 kΩ	10 kΩ
1.8 V	12.5 kΩ	10 kΩ
2.5 V	21 kΩ	10 kΩ
3.3 V	30.9 kΩ	10 kΩ
5 V	52.3 kΩ	10 kΩ

# 8.2 Typical Application

Figure 31 illustrates the connections for the device.




Figure 31. Typical Application Circuit

Copyright © 2011–2015, Texas Instruments Incorporated

Submit D



# **Typical Application (continued)**

# 8.2.1 Design Requirements

## 8.2.1.1 Dropout Voltage

The TPS7A8101 uses a PMOS pass transistor to achieve low dropout. When  $(V_{IN} - V_{OUT})$  is less than the dropout voltage  $(V_{DO})$ , the PMOS pass device is in its linear region of operation and the input-to-output resistance is the  $R_{DS(ON)}$  of the PMOS pass element.  $V_{DO}$  scales approximately with output current because the PMOS device in dropout behaves the same way as a resistor.

As with any linear regulator, PSRR and transient response are degraded as  $(V_{IN} - V_{OUT})$  approaches dropout. This effect is shown in Figure 19 and Figure 20 in the *Typical Characteristics* section.

#### 8.2.1.2 Minimum Load

The TPS7A8101 is stable and well-behaved with no output load. Traditional PMOS LDO regulators suffer from lower loop gain at very light output loads. The TPS7A8101 employs an innovative low-current mode circuit to increase loop gain under very light or no-load conditions, resulting in improved output voltage regulation performance down to zero output current.

#### 8.2.1.3 Input and Output Capacitor Requirements

Although an input capacitor is not required for stability, it is good analog design practice to connect a 0.1-µF to 1-µF low equivalent series resistance (ESR) capacitor across the input supply near the regulator. This capacitor counteracts reactive input sources and improves transient response, noise rejection, and ripple rejection. A higher-value capacitor may be necessary if large, fast rise-time load transients are anticipated or if the device is located several inches from the power source. If source impedance is not sufficiently low, a 0.1-µF input capacitor may be necessary to ensure stability.

The TPS7A8101 is designed to be stable with standard ceramic capacitors of capacitance values 4.7  $\mu$ F or larger. This device is evaluated using a 10- $\mu$ F ceramic capacitor of 10-V rating, 10% tolerance, X5R type, and 0805 size (2 mm × 1.25 mm).

X5R- and X7R-type capacitors are highly recommended because they have minimal variation in value and ESR over temperature. Maximum ESR should be less than 1  $\Omega$ .

#### 8.2.2 Detailed Design Procedure

The voltage on the FB pin sets the output voltage and is determined by the values of  $R_1$  and  $R_2$ . The values of  $R_1$  and  $R_2$  can be calculated for any voltage using the formula given in Equation 2:

$$V_{OUT} = \frac{(R_1 + R_2)}{R_2} \times 0.800$$
 (2)

Table 2 shows sample resistor values for common output voltages. In Table 2, E96 series resistors are used, and all values meet 1% of the target  $V_{OUT}$ , assuming resistors with zero error. For the actual design, pay attention to any resistor error factors. Using lower values for  $R_1$  and  $R_2$  reduces the noise injected from the FB pin.

## 8.2.2.1 Output Noise

In most LDOs, the bandgap is the dominant noise source. If a noise reduction capacitor ( $C_{NR}$ ) is used with the TPS7A8101, the bandgap does not contribute significantly to noise. Instead, noise is dominated by the output resistor divider and the error amplifier input. If a bypass capacitor ( $C_{BYPASS}$ ) across the high-side feedback resistor ( $R_1$ ) is used with the TPS7A8101 in addition to  $C_{NR}$ , noise from these other sources can also be significantly reduced.

To maximize noise performance in a given application, use a 0.47-μF noise-reduction capacitor plus a 0.47-μF bypass capacitor.

Product Folder Links: TPS7A8101



# **Typical Application (continued)**

#### 8.2.2.2 Transient Response

As with any regulator, increasing the size of the output capacitor reduces overshoot and undershoot magnitude but increases duration of the transient response. Line transient performance can be improved by using a larger noise reduction capacitor ( $C_{NR}$ ) and/or bypass capacitor ( $C_{BYPASS}$ ).

#### 8.2.3 Application Curve




Figure 32. Enable Pulse Response

# 9 Power Supply Recommendations

The device is designed to operate from an input voltage supply range from 2.2 V to 6.5 V. The input voltage range should provide adequate headroom for the device to have a regulated output. This input supply should be well regulated. If the input supply is noisy, additional input capacitors with low ESR can help improve the output noise performance.

Product Folder Links: TPS7A8101



# 10 Layout

## 10.1 Layout Guidelines

# 10.1.1 Board Layout Recommendations to Improve PSRR and Noise Performance

To improve AC performance such as PSRR, output noise, and transient response, TI recommends designing the board with separate ground planes for  $V_{IN}$  and  $V_{OUT}$ , with each ground plane connected only at the GND pin of the device. In addition, the ground connection for the bypass capacitor should connect directly to the GND pin of the device.

# 10.2 Layout Example




Figure 33. TPS7A8101 Layout Example

## 10.3 Thermal Protection

Thermal protection disables the output when the junction temperature rises to approximately 160°C, allowing the device to cool. When the junction temperature cools to approximately 140°C the output circuitry is again enabled. Depending on power dissipation, thermal resistance, and ambient temperature, the thermal protection circuit may cycle on and off. This cycling limits the dissipation of the regulator, protecting it from damage because of overheating.

Any tendency to activate the thermal protection circuit indicates excessive power dissipation or an inadequate heatsink. For reliable operation, junction temperature should be limited to 125°C maximum. To estimate the margin of safety in a complete design (including heatsink), increase the ambient temperature until the thermal protection is triggered; use worst-case loads and signal conditions. For good reliability, thermal protection should trigger at least 35°C above the maximum expected ambient condition of your particular application. This configuration produces a worst-case junction temperature of 125°C at the highest expected ambient temperature and worst-case load.

The internal protection circuitry of the TPS7A8101 has been designed to protect against overload conditions. It was not intended to replace proper heatsinking. Continuously running the TPS7A8101 into thermal shutdown degrades device reliability.

Submit Documentation Feedback

Copyright © 2011–2015, Texas Instruments Incorporated



# 10.4 Power Dissipation

Knowing the device power dissipation and proper sizing of the thermal plane that is connected to the tab or pad is critical to avoiding thermal shutdown and ensuring reliable operation.

Power dissipation of the device depends on input voltage and load conditions and can be calculated using Equation 3:


$$P_{D} = (V_{IN} - V_{OUT}) \times I_{OUT}$$
(3)

Power dissipation can be minimized and greater efficiency can be achieved by using the lowest possible input voltage necessary to achieve the required output voltage regulation.

On the SON (DRB) package, the primary conduction path for heat is through the exposed pad to the printed-circuit-board (PCB). The pad can be connected to ground or be left floating; however, it should be attached to an appropriate amount of copper PCB area to ensure the device does not overheat. The maximum junction-to-ambient thermal resistance depends on the maximum ambient temperature, maximum device junction temperature, and power dissipation of the device and can be calculated using Equation 4:

$$R_{\theta,JA} = \frac{(+125^{\circ}C - T_A)}{P_D} \tag{4}$$

Knowing the maximum  $R_{\theta JA}$ , the minimum amount of PCB copper area needed for appropriate heatsinking can be estimated using Figure 34.



Note:  $\theta_{JA}$  value at board size of 9 in<sup>2</sup> (that is, 3 in x 3 in) is a JEDEC standard.

Figure 34.  $\theta_{JA}$  vs Board Size

Figure 34 shows the variation of  $\theta_{JA}$  as a function of ground plane copper area in the board. It is intended only as a guideline to demonstrate the effects of heat spreading in the ground plane and should not be used to estimate actual thermal performance in real application environments.

#### NOTE

When the device is mounted on an application PCB, it is strongly recommended to use  $\Psi_{JT}$  and  $\Psi_{JB}$ , as explained in the *Estimating Junction Temperature* section.

#### 10.5 Estimating Junction Temperature

Using the thermal metrics  $\Psi_{JT}$  and  $\Psi_{JB}$ , as shown in the *Thermal Information* table, the junction temperature can be estimated with corresponding formulas (given in Equation 5). For backwards compatibility, an older  $\theta_{JC}$ , *Top* parameter is listed as well.

$$\Psi_{JT}: \quad T_{J} = T_{T} + \Psi_{JT} \bullet P_{D}$$

$$\Psi_{JB}: \quad T_{J} = T_{B} + \Psi_{JB} \bullet P_{D}$$
(5)

Copyright © 2011–2015, Texas Instruments Incorporated

Submit Documentation Feedback



# **Estimating Junction Temperature (continued)**

Where  $P_D$  is the power dissipation shown by Equation 4,  $T_T$  is the temperature at the center-top of the IC package, and  $T_B$  is the PCB temperature measured 1 mm away from the IC package *on the PCB surface* (as Figure 35 shows).




Figure 35. Measuring Points for T<sub>T</sub> and T<sub>B</sub>

#### **NOTE**

Both  $T_T$  and  $T_B$  can be measured on actual application boards using an infrared thermometer.

For more information about measuring  $T_T$  and  $T_B$ , see the application note SBVA025, *Using New Thermal Metrics*, available for download at www.ti.com.

By looking at Figure 36, the new thermal metrics ( $\Psi_{JT}$  and  $\Psi_{JB}$ ) have very little dependency on board size. That is, using  $\Psi_{JT}$  or  $\Psi_{JB}$  with Equation 5 is a good way to estimate  $T_J$  by simply measuring  $T_T$  or  $T_B$ , regardless of the application board size.




Figure 36.  $\Psi_{JT}$  and  $\Psi_{JB}$  vs Board Size

For a more detailed discussion of why TI does not recommend using  $\theta_{\text{JC(top)}}$  to determine thermal characteristics, refer to application report SBVA025, *Using New Thermal Metrics*, available for download at www.ti.com. For further information, refer to application report SPRA953, *IC Package Thermal Metrics*, also available on the TI website.

Submit Documentation Feedback



# 11 Device and Documentation Support

## 11.1 Device Support

#### 11.1.1 Device Nomenclature

PRODUCT	V <sub>OUT</sub>			
TPS7A8101 <i>yyyz</i>	YYY is package designator.			
	<b>Z</b> is package quantity.			

# 11.2 Documentation Support

#### 11.2.1 Related Documentation

For related documentation see the following:

- LDO noise examined in detail, SLYT489
- LDO Performance Near Dropout, SBVA029
- TPS7A8101EVM Evaluation Module, SLVU600
- Wide Bandwidth PSRR of LDOs by Nogawa and Van Renterghem in Bodo's Power Systems<sup>®</sup>: Electronics in Motion and Conversion, March 2011

## 11.3 Community Resources

The following links connect to TI community resources. Linked contents are provided "AS IS" by the respective contributors. They do not constitute TI specifications and do not necessarily reflect TI's views; see TI's Terms of

TI E2E™ Online Community TI's Engineer-to-Engineer (E2E) Community. Created to foster collaboration among engineers. At e2e.ti.com, you can ask questions, share knowledge, explore ideas and help solve problems with fellow engineers.

**Design Support** *TI's Design Support* Quickly find helpful E2E forums along with design support tools and contact information for technical support.

#### 11.4 Trademarks

E2E is a trademark of Texas Instruments.

Bodo's Power Systems is a registered trademark of Arlt Bodo.

All other trademarks are the property of their respective owners.

#### 11.5 Electrostatic Discharge Caution



These devices have limited built-in ESD protection. The leads should be shorted together or the device placed in conductive foam during storage or handling to prevent electrostatic damage to the MOS gates.

## 11.6 Glossary

SLYZ022 — TI Glossary.

This glossary lists and explains terms, acronyms, and definitions.

# 12 Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

Product Folder Links: TPS7A8101

www.ti.com

31-Oct-2025

#### PACKAGING INFORMATION

Orderable part number	Status	Material type	Package   Pins	Package qty   Carrier	RoHS	Lead finish/ Ball material	MSL rating/ Peak reflow	Op temp (°C)	Part marking (6)
	` ,	` '			. ,	(4)	(5)		. ,
TPS7A8101DRBR	Active	Production	SON (DRB)   8	3000   LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	SAU
TPS7A8101DRBR.A	Active	Production	SON (DRB)   8	3000   LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	SAU
TPS7A8101DRBRG4	Active	Production	SON (DRB)   8	3000   LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	SAU
TPS7A8101DRBRG4.A	Active	Production	SON (DRB)   8	3000   LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	SAU
TPS7A8101DRBT	Active	Production	SON (DRB)   8	250   SMALL T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	SAU
TPS7A8101DRBT.A	Active	Production	SON (DRB)   8	250   SMALL T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	SAU

<sup>(1)</sup> Status: For more details on status, see our product life cycle.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

<sup>(2)</sup> Material type: When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

<sup>(3)</sup> RoHS values: Yes, No, RoHS Exempt. See the TI RoHS Statement for additional information and value definition.

<sup>(4)</sup> Lead finish/Ball material: Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

<sup>(5)</sup> MSL rating/Peak reflow: The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

<sup>(6)</sup> Part marking: There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

# PACKAGE OPTION ADDENDUM

www.ti.com 31-Oct-2025

#### OTHER QUALIFIED VERSIONS OF TPS7A8101:

Automotive: TPS7A8101-Q1

NOTE: Qualified Version Definitions:

• Automotive - Q100 devices qualified for high-reliability automotive applications targeting zero defects

# **PACKAGE MATERIALS INFORMATION**

www.ti.com 18-Jun-2025

# TAPE AND REEL INFORMATION





	Dimension designed to accommodate the component width
В0	Dimension designed to accommodate the component length
K0	Dimension designed to accommodate the component thickness
W	Overall width of the carrier tape
P1	Pitch between successive cavity centers

## QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE



#### \*All dimensions are nominal

Device	Package Type	Package Drawing		SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
TPS7A8101DRBR	SON	DRB	8	3000	330.0	12.4	3.3	3.3	1.1	8.0	12.0	Q2
TPS7A8101DRBRG4	SON	DRB	8	3000	330.0	12.4	3.3	3.3	1.1	8.0	12.0	Q2
TPS7A8101DRBT	SON	DRB	8	250	180.0	12.4	3.3	3.3	1.1	8.0	12.0	Q2

www.ti.com 18-Jun-2025



# \*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
TPS7A8101DRBR	SON	DRB	8	3000	346.0	346.0	33.0
TPS7A8101DRBRG4	SON	DRB	8	3000	346.0	346.0	33.0
TPS7A8101DRBT	SON	DRB	8	250	182.0	182.0	20.0



Images above are just a representation of the package family, actual package may vary. Refer to the product data sheet for package details.

4203482/L





PLASTIC SMALL OUTLINE - NO LEAD



#### NOTES:

- All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
- 2. This drawing is subject to change without notice.
- 3. The package thermal pad must be soldered to the printed circuit board for thermal and mechanical performance.



PLASTIC SMALL OUTLINE - NO LEAD



NOTES: (continued)

- 4. This package is designed to be soldered to a thermal pad on the board. For more information, see Texas Instruments literature number SLUA271 (www.ti.com/lit/slua271).
- 5. Vias are optional depending on application, refer to device data sheet. If any vias are implemented, refer to their locations shown on this view. It is recommended that vias under paste be filled, plugged or tented.



PLASTIC SMALL OUTLINE - NO LEAD



NOTES: (continued)

6. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.



## IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you fully indemnify TI and its representatives against any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale, TI's General Quality Guidelines, or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products. Unless TI explicitly designates a product as custom or customer-specified, TI products are standard, catalog, general purpose devices.

TI objects to and rejects any additional or different terms you may propose.

Copyright © 2025, Texas Instruments Incorporated

Last updated 10/2025