

SLUS317B - JANUARY 2000 - REVISED FEBRUARY 2004

- Fast Transient Response
- 10-mA to 3-A Load Current
- Short Circuit Protection
- Maximum Dropout of 450-mV at 3-A Load Current
- Separate Bias and VIN Pins
- Available in Adjustable or Fixed-Output Voltages
- 5-Pin Package Allows Kelvin Sensing of Load Voltage
- Reverse Current Protection

5-PIN TO-220 T PACKAGE (TOP VIEW)







Note: Tab = Ground


description

The UC382 is a low-dropout-linear regulator providing a quick response to fast load changes. Combined with its precision onboard reference, the UC382 excels at driving GTL and BTL buses. Due to its fast response to load transients, the total capacitance required to decouple the regulator's output can be significantly decreased when compared to standard LDO linear regulators.

Dropout voltage (VIN to VOUT) is only 450 mV maximum at 100°C and 350 mV typical at 3-A load.

The onboard bandgap reference is stable with temperature and scaled for a 1.2-V input to the internal-power amplifier. The UC382 is available in fixed-output voltages of 1.5 V, 2.1 V, or 2.5 V. The output voltage of the adjustable version can be set with two external resistors. If the external resistors are omitted, the output voltage defaults to 1.2 V.

block diagram



₩.

Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

All trademarks are the property of their respective owners.

TEXAS INSTRUMENTS

UC282-1, UC282-2, UC282-3, UC282-ADJ, UC382-1, UC382-2, UC382-3, UC382-ADJ FAST LDO LINEAR REGULATOR

SLUS317B - JANUARY 2000 - REVISED FEBRUARY 2004

absolute maximum ratings over operating	g free-air temperature (unless otherwise noted) ^{†‡}
VB	
VIN	7.5 V
Output voltage	1.2 V to 6.0 V
Storage temperature, T _{stg}	–65°C to 150°C
Junction temperature, T _J	
	300°C

AVAILABLE OPTIONS(1)

	PACKAGED DEVICES										
_		TO-2	20 (T)		TO-263 (TD) ⁽²⁾						
TJ		OUTPUT	VOLTAGE		OUTPUT VOLTAGE						
	1.5 V	2.1 V	2.5 V	1.2 V or ADJ	1.5 V	2.1 V	2.5 V	1.2 V or ADJ			
–40°C to 100°C	282T-1	282T-2	282T-3	282T-ADJ	282TD-1	282TD-2	282TD-3	282TD-ADJ			
0°C to 100°C	382T-1	382T-2	382T-3	382T-ADJ	382TD-1	382TD-2	382TD-3	382TD-ADJ			

^{1.} For more package and ordering information, see the Package Option Addendum located at the end of this data sheet.

electrical characteristics, $T_A = -40^{\circ}\text{C}$ to 100°C for the UC282-X series and 0°C to 100°C for the UC382-X, VB = 5 V, VIN = 3.3 V, VOUT = 2.5 V for the UC382-ADJ, $T_A = T_J$, (unless otherwise stated)

UC382-3 fixed 2.5 V, 3-A family

PARAMETERS	TE	TEST CONDITIONS				UNITS
Outratualisms (I	UC382-3		2.475	2.500	2.525	V
Output voltage (I _{VOUT} = 100 mA)	UC282-3		2.450	2.500	2.525	V
Load regulation	I _{VOUT} = 10 mA to 3 A	I _{VOUT} = 10 mA to 3 A				mV
VIN PSSR			80	100		dB
VB PSSR			50	60		dB
	I _{VOUT} = 3 A,	T _J = 25°C		350	425	mV
VIN dropout voltage = VIN-VOUT	I _{VOUT} = 3 A,	UC382-3		350	450	mV
	I _{VOUT} = 3 A,	UC282-3		350	500	mV
VP dramant VP VOLIT	I _{VOUT} = 3 A,	UC382-3		1.8	2.10	V
VB dropout = VB–VOUT	I _{VOUT} = 3 A,	UC282-3		1.8	2.20	V
Short circuit current limit			3.3		4.5	Α
VP	I _{VOUT} = 10 mA			6	11	mA
VB current	I _{VOUT} = 3 A			18	60	mA
VIN current	I _{VOUT} = 3 A		2.94	2.97		А



[†] Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

[‡]Currents are positive into, negative out of the specified terminal. Consult Packaging Section of Databook for thermal limitations and considerations of packages.

^{2.} For 50 piece reel, add KTTT (e.g., UC282TDKTTT-1); for 500 piece reel, add TR (e.g., UC282TDTR-1).

UC282-1, UC282-2, UC282-3, UC282-ADJ, UC382-1, UC382-2, UC382-3, UC382-ADJ FAST LDO LINEAR REGULATOR

SLUS317B - JANUARY 2000 - REVISED FEBRUARY 2004

electrical characteristics, $T_A = -40^{\circ}C$ to $100^{\circ}C$ for the UC282-X series and $0^{\circ}C$ to $100^{\circ}C$ for the UC382-X, VB = 5 V, VIN = 3.3 V, VOUT = 2.5 V for the UC382-ADJ, $T_A = T_J$, (unless otherwise stated)

UC382-2 fixed 2.1 V, 3-A family

PARAMETERS	TE	ST CONDITIONS	MIN	TYP	MAX	UNITS
Outratuality as (I	UC382-2		2.079	2.100	2.121	V
Output voltage (I _{VOUT} = 100 mA)	UC282-2		2.058	2.100	2.121	V
Load regulation	$I_{VOUT} = 10 \text{ mA to } 3 \text{ A}$	4		0.5	4	mV
VIN PSSR			80	100		dB
VB PSSR			52	62		dB
	I _{VOUT} = 3 A,	T _J = 25°C		350	425	mV
VIN dropout voltage = VIN-VOUT	I _{VOUT} = 3 A,	UC382-2		350	450	mV
	I _{VOUT} = 3 A,	UC282-2		350	500	mV
VP days and VP VOLIT	I _{VOUT} = 3 A,	UC382-2		1.8	2.10	V
VB dropout = VB-VOUT	I _{VOUT} = 3 A,	UC282-2		1.8	2.20	V
Short circuit current limit			3.3		4.5	Α
VB .	I _{VOUT} = 10 mA			6	11	mA
VB current	I _{VOUT} = 3 A			18	60	mA
VIN current	I _{VOUT} = 3 A		2.94	2.97		Α

UC382-1 fixed 1.5 V, 3-A family

PARAMETERS	TE	ST CONDITIONS	MIN	TYP	MAX	UNITS
	UC382-1		1.485	1.500	1.515	V
Output voltage (I _{VOUT} = 100 mA)	UC282-1		1.470	1.500	1.515	V
Load regulation	I _{VOUT} = 10 mA to 3 A	A		0.5	4	mV
VIN PSSR			80	100		dB
VB PSSR			55	65		dB
VIN dropout voltage = VIN-VOUT	I _{VOUT} = 3 A,	T _J = 25°C		350	425	mV
	I _{VOUT} = 3 A,	UC382-1		350	450	mV
	I _{VOUT} = 3 A,	UC282-1		350	500	mV
VD draway VD VOLIT	I _{VOUT} = 3 A,	UC382-1		1.8	2.10	V
VB dropout = VB-VOUT	I _{VOUT} = 3 A,	UC282-1		1.8	2.20	V
Short circuit current limit			3.3		4.5	Α
VB current	I _{VOUT} = 10 mA			6	11	mA
	IVOUT = 3 A			18	60	mA
VIN current	I _{VOUT} = 3 A		2.94	2.97		Α

UC282-1, UC282-2, UC282-3, UC282-ADJ, UC382-1, UC382-2, UC382-3, UC382-ADJ FAST LDO LINEAR REGULATOR

SLUS317B - JANUARY 2000 - REVISED FEBRUARY 2004

electrical characteristics, $T_A = -40^{\circ}\text{C}$ to 100°C for the UC282-X series and 0°C to 100°C for the UC382-X, VB = 5 V, VIN = 3.3 V, VOUT = 2.5 V for the UC382-ADJ, $T_A = T_J$, (unless otherwise stated)

UC382-ADJ adjustable, 3-A family

PARAMETERS	TE	TEST CONDITIONS				UNITS
AD Localita are (I	UC382-ADJ		1.188	1.200	1.212	V
ADJ voltage (I _{VOUT} = 100 mA)	UC282-ADJ		1.176	1.200	1.212	V
Load regulation	I _{VOUT} = 10 mA to 3 A	Ą		0.5	4	mV
VIN PSSR	VOUT programmed for	or 2.5 V	80	100		dB
VB PSSR	VOUT programmed for	VOUT programmed for 2.5 V				dB
	I _{VOUT} = 3 A,	T _J = 25°C		350	425	mV
VIN dropout voltage = VIN-VOUT	I _{VOUT} = 3 A,	UC382-ADJ		350	450	mV
	I _{VOUT} = 3 A,	UC282-ADJ		350	500	mV
VP decreed VP VOLT	I _{VOUT} = 3 A,	UC382-ADJ		1.8	2.10	V
VB dropout = VB-VOUT	I _{VOUT} = 3 A,	UC282-ADJ		1.8	2.20	V
Short circuit current limit			3.3		4.5	Α
	I _{VOUT} = 10 mA			6	11	mA
VB current	I _{VOUT} = 3 A	<u> </u>		18	60	mA
VIN current	I _{VOUT} = 3 A		2.94	2.97		Α

pin descriptions

ADJ: In the adjustable version, the user programs the output voltage with two external resistors. The resistors should be 0.1% for high accuracy. The output amplifier is configured as a non-inverting-operational amplifier. The resistors should meet the criteria of R3 || R4 < 100 Ω . Connect ADJ to VOUT for an output voltage of 1.2 V. Note that the point at which the feedback network is connected to the output is the Kelvin sense point. For -1, -2, and -3 versions, ADJ pin is tied to VOUT to obtain specified output voltage.

GND: For accurate results, the GND pin should be referenced to the load ground.


VB: Supplies power to all circuits of the regulator except the collector of the output-power transistor. The 2-V headroom from VB to VOUT allows the use of a Darlington output stage for inherently-low-output impedance and fast response. (Dropout is derated for junction temperatures below 0°C.)

VIN: Supplies the current to the collector of the output-power transistor only. The dropout (VIN–VOUT) is under 100 mV for light loads; maximum dropout is 450 mV at 3 A for $T_J = 0^{\circ}$ C to 100° C. (Dropout is derated for junction temperatures over 100° C.) At full load, the majority of the VB current is going to the load.

VOUT: This pin should be connected to the load via a low impedance path. Avoid connectors which add significant inductance and resistance. Note that even though a Kelvin sense is available through a 5-pin package, care must be taken since voltage drops along wire traces add to the dropout voltage.



pin descriptions (continued)



APPLICATION INFORMATION

The UC382 is easy to use. The adjustable version requires two 0.1% resistors to set the output voltage. The fixed versions of the UC382 require no external resistors. All versions of the UC382 require decoupling capacitors on the input and output. In a typical application, VB and VIN are driven from switching power supplies which may have large filter capacitors at their outputs. If the UC382 is further than 12 inches from the power supply, it is recommended to add local decoupling as close as possible to the linear regulator.


Decouple the output of the UC382 with at least 100 μ F of high-quality tantalum or Sanyo OSCON capacitors close to the VOUT pin for maximum stability. Many applications involving Ultra-Fast GTL or BTL applications require additional capacitance close to the load. The exact amount will vary according to speed and magnitude of the load transients and the tolerance allowed for transients on VOUT. When specifying the decoupling capacitors, the series resistance of the capacitor bank is an important factor in its ability to filter load transients.


The UC382 allows for Kelvin sensing the voltage at the load. This improves regulation performance and eliminates the voltage drops due to wire-trace resistance. This voltage drop must be added to the headroom (VIN to VOUT and VB to VOUT). The dropout of 450 mV is measured at the pins and does not include additional drops due to trace resistance. The minimum load current is 10 mA.

Two or more UC382's may be used in parallel. While stable, this arrangement does degrade the transient response.



SLUS317B - JANUARY 2000 - REVISED FEBRUARY 2004





APPLICATION INFORMATION




Figure 6. Transient Test Circuit

10 mA to 3 A/μs Load Transient Response




Figure 7

SLUS317B - JANUARY 2000 - REVISED FEBRUARY 2004

APPLICATION INFORMATION




Figure 8. Typical UC382-ADJ Application

UDG-00082




Figure 9. Typical UC382-1, -2, or -3 Application

www.ti.com 11-Nov-2025

PACKAGING INFORMATION

Orderable part number	Status	Material type	Package Pins	Package qty Carrier	RoHS	Lead finish/ Ball material	MSL rating/ Peak reflow	Op temp (°C)	Part marking (6)
						(4)	(5)		
UC282T-ADJ	Active	Production	TO-220 (KC) 5	50 TUBE	Yes	SN	N/A for Pkg Type	-40 to 100	UC282T-ADJ
UC282T-ADJ.A	Active	Production	TO-220 (KC) 5	50 TUBE	Yes	SN	N/A for Pkg Type	-40 to 100	UC282T-ADJ
UC282TDKTTT-1	Active	Production	DDPAK/ TO-263 (KTT) 5	50 TUBE	Yes	SN	Level-2-260C-1 YEAR	-40 to 100	UC282TD-1
UC282TDKTTT-1.A	Active	Production	DDPAK/ TO-263 (KTT) 5	50 TUBE	Yes	SN	Level-2-260C-1 YEAR	-40 to 100	UC282TD-1
UC282TDTR-3	Active	Production	DDPAK/ TO-263 (KTT) 5	500 LARGE T&R	Yes	SN	Level-2-260C-1 YEAR	-40 to 100	UC282TD-3
UC282TDTR-3.A	Active	Production	DDPAK/ TO-263 (KTT) 5	500 LARGE T&R	Yes	SN	Level-2-260C-1 YEAR	-40 to 100	UC282TD-3
UC282TDTR-ADJ	Active	Production	DDPAK/ TO-263 (KTT) 5	500 LARGE T&R	Yes	SN	Level-2-260C-1 YEAR	-40 to 100	UC282TD-ADJ
UC282TDTR-ADJ.A	Active	Production	DDPAK/ TO-263 (KTT) 5	500 LARGE T&R	Yes	SN	Level-2-260C-1 YEAR	-40 to 100	UC282TD-ADJ
UC382T-ADJ	Active	Production	TO-220 (KC) 5	50 TUBE	Yes	SN	N/A for Pkg Type	-	UC382T-ADJ
UC382T-ADJ.A	Active	Production	TO-220 (KC) 5	50 TUBE	Yes	SN	N/A for Pkg Type	0 to 100	UC382T-ADJ
UC382T-ADJG3	Active	Production	TO-220 (KC) 5	50 TUBE	Yes	SN	N/A for Pkg Type	0 to 100	UC382T-ADJ
UC382TDKTTT-2	Active	Production	DDPAK/ TO-263 (KTT) 5	50 TUBE	Yes	SN	Level-2-260C-1 YEAR	0 to 70	UC382TD-2
UC382TDKTTT-2.A	Active	Production	DDPAK/ TO-263 (KTT) 5	50 TUBE	Yes	SN	Level-2-260C-1 YEAR	0 to 70	UC382TD-2
UC382TDTR-ADJ	Active	Production	DDPAK/ TO-263 (KTT) 5	500 LARGE T&R	Yes	SN	Level-2-260C-1 YEAR	-	UC382TD-ADJ
UC382TDTR-ADJ.A	Active	Production	DDPAK/ TO-263 (KTT) 5	500 LARGE T&R	Yes	SN	Level-2-260C-1 YEAR	0 to 100	UC382TD-ADJ

⁽¹⁾ Status: For more details on status, see our product life cycle.

⁽²⁾ Material type: When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

⁽³⁾ RoHS values: Yes, No, RoHS Exempt. See the TI RoHS Statement for additional information and value definition.



PACKAGE OPTION ADDENDUM

www.ti.com 11-Nov-2025

(4) Lead finish/Ball material: Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

(5) MSL rating/Peak reflow: The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

(6) Part marking: There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

PACKAGE MATERIALS INFORMATION

www.ti.com 19-Aug-2025

TAPE AND REEL INFORMATION



A0	Dimension designed to accommodate the component width
В0	Dimension designed to accommodate the component length
K0	Dimension designed to accommodate the component thickness
W	Overall width of the carrier tape
P1	Pitch between successive cavity centers

QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE



*All dimensions are nominal

Device	Package Type	Package Drawing		SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
UC282TDTR-3	DDPAK/ TO-263	KTT	5	500	330.0	24.4	10.9	16.1	4.9	16.0	24.0	Q2
UC282TDTR-ADJ	DDPAK/ TO-263	KTT	5	500	330.0	24.4	10.9	16.1	4.9	16.0	24.0	Q2
UC382TDTR-ADJ	DDPAK/ TO-263	KTT	5	500	330.0	24.4	10.9	16.1	4.9	16.0	24.0	Q2



www.ti.com 19-Aug-2025



*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)	
UC282TDTR-3	DDPAK/TO-263	KTT	5	500	356.0	356.0	45.0	
UC282TDTR-ADJ	DDPAK/TO-263	KTT	5	500	356.0	356.0	45.0	
UC382TDTR-ADJ	DDPAK/TO-263	KTT	5	500	356.0	356.0	45.0	

PACKAGE MATERIALS INFORMATION

www.ti.com 19-Aug-2025

TUBE



*All dimensions are nominal

Device	Package Name	Package Type	Pins	SPQ	L (mm)	W (mm)	T (µm)	B (mm)
UC282T-ADJ	KC	TO-220	5	50	546	31	11930	3.17
UC282T-ADJ.A	KC	TO-220	5	50	546	31	11930	3.17
UC382T-ADJ	KC	TO-220	5	50	546	31	11930	3.17
UC382T-ADJ.A	KC	TO-220	5	50	546	31	11930	3.17
UC382T-ADJG3	KC	TO-220	5	50	546	31	11930	3.17

KTT (R-PSFM-G5)

PLASTIC FLANGE-MOUNT PACKAGE



NOTES:

- A. All linear dimensions are in millimeters.
- B. This drawing is subject to change without notice.
- C. Body dimensions do not include mold flash or protrusion. Mold flash or protrusion not to exceed 0.005 (0,13) per side.
- Falls within JEDEC T0—263 variation BA, except minimum lead thickness, maximum seating height, and minimum body length.





NOTES: A.

- A. All linear dimensions are in millimeters.
- B. This drawing is subject to change without notice.
- C. Publication IPC-SM-782 is recommended for alternate designs.
- D. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release.

 Customers should contact their board assembly site for stencil design recommendations. Refer to IPC-7525.
- E. Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.
- F. This package is designed to be soldered to a thermal pad on the board. Refer to the Product Datasheet for specific thermal information, via requirements, and recommended thermal pad size. For thermal pad sizes larger than shown a solder mask defined pad is recommended in order to maintain the solderable pad geometry while increasing copper area.





TO-220



NOTES:

- All controlling linear dimensions are in inches. Dimensions in brackets are in millimeters. Any dimension in brackets or parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
 This drawing is subject to change without notice.
- 3. Shape may vary per different assembly sites.



TO-220



IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you fully indemnify TI and its representatives against any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale, TI's General Quality Guidelines, or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products. Unless TI explicitly designates a product as custom or customer-specified, TI products are standard, catalog, general purpose devices.

TI objects to and rejects any additional or different terms you may propose.

Copyright © 2025, Texas Instruments Incorporated

Last updated 10/2025