

SLUS215B - OCTOBER 1998 - REVISED FEBRUARY 2004

- **Precision Positive Linear Series Pass Voltage Regulation**
- 0.45 V Dropout at 3 A
- 50 mV Dropout at 10 mA
- Quiescent Current Under 650 µA Irrespective of Load
- Adjustable (5-Lead) Output Voltage Version
- Fixed (3-Lead) Versions for 3.3-V and 5-V **Outputs**
- Logic Shutdown Capability
- **Short-Circuit Power Limit of** $(3\% \times V_{IN} \times I_{SHORT})$
- Low V_{OUT} to V_{IN} Reverse Leakage
- **Thermal Shutdown**


description

The UCC283-3/-5/-ADJ family of positive linear series pass voltage regulators are tailored for low-drop-out applications where low quiescent power is important. Fabricated with a BiCMOS technology ideally suited for low input-to-output differential applications, the UCC283-5 passes 3 A while requiring only 0.45 V of typical input voltage headroom (ensured 0.6-V dropout).





TO-220-5 T PACKAGE



These regulators include reverse voltage sensing that prevents current in the reverse direction. Quiescent current is always less than 650 μA. These devices have been internally compensated in such a way that the need for a minimum output capacitor has been eliminated.

UCC283-3 and UCC283-5 versions are in 3-lead packages and have preset outputs at 3.3 V and 5.0 V respectively. The output voltage is regulated to 1.5% at room temperature. The UCC283-ADJ version, in a 5-lead package, regulates the output voltage programmed by an external resistor ratio.

Short-circuit current is internally limited. The device responds to a sustained overcurrent condition by turning off after a t_{ON} time delay. The device then stays off for a period, t_{OFF} , that is 32 times the t_{ON} delay. The device then begins pulsing on and off at the $t_{ON}/(t_{ON}+t_{OFF})$ duty cycle of 3%. This drastically reduces the power dissipation during short-circuit and means heat sinks need only accommodate normal operation. On the 3-leaded versions of the device t_{ON} is fixed at 750 μ s, on the adjustable 5-leaded versions an external capacitor sets the on time. The off time is always $32 \times t_{ON}$. The external timing control pin, CT, on the 5-leaded versions also serves as a shutdown input when pulled low.

Internal power dissipation is further controlled with thermal overload protection circuitry. Thermal shutdown occurs if the junction temperature exceeds 165°C. The chip remains off until the temperature has dropped 20°C.

The UCC283 series is specified for operation over the industrial range of -40°C to 85°C, and the UCC383 series is specified from 0°C to 70°C. These devices are available in 3- and 5-pin TO-220 and TO-263 power packages.



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

All trademarks are the property of their respective owners



UCC283-3, UCC283-5, UCC283-ADJ, UCC383-3, UCC383-5, UCC383-ADJ LOW-DROPOUT 3-A LINEAR REGULATOR FAMILY


SLUS215B - OCTOBER 1998 - REVISED FEBRUARY 2004

AVAILABLE OPTIONS(1)

TA	OUTDI	IT VOLTA	OF 00	PACKAGE DEVICES						
	OUTP	JT VOLTA	GE (V)	TO-263-3(2)	TO-263-5(2)	TO-220-3	TO-220-5			
	MIN TYP MAX			Т	D	Ť				
	3.22	3.3	3.58	UCC283TD-3	_	UCC283T-3	_			
-40°C to 85°C	4.875	5.00	5.125	UCC283TD-5	_	UCC283T-5	_			
	ADJ			_	UCC283TD-ADJ	_	UCC283T-ADJ			
	3.22	3.3	3.58	UCC383TD-3	_	UCC383T-3	_			
0°C to 70°C	4.875	5.00	5.125	UCC383TD-5	_	UCC383T-5	_			
		ADJ		_	UCC383TD-ADJ	_	UCC383T-ADJ			

- 1. For more package and ordering information, see the Package Option Addendum located at the end of this data sheet.
- 2. For 50 piece reel, add KTTT (e.g., UCC283TDKTTT-3); for 500 piece reel, add TR (e.g., UCC283TDTR-3).

functional block diagram



UCC283-3, UCC283-5, UCC283-ADJ, UCC383-3, UCC383-5, UCC383-ADJ LOW-DROPOUT 3-A LINEAR REGULATOR FAMILY

SLUS215B - OCTOBER 1998 - REVISED FEBRUARY 2004

electrical characteristics $T_A=0^{\circ}C$ to $70^{\circ}C$ for the UCC383–x series, $T_A=-40^{\circ}C$ to $85^{\circ}C$ for the UCC283–x, $V_{VIN}=V_{VOUT}+1.5$ V, $I_{OUT}=10$ mA, $C_{IN}=10$ μF , $C_{OUT}=22$ μF . For the UCC283–ADJ, $V_{VIN}=6.5$ V, $V_{OUT}=5.0$ V, $C_T=750$ pF, $T_J=T_A$ unless otherwise stated

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNITS
UCC283-5 Fixed 5 V, 3 A Family					
	T _J = 25°C	4.925	5	5.075	V
Output voltage	Over temperature	4.875		5.125	V
Line regulation	V _{VIN} = 5.15 V to 9 V		2	10	mV
Load regulation	I _{OUT} = 10 mA to 3 A		10	20	mV
	I _{OUT} = 3 A, V _{OUT} = 4.85 V		0.4	0.6	V
Dropout voltage, VDROPOUT = VVIN - VVOUT	$I_{OUT} = 1.5 \text{ A}, \qquad V_{OUT} = 4.85 \text{ V}$		0.2	0.45	V
	$I_{OUT} = 10 \text{ mA}, \qquad V_{OUT} = 4.85 \text{ V}$		50	150	mV
Peak current limit	V _{VOUT} = 0 V	4	7	10	Α
Overcurrent threshold		3	4	5.5	Α
Current limit duty cycle	V _{VOUT} = 0 V		3%	5%	
Overcurrent time out, t _{ON}	V _{VOUT} = 0 V	400	750	1400	μs
Quiescent current	No load		400	650	μΑ
Reverse leakage current	1 V < V _{VIN} < V _{VOUT} , V _{VOUT} ≤ 5.1 V, at V _{VOUT}		30	75	μΑ
Undervoltage lockout	VIN where VOUT passes current	2.5	2.8	3	V
UCC283-3 Fixed 3.3 V, 3 A Family					
Q	T _J = 25°C	3.25	3.3	3.35	V
Output voltage	Over temperature	3.22		3.38	V
Line regulation voltage	V _{VIN} = 3.45 V to 9 V		2	7	mV
Load regulation voltage	I _{OUT} = 10 mA to 3 A		7	15	mV
	I _{OUT} = 3A, VOUT = 3.15 V		0.5	1	V
Dropout voltage, V _{DROPOUT} = V _{VIN} - V _{VOUT}	$I_{OUT} = 1.5A, VOUT = 3.15 V$		0.25	0.6	V
	$I_{OUT} = 10mA$, $VOUT = 3.15 V$		50	150	mV
Peak current limit	V _{VOUT} = 0 V	4	7	10	Α
Overcurrent threshold		3	4	5.5	Α
Current limit duty cycle	V _{VOUT} = 0 V		3%	5%	
Overcurrent time out, t _{ON}	V _{VOUT} = 0 V	400	750	1400	μs
Quiescent current	No load		400	650	μΑ
Reverse leakage current	1 V < V _{VIN} < V _{VOUT} , V _{VOUT} ≤ 3.35 V at V _{VOUT}		30	75	μΑ
Undervoltage lockout	VIN where VOUT passes current	2.5	2.8	3	V



UCC283-3, UCC283-5, UCC283-ADJ, UCC383-3, UCC383-5, UCC383-ADJ LOW-DROPOUT 3-A LINEAR REGULATOR FAMILY

SLUS215B - OCTOBER 1998 - REVISED FEBRUARY 2004

electrical characteristics $T_A=0^{\circ}C$ to $70^{\circ}C$ for the UCC383–x series, $T_A=-40^{\circ}C$ to $85^{\circ}C$ for the UCC283–x, V_{VIN} = V_{VOUT} + 1.5 V, I_{OUT} = 10 mA, C_{IN} = 10 μ F, C_{OUT} = 22 μ F. For the UCC283–ADJ, V_{VIN} = 6.5 V, V_{OUT} = 5.0 V, C_T = 750 pF, T_J = T_A unless otherwise stated

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNITS
UCC283-ADJ Adjustable Output, 3 A Family					
B 1.6 % AB1 :	TJ = 25°C	1.23	1.25	1.27	V
Regulating voltage at ADJ pin	Over temperature	1.22		1.28	V
Line regulation voltage, at ADJ input	$V_{VIN} = V_{VOUT} + 150 \text{ mV to } 9 \text{ V}$		1	3	mV
Load regulation voltage, at ADJ input	I _{OUT} = 10 mA to 3 A		2	5	mV
	V _{OUT} = 4.85 V, I _{OUT} = 3 A		0.4	0.6	V
Dropout voltage, VDROPOUT = VIN - VOUT	$V_{OUT} = 4.85 \text{ V}, \qquad I_{OUT} = 1.5 \text{ A}$		0.2	0.45	V
	V _{OUT} = 4.85 V, I _{OUT} = 10 mA		50	150	mV
Peak current limit	V _{VOUT} = 0 V	4	7	10	Α
Overcurrent threshold		3	4	5.5	Α
Current limit duty cycle	V _{VOUT} = 0 V		3	5	%
Overcurrent time out, tON	V _{VOUT} = 0 V	300	575	1200	μs
Reverse leakage current	1 V < V _{VIN} < V _{VOUT} V _{VOUT} ≤ 9 V, at V _{VOUT}		30	100	μΑ
Bias current at ADJ input			20	250	nA
Quiescent current	No load		400	650	μΑ
Shutdown threshold	At CT input	0.25	0.65		V
Quiescent current in shutdown	V _{VIN} = 9 V		40	75	μΑ
UVLO	VIN where VOUT passes current	2.5	2.8	3	V

absolute maximum ratings over operating free-air temperature (unless otherwise noted)†

Input voltage

VIN
CT –0.3 V to 3 V
ADJ
Storage Temperature, T _{stq} –65°C to 150°C
Storage Temperature, T_{stg}
Lead Temperature (soldering, 10 seconds)

[†] Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

UCC283-3, UCC283-5, UCC283-ADJ, UCC383-3, UCC383-5, UCC383-ADJ LOW-DROPOUT 3-A LINEAR REGULATOR FAMILY

SLUS215B - OCTOBER 1998 - REVISED FEBRUARY 2004

pin descriptions

ADJ: Adjust pin for the UCC283–ADJ version only. Feedback pin for the linear regulator. Program the output voltage with R1 connected from ADJ to GND and R2 connected from VOUT to ADJ. Output voltage is given by:

$$V_{OUT} = \frac{1.25 \text{ V} \times (R1 + R2)}{R1}$$

CT: Short-circuit timing capacitor and shutdown input for the UCC283–ADJ version. Pulling CT below 0.25 V turns off the regulator and places it in a low quiescent-current mode. A timing capacitor, C, from CT to GND programs the duration of the pulsed short-circuit on-time. On-time, t_{ON}, is approximately given by:

$$t_{ON} = 750 \text{ k} \times \text{C}$$

GND: Reference ground.

VIN: Input voltage, This pin must be bypassed with a low ESL/ESR 1-μF or larger capacitor to GND. VIN can range from (VOUT + V_{DROPOUT}) to 9 V. If VIN is reduced to zero while VOUT is held high, the reverse leakage from VOUT to VIN is less than 75μA.

VOUT: Regulated output voltage. A bypass capacitor is not required at VOUT, but may be desired for good transient response. The bypass capacitor must not exceed a maximum value in order to insure the regulator can start.

APPLICATION INFORMATION

overview

The UCC383 family of low dropout linear (LDO) regulators provide a regulated output voltage for applications with up to 3 A of load current. The regulators feature a low dropout voltage and short-circuit protection, making their use ideal for demanding high-current applications requiring fault protection.

short-circuit-protection

The UCC383 provides unique short-circuit protection circuitry that reduces power dissipation during a fault. When an overload situation is detected, the device enters a pulsed mode of operation at 3% duty cycle reducing the heat sink requirements during a fault. The UCC383 has two current thresholds that determine its behavior during a fault as shown in Figure 1. When the regulator current exceeds the **overcurrent threshold** for a period longer than t_{ON} , the UCC383 shuts off for a period (t_{OFF}) which is $32 \times t_{ON}$. During an overload, the regulator actively limits the maximum current to the **peak current limit** value. The peak current limit is nominally 3 A greater than the overcurrent threshold. The regulator continues in pulsed mode until the fault is cleared as illustrated in Figure 1.



APPLICATION INFORMATION




Figure 1. UCC383 Short-Circuit Timing

A capacitive load on the regulator's output appears as a short-circuit during start-up. If the capacitance is too large, the output voltage does not come into regulation during the initial $t_{\rm ON}$ period and the UCC383 enters pulsed mode operation. The peak current limit, $t_{\rm ON}$ period, and load characteristics determine the maximum value of output capacitor that can be charged. For a constant current load the maximum output capacitance is given as follows:

$$C_{OUT(max)} = \left(I_{CL} - I_{LOAD}\right) \times \frac{t_{ON}}{V_{OUT}}$$
 Farads (1)

For worst case calculations, the minimum values of on time (t_{ON}) and peak current limit (l_{CL}) should be used. The adjustable version allows the t_{ON} time to be adjusted with a capacitor on the CT pin:

$$t_{ON(adj)} = 750,000 \times C (\mu \text{ Farad}) \text{ microseconds}$$
 (2)

For a resistive load (R_{LOAD}) the maximum output capacitor can be estimated from:

$$C_{OUT(max)} = \frac{{}^{t}ON(sec)}{R_{LOAD} \times \ell n \left(\frac{1}{1 - \frac{VOUT}{I_{CL} \times R_{LOAD}}}\right)}$$
Farads (3)

SLUS215B - OCTOBER 1998 - REVISED FEBRUARY 2004

I_{OUT}= 3 A

4.5

5


APPLICATION INFORMATION

dropout performance

Referring to the *Block Diagram*, the dropout voltage of the UCC383 is equal to the minimum voltage drop (V_{IN} to V_{OUT}) across the N-channel MOSFET. The dropout voltage is dependent on operating conditions such as load current, input and load voltages, as well as temperature. The UCC383 achieves a low Rds(on) through the use of an internal charge-pump (V_{PUMP}) that drives the MOSFET gate. Figure 2 depicts typical dropout voltages versus load current for the 3.3-V and 5-V versions of the part, as well as the adjustable version programmed to 3.0 V.

Figure 3 depicts the typical dropout performance of the adjustable version with various output voltages and load currents.


Operating temperatures also affect the Rds(on) and dropout voltage of the UCC383. Figure 4 graphs the typical dropout for the 3.3-V and 5-V versions with a 3-A load over temperature.



APPLICATION INFORMATION

voltage programming and shutdown feature for adjustable version

A typical application circuit based on the UCC383 adjustable version is shown in Figure 5. The output voltage is externally programmed through a resistive divider at the ADJ pin.



$$V_{OUT} = 1.25 \times \left(1 + \frac{R2}{R1}\right) \text{ Volts}$$
 (4)

The maximum programmed output voltage is constrained by the 9-V absolute rating of the IC (this includes the charge pump voltage) and its ability to enhance the N-channel MOSFET. Unless the load current is below the 3-A rating of the device, output voltages above 7 V are not recommended. The minimum output voltage can be programmed down to 1.25 V. However, the input voltage must always be greater than the UVLO of the part.

The adjustable version includes a shutdown feature, limiting quiescent current to 40 μ A typical. The UCC383 is shut down by pulling the CT pin to below 0.25 V. As shown in Figure 5, a small logic level MOSFET or BJT transistor in parallel with the timing capacitor can be driven with a digital signal, putting the device in shutdown. If the CT pin is not pulled low, the IC internally pulls up the pin enabling the regulator. The CT pin should not be forced high, as this interferes with the short-circuit-protection feature. Selection of the timing capacitor is explained in *Short-Circuit-Protection*.

The adjustable version can be used in applications requiring remote voltage sensing (i.e. monitoring a voltage other than or not directly tied to the VOUT pin). This is possible since the inverting input of the error-voltage amplifier (see *Block Diagram*) is brought out to the ADJ pin.

SLUS215B - OCTOBER 1998 - REVISED FEBRUARY 2004

APPLICATION INFORMATION

thermal design

The Package Information section of the Power Supply Control Products Data Book, Volume 3 (Literature No. SLUD003) contains reference material for the thermal ratings of various packages. The section also includes an excellent article *Thermal Characteristics of Surface Mount Packages*, that is the basis of the following discussion.

Thermal design for the UCC383 family of linear regulators includes two modes of operation, normal and pulsed mode. In normal operation, the linear regulator and heat sink must dissipate power equal to the maximum forward voltage drop multiplied by the maximum load current. Assuming a constant current load, the expected heat rise at the regulator's junction can be calculated as follows:

$$t_{RISE}(\theta) = P_{DISS} \times (\theta_{jc} + \theta_{ca})$$
 °C (5)

Where theta, (θ) is thermal resistance and P_{DISS} is the power dissipated. The thermal resistance of both the TO–220 and TO–263 packages (junction to case) is 3°C per Watt. In order to prevent the regulator from going into thermal shutdown, the case to ambient theta must keep the junction temperature below 150°C. If the LDO is mounted on a 5-square inch pad of 1-ounce copper, for example, the thermal resistance from junction to ambient becomes 60°C per Watt. If a lower thermal resistance is required by the application, the device heat sinking would need to be improved.

When the UCC383 regulator is in pulsed mode due to an overload or short-circuit in the application, the maximum average power dissipation is calculated as follows:

$$P_{\text{PULSE(avg)}} = \left(V_{\text{IN}} - V_{\text{OUT}}\right) \times I_{\text{CL}} \times \frac{t_{\text{ON}}}{33 \times t_{\text{ON}}} \text{ Watts}$$
(6)

As seen in Equation 6, the average power during a fault is reduced dramatically by the duty cycle, allowing the heat sink to be sized for normal operation. Although the peak power in the regulator during the t_{ON} period can be significant, the thermal mass of the package generally keeps the junction temperature from rising unless the t_{ON} period is increased to tens of milliseconds.

ripple rejection

Even though the UCC383 family of linear regulators are not optimized for fast transient applications (Refer to the UC182 Fast LDO Linear Regulator), they do offer significant power supply rejection at lower frequencies. Figure 6 depicts ripple rejection performance in a typical application. The performance can be improved with additional filtering.

APPLICATION INFORMATION




Figure 5. Typical Application for 5-Pin Adjustable Version




Figure 6. Ripple Rejection vs. Frequency

www.ti.com

18-Nov-2025

PACKAGING INFORMATION

Orderable part number	Status (1)	Material type	Package Pins	Package qty Carrier	RoHS (3)	Lead finish/ Ball material	MSL rating/ Peak reflow	Op temp (°C)	Part marking (6)
UCC283T-ADJ	Active	Production	TO-220 (KC) 5	50 TUBE	Yes	SN	N/A for Pkg Type	-	UCC283T-ADJ
UCC283T-ADJ.A	Active	Production	TO-220 (KC) 5	50 TUBE	Yes	SN	N/A for Pkg Type	-40 to 85	UCC283T-ADJ
UCC283TDKTTT-5	Active	Production	DDPAK/ TO-263 (KTT) 3	50 TUBE	Yes	SN	Level-2-260C-1 YEAR	-40 to 85	UCC283TD-5
UCC283TDKTTT-5.A	Active	Production	DDPAK/ TO-263 (KTT) 3	50 TUBE	Yes	SN	Level-2-260C-1 YEAR	-40 to 85	UCC283TD-5
UCC283TDTR-3	Active	Production	DDPAK/ TO-263 (KTT) 3	500 LARGE T&R	Yes	SN	Level-2-260C-1 YEAR	-	UCC283TD-3
UCC283TDTR-3.A	Active	Production	DDPAK/ TO-263 (KTT) 3	500 LARGE T&R	Yes	SN	Level-2-260C-1 YEAR	-40 to 85	UCC283TD-3
UCC283TDTR-ADJ	Active	Production	DDPAK/ TO-263 (KTT) 5	500 LARGE T&R	Yes	SN	Level-2-260C-1 YEAR	-40 to 85	UCC283TD-ADJ
UCC283TDTR-ADJ.A	Active	Production	DDPAK/ TO-263 (KTT) 5	500 LARGE T&R	Yes	SN	Level-2-260C-1 YEAR	-40 to 85	UCC283TD-ADJ
UCC383T-ADJ	Active	Production	TO-220 (KC) 5	50 TUBE	Yes	SN	N/A for Pkg Type	-	UCC383T-ADJ
UCC383T-ADJ.A	Active	Production	TO-220 (KC) 5	50 TUBE	Yes	SN	N/A for Pkg Type	See UCC383T-ADJ	UCC383T-ADJ
UCC383TDKTTT-5	Active	Production	DDPAK/ TO-263 (KTT) 3	50 TUBE	Yes	SN	Level-2-260C-1 YEAR	0 to 70	UCC383TD-5
UCC383TDKTTT-5.A	Active	Production	DDPAK/ TO-263 (KTT) 3	50 TUBE	Yes	SN	Level-2-260C-1 YEAR	0 to 70	UCC383TD-5
UCC383TDTR-3	Active	Production	DDPAK/ TO-263 (KTT) 3	500 LARGE T&R	Yes	SN	Level-2-260C-1 YEAR	-	UCC383TD-3
UCC383TDTR-3.A	Active	Production	DDPAK/ TO-263 (KTT) 3	500 LARGE T&R	Yes	SN	Level-2-260C-1 YEAR	See UCC383TDTR-3	UCC383TD-3
UCC383TDTR-ADJ	Active	Production	DDPAK/ TO-263 (KTT) 5	500 LARGE T&R	Yes	SN	Level-2-260C-1 YEAR	-	UCC383TD-ADJ
UCC383TDTR-ADJ.A	Active	Production	DDPAK/ TO-263 (KTT) 5	500 LARGE T&R	Yes	SN	Level-2-260C-1 YEAR	See UCC383TDTR- ADJ	UCC383TD-ADJ

⁽¹⁾ Status: For more details on status, see our product life cycle.



PACKAGE OPTION ADDENDUM

www.ti.com 18-Nov-2025

- (2) Material type: When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.
- (3) RoHS values: Yes, No, RoHS Exempt. See the TI RoHS Statement for additional information and value definition.
- (4) Lead finish/Ball material: Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.
- (5) MSL rating/Peak reflow: The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.
- (6) Part marking: There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

PACKAGE MATERIALS INFORMATION

www.ti.com 1-Oct-2025

TAPE AND REEL INFORMATION





A0	Dimension designed to accommodate the component width
В0	Dimension designed to accommodate the component length
K0	Dimension designed to accommodate the component thickness
W	Overall width of the carrier tape
P1	Pitch between successive cavity centers

QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE



*All dimensions are nominal

Device	Package Type	Package Drawing		SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
UCC283TDTR-3	DDPAK/ TO-263	KTT	3	500	330.0	24.4	10.9	16.1	4.9	16.0	24.0	Q2
UCC283TDTR-ADJ	DDPAK/ TO-263	KTT	5	500	330.0	24.4	10.9	16.1	4.9	16.0	24.0	Q2
UCC383TDTR-3	DDPAK/ TO-263	KTT	3	500	330.0	24.4	10.9	16.1	4.9	16.0	24.0	Q2
UCC383TDTR-ADJ	DDPAK/ TO-263	KTT	5	500	330.0	24.4	10.9	16.1	4.9	16.0	24.0	Q2



www.ti.com 1-Oct-2025



*All dimensions are nominal

Device	evice Package Type		Device Package Type		Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
UCC283TDTR-3	DDPAK/TO-263	ктт	3	500	356.0	356.0	45.0		
UCC283TDTR-ADJ	DDPAK/TO-263	ктт	5	500	356.0	356.0	45.0		
UCC383TDTR-3	DDPAK/TO-263	KTT	3	500	356.0	356.0	45.0		
UCC383TDTR-ADJ	DDPAK/TO-263	KTT	5	500	356.0	356.0	45.0		

PACKAGE MATERIALS INFORMATION

www.ti.com 1-Oct-2025

TUBE



*All dimensions are nominal

Device	Package Name	Package Type	Pins	SPQ	L (mm)	W (mm)	T (µm)	B (mm)
UCC283T-ADJ	KC	TO-220	5	50	546	31	11930	3.17
UCC283T-ADJ.A	KC	TO-220	5	50	546	31	11930	3.17
UCC383T-ADJ	KC	TO-220	5	50	546	31	11930	3.17
UCC383T-ADJ.A	KC	TO-220	5	50	546	31	11930	3.17



TO-220



NOTES:

- All controlling linear dimensions are in inches. Dimensions in brackets are in millimeters. Any dimension in brackets or parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
 This drawing is subject to change without notice.
- 3. Shape may vary per different assembly sites.



TO-220



KTT (R-PSFM-G5)

PLASTIC FLANGE-MOUNT PACKAGE



NOTES:

- A. All linear dimensions are in millimeters.
- B. This drawing is subject to change without notice.
- C. Body dimensions do not include mold flash or protrusion. Mold flash or protrusion not to exceed 0.005 (0,13) per side.
- Falls within JEDEC T0—263 variation BA, except minimum lead thickness, maximum seating height, and minimum body length.





NOTES: A.


- A. All linear dimensions are in millimeters.
- B. This drawing is subject to change without notice.
- C. Publication IPC-SM-782 is recommended for alternate designs.
- D. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release.

 Customers should contact their board assembly site for stencil design recommendations. Refer to IPC-7525.
- E. Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.
- F. This package is designed to be soldered to a thermal pad on the board. Refer to the Product Datasheet for specific thermal information, via requirements, and recommended thermal pad size. For thermal pad sizes larger than shown a solder mask defined pad is recommended in order to maintain the solderable pad geometry while increasing copper area.



KTT (R-PSFM-G3)

PLASTIC FLANGE-MOUNT PACKAGE




NOTES:

- A. All linear dimensions are in millimeters.
- 3. This drawing is subject to change without notice.
- C. Body dimensions do not include mold flash or protrusion. Mold flash or protrusion not to exceed 0.005 (0,13) per side.
- ⚠ Falls within JEDEC T0—263 variation AA, except minimum lead thickness and minimum exposed pad length.



KTT (R-PSFM-G3)

PLASTIC FLANGE-MOUNT PACKAGE



NOTES: A.

- A. All linear dimensions are in millimeters.
- B. This drawing is subject to change without notice.
- C. Publication IPC-SM-782 is recommended for alternate designs.
- D. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release.

 Customers should contact their board assembly site for stencil design recommendations. Refer to IPC-7525.
- E. Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.
- F. This package is designed to be soldered to a thermal pad on the board. Refer to the Product Datasheet for specific thermal information, via requirements, and recommended thermal pad size. For thermal pad sizes larger than shown a solder mask defined pad is recommended in order to maintain the solderable pad geometry while increasing copper area.



IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you fully indemnify TI and its representatives against any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale, TI's General Quality Guidelines, or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products. Unless TI explicitly designates a product as custom or customer-specified, TI products are standard, catalog, general purpose devices.

TI objects to and rejects any additional or different terms you may propose.

Copyright © 2025, Texas Instruments Incorporated

Last updated 10/2025